



# FCC TEST REPORT

**Test report**  
**On Behalf of**  
**Yudong Innovations Co., Ltd**  
**For**  
**Espresso Machine**  
**Model No.: MEM03**

**FCC ID: 2BH5S-MEM03**

**Prepared for :** Yudong Innovations Co., Ltd  
1902 Tianlong Yidong Headquarters Building, Tongfa South Road, Xili Community,  
Xili Street, Nanshan District, Shenzhen, China

**Prepared By :** Shenzhen Tongzhou Testing Co.,Ltd  
1th Floor, Building 1, Haomai High-tech Park, Huating Road 387, Dalang Street,  
Longhua, Shenzhen, China

**Date of Test:** 2024/7/3 ~ 2024/7/29

**Date of Report:** 2024/7/30

**Report Number:** TZ240706018-NFC

The test report apply only to the specific sample(s) tested under stated test conditions  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

**TEST RESULT CERTIFICATION**

**Applicant's name** .....: **Yudong Innovations Co., Ltd**  
Address.....: 1902 Tianlong Yidong Headquarters Building, Tongfa South Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China

**Manufacture's Name** .....: **Yudong Innovations Co., Ltd**  
Address.....: 1902 Tianlong Yidong Headquarters Building, Tongfa South Road, Xili Community, Xili Street, Nanshan District, Shenzhen, China

**Product description**

Trade Mark .....:  **Meraki**

Product name .....: Espresso Machine

Model and/or type reference ..: MEM03

**Standards** .....: FCC Rules and Regulations Part 15.225  
ANSI C63.10:2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Tongzhou Testing Co.,Ltd is acknowledged as copyright owner and source of the material. Shenzhen Tongzhou Testing Co.,Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test**.....:   
Date (s) of performance of tests.....: **2024/7/3 ~ 2024/7/29**  
Date of Issue.....: **2024/7/30**  
Test Result.....: **Pass**

Testing Engineer : Allen Lai  
(Allen Lai)

Technical Manager : Hugo Chen  
(Hugo Chen)

Authorized Signatory : Andy Zhang  
(Andy Zhang)



Revision History

| Revision | Issue Date | Revisions     | Revised By |
|----------|------------|---------------|------------|
| 000      | 2024/7/30  | Initial Issue | Andy Zhang |
|          |            |               |            |
|          |            |               |            |



## TABLE OF CONTENTS

|                                                    |           |
|----------------------------------------------------|-----------|
| <b>1 GENERAL INFORMATION .....</b>                 | <b>5</b>  |
| 1.1 Description of Device (EUT).....               | 5         |
| 1.2 Wireless Function Tested in this Report .....  | 5         |
| 1.3 Objective.....                                 | 6         |
| 1.4 Environmental Conditions .....                 | 6         |
| 1.5 Description of Test Facility .....             | 7         |
| 1.6 Statement of the Measurement Uncertainty ..... | 8         |
| 1.7 Measurement Uncertainty .....                  | 8         |
| 1.8 Description of Test Modes .....                | 8         |
| 1.9 Antenna System .....                           | 8         |
| <b>2 TEST METHODOLOGY .....</b>                    | <b>9</b>  |
| 2.1 EUT Configuration.....                         | 9         |
| 2.2 EUT Exercise .....                             | 9         |
| 2.3 General Test Procedures .....                  | 9         |
| 2.4 Instrument Calibration.....                    | 9         |
| 2.5 Test Mode .....                                | 9         |
| <b>3 SYSTEM TEST CONFIGURATION .....</b>           | <b>10</b> |
| 3.1 Justification .....                            | 10        |
| 3.2 EUT Exercise Software.....                     | 10        |
| 3.3 Special Accessories .....                      | 10        |
| 3.4 Block Diagram/Schematics.....                  | 10        |
| 3.5 Equipment Modifications .....                  | 10        |
| <b>4 SUMMARY OF TEST RESULTS .....</b>             | <b>11</b> |
| <b>5 TEST ITEMS AND RESULTS .....</b>              | <b>12</b> |
| 5.1 AC Power line conducted emissions.....         | 12        |
| 5.2 Transmitter Field Strength of Emissions.....   | 15        |
| 5.3 20dB Bandwidth Emissions .....                 | 24        |
| 5.4 Frequency Tolerance.....                       | 25        |
| 5.5 Antenna Requirement .....                      | 27        |
| <b>6 LIST OF MEASURING EQUIPMENTS .....</b>        | <b>28</b> |
| <b>7 TEST SETUP PHOTOGRAPHS OF EUT .....</b>       | <b>29</b> |
| <b>8 EXTERIOR PHOTOGRAPHS OF THE EUT.....</b>      | <b>29</b> |
| <b>9 INTERIOR PHOTOGRAPHS OF THE EUT .....</b>     | <b>29</b> |



## 1 GENERAL INFORMATION

### 1.1 Description of Device (EUT)

|                   |                      |
|-------------------|----------------------|
| EUT               | : Espresso Machine   |
| Model Number      | : MEM03              |
| Model Declaration | : N/A                |
| Test Model        | : MEM03              |
| Power Supply      | : AC 120V by adapter |
| Hardware version  | : DVT1               |
| Software version  | : DVT1               |

### 1.2 Wireless Function Tested in this Report

|                       |                             |
|-----------------------|-----------------------------|
| NFC                   |                             |
| Frequency Range       | : 13.56MHz                  |
| Antenna Type And Gain | Loop Antenna, 0.0dBi (Max.) |

*Note 1: Antenna position refer to EUT Photos.*

*Note 2: the above information was supplied by the applicant.*



### 1.3 Objective

The primary objective of the manufacturer is compliance with Subpart C of Part 15 of FCC Rules for the radiated and conducted emissions of intentional radiators. Certification of these devices is required as a prerequisite to marketing as defined in Part 2 the FCC Rules.

Certification is a procedure where the manufacturer or a contracted laboratory makes measurements and submits the test data and technical information to the FCC. The FCC issues a grant of equipment authorization upon successful completion of their review of the submitted documents. Once the equipment authorization has been obtained, the label indicating compliance must be attached to all identical units, which are subsequently manufactured.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product which may result in increased emissions should be checked to ensure compliance has been maintained (i.e., printed circuit board layout changes, different line filter, different power supply, harnessing or I/O cable changes, etc.).

### 1.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 15-35°C
- Humidity: 30-60 %
- Atmospheric pressure: 86-106 kPa



## 1.5 Description of Test Facility

### FCC

Designation Number: CN1275

Test Firm Registration Number: 167722

Shenzhen Tongzhou Testing Co.,Ltd has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

### A2LA

Certificate Number: 5463.01

Shenzhen Tongzhou Testing Co.,Ltd has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

### IC

ISED#: 22033

CAB identifier: CN0099

Shenzhen Tongzhou Testing Co.,Ltd has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4 and CISPR 16-1-4:2010



## 1.6 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the Shenzhen Tongzhou Testing Co.,Ltd's quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 1.7 Measurement Uncertainty

| Test Item              |   | Frequency Range | Uncertainty | Note |
|------------------------|---|-----------------|-------------|------|
| Radiation Uncertainty  | : | 9KHz~30MHz      | ±3.08dB     | (1)  |
|                        |   | 30MHz~1000MHz   | ±4.42dB     | (1)  |
|                        |   | 1GHz~40GHz      | ±4.06dB     | (1)  |
| Conduction Uncertainty | : | 150kHz~30MHz    | ±2.23dB     | (1)  |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 1.8 Description of Test Modes

| Mode   | description              |
|--------|--------------------------|
| Mode 1 | TX(EUT work in 13.56MHz) |

## 1.9 Antenna System

The directional gains of antenna used for transmitting refer to section 1.1 of this report, and EUT uses an loop antenna which is permanently attached.



## 2 TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen Tongzhou Testing Co.,Ltd.

### 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2 EUT Exercise

The EUT was operated in the normal operating mode. The TX frequency that was fixed which was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.225 under the FCC Rules Part 15 Subpart C.

### 2.3 General Test Procedures

#### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 1.5 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

### 2.4 Instrument Calibration

All test equipment is regularly checked to ensure that performance is maintained in accordance with the manufacturer's specifications. All antennas are calibrated at regular intervals with respect to tuned half-wave dipoles. An exhibit of this report contains the list of test equipment used and calibration information.

### 2.5 Test Mode

The EUT has been tested under engineering mode. The field strength of radiation emission was measured in the following position: EUT stand-up position (Y axis), lie-down position (X, Z axis). The worst case of X axis was reported.



### **3 SYSTEM TEST CONFIGURATION**

#### **3.1 Justification**

The system was configured for testing in a continuous transmits condition.

#### **3.2 EUT Exercise Software**

N/A

#### **3.3 Special Accessories**

N/A

#### **3.4 Block Diagram/Schematics**

Please refer to the related document

#### **3.5 Equipment Modifications**

Shenzhen Tongzhou Testing Co.,Ltd. has not done any modification on the EUT.



#### 4 SUMMARY OF TEST RESULTS

| Rules                             | Description of test | Sample ID      | Result    |
|-----------------------------------|---------------------|----------------|-----------|
| §15.205<br>§15.209<br>§15.225 (d) | Radiated Emissions  | TZ240706018-1# | Compliant |
| §15.207                           | Conducted Emission  | TZ240706018-1# | Compliant |
| §15.225 (a) (b) (c)               | In-Band Emission    | TZ240706018-1# | Compliant |
| §15.215 (c)                       | 20dB Bandwidth      | TZ240706018-1# | Compliant |
| 15.225(e)                         | Frequency Tolerance | TZ240706018-1# | Compliant |
| §15.203                           | Antenna Requirement | TZ240706018-1# | Compliant |

Note: All buttons have been taken into consideration and only worst case reported.

## 5 TEST ITEMS AND RESULTS

### 5.1 AC Power line conducted emissions


#### 5.1.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range<br>(MHz) | Limits (dBμV) |          |
|--------------------------|---------------|----------|
|                          | Quasi-peak    | Average  |
| 0.15 to 0.50             | 66 to 56      | 56 to 46 |
| 0.50 to 5                | 56            | 46       |
| 5 to 30                  | 60            | 50       |

\* Decreasing linearly with the logarithm of the frequency

#### 5.1.2 Block Diagram of Test Setup




*Note: the distance between LISN and Vertical reference plane is 40 cm and the distance between LISN and EUT is 80 cm.*

#### 5.1.3 Test Results

|               |           |                |     |
|---------------|-----------|----------------|-----|
| Temperature   | 24.5°C    | Humidity       | 56% |
| Test Engineer | Allen Lai | Configurations | TX  |

**PASS.**

The test data please refer to following page.


**Neutral Line**

| Frequency<br>MHz | Level<br>dBµV | Transd<br>dB | Limit<br>dBµV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.231000         | 26.90         | 10.5         | 62            | 35.5         | QP       | N    | GND |
| 0.415500         | 24.20         | 10.0         | 58            | 33.3         | QP       | N    | GND |
| 0.870000         | 22.50         | 9.8          | 56            | 33.5         | QP       | N    | GND |
| 1.779000         | 21.10         | 9.7          | 56            | 34.9         | QP       | N    | GND |
| 3.448500         | 12.10         | 9.7          | 56            | 43.9         | QP       | N    | GND |
| 13.560000        | 54.50         | 9.9          | 60            | 5.5          | QP       | N    | GND |
| 24.045000        | 25.10         | 10.1         | 60            | 34.9         | QP       | N    | GND |

| Frequency<br>MHz | Level<br>dBµV | Transd<br>dB | Limit<br>dBµV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.217500         | 21.50         | 10.6         | 53            | 31.4         | AV       | N    | GND |
| 0.420000         | 18.50         | 10.0         | 47            | 28.9         | AV       | N    | GND |
| 0.829500         | 17.40         | 9.8          | 46            | 28.6         | AV       | N    | GND |
| 1.761000         | 16.00         | 9.7          | 46            | 30.0         | AV       | N    | GND |
| 3.340500         | 7.90          | 9.7          | 46            | 38.1         | AV       | N    | GND |
| 13.560000        | 53.90         | 9.9          | 50            | -3.9         | AV       | N    | GND |
| 27.123000        | 24.30         | 10.1         | 50            | 25.7         | AV       | N    | GND |

**Note:**

1.  $\text{Margin(dB)} = \text{Limit(dB}\mu\text{V)} - \text{Level(dB}\mu\text{V)}$
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.

**Live Line**

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.159000         | 28.40         | 10.0         | 66            | 37.1         | QP       | L1   | GND |
| 0.523500         | 21.40         | 9.9          | 56            | 34.6         | QP       | L1   | GND |
| 1.284000         | 20.10         | 9.7          | 56            | 35.9         | QP       | L1   | GND |
| 1.860000         | 19.40         | 9.7          | 56            | 36.6         | QP       | L1   | GND |
| 3.808500         | 13.70         | 9.7          | 56            | 42.3         | QP       | L1   | GND |
| 13.560000        | 52.30         | 9.9          | 60            | 7.7          | QP       | L1   | GND |
| 20.436000        | 27.80         | 10.4         | 60            | 32.2         | QP       | L1   | GND |

| Frequency<br>MHz | Level<br>dBμV | Transd<br>dB | Limit<br>dBμV | Margin<br>dB | Detector | Line | PE  |
|------------------|---------------|--------------|---------------|--------------|----------|------|-----|
| 0.213000         | 18.70         | 10.6         | 53            | 34.4         | AV       | L1   | GND |
| 0.420000         | 18.70         | 10.0         | 47            | 28.7         | AV       | L1   | GND |
| 1.270500         | 15.00         | 9.7          | 46            | 31.0         | AV       | L1   | GND |
| 1.576500         | 14.50         | 9.7          | 46            | 31.5         | AV       | L1   | GND |
| 3.156000         | 7.00          | 9.7          | 46            | 39.0         | AV       | L1   | GND |
| 13.560000        | 51.90         | 9.9          | 50            | -1.9         | AV       | L1   | GND |
| 27.123000        | 23.40         | 10.1         | 50            | 26.6         | AV       | L1   | GND |

Note:

1.  $\text{Margin(dB)} = \text{Limit(dB}\mu\text{V)} - \text{Level(dB}\mu\text{V)}$
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.



## 5.2 Transmitter Field Strength of Emissions

### 5.2.1 Limit

§ 15.225 Operation within the band 13.110-14.010 MHz.

(a) The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

$$=20*\log_{10}(15848)+40*\log_{10}(30/3) = 124 \text{ dBuV/m}$$

(b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

$$=20*\log_{10}(334)+40*\log_{10}(30/3) = 90.5 \text{ dBuV/m}$$

(c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

$$=20*\log_{10}(106)+40*\log_{10}(30/3) = 80.5 \text{ dBuV/m}$$

(d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz                        | MHz                 | MHz             | GHz              |
|----------------------------|---------------------|-----------------|------------------|
| 0.090 - 0.110              | 16.42 - 16.423      | 399.9 - 410     | 4.5 - 5.15       |
| <sup>1</sup> 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614       | 5.35 - 5.46      |
| 2.1735 - 2.1905            | 16.80425 - 16.80475 | 960 - 1240      | 7.25 - 7.75      |
| 4.125 - 4.128              | 25.5 - 25.67        | 1300 - 1427     | 8.025 - 8.5      |
| 4.17725 - 4.17775          | 37.5 - 38.25        | 1435 - 1626.5   | 9.0 - 9.2        |
| 4.20725 - 4.20775          | 73 - 74.6           | 1645.5 - 1646.5 | 9.3 - 9.5        |
| 6.215 - 6.218              | 74.8 - 75.2         | 1660 - 1710     | 10.6 - 12.7      |
| 6.26775 - 6.26825          | 108 - 121.94        | 1718.8 - 1722.2 | 13.25 - 13.4     |
| 6.31175 - 6.31225          | 123 - 138           | 2200 - 2300     | 14.47 - 14.5     |
| 8.291 - 8.294              | 149.9 - 150.05      | 2310 - 2390     | 15.35 - 16.2     |
| 8.362 - 8.366              | 156.52475 -         | 2483.5 - 2500   | 17.7 - 21.4      |
| 8.37625 - 8.38675          | 156.52525           | 2655 - 2900     | 22.01 - 23.12    |
| 8.41425 - 8.41475          | 156.7 - 156.9       | 3260 - 3267     | 23.6 - 24.0      |
| 12.29 - 12.293             | 162.0125 - 167.17   | 3332 - 3339     | 31.2 - 31.8      |
| 12.51975 - 12.52025        | 167.72 - 173.2      | 3345.8 - 3358   | 36.43 - 36.5     |
| 12.57675 - 12.57725        | 240 - 285           | 3600 - 4400     | ( <sup>2</sup> ) |
| 13.36 - 13.41              | 322 - 335.4         |                 |                  |

1 Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

2 Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009–0.490     | 2400/F (kHz)                      | 300                           |
| 0.490–1.705     | 24000/F (kHz)                     | 30                            |
| 1.705–30.0      | 30                                | 30                            |
| 30–88           | 100**                             | 3                             |
| 88–216          | 150**                             | 3                             |
| 216–960         | 200**                             | 3                             |
| Above 960       | 500                               | 3                             |

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54 72 MHz, 76 88 MHz, 174 216 MHz or 470 806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

#### 5.2.2 Measuring Instruments and Setting

Please refer to section 6 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter                        | Setting                                        |
|-------------------------------------------|------------------------------------------------|
| Attenuation                               | Auto                                           |
| Start Frequency                           | 1000 MHz                                       |
| Stop Frequency                            | 10th carrier harmonic                          |
| RB / VB (Emission in restricted band)     | 1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average |

| Spectrum Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |



### 5.2.3 Test Procedures

#### 1) Sequence of testing 9 kHz to 30 MHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

##### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

##### Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.



## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.




## 5.2.4 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


## 5.2.5 Results of Radiated Emissions (9 kHz ~30MHz)

|               |           |                |     |
|---------------|-----------|----------------|-----|
| Temperature   | 24.5°C    | Humidity       | 56% |
| Test Engineer | Allen Lai | Configurations | TX  |

For 9KHz-30MHz



# Coplanar



◆ QP Detector

## Suspected Data List

| NO. | Freq. [MHz] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] |
|-----|-------------|---------------|----------------|----------------|-------------|-------------|-----------|
| 1   | 0.0198      | 20.00         | 44.37          | 121.62         | 77.25       | 100         | 305       |
| 2   | 0.0353      | 20.15         | 47.64          | 116.54         | 68.90       | 100         | 354       |
| 3   | 0.0621      | 20.48         | 36.06          | 111.59         | 75.53       | 100         | 186       |
| 4   | 0.1649      | 19.92         | 40.79          | 103.03         | 62.24       | 100         | 173       |
| 5   | 0.4186      | 20.21         | 38.03          | 94.88          | 56.85       | 100         | 345       |
| 6   | 13.5601     | 19.70         | 57.50          | 124.0          | 66.50       | 100         | 68        |

\*\*\*Note:

- 1 · Level [dBμA/m] = Reading [dBμV] + Factor [dB/m]
- 2 · Margin [dB] = Limit [dBμV/m] - Level [dBμV/m]




### 5.2.6 Results of Radiated Emissions (30MHz~1GHz)

|               |           |                |     |
|---------------|-----------|----------------|-----|
| Temperature   | 24.5°C    | Humidity       | 56% |
| Test Engineer | Allen Lai | Configurations | TX  |

#### Below 1GHz

##### Vertical




##### Suspected Data List

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-------------|-----------|----------|
| 1   | 143.8       | 53.65          | -19.35        | 34.30          | 43.50          | 9.20        | 100         | 359       | Vertical |
| 2   | 175.8       | 56.11          | -17.71        | 38.40          | 43.50          | 5.10        | 100         | 318       | Vertical |
| 3   | 192.1       | 50.06          | -16.24        | 33.82          | 43.50          | 9.68        | 100         | 143       | Vertical |
| 4   | 207.8       | 50.42          | -15.20        | 35.22          | 43.50          | 8.28        | 100         | 60        | Vertical |
| 5   | 271.2       | 45.78          | -13.41        | 32.37          | 46.50          | 14.13       | 100         | 6         | Vertical |
| 6   | 783.5       | 42.37          | -3.13         | 39.24          | 46.50          | 7.26        | 100         | 357       | Vertical |

\*\*\*Note:

1. Level [dBμV/m] = Reading [dBμV] + Factor [dB/m]
2. Margin [dB] = Limit [dBμV/m] - Level [dBμV/m]

**Horizontal**

◆ QP Detector

**Suspected Data List**

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity   |
|-----|-------------|----------------|---------------|----------------|----------------|-------------|-------------|-----------|------------|
| 1   | 176.1       | 52.05          | -17.69        | 34.36          | 43.50          | 9.14        | 100         | 0         | Horizontal |
| 2   | 207.8       | 51.67          | -15.20        | 36.47          | 43.50          | 7.03        | 100         | 264       | Horizontal |
| 3   | 244.1       | 49.91          | -14.05        | 35.86          | 46.50          | 10.64       | 100         | 80        | Horizontal |
| 4   | 271.1       | 55.55          | -13.41        | 42.14          | 46.50          | 4.36        | 100         | 67        | Horizontal |
| 5   | 869.0       | 42.47          | -1.61         | 40.86          | 46.50          | 5.64        | 100         | 344       | Horizontal |

**Final Data List**

| NO. | Freq. [MHz] | Reading [dBμV] | Factor [dB/m] | QP Value [dBμV/m] | QP Limit [dBμV/m] | QP Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|-------------|----------------|---------------|-------------------|-------------------|----------------|-------------|-----------|----------|
| 1   | 759.14      | 40.05          | -3.55         | 36.50             | 46.50             | 10.00          | 120         | 310       | Horizont |

\*\*\*Note:


1. Level [dBμV/m] = Reading [dBμV] + Factor [dB/m]

2. Margin [dB] = Limit [dBμV/m] - Level [dBμV/m]



## 5.2.7 In-Band Emission (13.110-14.010 MHz)

|               |           |                |     |
|---------------|-----------|----------------|-----|
| Temperature   | 24.5°C    | Humidity       | 56% |
| Test Engineer | Allen Lai | Configurations | TX  |



| Suspected Data List |             |               |                |                |             |             |           |
|---------------------|-------------|---------------|----------------|----------------|-------------|-------------|-----------|
| NO.                 | Freq. [MHz] | Factor [dB/m] | Level [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] |
| 1                   | 13.3476     | 19.70         | 43.03          | 80.50          | 37.47       | 100         | 21        |
| 2                   | 13.4216     | 19.70         | 41.36          | 90.50          | 49.14       | 100         | 6         |
| 3                   | 13.4304     | 19.70         | 40.80          | 90.50          | 49.70       | 100         | 4         |
| 4                   | 13.5611     | 19.70         | 62.28          | 124.00         | 61.72       | 100         | 0         |
| 5                   | 13.585      | 19.70         | 37.72          | 90.50          | 52.78       | 100         | 353       |
| 6                   | 13.6504     | 19.70         | 38.67          | 90.50          | 51.83       | 100         | 45        |

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.



### 5.3 20dB Bandwidth Emissions

§FCC 15.215 (c)

#### 5.3.1 Limit


(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. In the case of intentional radiators operating under the provisions of subpart E, the emission bandwidth may span across multiple contiguous frequency bands identified in that subpart. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

#### 5.3.2 Test Procedure

With the EUT's antenna attached, the EUT's 20dB Bandwidth power was received by the test antenna which was connected to the spectrum analyzer with the START and STOP frequencies set to the EUT's operation band.

#### 5.3.3 Test Data

|               |           |                |     |
|---------------|-----------|----------------|-----|
| Temperature   | 24.5°C    | Humidity       | 56% |
| Test Engineer | Allen Lai | Configurations | TX  |





## 5.4 Frequency Tolerance

§FCC 15.225 (e)

### 5.4.1 Limit

(e) The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+ 50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 5.4.2 Test Procedure

a) Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies shown in 5.6.

b) Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.

NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

c) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

d) Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.

e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.

f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.

g) Measure the frequency at each of frequencies specified in 5.6.

h) Switch OFF the EUT but do not switch OFF the oscillator heater.

i) Lower the chamber temperature by not more than  $10\text{ }^{\circ}\text{C}$ , and allow the temperature inside the chamber to stabilize.



j) Repeat step f) through step i) down to the lowest specified temperature.

#### 5.4.3 Test Result

| $F_0 = 13.56\text{MHz}$  |                                    |                         |                    |              |
|--------------------------|------------------------------------|-------------------------|--------------------|--------------|
| Power Supply( $V_{AC}$ ) | Temperature ( $^{\circ}\text{C}$ ) | Measured Frequency(MHz) | FrequencyError (%) | Limit        |
| 120                      | -20                                | 13.5596283              | -0.00274           | $\pm 0.01\%$ |
|                          | -10                                | 13.5595605              | -0.00324           | $\pm 0.01\%$ |
|                          | 0                                  | 13.5599495              | -0.00037           | $\pm 0.01\%$ |
|                          | 10                                 | 13.5592635              | -0.00543           | $\pm 0.01\%$ |
|                          | 20                                 | 13.5595474              | -0.00334           | $\pm 0.01\%$ |
|                          | 30                                 | 13.5599785              | -0.00016           | $\pm 0.01\%$ |
|                          | 40                                 | 13.5596285              | -0.00274           | $\pm 0.01\%$ |
|                          | 50                                 | 13.5595703              | -0.00317           | $\pm 0.01\%$ |
| 102                      | 20                                 | 13.5596569              | -0.00253           | $\pm 0.01\%$ |
| 138                      | 20                                 | 13.5593095              | -0.00509           | $\pm 0.01\%$ |



## 5.5 Antenna Requirement

### 5.5.1 Standard Applicable

#### §FCC 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This EUT uses an Loop antenna, and maximum antenna gain is 0dBi

### 5.5.2 Result

Compliant.



## 6 LIST OF MEASURING EQUIPMENTS

| Item | Test Equipment       | Manufacturer    | Model No.   | Serial No. | Calibration Date | Calibration Due Date |
|------|----------------------|-----------------|-------------|------------|------------------|----------------------|
| 1    | Wideband Antenna     | schwarzbeck     | VULB 9163   | 958        | 2022/11/13       | 2025/11/12           |
| 2    | EMI Test Receiver    | R&S             | ESCI        | 100849/003 | 2024/1/4         | 2025/1/3             |
| 3    | Controller           | MF              | MF7802      | N/A        | N/A              | N/A                  |
| 4    | RF Cable(below 1GHz) | HUBER+SUHNER    | RG214       | N/A        | 2024/1/4         | 2025/1/3             |
| 5    | RF Cable(above 1GHz) | HUBER+SUHNER    | RG214       | N/A        | 2024/1/4         | 2025/1/3             |
| 6    | RE test software     | Tonscend        | JS32-RE     | V5.0.0.0   | N/A              | N/A                  |
| 7    | Loop Antenna         | schwarzbeck     | FMZB 1519 B | 00023      | 2022/11/13       | 2025/11/12           |
| 8    | Artificial Mains     | ROHDE & SCHWARZ | ENV 216     | 101333-IP  | 2024/1/4         | 2025/1/3             |
| 9    | EMI Test Software    | ROHDE & SCHWARZ | ESK1        | V1.71      | N/A              | N/A                  |
| 10   | MXA Signal Analyzer  | Keysight        | N9020A      | MY52091623 | 2024/1/4         | 2025/1/3             |



## **7 TEST SETUP PHOTOGRAPHS OF EUT**

Please refer to separated files for Test Setup Photos of the EUT.

## **8 EXTERIOR PHOTOGRAPHS OF THE EUT**

Please refer to separated files for External Photos of the EUT.

## **9 INTERIOR PHOTOGRAPHS OF THE EUT**

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----