

Dates of Tests: August 06, 2024
Test Report S/N: LR500112408F
Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

2BH6ENCRB40N01VI

APPLICANT

Nucode Co., Ltd.

Equipment Class	:	Digital Transmission System (DTS)
Manufacturing Description	:	Bluetooth Module
Manufacturer	:	Nucode Co., Ltd.
Model name	:	NCRB40N01VI
Variant Model name	:	NCRB40N01VC
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C ; ANSI C63.10 - 2013
Frequency Range	:	2402 ~ 2480 MHz
Max. Output Power	:	Max -0.39 dBm - Conducted
Data of issue	:	August 07, 2024

This test report is issued under the authority of:



Ja-Beom Koo, Manager

The test was supervised by:



Eun-Hwan Jung, Test Engineer

TABLE OF CONTENTS

1. GENERAL INFORMATION ----- 3

2. INFORMATION ABOUT TEST ITEM ----- 4

3. TEST REPORT ----- 5

 3.1 SUMMARY OF TESTS ----- 5

 3.2 RF EXPOSURE EVULATION----- 6

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
Web site : <http://www.ltalab.com>
E-mail : chahn@ltalab.com
Telephone : +82-31-323-6008
Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2025-03-29	FCC CAB
VCCI	JAPAN	C-4948,	2026-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2026-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2026-10-15	VCCI registration
VCCI	JAPAN	G-847	2024-12-13	VCCI registration
IC	CANADA	5799A-1	2024-08-15	IC filing

2. Information about test item

2-1 Client & Manufacturer

Client Company name : Nucode Co., Ltd.
Address : 704ho, Gasan-Digital-1ro, Geumcheon-Gu, Seoul, South Korea
Tel / Fax : +82-10-5061-5233 / -
Manufacturer : Nucode Co., Ltd.
Address : 704ho, Gasan-Digital-1ro, Geumcheon-Gu, Seoul, South Korea
Tel / Fax : +82-10-5061-5233 / -

2-2 Equipment Under Test (EUT)

Model name : NCRB40N01VI
Serial number : Identical prototype
Date of receipt : July 11 ,2024
EUT condition : Pre-production, not damaged
Antenna type : Dipole Antenna (Gain : 3.9 dBi)
Variant Antenna : Dipole Antenna (Gain : 2.5 dBi)
Chip Antenna(Gain : 1.8 dBi)
Frequency Range : 2402 ~ 2480 MHz
RF output power : Max -0.39 dBm – Conducted
Type of Modulation : GFSK, O-QPSK
Power Source : DC 3 V

2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz)	2402	2440	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	-	MS-1736	MSI

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
§ 1.1310 and §2.1091	RF EXPOSURE EVULATION	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

-

3.2 RF EXPOSURE EVULATION

1.1 Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength	Magnetic field Strength	Power density (mW/cm ²)	Averaging time
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz
* = Plane-wave equivalent power density

1.2 MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Power density at the specific separation:

$S = PG/(4R^2\pi)$ $S = (0.91 * 2.45) / (4 * 20^2 * \pi)$ $S = 0.0004 \text{ mW/cm}^2$	Where, S = Maximum power density (mW/cm ²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20 cm = limit for MPE)
--	--

1.3 MAXIMUM PERMISSIBLE EXPOSURE Prediction

- Calculated under the worst-case conditions of each mode.

(Measured power 3.5 dBm $\pm$ 0.5dB)

2.4GHz Mode

Max Peak output Power at antenna input terminal	-0.39	dBm
Max Peak output Power at antenna input terminal	0.91	mW
Prediction distance	20	cm
Prediction frequency	2480	MHz
Antenna Gain(typical)	3.90	dBi
Antenna Gain(numeric)	2.45	-

SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance $\leq$ 50 mm = **Used**

$[(\text{max.power of channel, including tune-up torelance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f}(\text{GHz})]$

$= [0.91 / 5] * [\sqrt{2.480}] = 0.29 \leq 3.0$, for 1g SAR

Thus, SAR for this device is not required.