FCC §15.247 (i), §2.1091 - RF Exposure

FCC ID: 2BH6J-HY400

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm²) | Averaging Time E ² , H ² or S (minutes) | |
|--------------------------|---|---|--------------------------------|--|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 | |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 | |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 | |
| 300-1500 | | | F/300 | 6 | |
| 1500-100,000 | | | 5 | 6 | |

Note: *f* is frequency in MHz

Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm²) | Averaging Time E ² , H ² or S (minutes) | |
|--------------------------|---|---|--------------------------------|--|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 | |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 | |
| 300-1500 | | | F/1500 | 30 | |
| 1500-100,000 | | | 1.0 | 30 | |

Note: f = frequency in MHz

^{* =} Power density limit is applicable at frequencies greater than 100 MHz

^{* =} Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna
G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=20cm

Test Result of RF Exposure Evaluation

| | Modes& Channel Freq. (MHz) | Tune up Produce power | Maximu m peak output power (dBm) | Output power to antenna (mW) | Antenna Gain (numeric) | Power Density (S) (mW/ cm2) | Limit (mW / cm2 | Result |
|--------------|-------------------------------------|-----------------------------|--|--|------------------------------|---|--------------------------|--------|
| 2.4G WIFI | 802.11g&2 412 | 12±1 | 13 | 19.9526 | 1.556 (1.92dBi) | 0.0062 | 1 | Pass |
| EDR | 8DPSK&L CH | 3±1 | 4 | 2.5119 | 1.6218 (2.1dBi) | 0.0008 | 1 | Pass |
| 5.2GWIFI | 802.11n(H T20)& 5240 | 15±1 | 16 | 39.8107 | 1.803 (2.56dBi) | 0.0143 | 1 | Pass |
| 5.8GWIFI | 802.11ac8 0&5775 | 14±1 | 15 | 31.6228 | 2.2029 (3.43dBi) | 0.0139 | 1 | Pass |