

# FCC RF EXPOSURE REPORT

## FCC ID: 2BH7FC220V2

**Report No.** : BTL-FCCP-2-2504G023  
**Equipment** : Pan/Tilt AI Home Security Wi-Fi Camera  
**Model Name** : Tapo C220, TC72, TCB72  
**Brand Name** : tp-link, tapo  
**Applicant** : TP-Link Systems Inc.  
**Address** : 10 Mauchly, Irvine, CA 92618  
**Manufacturer** : TP-Link Systems Inc.  
**Address** : 10 Mauchly, Irvine, CA 92618  
  
**Radio Function** : WLAN 2.4GHz  
  
**FCC Rule Part(s)** : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091  
FCC Title 47 Part 2.1091 & KDB 447498 D01 v06  
  
**Date of Receipt** : 2025/2/20  
**Date of Test** : 2025/3/8~2025/3/13  
**Issued Date** : 2025/6/6

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

**Prepared by** : Poken Huang  
Poken Huang, Engineer



**Approved by** : Peter Chen  
Peter Chen, Manager

**BTL Inc.**

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: [www.newbtl.com](http://www.newbtl.com) Service mail: [btl\\_qa@newbtl.com](mailto:btl_qa@newbtl.com)

**REVISION HISTORY**

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-2-2504G023	R00	Original Report.	2025/6/6	Valid

## 1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

## 2. ANTENNA SPECIFICATION

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	TP-Link Systems Inc.	Tapo C222+ANT	IFA	N/A	0

Note:

- (1) The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

## 3. CALCULATED RESULT

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
0	1.0000	22.37	108.8930	0.02167	1	Complies

Note:

- (1) The calculated distance is 20 cm.  
(2) Ratio=Power Density (S) (mW/cm<sup>2</sup>)/Limit of Power Density (S) (mW/cm<sup>2</sup>)

**End of Test Report**