

FCC RF EXPOSURE REPORT

FCC ID: 2BH7FC325WBV2

Report No. : BTL-FCCP-3-2410G026
Equipment : Outdoor Security Wi-Fi Camera
Model Name : Tapo C325WB
Brand Name : tapo, tp-link
Applicant : TP-Link Systems Inc.
Address : 10 Mauchly, Irvine, CA 92618
Manufacturer : TP-Link Systems Inc.
Address : 10 Mauchly, Irvine, CA 92618

Radio Function : Bluetooth Low Energy & WLAN 2.4GHz

FCC Rule Part(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091 & KDB 447498 D01 v06

Date of Receipt : 2025/1/22
Date of Test : 2025/2/25~2025/3/21
Issued Date : 2025/5/6

The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.

Prepared by

Ray Chen
Ray Chen, Engineer



Approved by

Peter Chen
Peter Chen, Manager

BTL Inc.

No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan

Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

REVISION HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-3-2410G026	R00	Original Report.	2025/5/6	Valid

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

2. ANTENNA SPECIFICATION

For LE:

Ant.	Manufacturer	P/N	Antenna Type	Connector	Gain (dBi)
1	TP-Link Systems Inc.	3101503989	Dipole	N/A	0.5

Note: The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

For 2.4G

Ant.	Brand	P/N	Antenna Type	Connector	Gain (dBi)
1	TP-Link Systems Inc.	3101503989	Dipole	N/A	0.5
2	TP-Link Systems Inc.	3101503989	Dipole	N/A	0.5

Note:

- (1) The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
- (2) Smart antenna system with two transmit/receive chains, but operating in a mode where only one transmit/receive chain is used.

3. CALCULATED RESULT

For BT LE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0.5	1.1220	7.33	5.4075	0.00121	1	Complies

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0.5	1.1220	20.02	100.4616	0.02244	1	Complies

Note:

- (1) The calculated distance is 20 cm.
- (2) Ratio=Power Density (S) (mW/cm²)/Limit of Power Density (S) (mW/cm²)
- (3) BT LE and WLAN 2.4GHz can not simultaneous transmission

End of Test Report