

MEASUREMENT REPORT

FCC ID : 2BH7FEAP787
Applicant : TP-Link Systems Inc.
Application Type : Certification
Product : BE15000 Ceiling Mount Tri-Band Wi-Fi 7 Access Point
Model No. : EAP787
Brand Name : tp-link
FCC Classification : Digital Transmission System (DTS)
FCC Rule Part(s) : Part15 Subpart C (Section 15.247)
Received Date : April 22, 2025
Test Date : April 29, 2025~ May 22, 2025

Test By : *Owen Tsai*
(Owen Tsai)
Reviewed By : *Paddy Chen*
(Paddy Chen)
Approved By : *Chenz Ker*
(Chenz Ker)



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2504TW0121-U2	1.0	Original Report	2025-07-25	

CONTENTS

Description	Page
1. INTRODUCTION	6
1.1. Scope	6
1.2. MRT Test Location	6
2. PRODUCT INFORMATION	7
2.1. Feature of Equipment under Test	7
2.2. Product Specification Subjective to this Report	7
2.3. Working Frequencies for this report	8
2.4. Description of Available Antennas	9
2.5. Test Mode	10
2.6. Configuration of Test System	11
2.7. Test System Details	12
2.8. Description of Test Software	12
2.9. Applied Standards	12
2.10. Duty Cycle	13
2.11. Test Configuration	14
2.12. EMI Suppression Device(s)/Modifications	14
2.13. Labeling Requirements	14
3. DESCRIPTION of TEST	15
3.1. Evaluation Procedure	15
3.2. AC Line Conducted Emissions	15
3.3. Radiated Emissions	16
4. ANTENNA REQUIREMENTS	17
5. TEST EQUIPMENT CALIBRATION DATE	18
6. MEASUREMENT UNCERTAINTY	20
7. TEST RESULT	21
7.1. Summary	21
7.2. 6dB Bandwidth Measurement	22
7.2.1. Test Limit	22
7.2.2. Test Procedure used	22
7.2.3. Test Setting	22
7.2.4. Test Setup	22
7.2.5. Test Result	23
7.3. Output Power Measurement	28

7.3.1. Test Limit	28
7.3.2. Test Procedure Used	28
7.3.3. Test Setting	28
7.3.4. Test Setup	28
7.3.5. Test Result	29
7.4. Power Spectral Density Measurement	31
7.4.1. Test Limit	31
7.4.2. Test Procedure Used	31
7.4.3. Test Setting	31
7.4.4. Test Setup	32
7.4.5. Test Result	33
7.5. Conducted Band Edge and Out-of-Band Emissions	42
7.5.1. Test Limit	42
7.5.2. Test Procedure Used	42
7.5.3. Test Setting	42
7.5.4. Test Setup	43
7.5.5. Test Result	44
7.6. Radiated Spurious Emission Measurement	236
7.6.1. Test Limit	236
7.6.2. Test Procedure Used	236
7.6.3. Test Setting	236
7.6.4. Test Setup	238
7.6.5. Test Result	239
7.7. Radiated Restricted Band Edge Measurement	291
7.7.1. Test Limit	291
7.7.2. Test Procedure Used	292
7.7.3. Test Setting	292
7.7.4. Test Setup	293
7.7.5. Test Result	294
7.8. AC Conducted Emissions Measurement	458
7.8.1. Test Limit	458
7.8.2. Test Setup	458
7.8.3. Test Result	459
8. CONCLUSION	461
Appendix A : Test Setup Photograph	462
Appendix B : External Photograph	462
Appendix C : Internal Photograph	462

General Information

Applicant	TP-Link Systems Inc.
Applicant Address	10 Mauchly, Irvine, CA 92618
Manufacturer	TP-Link Systems Inc.
Manufacturer Address	10 Mauchly, Irvine, CA 92618
Test Site	MRT Technology (Taiwan) Co., Ltd
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT FCC Registration No.	291082
FCC Rule Part(s)	Part 15.247

Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Canada, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada and Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Feature of Equipment under Test

Product Name:	BE15000 Ceiling Mount Tri-Band Wi-Fi 7 Access Point
Model No.:	EAP787
Brand Name:	tp-link
Specification:	WLAN: 802.11a/b/g/n/ac/ax/be WPAN: Bluetooth mode
Power Supply	Power: 12Vdc, 2.5A PoE: 802.3bt PoE
EUT Identification No.:	#1-1 (Conducted) #1-2 (Radiated)

2.2. Product Specification Subjective to this Report

Frequency Range:	802.11b/g/n-HT20/ax-HE20/be-EHT20: 2412 ~ 2462MHz 802.11n-HT40/ax-HE40/be-EHT40: 2422 ~ 2452MHz
Channel Number:	802.11b/g/n-HT20/ax-HE20/be-EHT20: 11 802.11n-HT40/ax-HE40/be-EHT40: 7
Type of Modulation:	802.11b: DSSS 802.11g/n: OFDM 802.11ax/be: OFDMA
Data Rate:	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 300Mbps 802.11ax: up to 574Mbps 802.11be: up to 688Mbps

Note: For other features of this EUT, test report will be issued separately.

2.3. Working Frequencies for this report

802.11b/g/n-HT20/ax-HE20/be-EHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40/ax-HE40/be-EHT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

2.4. Description of Available Antennas

Antenna Type	Frequency Band (MHz)	Tx Paths	Number of spatial streams	Max Antenna Gain (dBi)	Beamforming Directional Gain(dBi)	CDD Directional Gain (dBi)	
						For Power	For PSD
BLE & Wi-Fi Antenna							
PIFA	2402 ~ 2480	1	1	3.00	--	--	--
	2412 ~ 2462	2	1	2.00	5.01	2.00	5.01
	5150 ~ 5850	4	1	2.00	8.02	2.00	8.02

Remark:

1. The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.

If all antennas have the same gain, G_{ANT} , Directional gain = $G_{ANT} + \text{Array Gain}$, where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log (N_{ANT}/ N_{SS})$ dB;

- For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB for $N_{ANT} \leq 4$;

2. The EUT also supports Beam Forming mode, and the Beam Forming support 802.11ac/ax/be, not include 802.11a/b/g/n. BF Directional gain = $G_{ANT} + 10 \log (N_{ANT})$.

3. All messages of antenna were declared by manufacturer.


Test Mode	Tx Paths	CDD Mode	Beamforming Mode
802.11b/g/n (DTS)	2	√	X
802.11ax/be (DTS)	2	√	√
802.11a/n (NII)	4	√	X
802.11ac/ax/be (NII)	4	√	√

2.5. Test Mode

CDD Mode
Mode 1: Transmit by 802.11b_N _{ss} =1 (1Mbps)
Mode 2: Transmit by 802.11g_N _{ss} =1 (6Mbps)
Mode 3: Transmit by 802.11n-HT20_N _{ss} =1 (MCS0)
Mode 4: Transmit by 802.11n-HT40_N _{ss} =1 (MCS0)
Mode 5: Transmit by 802.11ax-HE20_N _{ss} =1 (MCS0)
Mode 6: Transmit by 802.11ax-HE40_N _{ss} =1 (MCS0)
Mode 7: Transmit by 802.11be-EHT20_N _{ss} =1 (MCS0)
Mode 8: Transmit by 802.11be-EHT40_N _{ss} =1 (MCS0)
Remark:
<ol style="list-style-type: none">1. For Radiated emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.2. This device supports 2 N_{ss} and power level of 2 N_{ss} is less than or equal to the power of 1 N_{ss}. The worst case is N_{ss}=1.3. For beamforming operation, the manufacturer automatically reduces power based on a factor calculated as the difference between the beamforming directional gain and the CDD directional power gain. Thus, only the CDD mode was evaluated in this report.4. EUT supports one configuration only in 802.11ax/be full RU mode.5. As Designated by manufacturer, the lowest data rate was the worst condition, so all the tests were done with lowest data rate.

2.6. Configuration of Test System

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram	
	
Signal Cable Type	Signal Cable Description
A	LAN Cable

2.7. Test System Details

The types for all equipments, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook PC	Lenovo	MP25ZAKY	N/A	Non-shielded, 0.8m

Note: EUT is powered by Adapter (Brand: tp-link, M/N: T120250-2B4)

2.8. Description of Test Software

The test utility software used during testing was “QSPR”, the version is ver5.0-00202.

Note: Final power setting please refer to operational description.

2.9. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:


- FCC Part 15.247
- KDB 662911 D01v02r01
- ANSI C63.10-2013

2.10. Duty Cycle

2.4GHz WLAN (DTS) operation is possible in 20MHz and 40MHz channel bandwidths. The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Test Mode	Duty Cycle
802.11b	99.70%
802.11g	99.25%
802.11n-HT20	97.84%
802.11n-HT40	96.96%
802.11ax-HE20	98.91%
802.11ax-HE40	97.32%
802.11be-EHT20	94.55%
802.11be-EHT40	96.80%





2.11. Test Configuration

The device was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.12. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.13. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance was used in the measurement.

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst-case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2026/3/5
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2026/4/14
EMI Test Receiver	R&S	ESR3	MRTTWA00045	1 year	2026/5/13

Radiated Emissions

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	MRTTWA00002	1 year	2026/4/16
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00086	1 year	2025/11/5
Broadband Hornantenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2026/2/11
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2026/2/11
Breitband Hornantenna	SCHWARZBECK	BBHA 9170	MRTTWA00004	1 year	2026/3/27
Broadband Amplifier	SCHWARZBECK	BBV 9721	MRTTWA00006	1 year	2026/3/20
Broadband Hornantenna	RFSPIN	DRH18-E	MRTTWA00087	1 year	2026/5/14
Broadband Preamplifier	EMC Instruments corporation	EMC118A45S E	MRTTWA00088	1 year	2026/5/12
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2026/3/4
Signal Analyzer	R&S	FSV40	MRTTWA00007	1 year	2026/5/20
Antenna Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2025/6/14
Cable	Rosnol	K1K50-UP02 64-K1K50-4M	MRTTWE00012	1 year	2025/6/14
Temperature/Humidity Meter	TFA	35.1083	MRTTWA00050	1 year	2025/6/2

Conducted Test Equipment

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00014	1 year	2026/4/15
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2025/9/24
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2025/8/12
Attenuator	WTI	218FS-20	MRTTWE00026	1 year	2025/10/31
Attenuator	WTI	218FS-10	MRTTWE00027	1 year	2025/6/13
Attenuator	WTI	218FS-06	MRTTWE00028	1 year	2025/6/13
Temperature & Humidity Chamber	TEN BILLION	TTH-B3UP	MRTTWA00036	1 year	2025/6/6
DIVA PLUS Funk-Wetterstation	TFA	35.1083	MRTTWA00050	1 year	2025/6/2

Software	Version	Function
e3	9.160520a	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 150kHz~30MHz: $\pm 2.53\text{dB}$
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 9kHz ~ 1GHz: $\pm 4.25\text{dB}$ 1GHz ~ 40GHz: $\pm 4.45\text{dB}$
Conducted Power (Carrier Power / Power Density)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 0.84\text{dB}$
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 2.65\text{ dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 3.3\%$
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): $\pm 0.82^\circ\text{C}$ / $\pm 3\%$

7. TEST RESULT

7.1. Summary

FCC Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	$\geq 500\text{kHz}$	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	$\leq 30\text{dBm}$		Pass	Section 7.3
15.247(e)	Power Spectral Density	$\leq 8\text{dBm/3kHz}$		Pass	Section 7.4
15.247(d)	Band Edge / Out-of-Band Emissions	$\geq 30\text{dBc (Average)}$		Pass	Section 7.5
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	Section 7.6 & 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.8

Notes:

- 1) Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


7.2.2. Test Procedure used

ANSI C63.10 - 2013 Section 11.8

7.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace was allowed to stabilize


7.2.4. Test Setup





7.2.5. Test Result


Product	BE15000 Ceiling Mount Tri-Band Wi-Fi 7 Access Point	Temperature	25°C
Test Engineer	Fran	Relative Humidity	54%
Test Site	SR6	Test Date	2025/5/6

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Ant 0						
802.11b	1Mbps	01	2412	8.026	≥ 0.5	Pass
802.11b	1Mbps	06	2437	7.748	≥ 0.5	Pass
802.11b	1Mbps	11	2462	8.016	≥ 0.5	Pass
802.11g	6Mbps	01	2412	16.39	≥ 0.5	Pass
802.11g	6Mbps	06	2437	16.39	≥ 0.5	Pass
802.11g	6Mbps	11	2462	16.39	≥ 0.5	Pass
802.11n-HT20	MCS0	01	2412	17.63	≥ 0.5	Pass
802.11n-HT20	MCS0	06	2437	17.63	≥ 0.5	Pass
802.11n-HT20	MCS0	11	2462	17.63	≥ 0.5	Pass
802.11n-HT40	MCS0	03	2422	36.44	≥ 0.5	Pass
802.11n-HT40	MCS0	06	2437	36.44	≥ 0.5	Pass
802.11n-HT40	MCS0	09	2452	36.43	≥ 0.5	Pass
802.11ax-HE20	MCS0	01	2412	19.03	≥ 0.5	Pass
802.11ax-HE20	MCS0	06	2437	18.98	≥ 0.5	Pass
802.11ax-HE20	MCS0	11	2462	19.02	≥ 0.5	Pass
802.11ax-HE40	MCS0	03	2422	38.17	≥ 0.5	Pass
802.11ax-HE40	MCS0	06	2437	38.26	≥ 0.5	Pass
802.11ax-HE40	MCS0	09	2452	38.07	≥ 0.5	Pass
802.11be-EHT20	MCS0	01	2412	19.02	≥ 0.5	Pass
802.11be-EHT20	MCS0	06	2437	19.08	≥ 0.5	Pass
802.11be-EHT20	MCS0	11	2462	19.04	≥ 0.5	Pass
802.11be-EHT40	MCS0	03	2422	38.22	≥ 0.5	Pass
802.11be-EHT40	MCS0	06	2437	38.08	≥ 0.5	Pass
802.11be-EHT40	MCS0	09	2452	38.09	≥ 0.5	Pass









7.3. Output Power Measurement

7.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.3.2. Test Procedure Used


ANSI C63.10 - 2013 Section 11.9.2.3.2

7.3.3. Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

7.3.4. Test Setup



7.3.5. Test Result

Product	BE15000 Ceiling Mount Tri-Band Wi-Fi 7 Access Point	Temperature	25°C
Test Engineer	Fran	Relative Humidity	54%
Test Site	SR6	Test Date	2025/5/6

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 1 Average Power (dBm)	Total Average Power (dBm)	Limit (dBm)	Result
CDD Mode								
802.11b	1Mbps	01	2412	11.64	11.60	14.63	≤ 30.00	Pass
802.11b	1Mbps	02	2417	16.01	15.77	18.90	≤ 30.00	Pass
802.11b	1Mbps	06	2437	18.88	18.61	21.76	≤ 30.00	Pass
802.11b	1Mbps	07	2442	16.53	16.12	19.34	≤ 30.00	Pass
802.11b	1Mbps	08	2447	14.85	14.77	17.82	≤ 30.00	Pass
802.11b	1Mbps	09	2452	13.21	13.18	16.21	≤ 30.00	Pass
802.11b	1Mbps	10	2457	11.42	11.10	14.27	≤ 30.00	Pass
802.11b	1Mbps	11	2462	10.45	10.22	13.35	≤ 30.00	Pass
802.11g	6Mbps	01	2412	15.94	15.88	18.92	≤ 30.00	Pass
802.11g	6Mbps	02	2417	20.31	20.19	23.26	≤ 30.00	Pass
802.11g	6Mbps	06	2437	22.44	21.92	25.20	≤ 30.00	Pass
802.11g	6Mbps	10	2457	19.55	19.21	22.39	≤ 30.00	Pass
802.11g	6Mbps	11	2462	15.17	15.00	18.10	≤ 30.00	Pass
802.11n-HT20	MCS0	01	2412	15.51	15.47	18.50	≤ 30.00	Pass
802.11n-HT20	MCS0	02	2417	21.28	21.23	24.27	≤ 30.00	Pass
802.11n-HT20	MCS0	06	2437	22.44	22.06	25.26	≤ 30.00	Pass
802.11n-HT20	MCS0	10	2457	20.92	20.77	23.86	≤ 30.00	Pass
802.11n-HT20	MCS0	11	2462	15.76	15.54	18.66	≤ 30.00	Pass

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 1 Average Power (dBm)	Total Average Power (dBm)	Limit (dBm)	Result
CDD Mode								
802.11n-HT40	MCS0	03	2422	15.57	15.40	18.50	≤ 30.00	Pass
802.11n-HT40	MCS0	04	2427	17.65	17.21	20.45	≤ 30.00	Pass
802.11n-HT40	MCS0	06	2437	20.18	19.60	22.91	≤ 30.00	Pass
802.11n-HT40	MCS0	08	2447	18.12	17.82	20.98	≤ 30.00	Pass
802.11n-HT40	MCS0	09	2452	16.70	16.26	19.50	≤ 30.00	Pass
802.11ax-HE20	MCS0	01	2412	15.55	15.48	18.53	≤ 30.00	Pass
802.11ax-HE20	MCS0	02	2417	19.09	18.94	22.03	≤ 30.00	Pass
802.11ax-HE20	MCS0	06	2437	22.00	21.63	24.83	≤ 30.00	Pass
802.11ax-HE20	MCS0	09	2452	19.63	19.50	22.58	≤ 30.00	Pass
802.11ax-HE20	MCS0	10	2457	17.26	17.04	20.16	≤ 30.00	Pass
802.11ax-HE20	MCS0	11	2462	14.19	14.13	17.17	≤ 30.00	Pass
802.11ax-HE40	MCS0	03	2422	15.62	15.40	18.52	≤ 30.00	Pass
802.11ax-HE40	MCS0	06	2437	18.74	18.16	21.47	≤ 30.00	Pass
802.11ax-HE40	MCS0	09	2452	17.13	16.79	19.97	≤ 30.00	Pass
802.11be-EHT20	MCS0	01	2412	16.56	16.39	19.49	≤ 30.00	Pass
802.11be-EHT20	MCS0	02	2417	20.48	20.28	23.39	≤ 30.00	Pass
802.11be-EHT20	MCS0	06	2437	22.54	22.06	25.32	≤ 30.00	Pass
802.11be-EHT20	MCS0	09	2452	21.82	21.61	24.73	≤ 30.00	Pass
802.11be-EHT20	MCS0	10	2457	19.20	18.78	22.01	≤ 30.00	Pass
802.11be-EHT20	MCS0	11	2462	15.33	15.01	18.18	≤ 30.00	Pass
802.11be-EHT40	MCS0	03	2422	15.51	15.30	18.42	≤ 30.00	Pass
802.11be-EHT40	MCS0	06	2437	18.56	18.09	21.34	≤ 30.00	Pass
802.11be-EHT40	MCS0	09	2452	16.50	16.24	19.38	≤ 30.00	Pass

Note: Total Average Power (dBm) = $10 \times \log \{10^{(\text{Ant 0 Average Power /10})} + 10^{(\text{Ant 1 Average Power /10})}\}$.

7.4. Power Spectral Density Measurement

7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.


7.4.2. Test Procedure Used

ANSI C63.10 - 2013 Section 11.10.5

7.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10 kHz.
5. VBW = 30 kHz.
6. Detector = RMS.
7. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
8. Sweep time = auto couple.
9. Don't use sweep triggering. Allow sweep to "free run".
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add $10 \log (1/x)$, where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

7.4.4. Test Setup



7.4.5. Test Result

Product	BE15000 Ceiling Mount Tri-Band Wi-Fi 7 Access Point					Temperature		25°C	
Test Engineer	Fran					Relative Humidity		54%	
Test Site	SR6					Test Date		2025/5/6	

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0	Ant 1	Duty Cycle (%)	Total PSD (dBm/ 10kHz)	Limit (dBm/ 3kHz)	Result
				PSD (dBm/ 10kHz)					
802.11b	1Mbps	01	2412	-13.810	-14.090	99.70%	-10.924	≤ 8.00	Pass
802.11b	1Mbps	06	2437	-5.994	-7.362	99.70%	-3.601	≤ 8.00	Pass
802.11b	1Mbps	11	2462	-15.057	-15.084	99.70%	-12.047	≤ 8.00	Pass
802.11g	6Mbps	01	2412	-12.625	-12.539	99.25%	-9.539	≤ 8.00	Pass
802.11g	6Mbps	06	2437	-6.131	-6.737	99.25%	-3.380	≤ 8.00	Pass
802.11g	6Mbps	11	2462	-13.392	-13.914	99.25%	-10.602	≤ 8.00	Pass
802.11n-HT20	MCS0	01	2412	-13.501	-12.869	97.84%	-10.068	≤ 8.00	Pass
802.11n-HT20	MCS0	06	2437	-6.512	-7.072	97.84%	-3.678	≤ 8.00	Pass
802.11n-HT20	MCS0	11	2462	-13.469	-13.604	97.84%	-10.431	≤ 8.00	Pass
802.11n-HT40	MCS0	03	2422	-16.163	-16.425	96.96%	-13.148	≤ 8.00	Pass
802.11n-HT40	MCS0	06	2437	-11.637	-12.301	96.96%	-8.812	≤ 8.00	Pass
802.11n-HT40	MCS0	09	2452	-15.218	-15.699	96.96%	-12.307	≤ 8.00	Pass
802.11ax-HE20	MCS0	01	2412	-14.729	-15.182	98.91%	-11.892	≤ 8.00	Pass
802.11ax-HE20	MCS0	06	2437	-8.245	-9.018	98.91%	-5.556	≤ 8.00	Pass
802.11ax-HE20	MCS0	11	2462	-16.381	-16.511	98.91%	-13.388	≤ 8.00	Pass
802.11ax-HE40	MCS0	03	2422	-17.627	-17.836	97.32%	-14.602	≤ 8.00	Pass
802.11ax-HE40	MCS0	06	2437	-14.836	-15.315	97.32%	-11.941	≤ 8.00	Pass
802.11ax-HE40	MCS0	09	2452	-16.305	-16.476	97.32%	-13.261	≤ 8.00	Pass
802.11be-EHT20	MCS0	01	2412	-14.032	-14.206	94.55%	-10.864	≤ 8.00	Pass
802.11be-EHT20	MCS0	06	2437	-7.974	-8.485	94.55%	-4.968	≤ 8.00	Pass
802.11be-EHT20	MCS0	11	2462	-15.208	-15.177	94.55%	-11.939	≤ 8.00	Pass
802.11be-EHT40	MCS0	03	2422	-17.945	-18.106	96.80%	-14.873	≤ 8.00	Pass
802.11be-EHT40	MCS0	06	2437	-14.988	-15.091	96.80%	-11.888	≤ 8.00	Pass
802.11be-EHT40	MCS0	09	2452	-17.063	-16.945	96.80%	-13.852	≤ 8.00	Pass

Note 1: Total AVGPSD = $10^{\log \{10^{(Ant 0 \text{ AVGPSD}/10)} + 10^{(Ant 1 \text{ AVGPSD}/10)}\}} + 10^{\log (1/\text{Duty Cycle})}$.

