



# FCC TEST REPORT

## FCC ID:2BH7V-BK24

Applicant: Shenzhen Zhiding Manufacturing Co., Ltd  
Address: Room 401, No. 1 Factory Building, Scary Industrial Plant, No.7 Ganli 6th Road, Gankeng Community, Jihua Street, Longgang District, Shenzhen  
Manufacturer: Shenzhen Zhiding Manufacturing Co., Ltd  
Address: Room 401, No. 1 Factory Building, Scary Industrial Plant, No.7 Ganli 6th Road, Gankeng Community, Jihua Street, Longgang District, Shenzhen  
EUT: Car mounted phone holder  
Trade Mark: N/A  
Model Number: BK24  
BK24-S, BK24-A, BK24-X, BK24-P  
Date of Receipt: Mar. 18, 2025  
Test Date: Mar. 18, 2025 - Mar. 24, 2025  
Date of Report: Mar. 24, 2025  
Prepared By: Shenzhen DL Testing Technology Co., Ltd.  
Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China  
Applicable Standards: FCC CFR Title 47 Part 15 Subpart C  
Test Result: Pass  
Report Number: DLE-250401029R

Prepared (Test Engineer): Dimon Tan

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



## TABLE OF CONTENTS

|                                                         |           |
|---------------------------------------------------------|-----------|
| <b>1. VERSION .....</b>                                 | <b>3</b>  |
| <b>2. TEST SUMMARY .....</b>                            | <b>4</b>  |
| 2.1 TEST FACILITY .....                                 | 5         |
| 2.2 MEASUREMENT UNCERTAINTY .....                       | 5         |
| <b>3. GENERAL INFORMATION .....</b>                     | <b>6</b>  |
| 3.1 GENERAL DESCRIPTION OF EUT .....                    | 6         |
| 3.2 Test mode .....                                     | 6         |
| 3.3 Block Diagram of EUT Configuration .....            | 8         |
| 3.4 Test Conditions .....                               | 8         |
| 3.5 Description Of Support Units (Conducted Mode) ..... | 8         |
| 3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS .....            | 9         |
| <b>4. CONDUCTED EMISSION TEST .....</b>                 | <b>11</b> |
| 4.1 CONDUCTED EMISSION MEASUREMENT .....                | 11        |
| 4.1.1 POWER LINE CONDUCTED EMISSION Limits .....        | 11        |
| 4.1.2 TEST PROCEDURE .....                              | 11        |
| 4.1.3 DEVIATION FROM TEST STANDARD .....                | 11        |
| 4.1.4 TEST SETUP .....                                  | 12        |
| 4.1.5 EUT OPERATING CONDITIONS .....                    | 12        |
| 4.1.6 Test Result .....                                 | 13        |
| <b>5. RADIATED EMISSION MEASUREMENT .....</b>           | <b>15</b> |
| 5.1 Radiated Emission Limits .....                      | 15        |
| 5.2 Anechoic Chamber Test Setup Diagram .....           | 16        |
| 5.3 Test Procedure .....                                | 16        |
| 5.4 DEVIATION FROM TEST STANDARD .....                  | 17        |
| 5.5 Test Result .....                                   | 17        |
| <b>6. 20DB BANDWIDTH TEST .....</b>                     | <b>20</b> |
| <b>7. ANTENNA REQUIREMENT .....</b>                     | <b>22</b> |
| <b>8. TEST SETUP PHOTO .....</b>                        | <b>23</b> |
| <b>9. EUT CONSTRUCTIONAL DETAILS .....</b>              | <b>23</b> |



**1. VERSION**

| Report No.     | Version | Description             | Approved      |
|----------------|---------|-------------------------|---------------|
| DLE-250401029R | Rev.01  | Initial issue of report | Mar. 24, 2025 |
|                |         |                         |               |



## 2. TEST SUMMARY

| Test Item                        | Section in CFR 47 | Result |
|----------------------------------|-------------------|--------|
| Antenna requirement              | 15.203            | Pass   |
| AC Power Line Conducted Emission | 15.207            | Pass   |
| Spurious Emission                | 15.209(a)(f)      | Pass   |
| 20dB Bandwidth                   | 15.215            | Pass   |

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



## 2.1 TEST FACILITY

Test lab: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Roa Baolong Industrial Zone, Baolong Street, Longgang Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: 27485

CAB ID.: CN0118

## 2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 % °

| No. | Item                                              | Uncertainty |
|-----|---------------------------------------------------|-------------|
| 1   | 3m camber Radiated spurious emission(9KHz-30MHz)  | U=4.5dB     |
| 2   | 3m camber Radiated spurious emission(30MHz-1GHz)  | U=4.8dB     |
| 3   | 3m chamber Radiated spurious emission(1GHz-6GHz)  | U=4.9dB     |
| 4   | 3m chamber Radiated spurious emission(6GHz-40GHz) | U=5.0dB     |
| 5   | Conducted disturbance                             | U=3.2dB     |
| 6   | RF Band Edge                                      | U=1.68dB    |
| 7   | RF power conducted                                | U=1.86dB    |
| 8   | RF conducted Spurious Emission                    | U=2.2dB     |
| 9   | RF Occupied Bandwidth                             | U=1.8dB     |
| 10  | RF Power Spectral Density                         | U=1.75dB    |
| 11  | humidity uncertainty                              | U=5.3%      |
| 12  | Temperature uncertainty                           | U=0.59°C    |



### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

|                      |                                                                                                                                            |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:        | Car mounted phone holder                                                                                                                   |
| Model No.:           | BK24<br>BK24-S, BK24-A, BK24-X, BK24-P                                                                                                     |
| Model Difference:    | Only the appearance of the color difference                                                                                                |
| Hardware version:    | H 1.0                                                                                                                                      |
| Software version:    | V 1.1                                                                                                                                      |
| Operation Frequency: | 115kHz~205kHz                                                                                                                              |
| Modulation type:     | ASK                                                                                                                                        |
| Antenna Type:        | ANT: Loop Coil Antenna                                                                                                                     |
| Antenna gain:        | ANT: 0dBi                                                                                                                                  |
| Ratings:             | Input: 5V $\overline{=}$ 2A, 9V $\overline{=}$ 1.67A<br>Output: 15W, 10W, 7.5W, 5W<br>The battery of 3.7V is used to power the motor alone |
| Transmitting mode    | Keep the EUT in continuously wireless charging mode                                                                                        |

#### 3.2 Test mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Power: | Test Modes: | Test Coil | Description:                                                 |
|--------|-------------|-----------|--------------------------------------------------------------|
| 15W    | Mode 1      | ANT       | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: <1%)  |
|        | Mode 2      |           | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: 50%)  |
|        | Mode 3      |           | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: >98%) |

| Power: | Test Modes: | Test Coil | Description:                                                 |
|--------|-------------|-----------|--------------------------------------------------------------|
| 10W    | Mode 4      | ANT       | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: <1%)  |
|        | Mode 5      |           | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: 50%)  |
|        | Mode 6      |           | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: >98%) |

| Power: | Test Modes: | Test Coil | Description:                                                 |
|--------|-------------|-----------|--------------------------------------------------------------|
| 7.5W   | Mode 7      | ANT       | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: <1%)  |
|        | Mode 8      |           | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: 50%)  |
|        | Mode 9      |           | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: >98%) |



| Power: | Test Modes: | Test Coil | Description:                                                 |
|--------|-------------|-----------|--------------------------------------------------------------|
| 5W     | Mode 10     | ANT       | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: <1%)  |
|        | Mode 11     |           | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: 50%)  |
|        | Mode 12     |           | AC/DC Adapter(9V/1.67A) + EUT + Phone (Battery Status: >98%) |

| Power: | Test Modes: | Test Coil | Description:                                              |
|--------|-------------|-----------|-----------------------------------------------------------|
| 10W    | Mode 13     | ANT       | AC/DC Adapter(5V/2A) + EUT + Phone (Battery Status: <1%)  |
|        | Mode 14     |           | AC/DC Adapter(5V/2A) + EUT + Phone (Battery Status: 50%)  |
|        | Mode 15     |           | AC/DC Adapter(5V/2A) + EUT + Phone (Battery Status: >98%) |


| Power: | Test Modes: | Test Coil | Description:                                              |
|--------|-------------|-----------|-----------------------------------------------------------|
| 7.5W   | Mode 16     | ANT       | AC/DC Adapter(5V/2A) + EUT + Phone (Battery Status: <1%)  |
|        | Mode 17     |           | AC/DC Adapter(5V/2A) + EUT + Phone (Battery Status: 50%)  |
|        | Mode 18     |           | AC/DC Adapter(5V/2A) + EUT + Phone (Battery Status: >98%) |

| Power: | Test Modes: | Test Coil | Description:                                              |
|--------|-------------|-----------|-----------------------------------------------------------|
| 5W     | Mode 19     | ANT       | AC/DC Adapter(5V/2A) + EUT + Phone (Battery Status: <1%)  |
|        | Mode 20     |           | AC/DC Adapter(5V/2A) + EUT + Phone (Battery Status: 50%)  |
|        | Mode 21     |           | AC/DC Adapter(5V/2A) + EUT + Phone (Battery Status: >98%) |




### 3.3 Block Diagram of EUT Configuration

#### Conducted Emission



#### Radiated Emission



### 3.4 Test Conditions

Temperature: 23~26℃

Relative Humidity: 54~63 %

### 3.5 Description Of Support Units (Conducted Mode)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment                | Mfr/Brand | Model/Type No. | Series No. | Note      |
|------|--------------------------|-----------|----------------|------------|-----------|
| E-1  | Car mounted phone holder | N/A       | BK24           | N/A        | EUT       |
| E-2  | Power Adapter            | GS        | GA-0502000V    | N/A        | Auxiliary |
| E-3  | Phone                    | Apple     | iPhone 13      | N/A        | Auxiliary |

| Item | Shielded Type | Ferrite Core | Length | Note                |
|------|---------------|--------------|--------|---------------------|
| C1   | NO            | NO           | 0.8M   | DC cable unshielded |
|      |               |              |        |                     |

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



## 3.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

## Conduction Emissions Test

| Item | Kind of Equipment | Manufacturer | Type No. | Serial No.        | Firmware Version | Last calibration | Calibrated until |
|------|-------------------|--------------|----------|-------------------|------------------|------------------|------------------|
| 1    | LISN              | R&S          | ENV216   | 101471            | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 2    | LISN              | CYBERTEK     | EM5040A  | E1850400149       | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 3    | Test Cable        | N/A          | C-01     | N/A               | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 4    | EMI Test Receiver | R&S          | ESCI3    | 101393            | 4.42 SP3         | Sep. 29, 2024    | Sep. 28, 2025    |
| 5    | EMC Software      | Frad         | EZ-EMC   | Ver.EMC-CON 3A1.1 | N/A              | \                | \                |

## Radiation Emissions &amp; Radiation Spurious Emissions Test

| Item | Equipment                         | Manufacturer   | Type No.        | Serial No.         | Firmware Version | Last calibration | Calibrated until |
|------|-----------------------------------|----------------|-----------------|--------------------|------------------|------------------|------------------|
| 1    | Spectrum Analyzer (9kHz-26.5GHz)  | KEYSIGHT       | N9020A          | MY55370835         | A.17.05          | Sep. 29, 2024    | Sep. 28, 2025    |
| 2    | Spectrum Analyzer (10kHz-39.9GHz) | R&S            | FSV40-N         | 100363             | 1.71 SP2         | Sep. 30, 2024    | Sep. 29, 2025    |
| 3    | EMI Test Receiver (9kHz-7GHz)     | R&S            | ESCI7           | 100969             | 4.32             | Sep. 29, 2024    | Sep. 28, 2025    |
| 4    | Bilog Antenna (30MHz-1500MHz)     | Schwarzbeck    | VULB9168        | 00877              | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 5    | Horn Antenna (1GHz-18GHz)         | Agilent        | AH-118          | 071145             | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 6    | Horn Antenna (15GHz-40GHz)        | A.H.System     | SAS-574         | 588                | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 7    | Loop Antenna                      | TESEQ          | HLA6121         | 58357              | N/A              | Oct. 11, 2024    | Oct. 10, 2025    |
| 8    | Amplifier (30-1000MHz)            | EM Electronics | EM330 Amplifier | 60747              | N/A              | Sep. 29, 2024    | Sep. 28, 2025    |
| 9    | Amplifier (1GHz-26.5GHz)          | HuiPu          | 8449B           | 3008A00315         | N/A              | Sep. 29, 2024    | Sep. 28, 2025    |
| 10   | Amplifier (500MHz-40GHz)          | QuanJuDa       | DLE-161         | 097                | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 11   | Test Cable                        | N/A            | R-01            | N/A                | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 12   | Test Cable                        | N/A            | R-02            | N/A                | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 13   | Test Cable                        | N/A            | R-03            | N/A                | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 14   | D.C. Power Supply                 | LongWei        | TPR-6405D       | GQ7516             | N/A              | Sep. 29, 2024    | Sep. 28, 2025    |
| 15   | EMC Software                      | Frad           | EZ-EMC          | Ver.EMC-CO N 3A1.1 | N/A              | \                | \                |
| 16   | Turntable                         | MF             | MF-7802BS       | N/A                | N/A              | \                | \                |
| 17   | Antenna tower                     | MF             | MF-7802BS       | N/A                | N/A              | \                | \                |



## RF Conducted Test

| Item | Equipment                         | Manufacturer                | Type No.    | Serial No. | Firmware Version | Last calibration | Calibrated until |
|------|-----------------------------------|-----------------------------|-------------|------------|------------------|------------------|------------------|
| 1    | Spectrum Analyzer (9kHz-26.5GHz)  | KEYSIGHT                    | N9020A      | MY55370835 | A.17.05          | Sep. 29, 2024    | Sep. 28, 2025    |
| 2    | Spectrum Analyzer (10kHz-39.9GHz) | R&S                         | FSV40-N     | 100363     | 1.71 SP2         | Sep. 30, 2024    | Sep. 29, 2025    |
| 3    | Test Cable                        | N/A                         | RF-01       | N/A        | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 4    | Test Cable                        | N/A                         | RF-02       | N/A        | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 5    | Test Cable                        | N/A                         | RF-03       | N/A        | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 6    | ESG Signal Generator              | Agilent                     | E4421B      | GB40051203 | B.03.84          | Sep. 29, 2024    | Sep. 28, 2025    |
| 7    | Signal Generator                  | Agilent                     | N5182A      | MY47420215 | A.01.87          | Sep. 29, 2024    | Sep. 28, 2025    |
| 8    | Magnetic Field Probe Tester       | Narda                       | ELT-400     | 0-0344     | N/A              | Sep. 29, 2024    | Sep. 28, 2025    |
| 9    | Van der Hoofden measuring head    | Schwarzbeck Mess-elektronik | VDHH 9502   | 9502-039   | N/A              | Sep. 30, 2024    | Sep. 29, 2025    |
| 10   | Wideband Radio Communication Test | R&S                         | CMW500      | 106504     | V 3.7.22         | Sep. 30, 2024    | Sep. 29, 2025    |
| 11   | MWRF Power Meter Test system      | MW                          | MW100-RF CB | 10371      | N/A              | Sep. 29, 2024    | Sep. 28, 2025    |
| 12   | Power Meter                       | KEYSIGHT                    | N1912AP     | 926431     | A.05.00          | Sep. 29, 2024    | Sep. 28, 2025    |
| 13   | D.C. Power Supply                 | LongWei                     | TPR-6405D   | GQ7516     | N/A              | Sep. 29, 2024    | Sep. 28, 2025    |
| 14   | RF Software                       | MW                          | MTS8310     | V2.0.0.0   | N/A              | \                | \                |



#### 4. CONDUCTED EMISSION TEST

##### 4.1 CONDUCTED EMISSION MEASUREMENT

|                       |                                      |
|-----------------------|--------------------------------------|
| Test Requirement:     | FCC Part15 C Section 15.207          |
| Test Method:          | ANSI C63.10:2013                     |
| Test Frequency Range: | 150KHz to 30MHz                      |
| Receiver setup:       | RBW=9KHz, VBW=30KHz, Sweep time=auto |

##### 4.1.1 POWER LINE CONDUCTED EMISSION Limits

| FREQUENCY (MHz) | Limit (dBuV) |           | Standard |
|-----------------|--------------|-----------|----------|
|                 | Quas-peak    | Average   |          |
| 0.15 -0.5       | 66 - 56 *    | 56 - 46 * | FCC      |
| 0.50 -5.0       | 56.00        | 46.00     | FCC      |
| 5.0 -30.0       | 60.00        | 50.00     | FCC      |

Note:

(1) \*Decreases with the logarithm of the frequency.

##### 4.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

##### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation



#### 4.1.4 TEST SETUP



**Note: 1.Support units were connected to second LISN.**

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes**


#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



## 4.1.6 Test Result

|                |              |                    |        |
|----------------|--------------|--------------------|--------|
| Temperature:   | 26℃          | Relative Humidity: | 54%    |
| Pressure:      | 101kPa       | Phase :            | L      |
| Test Voltage : | AC 120V/60Hz | Test Mode:         | Mode 1 |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F | Remark |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|--------|
| 1   | 0.1949          | 33.97          | 20.36       | 54.33        | 63.83        | -9.50       | QP       | P   |        |
| 2   | 0.1949          | 14.21          | 20.36       | 34.57        | 53.83        | -19.26      | AVG      | P   |        |
| 3   | 0.5684          | 27.03          | 20.29       | 47.32        | 56.00        | -8.68       | QP       | P   |        |
| 4   | 0.5684          | 10.63          | 20.29       | 30.92        | 46.00        | -15.08      | AVG      | P   |        |
| 5   | 1.6169          | 27.27          | 20.30       | 47.57        | 56.00        | -8.43       | QP       | P   |        |
| 6   | 1.6304          | 15.87          | 20.30       | 36.17        | 46.00        | -9.83       | AVG      | P   |        |
| 7   | 4.2315          | 20.64          | 20.35       | 40.99        | 56.00        | -15.01      | QP       | P   |        |
| 8   | 4.2900          | 7.25           | 20.35       | 27.60        | 46.00        | -18.40      | AVG      | P   |        |
| 9   | 11.2380         | 19.03          | 20.46       | 39.49        | 60.00        | -20.51      | QP       | P   |        |
| 10  | 11.2650         | 7.80           | 20.46       | 28.26        | 50.00        | -21.74      | AVG      | P   |        |
| 11  | 15.6930         | 20.44          | 20.49       | 40.93        | 60.00        | -19.07      | QP       | P   |        |
| 12  | 15.9585         | 11.00          | 20.49       | 31.49        | 50.00        | -18.51      | AVG      | P   |        |

## Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi - Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Reading level + Correct Factor.
4. Correct Factor = Lism factor+ Cable loss factor + limiter factor.
5. Margin = Measurement Level-Limit.
6. All test modes were tested, with only the worst Mode 1 recorded.



|                |              |                    |        |
|----------------|--------------|--------------------|--------|
| Temperature:   | 26℃          | Relative Humidity: | 54%    |
| Pressure:      | 101kPa       | Phase :            | N      |
| Test Voltage : | AC 120V/60Hz | Test Mode:         | Mode 1 |



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F | Remark |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|--------|
| 1   | 0.1860          | 33.03          | 20.32       | 53.35        | 64.21        | -10.86      | QP       | P   |        |
| 2   | 0.1860          | 13.39          | 20.32       | 33.71        | 54.21        | -20.50      | AVG      | P   |        |
| 3   | 0.7214          | 27.84          | 20.29       | 48.13        | 56.00        | -7.87       | QP       | P   |        |
| 4   | 0.7304          | 13.74          | 20.29       | 34.03        | 46.00        | -11.97      | AVG      | P   |        |
| 5   | 1.6169          | 25.92          | 20.30       | 46.22        | 56.00        | -9.78       | QP       | P   |        |
| 6   | 1.6169          | 15.33          | 20.30       | 35.63        | 46.00        | -10.37      | AVG      | P   |        |
| 7   | 3.9885          | 5.11           | 20.33       | 25.44        | 46.00        | -20.56      | AVG      | P   |        |
| 8   | 4.0200          | 20.42          | 20.33       | 40.75        | 56.00        | -15.25      | QP       | P   |        |
| 9   | 11.3415         | 18.67          | 20.48       | 39.15        | 60.00        | -20.85      | QP       | P   |        |
| 10  | 11.3415         | 7.72           | 20.48       | 28.20        | 50.00        | -21.80      | AVG      | P   |        |
| 11  | 24.0045         | 23.36          | 20.64       | 44.00        | 60.00        | -16.00      | QP       | P   |        |
| 12  | 24.2744         | 11.64          | 20.65       | 32.29        | 50.00        | -17.71      | AVG      | P   |        |

## Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi - Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Reading level + Correct Factor.
4. Correct Factor = Lism factor+ Cable loss factor + limiter factor.
5. Margin = Measurement Level-Limit.
6. All test modes were tested, with only the worst Mode 1 recorded.

**5. RADIATED EMISSION MEASUREMENT**

|                       |                             |            |        |        |            |
|-----------------------|-----------------------------|------------|--------|--------|------------|
| Test Requirement:     | FCC Part15 C Section 15.209 |            |        |        |            |
| Test Method:          | ANSI C63.10:2013            |            |        |        |            |
| Test Frequency Range: | 9kHz to 1GHz                |            |        |        |            |
| Test site:            | Measurement Distance: 3m    |            |        |        |            |
| Receiver setup:       | Frequency                   | Detector   | RBW    | VBW    | Value      |
|                       | 9KHz-150KHz                 | Quasi-peak | 200Hz  | 600Hz  | Quasi-peak |
|                       | 150KHz-30MHz                | Quasi-peak | 9KHz   | 30KHz  | Quasi-peak |
|                       | 30MHz-1GHz                  | Quasi-peak | 100KHz | 300KHz | Quasi-peak |
|                       | Above 1GHz                  | Peak       | 1MHz   | 3MHz   | Peak       |
|                       |                             | Peak       | 1MHz   | 10Hz   | Average    |

**5.1 Radiated Emission Limits****Limits for frequency below 30MHz**

| Frequency   | Limit (uV/m) | Measurement Distance(m) | Remark           |
|-------------|--------------|-------------------------|------------------|
| 0.009-0.490 | 2400/F(kHz)  | 300                     | Quasi-peak Value |
| 0.490-1.705 | 24000/F(kHz) | 30                      | Quasi-peak Value |
| 1.705-30    | 30           | 30                      | Quasi-peak Value |


**Limits for frequency Above 30MHz**

| Frequency     | Limit (dBuV/m @3m) | Remark           |
|---------------|--------------------|------------------|
| 30MHz-88MHz   | 40.00              | Quasi-peak Value |
| 88MHz-216MHz  | 43.50              | Quasi-peak Value |
| 216MHz-960MHz | 46.00              | Quasi-peak Value |
| 960MHz-1GHz   | 54.00              | Quasi-peak Value |
| Above 1GHz    | 54.00              | Average Value    |
|               | 74.00              | Peak Value       |




## 5.2 Anechoic Chamber Test Setup Diagram

### (A) Radiated Emission Test-Up Frequency Below 30MHz



### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.205 limits.

## 5.3 Test Procedure

The EUT is placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna (calibrated by dipole antenna) are used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on measurement.



## 5.4 DEVIATION FROM TEST STANDARD

No deviation

## 5.5 Test Result


Measurement data:

Note: Limit dBuV/m @3m = Limit dBuV/m @300m+ 80

Limit dBuV/m @3m = Limit dBuV/m @30m + 40

9 kHz~30 MHz:

|               |         |                    |         |
|---------------|---------|--------------------|---------|
| Temperature:  | 26°C    | Relative Humidity: | 54%     |
| Pressure:     | 101 kPa | Polarization:      | coaxial |
| Test Voltage: | DC 9V   | Test Mode:         | Mode 1  |



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 0.0183          | 50.25          | 20.47         | 70.72          | 122.36         | -51.64      | peak     |
| 2   | 0.0483          | 45.43          | 19.79         | 65.22          | 113.93         | -48.71      | peak     |
| 3   | 0.1467          | 71.39          | 20.04         | 91.43          | 104.28         | -12.85      | peak     |
| 4   | 0.3326          | 31.09          | 20.13         | 51.22          | 97.17          | -45.95      | peak     |
| 5   | 0.7043          | 28.25          | 20.38         | 48.63          | 70.65          | -22.02      | peak     |
| 6   | 1.4916          | 21.68          | 19.88         | 41.56          | 64.13          | -22.57      | peak     |


Remarks:

1. An initial pre-scan was performed on the peak detector.
2. Quasi-Peak measurement were performed at the frequencies with maximized peak emission.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Final Level = Reading level + Correct Factor.
5. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
6. Margin= Measurement Level-Limit.



30MHz-1GHz

|               |         |                    |            |
|---------------|---------|--------------------|------------|
| Temperature:  | 26°C    | Relative Humidity: | 54%        |
| Pressure:     | 101 kPa | Polarization:      | Horizontal |
| Test Voltage: | DC 9V   | Test Mode:         | Mode 1     |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|----------|
| 1   | 30.7454         | 36.89          | -14.23        | 22.66          | 40.00          | -17.34      | QP       |
| 2   | 62.2128         | 39.12          | -14.71        | 24.41          | 40.00          | -15.59      | QP       |
| 3   | 84.9993         | 42.37          | -19.71        | 22.66          | 40.00          | -17.34      | QP       |
| 4   | 148.4410        | 39.04          | -16.40        | 22.64          | 43.50          | -20.86      | QP       |
| 5   | 274.1938        | 46.60          | -14.30        | 32.30          | 46.00          | -13.70      | QP       |
| 6   | 381.2485        | 44.56          | -16.15        | 28.41          | 46.00          | -17.59      | QP       |

## Remarks:

1. An initial pre-scan was performed on the peak detector.
2. Quasi-Peak measurement were performed at the frequencies with maximized peak emission.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Final Level = Reading level + Correct Factor.
5. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
6. Margin= Measurement Level-Limit.
7. All test modes were tested, with only the worst Mode 1 recorded.



|               |        |                    |          |
|---------------|--------|--------------------|----------|
| Temperature:  | 26℃    | Relative Humidity: | 54%      |
| Pressure:     | 101kPa | Polarization:      | Vertical |
| Test Voltage: | DC 9V  | Test Mode:         | Mode 1   |



## Remarks:

1. An initial pre-scan was performed on the peak detector.
2. Quasi-Peak measurement were performed at the frequencies with maximized peak emission.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Final Level = Reading level + Correct Factor.
5. Correct Factor = Antenna factor+ Cable loss factor - Amplifier factor.
6. Margin= Measurement Level-Limit.
7. All test modes were tested, with only the worst Mode 1 recorded.



## 6. 20DB BANDWIDTH TEST

1. Se span = 1.5 ~ 5 times OBW.
2. Set RBW = 1KHz.
3. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
4. Detector = peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP






|              |        |                    |       |
|--------------|--------|--------------------|-------|
| Temperature: | 26 °C  | Relative Humidity: | 54%   |
| Pressure:    | 101kPa | Test Voltage:      | DC 9V |

| Test Coil | Frequency (kHz) | 20dB Bandwidth (kHz) | Result |
|-----------|-----------------|----------------------|--------|
| ANT       | 146.72          | 2.713                | Pass   |

ANT 1:





## 7. ANTENNA REQUIREMENT

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| Standard requirement:                                                                                                                                                                                                                                                                                                                                                                                                                                                     | FCC Part15 C Section 15.203 |
| 15.203 requirement:<br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |                             |
| EUT Antenna:                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                             |
| The antenna is Loop Coil antenna, the best case gain of the antennas is 0dBi, reference to the appendix II for details                                                                                                                                                                                                                                                                                                                                                    |                             |



## 8. TEST SETUP PHOTO

Reference to the appendix I for details.

## 9. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

\*\*\*\*\* END OF REPORT \*\*\*\*\*