

TEST REPORT

Reference No...... : WTF25X08224704W001
FCC ID..... : 2BH83-HERO
Applicant..... : FULL TECHNOLOGY TRADE LIMITED
Address..... : RM 13,UNIT A1,2/F.,PHASE 1,KAISER ESTATE,NO.41 MAN YUE
STREET,HUNG HOM,KLN HONG KONG
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : Mobile Phone
Model No...... : HERO
Standards..... : FCC Part 22H, FCC Part 24E, FCC Part 27
Date of Receipt sample..... : 2025-08-21
Date of Test..... : 2025-08-21 to 2025-09-11
Date of Issue..... : 2025-09-11
Test Report Form No...... : WTX_Part 22_Part 24_Part 27W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.


Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Mike Shi/Project Engineer

Approved by:



Jason Su/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION..... 4

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4

1.2 TEST STANDARDS6

1.3 TEST METHODOLOGY6

1.4 TEST FACILITY 6

1.5 EUT SETUP AND TEST MODE 7

1.6 MEASUREMENT UNCERTAINTY9

1.7 TEST EQUIPMENT LIST AND DETAILS 10

2. SUMMARY OF TEST RESULTS 14

3. SPURIOUS RADIATED EMISSIONS 15

3.1 STANDARD APPLICABLE15

3.2 TEST PROCEDURE 15

3.3 SUMMARY OF TEST RESULTS/PLOTS 15

APPENDIX PHOTOGRAPHS22

Report version

Version No.	Date of issue	Description
Rev.00	2025-09-11	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT:	
Product Name:	Mobile Phone
Trade Name:	Lifephone
Model No.:	HERO
Adding Model(s):	/
Rated Voltage:	DC3.85V
Battery:	4900mAh
Adapter Model:	Model:UT-681A-5200MY Input:AC100-220V 50/60Hz 0.35A Output:DC5.0V2.0A 10.0W
<i>The test data is gathered from a production sample provided by the manufacturer.</i>	

Technical Characteristics of EUT:	
2G	
Support Networks:	GSM, GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS/EDGE 850: 869~894MHz GSM/GPRS/EDGE 1900: 1930~1990MHz
Max RF Output Power:	GSM850: 32.17dBm, GSM1900: 28.73dBm EDGE850: 24.72dBm, EDGE1900: 23.70dBm
Type of Emission:	GSM850: 244KGXW, GSM1900: 243KGXW EDGE850: 247KG7W, EDGE1900: 244KG7W
Type of Modulation:	GMSK, 8PSK
Type of Antenna:	FPC Antenna
Antenna Gain:	GSM850: -0.45dBi; GSM1900: -1.01dBi
GPRS/EDGE Class:	Class 12
3G	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band 2, WCDMA Band 4, WCDMA Band 5
Uplink Frequency:	WCDMA Band 2: 1850~1910MHz WCDMA Band 4: 1710~1755MHz WCDMA Band 5: 824~849MHz
Downlink Frequency:	WCDMA Band 2: 1930~1990MHz WCDMA Band 4: 2110~2155MHz WCDMA Band 5: 869~894MHz
RF Output Power:	WCDMA Band 2: 23.16dBm, WCDMA Band 4: 23.02dBm WCDMA Band 5: 23.09dBm
Type of Emission:	WCDMA Band 2: 4M15F9W WCDMA Band 4: 4M16F9W WCDMA Band 5: 4M16F9W
Type of Modulation:	BPSK, QPSK, 16QAM
Antenna Type:	FPC Antenna
Antenna Gain:	WCDMA Band 2: -1.01dBi, WCDMA Band 4: -0.08dBi, WCDMA Band 5: -0.45dBi
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 2: Frequency Allocations and Radio Treaty Matters; General Rules and Regulations.

FCC Rules Part 22: Private Land Mobile Radio Services.

FCC Rules Part 24: Public Mobile Services.

FCC Rules Part 27: Miscellaneous Wireless Communications Services.

TIA/EIA 603 E March 2016: Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

ANSI C63.26-2015: American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services

KDB 971168 D01 Power Measurement License Digital Systems v03r01: Measurement Guidance for Certification of Licensed Digital Transmitters.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with TIA/EIA 603 E/ KDB 971168/ ANSI C63.26. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	EDGE 850	Low, Middle, High Channels
TM4	GSM 1900	Low, Middle, High Channels
TM5	GPRS 1900	Low, Middle, High Channels
TM6	EDGE 1900	Low, Middle, High Channels
TM7	WCDMA Band 5	Low, Middle, High Channels
TM8	HSDPA Band 5	Low, Middle, High Channels
TM9	HSUPA Band 5	Low, Middle, High Channels
TM10	WCDMA Band 4	Low, Middle, High Channels
TM11	HSDPA Band 4	Low, Middle, High Channels
TM12	HSUPA Band 4	Low, Middle, High Channels
TM13	WCDMA Band 2	Low, Middle, High Channels
TM14	HSDPA Band 2	Low, Middle, High Channels
TM15	HSUPA Band 2	Low, Middle, High Channels

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EDGE	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EDGE	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band 5	WCDMA/HSDPA/HSUPA	826.4 MHz	4132
		836.6 MHz	4183
		846.6 MHz	4233
WCDMA Band 4	WCDMA/HSDPA/HSUPA	1712.4 MHz	1312
		1732.4 MHz	1412
		1752.6 MHz	1513
WCDMA Band 2	WCDMA/HSDPA/HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538
Note: the transmitter has been tested on the communications mode of GSM, GPRS, EDGE, WCDMA, HSDPA, HSUPA compliance test and record the worst case.			

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~75 %
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	0.75	Shielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Earphone Cable	1.0	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	TianYi 100-14IBD	PF0F4ABV

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	0.57dB
Occupied Bandwidth	Conducted	0.015MHz
Frequency Stability	Conducted	2.3%
Transmitter Spurious Emissions	Conducted	0.42dB
Transmitter Spurious Emissions	Radiated	30-200MHz, 4.52dB
		0.2-1GHz 5.56dB
		1-6GHz, 3.84dB
		6-18GHz, 3.92dB

1.7 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041 A1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2025-02-23	2026-02-22
WTXE1022 A1002	GSM Tester	Rohde & Schwarz	CMU200	114403	2025-02-23	2026-02-22
WTXE1104 A1001	MXG Vector Signal Generator	Agilent	N5182A	MY47420108	2025-02-23	2026-02-22
WTXE1104 A1002	DC Power Supply	Agilent	E3634A	MY40009294	2025-02-23	2026-02-22
WTXE1104 A1003	EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61252892	2025-02-23	2026-02-22
WTXE1104 A1004	Spectrum Analyzer	Rohde&Schwarz	FSV40-N	101559	2025-02-23	2026-02-22
WTXE1104 A1005-2	Band Reject Filter Group	Tonscend	JS0806-F	23A806F0658	2025-02-23	2026-02-22
WTXE1103 A1003	Attenuator	Pasternack	PE4007-4	/	2025-02-23	2026-02-22
WTXE1003 A1-005	Coaxial Cable	/	0M4RFC	/	2025-02-23	2026-02-22
☐ Chamber A: Below 1GHz						
WTXE1005 A1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2025-02-23	2026-02-22
WTXE1001 A1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22
WTXE1007 A1001	Amplifier	HP	8447F	2805A03475	2025-02-23	2026-02-22
WTXE1010 A1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1010 A1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2025-02-23	2026-02-22
WTXE1104 A1032-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104 A1032-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104 A1032-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☐ Chamber A: Above 1GHz						
WTXE1005 A1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2025-02-23	2026-02-22

WTXE1001 A1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22
WTXE1065 A1001	Amplifier	C&D	PAP-1.0G18	14918	2025-02-23	2026-02-22
WTXE1010 A1005	Horn Antenna	ETS	3117	00086197	2025-02-23	2026-02-22
WTXE1010 A1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003 A1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1004 A1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2025-02-23	2026-02-22
WTXE1104 A1033-1	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104 A1033-2	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104 A1033-3	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
☐ Chamber B:Below 1GHz						
WTXE1010 A1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038 A1001	Amplifier	Agilent	8447D	2944A10457	2025-02-23	2026-02-22
WTXE1001 A1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2025-02-23	2026-02-22
WTXE1104 A1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2025-02-23	2026-02-22
WTXE1104 A1031-2	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104 A1031-3	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
☒ Chamber C:Below 1GHz						
WTXE1093 A1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1010 A1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1007 A1002	Amplifier	HP	8447F	2944A03869	2025-02-23	2026-02-22
WTXE1010 A1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25

WTXE1104 A1034-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104 A1034-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104 A1034-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☒ Chamber C: Above 1GHz						
WTXE1093 A1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1103 A1005	Horn Antenna	POAM	RTF-118A	1820	2025-06-13	2027-06-12
WTXE1103 A1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2025-02-23	2026-02-22
WTXE1010 A1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003 A1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104 A1035-1	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104 A1035-2	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104 A1035-3	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
☐ Conducted Room 1#						
WTXE1104 A1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2024-12-08	2025-12-07
WTXE1002 A1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2025-02-23	2026-02-22
WTXE1003 A1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2025-02-23	2026-02-22
WTXE1104 A1036	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104 A1038	Coaxial Cable	/	6MRFC-DP	/	2025-02-23	2026-02-22
☐ Conducted Room 2#						
WTXE1001 A1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2025-02-23	2026-02-22
WTXE1003 A1003	LISN	Rohde & Schwarz	ENV 216	100097	2025-02-23	2026-02-22
WTXE1104 A1037	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission A)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission B)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission C)	Farad	EZ-EMC	RA-03A1-2 (1.1.4.2)

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§22.913(a), §24.232(c), §27.50(d)	RF Output Power	N/A
§24.51, §27.50	Peak-to-average Ratio (PAR) of Transmitter	N/A
§22.917(b), §24.238(b), §27.53	Emission Bandwidth	N/A
§22.917(a), §24.238(a), §27.53(h)	Spurious Emissions at Antenna Terminal	N/A
§22.917(a), §24.238(a), §27.53(h)	Spurious Radiation Emissions	Compliant
§22.917(a), §24.238(a), §27.53(h)	Out of Band Emissions	N/A
§22.355, §24.235, §27.54	Frequency Stability	N/A

Class II Permissive Change: DDR model has been changed. The memory package has become larger. Previously it was LPDDR4, now it has been modified to the EMCP format. The PCB model (labeled) has also been changed simultaneously.

Note: Report is for Class II Permissive Change only. Updated test data include Spurious Radiation Emissions. The test data refer to Original equipment (FCC ID: 2BH83-HERO), the original FCC ID issue date: 09/02/2024.

3. Spurious Radiated Emissions

3.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

3.2 Test Procedure

1. The setup of EUT is according with per ANSI/TIA Standard 603E and ANSI C63.26 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.


Spurious attenuation limit in dB = $43 + 10 \log_{10}(\text{power out in Watts})$

3.3 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Spurious Emissions Below 1GHz

For Cellular Band			
Test Channel	GSM1900	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	48.0392	-70.15	3.31	-66.84	-13.00	-53.84	ERP
2	58.4855	-70.31	2.47	-67.84	-13.00	-54.84	ERP
3	148.9175	-68.36	0.75	-67.61	-13.00	-54.61	ERP
4	255.8226	-68.14	8.07	-60.07	-13.00	-47.07	ERP
5	642.2923	-68.67	9.37	-59.30	-13.00	-46.30	ERP
6	945.3336	-66.06	13.62	-52.44	-13.00	-39.44	ERP


For Cellular Band			
Test Channel	GSM1900	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	51.5365	-70.91	3.47	-67.44	-13.00	-54.44	ERP
2	67.3109	-69.81	3.15	-66.66	-13.00	-53.66	ERP
3	163.1623	-70.14	7.37	-62.77	-13.00	-49.77	ERP
4	309.2710	-68.96	3.50	-65.46	-13.00	-52.46	ERP
5	409.6506	-68.93	5.54	-63.39	-13.00	-50.39	ERP
6	693.9101	-66.67	10.01	-56.66	-13.00	-43.66	ERP


Note: Margin= (Reading+ Correct)- Limit

Test Channel	WCDMA Band IV	Polarity:	Horizontal
--------------	---------------	-----------	------------



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	43.2333	-69.32	2.86	-66.46	-13.00	-53.46	ERP
2	57.2654	-70.33	2.62	-67.71	-13.00	-54.71	ERP
3	158.6399	-68.95	0.97	-67.98	-13.00	-54.98	ERP
4	254.0312	-68.29	8.21	-60.08	-13.00	-47.08	ERP
5	509.3559	-67.48	7.37	-60.11	-13.00	-47.11	ERP
6	850.7603	-66.63	13.61	-53.02	-13.00	-40.02	ERP

Test Channel	WCDMA Band IV	Polarity:	Vertical
--------------	---------------	-----------	----------



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	40.5837	-69.98	2.61	-67.37	-13.00	-54.37	ERP
2	66.8395	-68.42	3.15	-65.27	-13.00	-52.27	ERP
3	162.0197	-68.64	7.57	-61.07	-13.00	-48.07	ERP
4	418.3784	-68.69	5.70	-62.99	-13.00	-49.99	ERP
5	651.3831	-66.62	9.48	-57.14	-13.00	-44.14	ERP
6	979.1392	-65.87	12.85	-53.02	-13.00	-40.02	ERP

Note: Margin= (Reading+ Correct)- Limit

➤ Spurious Emissions Above 1GHz

➤ For PCS Band_GSM1900 Mode

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1850.2MHz)						
3700.4	-43.55	-13	-30.55	3700.4	-43.55	H
5550.6	-39.04	-13	-26.04	5550.6	-39.04	H
3700.4	-34.93	-13	-21.93	3700.4	-34.93	V
5550.6	-31.80	-13	-18.80	5550.6	-31.80	V
Middle Channel (1880MHz)						
3760.0	-42.84	-13	-29.84	3760.0	-42.84	H
5640.0	-40.21	-13	-27.21	5640.0	-40.21	H
3760.0	-34.37	-13	-21.37	3760.0	-34.37	V
5640.0	-32.53	-13	-19.53	5640.0	-32.53	V
High Channel (1909.8MHz)						
3819.6	-43.95	-13	-30.95	3819.6	-43.95	H
5729.4	-41.12	-13	-28.12	5729.4	-41.12	H
3819.6	-33.62	-13	-20.62	3819.6	-33.62	V
5729.4	-30.93	-13	-17.93	5729.4	-30.93	V

➤ For WCDMA Band IV Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1712.4MHz)						
3424.8	-48.33	-13	-35.33	3424.8	-48.33	H
5137.2	-38.31	-13	-25.31	5137.2	-38.31	H
3424.8	-51.45	-13	-38.45	3424.8	-51.45	V
5137.2	-46.63	-13	-33.63	5137.2	-46.63	V
Middle Channel (1732.4MHz)						
3466.8	-47.19	-13	-34.19	3466.8	-47.19	H
5200.2	-36.69	-13	-23.69	5200.2	-36.69	H
3466.8	-50.49	-13	-37.49	3466.8	-50.49	V
5200.2	-47.07	-13	-34.07	5200.2	-47.07	V
High Channel (1752.6MHz)						
3505.2	-49.84	-13	-36.84	3505.2	-49.84	H
5257.8	-35.73	-13	-22.73	5257.8	-35.73	H
3505.2	-49.48	-13	-36.48	3505.2	-49.48	V
5257.8	-47.79	-13	-34.79	5257.8	-47.79	V

Note: Result=Reading+ Correct, Margin= Result- Limit

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****