

TEST REPORT

Reference No..... : WTF24X08182130W009
FCC ID : 2BH83-IDOL
Applicant : FULL TECHNOLOGY TRADE LIMITED
Address..... : RM 13,UNIT A1,2/F.,PHASE 1,KAISER ESTATE,NO.41 MAN YUE
STREET,HUNGHOM,KLN HONG KONG
Manufacturer : FULL TECHNOLOGY TRADE LIMITED
Address..... : RM 13,UNIT A1,2/F.,PHASE 1,KAISER ESTATE,NO.41 MAN YUE
STREET,HUNGHOM,KLN HONG KONG
Product Name : Mobile Phone
Model No..... : IDOL
Standards : FCC Part 2.1093
IEEE Std C95.1: 2019
IEEE Std C95.3: 2002 + Rev. 2008
IEC/IEEE 62209-1528 Ed. 1.0 (2020-10)
Date of Receipt sample : 2024-08-09
Date of Test..... : 2024-08-09 to 2024-08-21
Date of Issue : 2024-08-23
Test Report Form No. : WTX_IEEE_1528W
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Jack Sun

Jack Sun

Approved by:

Jason Su

Jason Su

TABLE OF CONTENTS

1. General Information	4
1.1 Product Description for Equipment Under Test (EUT)	4
1.2 Test Standards	8
1.3 Test Methodology	8
1.4 Test Facility	8
2. Summary of Test Results	9
3. Specific Absorption Rate (SAR)	10
3.1 Introduction	10
3.2 SAR Definition	10
4. SAR Measurement System	11
4.1 The Measurement System	11
4.2 Probe	11
4.3 Probe Calibration Process	13
4.4 Phantom	14
4.5 Device Holder	14
4.6 Test Equipment List	15
5. Tissue Simulating Liquids	16
5.1 Composition of Tissue Simulating Liquid	16
5.2 Tissue Dielectric Parameters for Head and Body Phantoms	17
5.3 Tissue Calibration Result	18
6. SAR Measurement Evaluation	19
6.1 Purpose of System Performance Check	19
6.2 System Setup	19
6.3 Validation Results	20
7. EUT Testing Position	22
7.1 Define Two Imaginary Lines on The Handset	22
7.2 Cheek Position	23
7.3 Tilted Position	23
7.4 Body Position	24
7.5 EUT Antenna Position	24
7.6 EUT Testing Position	25
8. SAR Measurement Procedures	26
8.1 Measurement Procedures	26
8.2 Spatial Peak SAR Evaluation	26
8.3 Area & Zoom Scan Procedures	27
8.4 Volume Scan Procedures	27
8.5 SAR Averaged Methods	27
8.6 Power Drift Monitoring	27
9. SAR Test Result	28
9.1 Conducted RF Output Power	28
9.2 Test Results for Standalone SAR Test	69
9.3 Simultaneous Multi-band Transmission SAR Analysis	85
10. Measurement Uncertainty	90
10.1 Uncertainty for SAR Test	90
Annex A. Plots of System Performance Check	92
Annex B. Plots of SAR Measurement	112
Annex C. EUT Photos	206
Annex D. Test Setup Photos	208
Annex E. Calibration Certificate	213

Report version

Version No.	Date of issue	Description
Rev.00	2024-08-23	Original
/	/	/

1. General Information

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT:	
Product Name:	Mobile Phone
Brand Name:	Lifephone
Model No.:	IDOL
Adding Model(s):	/
Rated Voltage:	DC3.85V
Battery Capacity:	4900mAh
Power Adapter:	805A-18A-1A Input:AC100-240V 50/60Hz 0.5A Output:DC5V3A/9V2A/12V1.5A
Note: The test data is gathered from a production sample provided by the manufacturer.	

Technical Characteristics of EUT:	
2G	
Support Networks:	GSM, GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS/EDGE 850: 869~894MHz GSM/GPRS/EDGE 1900: 1930~1990MHz
RF Output Power:	GSM850:32.21dBm, GSM1900:28.42dBm EDGE850: 24.98dBm, EDGE1900: 24.76dBm
Type of Modulation:	GMSK, 8PSK
Type of Antenna:	FPC Antenna
Antenna Gain:	GSM850: -6.46dBi; GSM1900: -4.47dBi
GPRS/EDGE Class:	Class 12
3G	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band 2, WCDMA Band 4, WCDMA Band 5
Uplink Frequency:	WCDMA Band 2: 1850~1910MHz WCDMA Band 4: 1710-1755MHz WCDMA Band 5: 824~849MHz
Downlink Frequency:	WCDMA Band 2: 1930~1990MHz WCDMA Band 4: 2110-2155MHz WCDMA Band 5: 869~894MHz
RF Output Power:	WCDMA Band 2: 21.26dBm, WCDMA Band 4: 21.98dBm, WCDMA Band 5: 22.26dBm
Type of Modulation:	BPSK, QPSK, 16QAM
Antenna Type:	FPC Antenna
Antenna Gain:	WCDMA Band 2: -4.47dBi, WCDMA Band 4: -4.48dBi, WCDMA Band 5: -6.46dBi
4G	
Support Networks:	FDD-LTE, TDD-LTE
Support Band:	FDD-LTE Band 2, 4, 5, 7, 12, 13, 17, 66
Uplink Frequency:	FDD-LTE Band 2: Tx: 1850-1910MHz, FDD-LTE Band 4: Tx: 1710-1755MHz, FDD-LTE Band 5: Tx: 824-849MHz, FDD-LTE Band 7: Tx: 2500-2570MHz, FDD-LTE Band 12: Tx: 699-716MHz, FDD-LTE Band 13: Tx: 777-787MHz, FDD-LTE Band 17: Tx: 704-716MHz,

	FDD-LTE Band 66: Tx: 1710-1780MHz,
Downlink Frequency:	FDD-LTE Band 2: Rx: 1930-1990MHz, FDD-LTE Band 4: Rx: 2110-2155MHz, FDD-LTE Band 5: Rx: 869-894MHz, FDD-LTE Band 7: Rx: 2620-2690MHz, FDD-LTE Band 12: Rx: 729-746MHz, FDD-LTE Band 13: Rx: 746-756MHz, FDD-LTE Band 17: Rx: 734-746MHz, FDD-LTE Band 66: Rx: 2110-2200MHz,
RF Output Power:	FDD-LTE Band 2: 21.43dBm, FDD-LTE Band 4: 21.77dBm, FDD-LTE Band 5: 22.10dBm, FDD-LTE Band 7: 20.85dBm FDD-LTE Band 12: 22.44dBm, FDD-LTE Band 13: 22.25dBm, FDD-LTE Band 17: 22.44dBm, FDD-LTE Band 66: 22.23dBm
Type of Modulation:	QPSK, 16QAM
Antenna Type:	FPC Antenna
Antenna Gain:	FDD-LTE Band 2: -4.47dBi, FDD-LTE Band 4: -4.48dBi, FDD-LTE Band 5: -6.46dBi, FDD-LTE Band 7: -4.41dBi, FDD-LTE Band 12: -6.39dBi, FDD-LTE Band 13: -6.38dBi, FDD-LTE Band 17: -6.37dBi, FDD-LTE Band 66: -4.48dBi
WIFI(2.4GHz)	
Support Standards:	802.11b, 802.11g, 802.11n-HT20, 802.11n-HT40
Frequency Range:	2412-2462MHz for 11b/g/n(HT20), 2422-2452MHz for 11n(HT40)
Max. RF Output Power:	15.72dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Quantity of Channels:	11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40)
Channel Separation:	5MHz
Antenna Type:	FPC Antenna
Antenna Gain:	1.40dBi
Bluetooth	
Bluetooth Version:	Bluetooth V5.0
Frequency Range:	2402-2480MHz
Max. RF Output Power:	3.67dBm(Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Quantity of Channels:	79/40
Channel Separation:	1MHz/2MHz
Antenna Type:	FPC Antenna
Antenna Gain:	1.53dBi
WIFI(5GHz)	
Support Standards:	802.11a, 802.11n-HT20, 802.11n-HT40, 802.11ac-VHT20, 802.11ac-VHT40, 802.11ac-VHT80

Frequency Range:	5180-5240MHz, 5260-5320MHz, 5500-5700MHz, 5745-5825MHz
Max. RF Output Power:	15.25dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM
Type of Antenna:	FPC Antenna
Antenna Gain:	3.54dBi
<i>Note: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The following report is accordance with FCC 47 CFR Part 2.1093, IEEE Std C95.1: 2019, IEEE Std C95.3: 2002 + Rev. 2008, IEC/IEEE 62209-1528 Ed. 1.0 (2020-10), KDB 447498 D01 v06, KDB 648474 D04 v01r03, KDB 248227 D01 v02r02, KDB 941225 D01 v03r01, KDB 941225 D05 v02r05 , and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02.

The objective is to determine compliance with FCC Part 2.1093 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which is result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02. The public notice KDB 447498 D01 v06 for Mobile and Portable Devices RF Exposure Procedure also.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010. Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

2. Summary of Test Results

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Frequency Band	Head SAR	Body-worn (10mm Gap)	Hotspot (10mm Gap)	SAR _{1g} Limit (W/kg)
	Maximum SAR _{1g} (W/kg)	Maximum SAR _{1g} (W/kg)	Maximum SAR _{1g} (W/kg)	
GSM	0.111	0.293	0.415	1.6
WCDMA	0.072	0.399	0.580	1.6
LTE	0.143	0.526	0.684	1.6
WLAN 2.4GHz	0.171	0.038	0.038	1.6
WLAN 5GHz	0.593	0.098	0.186	1.6
Simultaneous Transmission	0.714	0.607	0.684	1.6

Remark:

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2.1093 and IEEE Std C95.1: 2019, and had been tested in accordance with the measurement methods and procedure specified in IEC/IEEE 62209-1528 Ed. 1.0 (2020-10) and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02.

3. Specific Absorption Rate (SAR)

3.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

4. SAR Measurement System

4.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.




The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

4.2 Probe

For the measurements the Specific Dosimetric E-Field Probe SSE2 3823-EPGO-435, and refer to the calibration report for probe parameters.

Probe calibration is realized, in compliance with EN 62209-1 and IEC/IEEE 62209-1528 Ed. 1.0 (2020-10) STD, with CALISAR, Antenna proprietary calibration system. The calibration is performed with the EN 62209-1 annexes technique using reference guide at the five frequencies.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\delta} \cos^2\left(\pi \frac{y}{a}\right) e^{-(2z/\delta)}$$

Where :

P_{fw} = Forward Power

P_{bw} = Backward Power

a and b =Waveguide dimensions

δ = Skin depth

Keithley configuration:

Rate = Medium; Filter = ON; RDGS = 10; Filter type = Moving Average; Range auto after each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it. The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N) = SAR(N)/V_{lin}(N) \quad (N=1,2,3)$$

The linearised output voltage $V_{lin}(N)$ is obtained from the displayed output voltage $V(N)$ using

$$V_{lin}(N) = V(N) * (1 + V(N)/DCP(N)) \quad (N=1,2,3)$$

where DCP is the diode compression point in mV.

4.3 Probe Calibration Process

Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an with CALISAR, Antenna proprietary calibration system.

Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1mW/cm².

Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:

Δt = exposure time (30 seconds),
 C = heat capacity of tissue (brain or muscle),
 ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = simulated tissue conductivity,


ρ = Tissue density (1.25 g/cm³ for brain tissue)

4.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

4.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1°.



System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005

4.6 Test Equipment List

Fixed asset Number	Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
WTXE1053A1006	E-Field Probe	MVG	SSE2	3823-EPGO-435	2024-07-11	2025-07-10
WTXE1053A1001-001	750MHz Dipole	MVG	SID750	SN 47/12 DIP 0G750-203	2023-08-20	2026-08-19
WTXE1053A1001-002	835MHz Dipole	MVG	SID835	SN 47/12 DIP 0G835-204	2023-08-20	2026-08-19
WTXE1053A1001-004	1800MHz Dipole	MVG	SID1800	SN 47/12 DIP 1G800-206	2023-08-20	2026-08-19
WTXE1053A1001-005	1900MHz Dipole	MVG	SID1900	SN 47/12 DIP 1G900-207	2023-08-20	2026-08-19
WTXE1053A1001-007	2450MHz Dipole	MVG	SID2450	SN 13/15 DIP 2G450-364	2023-08-20	2026-08-19
WTXE1053A1006-002	2600MHz Dipole	MVG	SID2600	SN 28/21 DIP 2G600-590	2024-07-11	2027-07-10
WTXE1035A1009	5 GHz Dipole	MVG	SID5000	SN 02/21 DIP 5G000-543	2024-07-11	2027-07-10
WTXE1053A1001-010	Dielectric Probe	SATIMO	SCLMP	SN 47/12 OCPG49	2024-02-24	2025-02-23
WTXE1075A1003	Power meter	Keithley	3500	1232959	2024-02-24	2025-02-23
WTXE1075A1002	Power meter	Keithley	3500	1162591	2024-02-24	2025-02-23
WTXE1104A1003	EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61252892	2024-02-24	2025-02-23
WTXE1022A1002	GSM Tester	Rohde & Schwarz	CMU200	114403	2024-02-27	2025-02-26
WTXE1041A1002	Communications Tester	Rohde & Schwarz	CMW500	148650	2024-03-19	2025-03-18
WTXE1036A1001	Network Analyzer	Rohde & Schwarz	ZVB 8	101353	2023-10-17	2024-10-16

5. Tissue Simulating Liquids

5.1 Composition of Tissue Simulating Liquid

For the measurement of the field distribution inside the SAM phantom with SMTIMO, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. Please see the following photos for the liquid height.



Liquid Height for Head/Body SAR

The Composition of Tissue Simulating Liquid

Frequency (MHz)	Water (%)	Salt (%)	Sugar (%)	HEC (%)	Preventol (%)	DGBE (%)
Head/Body						
750	41.1	1.4	57.0	0.2	0.3	0
835	40.3	1.4	57.9	0.2	0.2	0
1700-1900	55.2	0.3	0	0	0	44.5
2450	55.0	0.1	0	0	0	44.9
2600	54.9	0.1	0	0	0	45.0

Frequency (MHz)	Water (%)	Hexyl Carbitol (%)	Triton X-100 (%)
Head/Body			
5200-5800	65.52	17.24	17.24

5.2 Tissue Dielectric Parameters for Head and Body Phantoms

According to FCC KDBs, IEC/IEEE 62209-1528 Ed. 1.0 (2020-10) and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

Target Frequency (MHz)	Head	
	Conductivity (σ)	Permittivity (ϵ_r)
150	0.76	52.3
300	0.87	45.3
450	0.87	43.5
750	0.89	41.9
835	0.90	41.5
900	0.97	41.5
915	0.98	41.5
1450	1.20	40.5
1800-2000	1.40	40.0
2100	1.49	39.8
2300	1.67	39.5
2450	1.80	39.2
2600	1.96	39.0
3000	2.40	38.5
3500	2.91	37.9
4000	3.43	37.4
4500	3.94	36.8
5000	4.45	36.2
5200	4.66	36.0
5400	4.86	35.8
5600	5.07	35.5
5800	5.27	35.3
6000	5.48	35.1

5.3 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using COMOSAR Dielectric Probe Kit and an Agilent Network Analyzer.

Calibration Result for Dielectric Parameters of Tissue Simulating Liquid

Head Tissue Simulating Liquid									
Freq. MHz	Temp. (℃)	Conductivity			Permittivity			Limit (%)	Date
		Reading (σ)	Target (σ)	Delta (%)	Reading (ε r)	Target (ε r)	Delta (%)		
750	22.6	0.87	0.89	-2.25	41.08	41.90	-1.96	±5	2024-08-10
835	22.6	0.88	0.90	-2.22	40.98	41.50	-1.25	±5	2024-08-11
1800	22.4	1.39	1.40	-0.71	39.26	40.00	-1.85	±5	2024-08-13
1900	22.4	1.42	1.40	1.43	40.94	40.00	2.35	±5	2024-08-15
2450	22.5	1.76	1.80	-2.22	38.51	39.20	-1.76	±5	2024-08-17
2600	22.5	1.92	1.96	-2.04	39.82	39.00	2.10	±5	2024-08-19
5200	22.5	4.63	4.66	-0.64	37.45	36.00	4.03	±5	2024-08-20
5400	22.5	4.87	4.86	0.21	36.62	35.80	2.29	±5	2024-08-20
5600	22.6	5.10	5.07	0.59	35.88	35.50	1.07	±5	2024-08-21
5800	22.6	5.24	5.27	-0.57	34.74	35.30	-1.59	±5	2024-08-21


6. SAR Measurement Evaluation

6.1 Purpose of System Performance Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

6.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator at frequency 835MHz, 1800MHz, 1900MHz, 2450MHz, 2600MHz, and 5GHz. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom.



System Verification Setup Block Diagram



Setup Photo of Dipole Antenna

The output power on dipole port must be calibrated to 24 dBm(250 mW) before dipole is connected.

6.3 Validation Results

Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10 %. Table 6.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion.

Frequency	Power	Targeted SAR _{1g}	Measured SAR _{1g}	Normalized SAR _{1g}	Tolerance	Date
MHz	(mw)	(W/kg)	(W/kg)	(W/kg)	(%)	
Head						
750	250	8.78	2.051	8.204	-6.56	2024-08-10
835	250	9.65	2.210	8.84	-8.39	2024-08-11
1800	250	38.49	9.624	38.496	0.02	2024-08-13
1900	250	39.59	10.223	40.892	3.29	2024-08-15
2450	250	53.76	13.747	54.988	2.28	2024-08-17
2600	250	56.81	14.815	59.26	4.31	2024-08-19
5200	250	75.31	18.567	74.268	-1.38	2024-08-20
5400	250	79.56	18.979	75.916	-4.58	2024-08-20
5600	250	78.31	19.008	76.032	-2.91	2024-08-21
5800	250	78.05	18.087	72.348	-7.31	2024-08-21

Remark: Referring to IEC/IEEE 62209-1528 Ed. 1.0 (2020-10), the system check shall be performed at a test frequency that is within $\pm 10\%$ or ± 100 MHz of the compliance test mid-band frequency, so the 1750 MHz system verification is made of 1800MHz Dipole.

Targeted and Measurement SAR

Please refer to Annex A for the plots of system performance check.

7. EUT Testing Position

7.1 Define Two Imaginary Lines on The Handset

- (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Illustration for Handset Vertical and Horizontal Reference Lines

7.2 Cheek Position

(a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

(b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 7.2).




Illustration for Cheek Position

7.3 Tilted Position

(a) To position the device in the “cheek” position described above.

(b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 7.3).




Illustration for Tilted Position

7.4 Body Position

- (a) To position the device parallel to the phantom surface with each side.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 10mm.




Illustration for Body Position

7.5 EUT Antenna Position



Block Diagram for EUT Antenna Position

Distance of EUT antenna-to-edge/surface(mm),						
Antennas	Back side	Front side	Left Edge	Right Edge	Top Edge	Bottom Edge
WWAN	<25	<25	<25	<25	152	<25
WLAN/BT	<25	<25	45	<25	<25	152

7.6 EUT Testing Position

Head/Body mode SAR assessments are required for this device. This EUT was tested in different positions for different SAR test modes, more information as below:

Head SAR tests				
Antennas	Right Cheek	Left Cheek	Right Tilted	Left Tilted
WWAN	Yes	Yes	Yes	Yes
WLAN/BT	Yes	Yes	Yes	Yes

Body SAR tests, Test distance: 10mm						
Antennas	Back side	Front side	Left Edge	Right Edge	Top Edge	Bottom Edge
WWAN	Yes	Yes	Yes	Yes	No	Yes
WLAN/BT	Yes	Yes	No	Yes	Yes	No

Remark:

- Referring to KDB 941225 D06, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test separation distances is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge. When the form factor of a handset is smaller than $9\text{ cm} \times 5\text{ cm}$, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode.
- Referring to KDB 648474 D04 Handset SAR v01r03, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR $> 1.2\text{ W/kg}$.

Please refer to Annex D for the EUT test setup photos.

8. SAR Measurement Procedures

8.1 Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Annex D demonstrates.
- (e) Set scan area, grid size and other setting on the SATIMO software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.2 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The SATIMO software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

8.4 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.5 SAR Averaged Methods

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10g and 1 g requires a very fine resolution in the three dimensional scanned data array.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In SATIMO measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

9. SAR Test Result

9.1 Conducted RF Output Power

GSM - Burst Average Power (dBm)								
Band	GSM850			Tune-up power (dBm)	PCS1900			Tune-up power (dBm)
Channel	128	190	251		512	661	810	
Frequency (MHz)	824.2	836.6	848.8		1850.2	1880	1909.8	
GSM	32.08	32.21	32.06	32.5	28.42	28.31	28.24	28.5
GPRS (1 slot)	32.09	32.17	32.01	32.5	28.41	28.36	28.27	28.5
GPRS (2 slots)	29.92	30.05	29.96	30.5	26.16	26.08	25.94	26.5
GPRS (3 slots)	27.99	28.16	28.14	28.5	24.59	24.53	24.41	25.0
GPRS (4 slots)	25.91	26.11	26.15	26.5	22.67	22.64	22.52	23.0
EGPRS (1 slot)	24.88	24.74	24.98	25.0	24.76	24.44	23.58	25.0
EGPRS (2 slots)	23.74	23.78	24.06	24.5	22.71	22.57	21.72	23.0
EGPRS (3 slots)	21.39	21.39	21.67	22.0	20.53	20.35	19.60	21.0
EGPRS (4 slots)	19.07	19.14	19.39	20.0	18.60	18.48	17.64	19.0

GSM - Source-Based Time-Average Power (dBm)								
Band	GSM850			Tune-up power (dBm)	PCS1900			Tune-up power (dBm)
Channel	128	190	251		512	661	810	
Frequency (MHz)	824.2	836.6	848.8		1850.2	1880	1909.8	
GSM	23.08	23.21	23.06	23.5	19.42	19.31	19.24	20.0
GPRS (1 slot)	23.09	23.17	23.01	23.5	19.41	19.36	19.27	20.0
GPRS (2 slots)	23.92	24.05	23.96	24.5	20.16	20.08	19.94	20.5
GPRS (3 slots)	23.74	23.91	23.89	24.0	20.34	20.28	20.16	20.5
GPRS (4 slots)	22.91	23.11	23.15	23.5	19.67	19.64	19.52	20.0
EGPRS (1 slot)	15.88	15.74	15.98	16.0	15.76	15.44	14.58	16.0
EGPRS (2 slots)	17.74	17.78	18.06	18.5	16.71	16.57	15.72	17.0
EGPRS (3 slots)	17.14	17.14	17.42	17.5	16.28	16.10	15.35	16.5
EGPRS (4 slots)	16.07	16.14	16.39	17.0	15.60	15.48	14.64	16.0

Note: The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below:

Source based time-average power = Burst averaged power - Duty cycle factor in dB

Duty cycle factor = 9 dB for 1 Tx slot, 6 dB for 2 Tx slots, 4.25 dB for 3 Tx slots, 3 dB for 4 Tx slots

Remark:

1. For Head SAR testing, GSM should be evaluated; therefore the EUT was set in GSM for GSM850 and GSM1900 due to its highest source-based time-average power.
2. For Body SAR testing, GPRS should be evaluated; therefore the EUT was set in GPRS (2TX slots) for

GSM850 and GPRS (3TX slots) for GSM1900, due to its highest source-based time-average power.

3. Per KDB 447498 D01 v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.

4. The DUT do not support DTM function.

WCDMA - Average Power (dBm)								
Band	WCDMA Band II				WCDMA Band IV			
Channel	9262	9400	9538	Tune-up power (dBm)	1312	1413	1513	Tune-up power (dBm)
Frequency (MHz)	1852.4	1880.0	1907.6		1712.4	1732.6	1752.6	
RMC 12.2k	21.26	21.23	21.08	21.5	21.98	21.95	21.83	22.0
HSDPA Subtest-1	20.94	21.17	20.63	21.5	21.71	21.8	21.52	22.0
HSDPA Subtest-2	20.69	20.94	20.42	21.5	21.84	21.91	21.69	22.0
HSDPA Subtest-3	20.45	20.75	20.25	21.5	21.84	21.93	21.67	22.0
HSDPA Subtest-4	20.50	20.71	20.29	21.5	21.87	21.90	21.71	22.0
HSUPA Subtest-1	18.92	19.26	18.86	21.5	21.71	21.85	21.6	22.0
HSUPA Subtest-2	18.82	19.05	18.80	21.5	21.27	21.45	21.11	22.0
HSUPA Subtest-3	19.28	19.59	19.21	21.5	21.8	21.91	21.66	22.0
HSUPA Subtest-4	19.35	19.41	19.08	21.5	21.88	21.73	21.53	22.0
HSUPA Subtest-5	20.78	21.19	20.67	21.5	21.7	21.82	21.65	22.0

WCDMA - Average Power (dBm)								
Band	WCDMA Band V							
Channel	4132	4182	4233	Tune-up power (dBm)				
Frequency (MHz)	826.4	836.4	846.6					
RMC 12.2k	22.26	22.04	21.98	22.5				
HSDPA Subtest-1	21.78	21.28	21.09	22.5				
HSDPA Subtest-2	21.58	20.99	21.06	22.5				
HSDPA Subtest-3	20.98	20.59	20.51	22.5				
HSDPA Subtest-4	21.02	20.58	20.51	22.5				
HSUPA Subtest-1	20.01	19.46	19.43	22.5				
HSUPA Subtest-2	20.44	20.07	20.03	22.5				
HSUPA Subtest-3	20.04	19.52	19.5	22.5				
HSUPA Subtest-4	19.62	19.07	19.05	22.5				
HSUPA Subtest-5	21.45	21.54	21.37	22.5				

Remark:

1. Per KDB 941225 D01 v03, the 12.2kbps RMC mode was selected for SAR testing (the primary mode).
2. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

FDD-LTE Band 2:

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Verdict
Band2	1.4MHz	QPSK	18607	1RB#0	21.19	PASS
Band2	1.4MHz	16QAM	18607	1RB#0	20.64	PASS
Band2	1.4MHz	QPSK	18607	1RB#2	21.21	PASS
Band2	1.4MHz	16QAM	18607	1RB#2	20.61	PASS
Band2	1.4MHz	QPSK	18607	1RB#5	21.25	PASS
Band2	1.4MHz	16QAM	18607	1RB#5	20.64	PASS
Band2	1.4MHz	QPSK	18607	3RB#0	21.28	PASS
Band2	1.4MHz	16QAM	18607	3RB#0	20.69	PASS
Band2	1.4MHz	QPSK	18607	3RB#1	21.26	PASS
Band2	1.4MHz	16QAM	18607	3RB#1	20.80	PASS
Band2	1.4MHz	QPSK	18607	3RB#3	21.26	PASS
Band2	1.4MHz	16QAM	18607	3RB#3	20.68	PASS
Band2	1.4MHz	QPSK	18607	6RB#0	20.75	PASS
Band2	1.4MHz	16QAM	18607	6RB#0	19.97	PASS
Band2	1.4MHz	QPSK	18900	1RB#0	21.03	PASS
Band2	1.4MHz	16QAM	18900	1RB#0	21.10	PASS
Band2	1.4MHz	QPSK	18900	1RB#2	21.10	PASS
Band2	1.4MHz	16QAM	18900	1RB#2	21.08	PASS
Band2	1.4MHz	QPSK	18900	1RB#5	21.05	PASS
Band2	1.4MHz	16QAM	18900	1RB#5	21.10	PASS
Band2	1.4MHz	QPSK	18900	3RB#0	21.20	PASS
Band2	1.4MHz	16QAM	18900	3RB#0	20.65	PASS
Band2	1.4MHz	QPSK	18900	3RB#1	21.18	PASS
Band2	1.4MHz	16QAM	18900	3RB#1	20.66	PASS
Band2	1.4MHz	QPSK	18900	3RB#3	21.05	PASS
Band2	1.4MHz	16QAM	18900	3RB#3	20.68	PASS
Band2	1.4MHz	QPSK	18900	6RB#0	20.68	PASS
Band2	1.4MHz	16QAM	18900	6RB#0	19.77	PASS
Band2	1.4MHz	QPSK	19193	1RB#0	20.90	PASS
Band2	1.4MHz	16QAM	19193	1RB#0	20.58	PASS
Band2	1.4MHz	QPSK	19193	1RB#2	20.81	PASS
Band2	1.4MHz	16QAM	19193	1RB#2	20.55	PASS
Band2	1.4MHz	QPSK	19193	1RB#5	20.83	PASS
Band2	1.4MHz	16QAM	19193	1RB#5	20.59	PASS
Band2	1.4MHz	QPSK	19193	3RB#0	21.00	PASS
Band2	1.4MHz	16QAM	19193	3RB#0	20.05	PASS
Band2	1.4MHz	QPSK	19193	3RB#1	20.99	PASS
Band2	1.4MHz	16QAM	19193	3RB#1	20.09	PASS
Band2	1.4MHz	QPSK	19193	3RB#3	20.93	PASS

Band2	1.4MHz	16QAM	19193	3RB#3	20.05	PASS
Band2	1.4MHz	QPSK	19193	6RB#0	20.47	PASS
Band2	1.4MHz	16QAM	19193	6RB#0	19.59	PASS
Band2	3MHz	QPSK	18615	1RB#0	21.11	PASS
Band2	3MHz	16QAM	18615	1RB#0	20.52	PASS
Band2	3MHz	QPSK	18615	1RB#8	21.06	PASS
Band2	3MHz	16QAM	18615	1RB#8	20.47	PASS
Band2	3MHz	QPSK	18615	1RB#14	21.20	PASS
Band2	3MHz	16QAM	18615	1RB#14	20.48	PASS
Band2	3MHz	QPSK	18615	8RB#0	20.64	PASS
Band2	3MHz	16QAM	18615	8RB#0	19.84	PASS
Band2	3MHz	QPSK	18615	8RB#4	20.65	PASS
Band2	3MHz	16QAM	18615	8RB#4	19.84	PASS
Band2	3MHz	QPSK	18615	8RB#7	20.64	PASS
Band2	3MHz	16QAM	18615	8RB#7	19.82	PASS
Band2	3MHz	QPSK	18615	15RB#0	20.64	PASS
Band2	3MHz	16QAM	18615	15RB#0	19.75	PASS
Band2	3MHz	QPSK	18900	1RB#0	21.01	PASS
Band2	3MHz	16QAM	18900	1RB#0	20.73	PASS
Band2	3MHz	QPSK	18900	1RB#8	20.98	PASS
Band2	3MHz	16QAM	18900	1RB#8	20.64	PASS
Band2	3MHz	QPSK	18900	1RB#14	20.91	PASS
Band2	3MHz	16QAM	18900	1RB#14	20.65	PASS
Band2	3MHz	QPSK	18900	8RB#0	20.69	PASS
Band2	3MHz	16QAM	18900	8RB#0	19.90	PASS
Band2	3MHz	QPSK	18900	8RB#4	20.70	PASS
Band2	3MHz	16QAM	18900	8RB#4	19.86	PASS
Band2	3MHz	QPSK	18900	8RB#7	20.64	PASS
Band2	3MHz	16QAM	18900	8RB#7	19.88	PASS
Band2	3MHz	QPSK	18900	15RB#0	20.75	PASS
Band2	3MHz	16QAM	18900	15RB#0	19.63	PASS
Band2	3MHz	QPSK	19185	1RB#0	21.10	PASS
Band2	3MHz	16QAM	19185	1RB#0	20.41	PASS
Band2	3MHz	QPSK	19185	1RB#8	21.11	PASS
Band2	3MHz	16QAM	19185	1RB#8	20.39	PASS
Band2	3MHz	QPSK	19185	1RB#14	21.12	PASS
Band2	3MHz	16QAM	19185	1RB#14	20.47	PASS
Band2	3MHz	QPSK	19185	8RB#0	20.45	PASS
Band2	3MHz	16QAM	19185	8RB#0	19.51	PASS
Band2	3MHz	QPSK	19185	8RB#4	20.40	PASS
Band2	3MHz	16QAM	19185	8RB#4	19.54	PASS
Band2	3MHz	QPSK	19185	8RB#7	20.48	PASS

Band2	3MHz	16QAM	19185	8RB#7	19.59	PASS
Band2	3MHz	QPSK	19185	15RB#0	20.52	PASS
Band2	3MHz	16QAM	19185	15RB#0	19.52	PASS
Band2	5MHz	QPSK	18625	1RB#0	21.19	PASS
Band2	5MHz	16QAM	18625	1RB#0	20.24	PASS
Band2	5MHz	QPSK	18625	1RB#12	21.26	PASS
Band2	5MHz	16QAM	18625	1RB#12	20.32	PASS
Band2	5MHz	QPSK	18625	1RB#24	21.30	PASS
Band2	5MHz	16QAM	18625	1RB#24	20.29	PASS
Band2	5MHz	QPSK	18625	12RB#0	20.78	PASS
Band2	5MHz	16QAM	18625	12RB#0	19.77	PASS
Band2	5MHz	QPSK	18625	12RB#6	20.79	PASS
Band2	5MHz	16QAM	18625	12RB#6	19.77	PASS
Band2	5MHz	QPSK	18625	12RB#13	20.73	PASS
Band2	5MHz	16QAM	18625	12RB#13	19.74	PASS
Band2	5MHz	QPSK	18625	25RB#0	20.78	PASS
Band2	5MHz	16QAM	18625	25RB#0	19.98	PASS
Band2	5MHz	QPSK	18900	1RB#0	21.11	PASS
Band2	5MHz	16QAM	18900	1RB#0	20.75	PASS
Band2	5MHz	QPSK	18900	1RB#12	21.12	PASS
Band2	5MHz	16QAM	18900	1RB#12	20.76	PASS
Band2	5MHz	QPSK	18900	1RB#24	21.10	PASS
Band2	5MHz	16QAM	18900	1RB#24	20.81	PASS
Band2	5MHz	QPSK	18900	12RB#0	20.57	PASS
Band2	5MHz	16QAM	18900	12RB#0	19.79	PASS
Band2	5MHz	QPSK	18900	12RB#6	20.58	PASS
Band2	5MHz	16QAM	18900	12RB#6	19.79	PASS
Band2	5MHz	QPSK	18900	12RB#13	20.60	PASS
Band2	5MHz	16QAM	18900	12RB#13	19.81	PASS
Band2	5MHz	QPSK	18900	25RB#0	20.66	PASS
Band2	5MHz	16QAM	18900	25RB#0	19.72	PASS
Band2	5MHz	QPSK	19175	1RB#0	20.90	PASS
Band2	5MHz	16QAM	19175	1RB#0	20.21	PASS
Band2	5MHz	QPSK	19175	1RB#12	20.86	PASS
Band2	5MHz	16QAM	19175	1RB#12	20.25	PASS
Band2	5MHz	QPSK	19175	1RB#24	20.92	PASS
Band2	5MHz	16QAM	19175	1RB#24	20.14	PASS
Band2	5MHz	QPSK	19175	12RB#0	20.59	PASS
Band2	5MHz	16QAM	19175	12RB#0	19.51	PASS
Band2	5MHz	QPSK	19175	12RB#6	20.50	PASS
Band2	5MHz	16QAM	19175	12RB#6	19.42	PASS
Band2	5MHz	QPSK	19175	12RB#13	20.54	PASS

Band2	5MHz	16QAM	19175	12RB#13	19.45	PASS
Band2	5MHz	QPSK	19175	25RB#0	20.48	PASS
Band2	5MHz	16QAM	19175	25RB#0	19.50	PASS
Band2	10MHz	QPSK	18650	1RB#0	21.18	PASS
Band2	10MHz	16QAM	18650	1RB#0	20.80	PASS
Band2	10MHz	QPSK	18650	1RB#24	21.23	PASS
Band2	10MHz	16QAM	18650	1RB#24	20.78	PASS
Band2	10MHz	QPSK	18650	1RB#49	21.25	PASS
Band2	10MHz	16QAM	18650	1RB#49	20.81	PASS
Band2	10MHz	QPSK	18650	25RB#0	20.87	PASS
Band2	10MHz	16QAM	18650	25RB#0	19.89	PASS
Band2	10MHz	QPSK	18650	25RB#12	20.88	PASS
Band2	10MHz	16QAM	18650	25RB#12	19.91	PASS
Band2	10MHz	QPSK	18650	25RB#25	20.77	PASS
Band2	10MHz	16QAM	18650	25RB#25	19.85	PASS
Band2	10MHz	QPSK	18650	50RB#0	20.75	PASS
Band2	10MHz	16QAM	18650	50RB#0	19.94	PASS
Band2	10MHz	QPSK	18900	1RB#0	21.13	PASS
Band2	10MHz	16QAM	18900	1RB#0	20.52	PASS
Band2	10MHz	QPSK	18900	1RB#24	21.12	PASS
Band2	10MHz	16QAM	18900	1RB#24	20.56	PASS
Band2	10MHz	QPSK	18900	1RB#49	21.12	PASS
Band2	10MHz	16QAM	18900	1RB#49	20.56	PASS
Band2	10MHz	QPSK	18900	25RB#0	20.52	PASS
Band2	10MHz	16QAM	18900	25RB#0	19.85	PASS
Band2	10MHz	QPSK	18900	25RB#12	20.64	PASS
Band2	10MHz	16QAM	18900	25RB#12	19.85	PASS
Band2	10MHz	QPSK	18900	25RB#25	20.58	PASS
Band2	10MHz	16QAM	18900	25RB#25	19.82	PASS
Band2	10MHz	QPSK	18900	50RB#0	20.64	PASS
Band2	10MHz	16QAM	18900	50RB#0	19.70	PASS
Band2	10MHz	QPSK	19150	1RB#0	21.05	PASS
Band2	10MHz	16QAM	19150	1RB#0	20.72	PASS
Band2	10MHz	QPSK	19150	1RB#24	21.02	PASS
Band2	10MHz	16QAM	19150	1RB#24	20.63	PASS
Band2	10MHz	QPSK	19150	1RB#49	20.98	PASS
Band2	10MHz	16QAM	19150	1RB#49	20.57	PASS
Band2	10MHz	QPSK	19150	25RB#0	20.54	PASS
Band2	10MHz	16QAM	19150	25RB#0	19.57	PASS
Band2	10MHz	QPSK	19150	25RB#12	20.62	PASS
Band2	10MHz	16QAM	19150	25RB#12	19.59	PASS
Band2	10MHz	QPSK	19150	25RB#25	20.59	PASS

Band2	10MHz	16QAM	19150	25RB#25	19.57	PASS
Band2	10MHz	QPSK	19150	50RB#0	20.56	PASS
Band2	10MHz	16QAM	19150	50RB#0	19.59	PASS
Band2	15MHz	QPSK	18675	1RB#0	21.22	PASS
Band2	15MHz	16QAM	18675	1RB#0	20.62	PASS
Band2	15MHz	QPSK	18675	1RB#38	21.24	PASS
Band2	15MHz	16QAM	18675	1RB#38	20.56	PASS
Band2	15MHz	QPSK	18675	1RB#74	21.11	PASS
Band2	15MHz	16QAM	18675	1RB#74	20.47	PASS
Band2	15MHz	QPSK	18675	38RB#0	20.69	PASS
Band2	15MHz	16QAM	18675	38RB#0	20.70	PASS
Band2	15MHz	QPSK	18675	38RB#18	20.71	PASS
Band2	15MHz	16QAM	18675	38RB#18	20.71	PASS
Band2	15MHz	QPSK	18675	38RB#37	20.71	PASS
Band2	15MHz	16QAM	18675	38RB#37	20.72	PASS
Band2	15MHz	QPSK	18675	75RB#0	20.71	PASS
Band2	15MHz	16QAM	18675	75RB#0	19.90	PASS
Band2	15MHz	QPSK	18900	1RB#0	20.76	PASS
Band2	15MHz	16QAM	18900	1RB#0	20.50	PASS
Band2	15MHz	QPSK	18900	1RB#38	20.70	PASS
Band2	15MHz	16QAM	18900	1RB#38	20.46	PASS
Band2	15MHz	QPSK	18900	1RB#74	20.69	PASS
Band2	15MHz	16QAM	18900	1RB#74	20.40	PASS
Band2	15MHz	QPSK	18900	38RB#0	20.73	PASS
Band2	15MHz	16QAM	18900	38RB#0	20.71	PASS
Band2	15MHz	QPSK	18900	38RB#18	20.70	PASS
Band2	15MHz	16QAM	18900	38RB#18	20.71	PASS
Band2	15MHz	QPSK	18900	38RB#37	20.71	PASS
Band2	15MHz	16QAM	18900	38RB#37	20.71	PASS
Band2	15MHz	QPSK	18900	75RB#0	20.71	PASS
Band2	15MHz	16QAM	18900	75RB#0	19.72	PASS
Band2	15MHz	QPSK	19125	1RB#0	21.14	PASS
Band2	15MHz	16QAM	19125	1RB#0	20.77	PASS
Band2	15MHz	QPSK	19125	1RB#38	21.06	PASS
Band2	15MHz	16QAM	19125	1RB#38	20.59	PASS
Band2	15MHz	QPSK	19125	1RB#74	20.98	PASS
Band2	15MHz	16QAM	19125	1RB#74	20.61	PASS
Band2	15MHz	QPSK	19125	38RB#0	20.69	PASS
Band2	15MHz	16QAM	19125	38RB#0	20.70	PASS
Band2	15MHz	QPSK	19125	38RB#18	20.71	PASS
Band2	15MHz	16QAM	19125	38RB#18	20.72	PASS
Band2	15MHz	QPSK	19125	38RB#37	20.73	PASS

Band2	15MHz	16QAM	19125	38RB#37	20.73	PASS
Band2	15MHz	QPSK	19125	75RB#0	20.73	PASS
Band2	15MHz	16QAM	19125	75RB#0	19.71	PASS
Band2	20MHz	QPSK	18700	1RB#0	21.26	PASS
Band2	20MHz	16QAM	18700	1RB#0	20.57	PASS
Band2	20MHz	QPSK	18700	1RB#49	21.24	PASS
Band2	20MHz	16QAM	18700	1RB#49	20.47	PASS
Band2	20MHz	QPSK	18700	1RB#99	21.14	PASS
Band2	20MHz	16QAM	18700	1RB#99	20.39	PASS
Band2	20MHz	QPSK	18700	50RB#0	20.98	PASS
Band2	20MHz	16QAM	18700	50RB#0	19.96	PASS
Band2	20MHz	QPSK	18700	50RB#25	20.77	PASS
Band2	20MHz	16QAM	18700	50RB#25	19.94	PASS
Band2	20MHz	QPSK	18700	50RB#50	20.80	PASS
Band2	20MHz	16QAM	18700	50RB#50	19.89	PASS
Band2	20MHz	QPSK	18700	100RB#0	20.83	PASS
Band2	20MHz	16QAM	18700	100RB#0	19.97	PASS
Band2	20MHz	QPSK	18900	1RB#0	21.43	PASS
Band2	20MHz	16QAM	18900	1RB#0	21.28	PASS
Band2	20MHz	QPSK	18900	1RB#49	21.31	PASS
Band2	20MHz	16QAM	18900	1RB#49	21.26	PASS
Band2	20MHz	QPSK	18900	1RB#99	21.40	PASS
Band2	20MHz	16QAM	18900	1RB#99	21.29	PASS
Band2	20MHz	QPSK	18900	50RB#0	20.85	PASS
Band2	20MHz	16QAM	18900	50RB#0	19.91	PASS
Band2	20MHz	QPSK	18900	50RB#25	20.83	PASS
Band2	20MHz	16QAM	18900	50RB#25	19.91	PASS
Band2	20MHz	QPSK	18900	50RB#50	20.65	PASS
Band2	20MHz	16QAM	18900	50RB#50	19.89	PASS
Band2	20MHz	QPSK	18900	100RB#0	20.73	PASS
Band2	20MHz	16QAM	18900	100RB#0	19.87	PASS
Band2	20MHz	QPSK	19100	1RB#0	21.41	PASS
Band2	20MHz	16QAM	19100	1RB#0	20.64	PASS
Band2	20MHz	QPSK	19100	1RB#49	21.35	PASS
Band2	20MHz	16QAM	19100	1RB#49	20.42	PASS
Band2	20MHz	QPSK	19100	1RB#99	21.28	PASS
Band2	20MHz	16QAM	19100	1RB#99	20.49	PASS
Band2	20MHz	QPSK	19100	50RB#0	20.67	PASS
Band2	20MHz	16QAM	19100	50RB#0	19.86	PASS
Band2	20MHz	QPSK	19100	50RB#25	20.81	PASS
Band2	20MHz	16QAM	19100	50RB#25	19.86	PASS
Band2	20MHz	QPSK	19100	50RB#50	20.56	PASS

Band2	20MHz	16QAM	19100	50RB#50	19.81	PASS
Band2	20MHz	QPSK	19100	100RB#0	20.75	PASS
Band2	20MHz	16QAM	19100	100RB#0	19.75	PASS

FDD-LTE Band 4:

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Verdict
Band4	1.4MHz	QPSK	19957	1RB#0	21.36	PASS
Band4	1.4MHz	16QAM	19957	1RB#0	21.29	PASS
Band4	1.4MHz	QPSK	19957	1RB#2	21.32	PASS
Band4	1.4MHz	16QAM	19957	1RB#2	21.30	PASS
Band4	1.4MHz	QPSK	19957	1RB#5	21.33	PASS
Band4	1.4MHz	16QAM	19957	1RB#5	21.27	PASS
Band4	1.4MHz	QPSK	19957	3RB#0	21.35	PASS
Band4	1.4MHz	16QAM	19957	3RB#0	20.81	PASS
Band4	1.4MHz	QPSK	19957	3RB#1	21.34	PASS
Band4	1.4MHz	16QAM	19957	3RB#1	20.83	PASS
Band4	1.4MHz	QPSK	19957	3RB#3	21.36	PASS
Band4	1.4MHz	16QAM	19957	3RB#3	20.81	PASS
Band4	1.4MHz	QPSK	19957	6RB#0	20.83	PASS
Band4	1.4MHz	16QAM	19957	6RB#0	20.00	PASS
Band4	1.4MHz	QPSK	20175	1RB#0	21.35	PASS
Band4	1.4MHz	16QAM	20175	1RB#0	21.12	PASS
Band4	1.4MHz	QPSK	20175	1RB#2	21.37	PASS
Band4	1.4MHz	16QAM	20175	1RB#2	21.15	PASS
Band4	1.4MHz	QPSK	20175	1RB#5	21.32	PASS
Band4	1.4MHz	16QAM	20175	1RB#5	21.20	PASS
Band4	1.4MHz	QPSK	20175	3RB#0	21.26	PASS
Band4	1.4MHz	16QAM	20175	3RB#0	20.74	PASS
Band4	1.4MHz	QPSK	20175	3RB#1	21.26	PASS
Band4	1.4MHz	16QAM	20175	3RB#1	20.74	PASS
Band4	1.4MHz	QPSK	20175	3RB#3	21.29	PASS
Band4	1.4MHz	16QAM	20175	3RB#3	20.74	PASS
Band4	1.4MHz	QPSK	20175	6RB#0	20.75	PASS
Band4	1.4MHz	16QAM	20175	6RB#0	19.92	PASS
Band4	1.4MHz	QPSK	20393	1RB#0	21.34	PASS
Band4	1.4MHz	16QAM	20393	1RB#0	21.71	PASS
Band4	1.4MHz	QPSK	20393	1RB#2	21.30	PASS
Band4	1.4MHz	16QAM	20393	1RB#2	21.69	PASS
Band4	1.4MHz	QPSK	20393	1RB#5	21.33	PASS
Band4	1.4MHz	16QAM	20393	1RB#5	21.71	PASS
Band4	1.4MHz	QPSK	20393	3RB#0	21.32	PASS

Band4	1.4MHz	16QAM	20393	3RB#0	20.21	PASS
Band4	1.4MHz	QPSK	20393	3RB#1	21.34	PASS
Band4	1.4MHz	16QAM	20393	3RB#1	20.21	PASS
Band4	1.4MHz	QPSK	20393	3RB#3	21.31	PASS
Band4	1.4MHz	16QAM	20393	3RB#3	20.19	PASS
Band4	1.4MHz	QPSK	20393	6RB#0	20.84	PASS
Band4	1.4MHz	16QAM	20393	6RB#0	20.00	PASS
Band4	3MHz	QPSK	19965	1RB#0	21.28	PASS
Band4	3MHz	16QAM	19965	1RB#0	21.09	PASS
Band4	3MHz	QPSK	19965	1RB#8	21.27	PASS
Band4	3MHz	16QAM	19965	1RB#8	21.09	PASS
Band4	3MHz	QPSK	19965	1RB#14	21.32	PASS
Band4	3MHz	16QAM	19965	1RB#14	21.05	PASS
Band4	3MHz	QPSK	19965	8RB#0	20.80	PASS
Band4	3MHz	16QAM	19965	8RB#0	20.05	PASS
Band4	3MHz	QPSK	19965	8RB#4	20.84	PASS
Band4	3MHz	16QAM	19965	8RB#4	20.04	PASS
Band4	3MHz	QPSK	19965	8RB#7	20.76	PASS
Band4	3MHz	16QAM	19965	8RB#7	19.91	PASS
Band4	3MHz	QPSK	19965	15RB#0	20.87	PASS
Band4	3MHz	16QAM	19965	15RB#0	19.89	PASS
Band4	3MHz	QPSK	20175	1RB#0	21.27	PASS
Band4	3MHz	16QAM	20175	1RB#0	20.61	PASS
Band4	3MHz	QPSK	20175	1RB#8	21.22	PASS
Band4	3MHz	16QAM	20175	1RB#8	20.58	PASS
Band4	3MHz	QPSK	20175	1RB#14	21.28	PASS
Band4	3MHz	16QAM	20175	1RB#14	20.56	PASS
Band4	3MHz	QPSK	20175	8RB#0	20.72	PASS
Band4	3MHz	16QAM	20175	8RB#0	19.99	PASS
Band4	3MHz	QPSK	20175	8RB#4	20.73	PASS
Band4	3MHz	16QAM	20175	8RB#4	19.99	PASS
Band4	3MHz	QPSK	20175	8RB#7	20.62	PASS
Band4	3MHz	16QAM	20175	8RB#7	19.95	PASS
Band4	3MHz	QPSK	20175	15RB#0	20.77	PASS
Band4	3MHz	16QAM	20175	15RB#0	19.65	PASS
Band4	3MHz	QPSK	20385	1RB#0	21.31	PASS
Band4	3MHz	16QAM	20385	1RB#0	21.01	PASS
Band4	3MHz	QPSK	20385	1RB#8	21.32	PASS
Band4	3MHz	16QAM	20385	1RB#8	20.92	PASS
Band4	3MHz	QPSK	20385	1RB#14	21.26	PASS
Band4	3MHz	16QAM	20385	1RB#14	20.93	PASS
Band4	3MHz	QPSK	20385	8RB#0	20.79	PASS

Band4	3MHz	16QAM	20385	8RB#0	20.08	PASS
Band4	3MHz	QPSK	20385	8RB#4	20.92	PASS
Band4	3MHz	16QAM	20385	8RB#4	20.07	PASS
Band4	3MHz	QPSK	20385	8RB#7	20.89	PASS
Band4	3MHz	16QAM	20385	8RB#7	20.05	PASS
Band4	3MHz	QPSK	20385	15RB#0	20.90	PASS
Band4	3MHz	16QAM	20385	15RB#0	20.06	PASS
Band4	5MHz	QPSK	19975	1RB#0	21.32	PASS
Band4	5MHz	16QAM	19975	1RB#0	20.92	PASS
Band4	5MHz	QPSK	19975	1RB#12	21.36	PASS
Band4	5MHz	16QAM	19975	1RB#12	20.85	PASS
Band4	5MHz	QPSK	19975	1RB#24	21.37	PASS
Band4	5MHz	16QAM	19975	1RB#24	20.82	PASS
Band4	5MHz	QPSK	19975	12RB#0	20.85	PASS
Band4	5MHz	16QAM	19975	12RB#0	19.79	PASS
Band4	5MHz	QPSK	19975	12RB#6	20.93	PASS
Band4	5MHz	16QAM	19975	12RB#6	19.83	PASS
Band4	5MHz	QPSK	19975	12RB#13	20.85	PASS
Band4	5MHz	16QAM	19975	12RB#13	19.85	PASS
Band4	5MHz	QPSK	19975	25RB#0	20.70	PASS
Band4	5MHz	16QAM	19975	25RB#0	19.90	PASS
Band4	5MHz	QPSK	20175	1RB#0	21.31	PASS
Band4	5MHz	16QAM	20175	1RB#0	21.37	PASS
Band4	5MHz	QPSK	20175	1RB#12	21.19	PASS
Band4	5MHz	16QAM	20175	1RB#12	21.43	PASS
Band4	5MHz	QPSK	20175	1RB#24	21.26	PASS
Band4	5MHz	16QAM	20175	1RB#24	21.41	PASS
Band4	5MHz	QPSK	20175	12RB#0	20.81	PASS
Band4	5MHz	16QAM	20175	12RB#0	19.91	PASS
Band4	5MHz	QPSK	20175	12RB#6	20.84	PASS
Band4	5MHz	16QAM	20175	12RB#6	19.94	PASS
Band4	5MHz	QPSK	20175	12RB#13	20.71	PASS
Band4	5MHz	16QAM	20175	12RB#13	19.88	PASS
Band4	5MHz	QPSK	20175	25RB#0	20.81	PASS
Band4	5MHz	16QAM	20175	25RB#0	19.83	PASS
Band4	5MHz	QPSK	20375	1RB#0	21.25	PASS
Band4	5MHz	16QAM	20375	1RB#0	20.87	PASS
Band4	5MHz	QPSK	20375	1RB#12	21.34	PASS
Band4	5MHz	16QAM	20375	1RB#12	20.86	PASS
Band4	5MHz	QPSK	20375	1RB#24	21.33	PASS
Band4	5MHz	16QAM	20375	1RB#24	20.94	PASS
Band4	5MHz	QPSK	20375	12RB#0	20.75	PASS

Band4	5MHz	16QAM	20375	12RB#0	19.81	PASS
Band4	5MHz	QPSK	20375	12RB#6	20.77	PASS
Band4	5MHz	16QAM	20375	12RB#6	19.82	PASS
Band4	5MHz	QPSK	20375	12RB#13	20.83	PASS
Band4	5MHz	16QAM	20375	12RB#13	19.84	PASS
Band4	5MHz	QPSK	20375	25RB#0	20.87	PASS
Band4	5MHz	16QAM	20375	25RB#0	19.92	PASS
Band4	10MHz	QPSK	20000	1RB#0	21.35	PASS
Band4	10MHz	16QAM	20000	1RB#0	21.44	PASS
Band4	10MHz	QPSK	20000	1RB#24	21.30	PASS
Band4	10MHz	16QAM	20000	1RB#24	21.36	PASS
Band4	10MHz	QPSK	20000	1RB#49	21.31	PASS
Band4	10MHz	16QAM	20000	1RB#49	21.40	PASS
Band4	10MHz	QPSK	20000	25RB#0	20.81	PASS
Band4	10MHz	16QAM	20000	25RB#0	19.90	PASS
Band4	10MHz	QPSK	20000	25RB#12	20.94	PASS
Band4	10MHz	16QAM	20000	25RB#12	19.91	PASS
Band4	10MHz	QPSK	20000	25RB#25	20.92	PASS
Band4	10MHz	16QAM	20000	25RB#25	19.91	PASS
Band4	10MHz	QPSK	20000	50RB#0	20.88	PASS
Band4	10MHz	16QAM	20000	50RB#0	19.95	PASS
Band4	10MHz	QPSK	20175	1RB#0	21.35	PASS
Band4	10MHz	16QAM	20175	1RB#0	21.25	PASS
Band4	10MHz	QPSK	20175	1RB#24	21.18	PASS
Band4	10MHz	16QAM	20175	1RB#24	21.16	PASS
Band4	10MHz	QPSK	20175	1RB#49	21.09	PASS
Band4	10MHz	16QAM	20175	1RB#49	21.04	PASS
Band4	10MHz	QPSK	20175	25RB#0	20.76	PASS
Band4	10MHz	16QAM	20175	25RB#0	19.93	PASS
Band4	10MHz	QPSK	20175	25RB#12	20.69	PASS
Band4	10MHz	16QAM	20175	25RB#12	19.93	PASS
Band4	10MHz	QPSK	20175	25RB#25	20.73	PASS
Band4	10MHz	16QAM	20175	25RB#25	19.89	PASS
Band4	10MHz	QPSK	20175	50RB#0	20.75	PASS
Band4	10MHz	16QAM	20175	50RB#0	19.76	PASS
Band4	10MHz	QPSK	20350	1RB#0	21.34	PASS
Band4	10MHz	16QAM	20350	1RB#0	21.39	PASS
Band4	10MHz	QPSK	20350	1RB#24	21.34	PASS
Band4	10MHz	16QAM	20350	1RB#24	21.38	PASS
Band4	10MHz	QPSK	20350	1RB#49	21.36	PASS
Band4	10MHz	16QAM	20350	1RB#49	21.43	PASS
Band4	10MHz	QPSK	20350	25RB#0	20.93	PASS

Band4	10MHz	16QAM	20350	25RB#0	19.96	PASS
Band4	10MHz	QPSK	20350	25RB#12	20.96	PASS
Band4	10MHz	16QAM	20350	25RB#12	19.89	PASS
Band4	10MHz	QPSK	20350	25RB#25	20.94	PASS
Band4	10MHz	16QAM	20350	25RB#25	19.94	PASS
Band4	10MHz	QPSK	20350	50RB#0	20.80	PASS
Band4	10MHz	16QAM	20350	50RB#0	20.03	PASS
Band4	15MHz	QPSK	20025	1RB#0	21.40	PASS
Band4	15MHz	16QAM	20025	1RB#0	21.52	PASS
Band4	15MHz	QPSK	20025	1RB#38	21.32	PASS
Band4	15MHz	16QAM	20025	1RB#38	21.42	PASS
Band4	15MHz	QPSK	20025	1RB#74	21.29	PASS
Band4	15MHz	16QAM	20025	1RB#74	21.44	PASS
Band4	15MHz	QPSK	20025	38RB#0	20.87	PASS
Band4	15MHz	16QAM	20025	38RB#0	20.86	PASS
Band4	15MHz	QPSK	20025	38RB#18	20.85	PASS
Band4	15MHz	16QAM	20025	38RB#18	20.85	PASS
Band4	15MHz	QPSK	20025	38RB#37	20.85	PASS
Band4	15MHz	16QAM	20025	38RB#37	20.87	PASS
Band4	15MHz	QPSK	20025	75RB#0	20.86	PASS
Band4	15MHz	16QAM	20025	75RB#0	19.89	PASS
Band4	15MHz	QPSK	20175	1RB#0	21.30	PASS
Band4	15MHz	16QAM	20175	1RB#0	21.41	PASS
Band4	15MHz	QPSK	20175	1RB#38	21.23	PASS
Band4	15MHz	16QAM	20175	1RB#38	21.29	PASS
Band4	15MHz	QPSK	20175	1RB#74	21.00	PASS
Band4	15MHz	16QAM	20175	1RB#74	21.16	PASS
Band4	15MHz	QPSK	20175	38RB#0	20.73	PASS
Band4	15MHz	16QAM	20175	38RB#0	20.73	PASS
Band4	15MHz	QPSK	20175	38RB#18	20.73	PASS
Band4	15MHz	16QAM	20175	38RB#18	20.74	PASS
Band4	15MHz	QPSK	20175	38RB#37	20.74	PASS
Band4	15MHz	16QAM	20175	38RB#37	20.74	PASS
Band4	15MHz	QPSK	20175	75RB#0	20.73	PASS
Band4	15MHz	16QAM	20175	75RB#0	19.83	PASS
Band4	15MHz	QPSK	20325	1RB#0	21.32	PASS
Band4	15MHz	16QAM	20325	1RB#0	21.41	PASS
Band4	15MHz	QPSK	20325	1RB#38	21.23	PASS
Band4	15MHz	16QAM	20325	1RB#38	21.33	PASS
Band4	15MHz	QPSK	20325	1RB#74	21.24	PASS
Band4	15MHz	16QAM	20325	1RB#74	21.38	PASS
Band4	15MHz	QPSK	20325	38RB#0	20.81	PASS

Band4	15MHz	16QAM	20325	38RB#0	20.82	PASS
Band4	15MHz	QPSK	20325	38RB#18	20.83	PASS
Band4	15MHz	16QAM	20325	38RB#18	20.83	PASS
Band4	15MHz	QPSK	20325	38RB#37	20.83	PASS
Band4	15MHz	16QAM	20325	38RB#37	20.83	PASS
Band4	15MHz	QPSK	20325	75RB#0	20.83	PASS
Band4	15MHz	16QAM	20325	75RB#0	19.71	PASS
Band4	20MHz	QPSK	20050	1RB#0	21.59	PASS
Band4	20MHz	16QAM	20050	1RB#0	21.28	PASS
Band4	20MHz	QPSK	20050	1RB#49	21.55	PASS
Band4	20MHz	16QAM	20050	1RB#49	21.27	PASS
Band4	20MHz	QPSK	20050	1RB#99	21.46	PASS
Band4	20MHz	16QAM	20050	1RB#99	21.22	PASS
Band4	20MHz	QPSK	20050	50RB#0	20.94	PASS
Band4	20MHz	16QAM	20050	50RB#0	20.09	PASS
Band4	20MHz	QPSK	20050	50RB#25	20.96	PASS
Band4	20MHz	16QAM	20050	50RB#25	20.10	PASS
Band4	20MHz	QPSK	20050	50RB#50	20.93	PASS
Band4	20MHz	16QAM	20050	50RB#50	20.06	PASS
Band4	20MHz	QPSK	20050	100RB#0	20.93	PASS
Band4	20MHz	16QAM	20050	100RB#0	19.93	PASS
Band4	20MHz	QPSK	20175	1RB#0	21.48	PASS
Band4	20MHz	16QAM	20175	1RB#0	21.16	PASS
Band4	20MHz	QPSK	20175	1RB#49	21.42	PASS
Band4	20MHz	16QAM	20175	1RB#49	21.17	PASS
Band4	20MHz	QPSK	20175	1RB#99	21.29	PASS
Band4	20MHz	16QAM	20175	1RB#99	20.91	PASS
Band4	20MHz	QPSK	20175	50RB#0	20.93	PASS
Band4	20MHz	16QAM	20175	50RB#0	20.07	PASS
Band4	20MHz	QPSK	20175	50RB#25	20.94	PASS
Band4	20MHz	16QAM	20175	50RB#25	20.07	PASS
Band4	20MHz	QPSK	20175	50RB#50	20.68	PASS
Band4	20MHz	16QAM	20175	50RB#50	19.81	PASS
Band4	20MHz	QPSK	20175	100RB#0	20.80	PASS
Band4	20MHz	16QAM	20175	100RB#0	19.78	PASS
Band4	20MHz	QPSK	20300	1RB#0	21.77	PASS
Band4	20MHz	16QAM	20300	1RB#0	20.84	PASS
Band4	20MHz	QPSK	20300	1RB#49	21.57	PASS
Band4	20MHz	16QAM	20300	1RB#49	20.72	PASS
Band4	20MHz	QPSK	20300	1RB#99	21.60	PASS
Band4	20MHz	16QAM	20300	1RB#99	20.80	PASS
Band4	20MHz	QPSK	20300	50RB#0	20.89	PASS

Band4	20MHz	16QAM	20300	50RB#0	20.04	PASS
Band4	20MHz	QPSK	20300	50RB#25	20.91	PASS
Band4	20MHz	16QAM	20300	50RB#25	19.98	PASS
Band4	20MHz	QPSK	20300	50RB#50	20.81	PASS
Band4	20MHz	16QAM	20300	50RB#50	19.92	PASS
Band4	20MHz	QPSK	20300	100RB#0	20.88	PASS
Band4	20MHz	16QAM	20300	100RB#0	19.89	PASS

FDD-LTE Band 5:

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Verdict
Band5	1.4MHz	QPSK	20407	1RB#0	21.93	PASS
Band5	1.4MHz	16QAM	20407	1RB#0	22.05	PASS
Band5	1.4MHz	QPSK	20407	1RB#2	21.85	PASS
Band5	1.4MHz	16QAM	20407	1RB#2	22.08	PASS
Band5	1.4MHz	QPSK	20407	1RB#5	21.88	PASS
Band5	1.4MHz	16QAM	20407	1RB#5	22.01	PASS
Band5	1.4MHz	QPSK	20407	3RB#0	21.98	PASS
Band5	1.4MHz	16QAM	20407	3RB#0	20.91	PASS
Band5	1.4MHz	QPSK	20407	3RB#1	21.94	PASS
Band5	1.4MHz	16QAM	20407	3RB#1	20.91	PASS
Band5	1.4MHz	QPSK	20407	3RB#3	21.97	PASS
Band5	1.4MHz	16QAM	20407	3RB#3	20.91	PASS
Band5	1.4MHz	QPSK	20407	6RB#0	21.54	PASS
Band5	1.4MHz	16QAM	20407	6RB#0	20.53	PASS
Band5	1.4MHz	QPSK	20525	1RB#0	21.37	PASS
Band5	1.4MHz	16QAM	20525	1RB#0	21.56	PASS
Band5	1.4MHz	QPSK	20525	1RB#2	21.41	PASS
Band5	1.4MHz	16QAM	20525	1RB#2	21.60	PASS
Band5	1.4MHz	QPSK	20525	1RB#5	21.28	PASS
Band5	1.4MHz	16QAM	20525	1RB#5	21.52	PASS
Band5	1.4MHz	QPSK	20525	3RB#0	21.54	PASS
Band5	1.4MHz	16QAM	20525	3RB#0	20.47	PASS
Band5	1.4MHz	QPSK	20525	3RB#1	21.54	PASS
Band5	1.4MHz	16QAM	20525	3RB#1	20.50	PASS
Band5	1.4MHz	QPSK	20525	3RB#3	21.44	PASS
Band5	1.4MHz	16QAM	20525	3RB#3	20.34	PASS
Band5	1.4MHz	QPSK	20525	6RB#0	20.96	PASS
Band5	1.4MHz	16QAM	20525	6RB#0	20.40	PASS
Band5	1.4MHz	QPSK	20643	1RB#0	21.76	PASS
Band5	1.4MHz	16QAM	20643	1RB#0	21.93	PASS
Band5	1.4MHz	QPSK	20643	1RB#2	21.31	PASS

Band5	1.4MHz	16QAM	20643	1RB#2	21.51	PASS
Band5	1.4MHz	QPSK	20643	1RB#5	21.31	PASS
Band5	1.4MHz	16QAM	20643	1RB#5	21.30	PASS
Band5	1.4MHz	QPSK	20643	3RB#0	21.79	PASS
Band5	1.4MHz	16QAM	20643	3RB#0	20.74	PASS
Band5	1.4MHz	QPSK	20643	3RB#1	21.79	PASS
Band5	1.4MHz	16QAM	20643	3RB#1	20.80	PASS
Band5	1.4MHz	QPSK	20643	3RB#3	21.36	PASS
Band5	1.4MHz	16QAM	20643	3RB#3	20.34	PASS
Band5	1.4MHz	QPSK	20643	6RB#0	20.79	PASS
Band5	1.4MHz	16QAM	20643	6RB#0	20.31	PASS
Band5	3MHz	QPSK	20415	1RB#0	21.92	PASS
Band5	3MHz	16QAM	20415	1RB#0	21.57	PASS
Band5	3MHz	QPSK	20415	1RB#8	21.87	PASS
Band5	3MHz	16QAM	20415	1RB#8	21.50	PASS
Band5	3MHz	QPSK	20415	1RB#14	21.50	PASS
Band5	3MHz	16QAM	20415	1RB#14	21.14	PASS
Band5	3MHz	QPSK	20415	8RB#0	21.50	PASS
Band5	3MHz	16QAM	20415	8RB#0	20.61	PASS
Band5	3MHz	QPSK	20415	8RB#4	21.55	PASS
Band5	3MHz	16QAM	20415	8RB#4	20.66	PASS
Band5	3MHz	QPSK	20415	8RB#7	20.98	PASS
Band5	3MHz	16QAM	20415	8RB#7	20.70	PASS
Band5	3MHz	QPSK	20415	15RB#0	21.36	PASS
Band5	3MHz	16QAM	20415	15RB#0	20.45	PASS
Band5	3MHz	QPSK	20525	1RB#0	21.41	PASS
Band5	3MHz	16QAM	20525	1RB#0	21.12	PASS
Band5	3MHz	QPSK	20525	1RB#8	21.40	PASS
Band5	3MHz	16QAM	20525	1RB#8	21.07	PASS
Band5	3MHz	QPSK	20525	1RB#14	21.43	PASS
Band5	3MHz	16QAM	20525	1RB#14	21.12	PASS
Band5	3MHz	QPSK	20525	8RB#0	21.05	PASS
Band5	3MHz	16QAM	20525	8RB#0	20.20	PASS
Band5	3MHz	QPSK	20525	8RB#4	21.06	PASS
Band5	3MHz	16QAM	20525	8RB#4	20.20	PASS
Band5	3MHz	QPSK	20525	8RB#7	20.91	PASS
Band5	3MHz	16QAM	20525	8RB#7	20.46	PASS
Band5	3MHz	QPSK	20525	15RB#0	20.93	PASS
Band5	3MHz	16QAM	20525	15RB#0	20.33	PASS
Band5	3MHz	QPSK	20635	1RB#0	21.84	PASS
Band5	3MHz	16QAM	20635	1RB#0	21.44	PASS
Band5	3MHz	QPSK	20635	1RB#8	21.89	PASS

Band5	3MHz	16QAM	20635	1RB#8	21.46	PASS
Band5	3MHz	QPSK	20635	1RB#14	21.48	PASS
Band5	3MHz	16QAM	20635	1RB#14	21.13	PASS
Band5	3MHz	QPSK	20635	8RB#0	21.28	PASS
Band5	3MHz	16QAM	20635	8RB#0	20.47	PASS
Band5	3MHz	QPSK	20635	8RB#4	21.25	PASS
Band5	3MHz	16QAM	20635	8RB#4	20.46	PASS
Band5	3MHz	QPSK	20635	8RB#7	20.95	PASS
Band5	3MHz	16QAM	20635	8RB#7	20.40	PASS
Band5	3MHz	QPSK	20635	15RB#0	21.23	PASS
Band5	3MHz	16QAM	20635	15RB#0	20.13	PASS
Band5	5MHz	QPSK	20425	1RB#0	21.94	PASS
Band5	5MHz	16QAM	20425	1RB#0	21.48	PASS
Band5	5MHz	QPSK	20425	1RB#12	21.66	PASS
Band5	5MHz	16QAM	20425	1RB#12	21.07	PASS
Band5	5MHz	QPSK	20425	1RB#24	21.62	PASS
Band5	5MHz	16QAM	20425	1RB#24	21.33	PASS
Band5	5MHz	QPSK	20425	12RB#0	21.48	PASS
Band5	5MHz	16QAM	20425	12RB#0	20.38	PASS
Band5	5MHz	QPSK	20425	12RB#6	21.48	PASS
Band5	5MHz	16QAM	20425	12RB#6	20.39	PASS
Band5	5MHz	QPSK	20425	12RB#13	21.10	PASS
Band5	5MHz	16QAM	20425	12RB#13	20.42	PASS
Band5	5MHz	QPSK	20425	25RB#0	21.19	PASS
Band5	5MHz	16QAM	20425	25RB#0	20.57	PASS
Band5	5MHz	QPSK	20525	1RB#0	21.63	PASS
Band5	5MHz	16QAM	20525	1RB#0	21.62	PASS
Band5	5MHz	QPSK	20525	1RB#12	21.60	PASS
Band5	5MHz	16QAM	20525	1RB#12	21.64	PASS
Band5	5MHz	QPSK	20525	1RB#24	21.72	PASS
Band5	5MHz	16QAM	20525	1RB#24	21.79	PASS
Band5	5MHz	QPSK	20525	12RB#0	21.12	PASS
Band5	5MHz	16QAM	20525	12RB#0	20.26	PASS
Band5	5MHz	QPSK	20525	12RB#6	21.14	PASS
Band5	5MHz	16QAM	20525	12RB#6	20.29	PASS
Band5	5MHz	QPSK	20525	12RB#13	21.02	PASS
Band5	5MHz	16QAM	20525	12RB#13	20.43	PASS
Band5	5MHz	QPSK	20525	25RB#0	21.09	PASS
Band5	5MHz	16QAM	20525	25RB#0	20.38	PASS
Band5	5MHz	QPSK	20625	1RB#0	21.44	PASS
Band5	5MHz	16QAM	20625	1RB#0	20.93	PASS
Band5	5MHz	QPSK	20625	1RB#12	21.87	PASS

Band5	5MHz	16QAM	20625	1RB#12	21.27	PASS
Band5	5MHz	QPSK	20625	1RB#24	21.56	PASS
Band5	5MHz	16QAM	20625	1RB#24	20.93	PASS
Band5	5MHz	QPSK	20625	12RB#0	20.92	PASS
Band5	5MHz	16QAM	20625	12RB#0	20.23	PASS
Band5	5MHz	QPSK	20625	12RB#6	20.95	PASS
Band5	5MHz	16QAM	20625	12RB#6	20.26	PASS
Band5	5MHz	QPSK	20625	12RB#13	21.31	PASS
Band5	5MHz	16QAM	20625	12RB#13	20.26	PASS
Band5	5MHz	QPSK	20625	25RB#0	21.27	PASS
Band5	5MHz	16QAM	20625	25RB#0	20.39	PASS
Band5	10MHz	QPSK	20450	1RB#0	21.97	PASS
Band5	10MHz	16QAM	20450	1RB#0	22.10	PASS
Band5	10MHz	QPSK	20450	1RB#24	21.56	PASS
Band5	10MHz	16QAM	20450	1RB#24	21.93	PASS
Band5	10MHz	QPSK	20450	1RB#49	21.61	PASS
Band5	10MHz	16QAM	20450	1RB#49	21.52	PASS
Band5	10MHz	QPSK	20450	25RB#0	21.23	PASS
Band5	10MHz	16QAM	20450	25RB#0	20.51	PASS
Band5	10MHz	QPSK	20450	25RB#12	21.15	PASS
Band5	10MHz	16QAM	20450	25RB#12	20.51	PASS
Band5	10MHz	QPSK	20450	25RB#25	21.11	PASS
Band5	10MHz	16QAM	20450	25RB#25	20.12	PASS
Band5	10MHz	QPSK	20450	50RB#0	21.53	PASS
Band5	10MHz	16QAM	20450	50RB#0	20.51	PASS
Band5	10MHz	QPSK	20525	1RB#0	21.54	PASS
Band5	10MHz	16QAM	20525	1RB#0	21.65	PASS
Band5	10MHz	QPSK	20525	1RB#24	21.53	PASS
Band5	10MHz	16QAM	20525	1RB#24	21.49	PASS
Band5	10MHz	QPSK	20525	1RB#49	21.51	PASS
Band5	10MHz	16QAM	20525	1RB#49	21.50	PASS
Band5	10MHz	QPSK	20525	25RB#0	21.17	PASS
Band5	10MHz	16QAM	20525	25RB#0	20.10	PASS
Band5	10MHz	QPSK	20525	25RB#12	21.18	PASS
Band5	10MHz	16QAM	20525	25RB#12	20.14	PASS
Band5	10MHz	QPSK	20525	25RB#25	21.22	PASS
Band5	10MHz	16QAM	20525	25RB#25	20.31	PASS
Band5	10MHz	QPSK	20525	50RB#0	21.15	PASS
Band5	10MHz	16QAM	20525	50RB#0	20.40	PASS
Band5	10MHz	QPSK	20600	1RB#0	21.73	PASS
Band5	10MHz	16QAM	20600	1RB#0	21.77	PASS
Band5	10MHz	QPSK	20600	1RB#24	21.38	PASS

Band5	10MHz	16QAM	20600	1RB#24	21.48	PASS
Band5	10MHz	QPSK	20600	1RB#49	21.47	PASS
Band5	10MHz	16QAM	20600	1RB#49	21.48	PASS
Band5	10MHz	QPSK	20600	25RB#0	21.06	PASS
Band5	10MHz	16QAM	20600	25RB#0	20.30	PASS
Band5	10MHz	QPSK	20600	25RB#12	21.11	PASS
Band5	10MHz	16QAM	20600	25RB#12	20.32	PASS
Band5	10MHz	QPSK	20600	25RB#25	21.33	PASS
Band5	10MHz	16QAM	20600	25RB#25	20.32	PASS
Band5	10MHz	QPSK	20600	50RB#0	20.97	PASS
Band5	10MHz	16QAM	20600	50RB#0	20.33	PASS

FDD-LTE Band 7:

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Verdict
Band7	5MHz	QPSK	20775	1RB#0	20.47	PASS
Band7	5MHz	16QAM	20775	1RB#0	19.77	PASS
Band7	5MHz	QPSK	20775	1RB#12	20.44	PASS
Band7	5MHz	16QAM	20775	1RB#12	19.79	PASS
Band7	5MHz	QPSK	20775	1RB#24	20.50	PASS
Band7	5MHz	16QAM	20775	1RB#24	19.78	PASS
Band7	5MHz	QPSK	20775	12RB#0	19.72	PASS
Band7	5MHz	16QAM	20775	12RB#0	18.75	PASS
Band7	5MHz	QPSK	20775	12RB#6	19.68	PASS
Band7	5MHz	16QAM	20775	12RB#6	18.75	PASS
Band7	5MHz	QPSK	20775	12RB#13	19.74	PASS
Band7	5MHz	16QAM	20775	12RB#13	18.84	PASS
Band7	5MHz	QPSK	20775	25RB#0	19.77	PASS
Band7	5MHz	16QAM	20775	25RB#0	18.96	PASS
Band7	5MHz	QPSK	21100	1RB#0	20.28	PASS
Band7	5MHz	16QAM	21100	1RB#0	20.31	PASS
Band7	5MHz	QPSK	21100	1RB#12	20.27	PASS
Band7	5MHz	16QAM	21100	1RB#12	20.31	PASS
Band7	5MHz	QPSK	21100	1RB#24	20.19	PASS
Band7	5MHz	16QAM	21100	1RB#24	20.26	PASS
Band7	5MHz	QPSK	21100	12RB#0	19.61	PASS
Band7	5MHz	16QAM	21100	12RB#0	18.73	PASS
Band7	5MHz	QPSK	21100	12RB#6	19.65	PASS
Band7	5MHz	16QAM	21100	12RB#6	18.71	PASS
Band7	5MHz	QPSK	21100	12RB#13	19.61	PASS
Band7	5MHz	16QAM	21100	12RB#13	18.63	PASS

Band7	5MHz	QPSK	21100	25RB#0	19.64	PASS
Band7	5MHz	16QAM	21100	25RB#0	18.73	PASS
Band7	5MHz	QPSK	21425	1RB#0	20.34	PASS
Band7	5MHz	16QAM	21425	1RB#0	19.66	PASS
Band7	5MHz	QPSK	21425	1RB#12	20.24	PASS
Band7	5MHz	16QAM	21425	1RB#12	19.64	PASS
Band7	5MHz	QPSK	21425	1RB#24	20.39	PASS
Band7	5MHz	16QAM	21425	1RB#24	19.64	PASS
Band7	5MHz	QPSK	21425	12RB#0	19.72	PASS
Band7	5MHz	16QAM	21425	12RB#0	18.49	PASS
Band7	5MHz	QPSK	21425	12RB#6	19.74	PASS
Band7	5MHz	16QAM	21425	12RB#6	18.51	PASS
Band7	5MHz	QPSK	21425	12RB#13	19.68	PASS
Band7	5MHz	16QAM	21425	12RB#13	18.61	PASS
Band7	5MHz	QPSK	21425	25RB#0	19.73	PASS
Band7	5MHz	16QAM	21425	25RB#0	18.72	PASS
Band7	10MHz	QPSK	20800	1RB#0	20.44	PASS
Band7	10MHz	16QAM	20800	1RB#0	20.31	PASS
Band7	10MHz	QPSK	20800	1RB#24	20.39	PASS
Band7	10MHz	16QAM	20800	1RB#24	20.35	PASS
Band7	10MHz	QPSK	20800	1RB#49	20.40	PASS
Band7	10MHz	16QAM	20800	1RB#49	20.36	PASS
Band7	10MHz	QPSK	20800	25RB#0	19.83	PASS
Band7	10MHz	16QAM	20800	25RB#0	18.86	PASS
Band7	10MHz	QPSK	20800	25RB#12	19.86	PASS
Band7	10MHz	16QAM	20800	25RB#12	18.89	PASS
Band7	10MHz	QPSK	20800	25RB#25	19.69	PASS
Band7	10MHz	16QAM	20800	25RB#25	18.77	PASS
Band7	10MHz	QPSK	20800	50RB#0	19.81	PASS
Band7	10MHz	16QAM	20800	50RB#0	18.84	PASS
Band7	10MHz	QPSK	21100	1RB#0	20.37	PASS
Band7	10MHz	16QAM	21100	1RB#0	19.96	PASS
Band7	10MHz	QPSK	21100	1RB#24	20.33	PASS
Band7	10MHz	16QAM	21100	1RB#24	19.92	PASS
Band7	10MHz	QPSK	21100	1RB#49	20.34	PASS
Band7	10MHz	16QAM	21100	1RB#49	19.93	PASS
Band7	10MHz	QPSK	21100	25RB#0	19.72	PASS
Band7	10MHz	16QAM	21100	25RB#0	18.82	PASS
Band7	10MHz	QPSK	21100	25RB#12	19.55	PASS
Band7	10MHz	16QAM	21100	25RB#12	18.89	PASS
Band7	10MHz	QPSK	21100	25RB#25	19.59	PASS
Band7	10MHz	16QAM	21100	25RB#25	18.78	PASS

Band7	10MHz	QPSK	21100	50RB#0	19.63	PASS
Band7	10MHz	16QAM	21100	50RB#0	18.70	PASS
Band7	10MHz	QPSK	21400	1RB#0	20.34	PASS
Band7	10MHz	16QAM	21400	1RB#0	20.74	PASS
Band7	10MHz	QPSK	21400	1RB#24	20.32	PASS
Band7	10MHz	16QAM	21400	1RB#24	20.80	PASS
Band7	10MHz	QPSK	21400	1RB#49	20.49	PASS
Band7	10MHz	16QAM	21400	1RB#49	20.74	PASS
Band7	10MHz	QPSK	21400	25RB#0	19.69	PASS
Band7	10MHz	16QAM	21400	25RB#0	18.86	PASS
Band7	10MHz	QPSK	21400	25RB#12	19.73	PASS
Band7	10MHz	16QAM	21400	25RB#12	18.88	PASS
Band7	10MHz	QPSK	21400	25RB#25	19.60	PASS
Band7	10MHz	16QAM	21400	25RB#25	18.95	PASS
Band7	10MHz	QPSK	21400	50RB#0	19.68	PASS
Band7	10MHz	16QAM	21400	50RB#0	18.89	PASS
Band7	15MHz	QPSK	20825	1RB#0	20.43	PASS
Band7	15MHz	16QAM	20825	1RB#0	20.38	PASS
Band7	15MHz	QPSK	20825	1RB#38	20.36	PASS
Band7	15MHz	16QAM	20825	1RB#38	20.36	PASS
Band7	15MHz	QPSK	20825	1RB#74	20.24	PASS
Band7	15MHz	16QAM	20825	1RB#74	20.36	PASS
Band7	15MHz	QPSK	20825	38RB#0	19.76	PASS
Band7	15MHz	16QAM	20825	38RB#0	19.77	PASS
Band7	15MHz	QPSK	20825	38RB#18	19.77	PASS
Band7	15MHz	16QAM	20825	38RB#18	19.77	PASS
Band7	15MHz	QPSK	20825	38RB#37	19.77	PASS
Band7	15MHz	16QAM	20825	38RB#37	19.77	PASS
Band7	15MHz	QPSK	20825	75RB#0	19.78	PASS
Band7	15MHz	16QAM	20825	75RB#0	18.85	PASS
Band7	15MHz	QPSK	21100	1RB#0	20.10	PASS
Band7	15MHz	16QAM	21100	1RB#0	20.14	PASS
Band7	15MHz	QPSK	21100	1RB#38	19.98	PASS
Band7	15MHz	16QAM	21100	1RB#38	20.03	PASS
Band7	15MHz	QPSK	21100	1RB#74	19.99	PASS
Band7	15MHz	16QAM	21100	1RB#74	20.01	PASS
Band7	15MHz	QPSK	21100	38RB#0	19.59	PASS
Band7	15MHz	16QAM	21100	38RB#0	19.60	PASS
Band7	15MHz	QPSK	21100	38RB#18	19.59	PASS
Band7	15MHz	16QAM	21100	38RB#18	19.60	PASS
Band7	15MHz	QPSK	21100	38RB#37	19.59	PASS
Band7	15MHz	16QAM	21100	38RB#37	19.59	PASS

Band7	15MHz	QPSK	21100	75RB#0	19.59	PASS
Band7	15MHz	16QAM	21100	75RB#0	18.75	PASS
Band7	15MHz	QPSK	21375	1RB#0	20.30	PASS
Band7	15MHz	16QAM	21375	1RB#0	20.81	PASS
Band7	15MHz	QPSK	21375	1RB#38	20.34	PASS
Band7	15MHz	16QAM	21375	1RB#38	20.82	PASS
Band7	15MHz	QPSK	21375	1RB#74	20.45	PASS
Band7	15MHz	16QAM	21375	1RB#74	20.82	PASS
Band7	15MHz	QPSK	21375	38RB#0	19.68	PASS
Band7	15MHz	16QAM	21375	38RB#0	19.61	PASS
Band7	15MHz	QPSK	21375	38RB#18	19.61	PASS
Band7	15MHz	16QAM	21375	38RB#18	19.62	PASS
Band7	15MHz	QPSK	21375	38RB#37	19.61	PASS
Band7	15MHz	16QAM	21375	38RB#37	19.62	PASS
Band7	15MHz	QPSK	21375	75RB#0	19.62	PASS
Band7	15MHz	16QAM	21375	75RB#0	18.78	PASS
Band7	20MHz	QPSK	20850	1RB#0	20.63	PASS
Band7	20MHz	16QAM	20850	1RB#0	20.05	PASS
Band7	20MHz	QPSK	20850	1RB#49	20.60	PASS
Band7	20MHz	16QAM	20850	1RB#49	19.93	PASS
Band7	20MHz	QPSK	20850	1RB#99	20.53	PASS
Band7	20MHz	16QAM	20850	1RB#99	19.92	PASS
Band7	20MHz	QPSK	20850	50RB#0	19.77	PASS
Band7	20MHz	16QAM	20850	50RB#0	19.00	PASS
Band7	20MHz	QPSK	20850	50RB#25	19.80	PASS
Band7	20MHz	16QAM	20850	50RB#25	19.01	PASS
Band7	20MHz	QPSK	20850	50RB#50	19.75	PASS
Band7	20MHz	16QAM	20850	50RB#50	18.92	PASS
Band7	20MHz	QPSK	20850	100RB#0	19.76	PASS
Band7	20MHz	16QAM	20850	100RB#0	18.84	PASS
Band7	20MHz	QPSK	21100	1RB#0	20.33	PASS
Band7	20MHz	16QAM	21100	1RB#0	20.85	PASS
Band7	20MHz	QPSK	21100	1RB#49	20.41	PASS
Band7	20MHz	16QAM	21100	1RB#49	20.64	PASS
Band7	20MHz	QPSK	21100	1RB#99	20.38	PASS
Band7	20MHz	16QAM	21100	1RB#99	20.66	PASS
Band7	20MHz	QPSK	21100	50RB#0	19.70	PASS
Band7	20MHz	16QAM	21100	50RB#0	18.86	PASS
Band7	20MHz	QPSK	21100	50RB#25	19.68	PASS
Band7	20MHz	16QAM	21100	50RB#25	18.87	PASS
Band7	20MHz	QPSK	21100	50RB#50	19.53	PASS
Band7	20MHz	16QAM	21100	50RB#50	18.71	PASS

Band7	20MHz	QPSK	21100	100RB#0	19.59	PASS
Band7	20MHz	16QAM	21100	100RB#0	18.87	PASS
Band7	20MHz	QPSK	21350	1RB#0	20.45	PASS
Band7	20MHz	16QAM	21350	1RB#0	20.06	PASS
Band7	20MHz	QPSK	21350	1RB#49	20.45	PASS
Band7	20MHz	16QAM	21350	1RB#49	20.07	PASS
Band7	20MHz	QPSK	21350	1RB#99	20.46	PASS
Band7	20MHz	16QAM	21350	1RB#99	20.09	PASS
Band7	20MHz	QPSK	21350	50RB#0	19.61	PASS
Band7	20MHz	16QAM	21350	50RB#0	18.83	PASS
Band7	20MHz	QPSK	21350	50RB#25	19.63	PASS
Band7	20MHz	16QAM	21350	50RB#25	18.84	PASS
Band7	20MHz	QPSK	21350	50RB#50	19.65	PASS
Band7	20MHz	16QAM	21350	50RB#50	18.83	PASS
Band7	20MHz	QPSK	21350	100RB#0	19.66	PASS
Band7	20MHz	16QAM	21350	100RB#0	18.65	PASS

FDD-LTE Band 12:

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Verdict
Band12	1.4MHz	QPSK	23017	1RB#0	22.08	PASS
Band12	1.4MHz	16QAM	23017	1RB#0	21.73	PASS
Band12	1.4MHz	QPSK	23017	1RB#2	22.06	PASS
Band12	1.4MHz	16QAM	23017	1RB#2	21.74	PASS
Band12	1.4MHz	QPSK	23017	1RB#5	22.02	PASS
Band12	1.4MHz	16QAM	23017	1RB#5	21.71	PASS
Band12	1.4MHz	QPSK	23017	3RB#0	22.14	PASS
Band12	1.4MHz	16QAM	23017	3RB#0	21.21	PASS
Band12	1.4MHz	QPSK	23017	3RB#1	22.14	PASS
Band12	1.4MHz	16QAM	23017	3RB#1	21.08	PASS
Band12	1.4MHz	QPSK	23017	3RB#3	22.18	PASS
Band12	1.4MHz	16QAM	23017	3RB#3	21.12	PASS
Band12	1.4MHz	QPSK	23017	6RB#0	21.72	PASS
Band12	1.4MHz	16QAM	23017	6RB#0	20.65	PASS
Band12	1.4MHz	QPSK	23095	1RB#0	21.98	PASS
Band12	1.4MHz	16QAM	23095	1RB#0	21.73	PASS
Band12	1.4MHz	QPSK	23095	1RB#2	22.13	PASS
Band12	1.4MHz	16QAM	23095	1RB#2	21.69	PASS
Band12	1.4MHz	QPSK	23095	1RB#5	22.04	PASS
Band12	1.4MHz	16QAM	23095	1RB#5	21.68	PASS
Band12	1.4MHz	QPSK	23095	3RB#0	22.14	PASS

Band12	1.4MHz	16QAM	23095	3RB#0	21.06	PASS
Band12	1.4MHz	QPSK	23095	3RB#1	22.14	PASS
Band12	1.4MHz	16QAM	23095	3RB#1	21.03	PASS
Band12	1.4MHz	QPSK	23095	3RB#3	22.16	PASS
Band12	1.4MHz	16QAM	23095	3RB#3	21.05	PASS
Band12	1.4MHz	QPSK	23095	6RB#0	21.59	PASS
Band12	1.4MHz	16QAM	23095	6RB#0	21.11	PASS
Band12	1.4MHz	QPSK	23173	1RB#0	22.19	PASS
Band12	1.4MHz	16QAM	23173	1RB#0	21.00	PASS
Band12	1.4MHz	QPSK	23173	1RB#2	22.15	PASS
Band12	1.4MHz	16QAM	23173	1RB#2	21.34	PASS
Band12	1.4MHz	QPSK	23173	1RB#5	22.10	PASS
Band12	1.4MHz	16QAM	23173	1RB#5	21.33	PASS
Band12	1.4MHz	QPSK	23173	3RB#0	22.24	PASS
Band12	1.4MHz	16QAM	23173	3RB#0	21.32	PASS
Band12	1.4MHz	QPSK	23173	3RB#1	22.31	PASS
Band12	1.4MHz	16QAM	23173	3RB#1	21.32	PASS
Band12	1.4MHz	QPSK	23173	3RB#3	22.22	PASS
Band12	1.4MHz	16QAM	23173	3RB#3	21.65	PASS
Band12	1.4MHz	QPSK	23173	6RB#0	21.99	PASS
Band12	1.4MHz	16QAM	23173	6RB#0	21.00	PASS
Band12	3MHz	QPSK	23025	1RB#0	22.03	PASS
Band12	3MHz	16QAM	23025	1RB#0	21.78	PASS
Band12	3MHz	QPSK	23025	1RB#8	22.01	PASS
Band12	3MHz	16QAM	23025	1RB#8	21.71	PASS
Band12	3MHz	QPSK	23025	1RB#14	21.97	PASS
Band12	3MHz	16QAM	23025	1RB#14	21.57	PASS
Band12	3MHz	QPSK	23025	8RB#0	21.68	PASS
Band12	3MHz	16QAM	23025	8RB#0	20.91	PASS
Band12	3MHz	QPSK	23025	8RB#4	21.69	PASS
Band12	3MHz	16QAM	23025	8RB#4	20.85	PASS
Band12	3MHz	QPSK	23025	8RB#7	21.68	PASS
Band12	3MHz	16QAM	23025	8RB#7	20.67	PASS
Band12	3MHz	QPSK	23025	15RB#0	21.76	PASS
Band12	3MHz	16QAM	23025	15RB#0	20.63	PASS
Band12	3MHz	QPSK	23095	1RB#0	22.15	PASS
Band12	3MHz	16QAM	23095	1RB#0	20.99	PASS
Band12	3MHz	QPSK	23095	1RB#8	22.21	PASS
Band12	3MHz	16QAM	23095	1RB#8	20.88	PASS
Band12	3MHz	QPSK	23095	1RB#14	22.14	PASS
Band12	3MHz	16QAM	23095	1RB#14	20.87	PASS
Band12	3MHz	QPSK	23095	8RB#0	21.61	PASS

Band12	3MHz	16QAM	23095	8RB#0	20.75	PASS
Band12	3MHz	QPSK	23095	8RB#4	21.60	PASS
Band12	3MHz	16QAM	23095	8RB#4	20.84	PASS
Band12	3MHz	QPSK	23095	8RB#7	21.61	PASS
Band12	3MHz	16QAM	23095	8RB#7	21.21	PASS
Band12	3MHz	QPSK	23095	15RB#0	21.62	PASS
Band12	3MHz	16QAM	23095	15RB#0	20.88	PASS
Band12	3MHz	QPSK	23165	1RB#0	22.20	PASS
Band12	3MHz	16QAM	23165	1RB#0	21.74	PASS
Band12	3MHz	QPSK	23165	1RB#8	22.17	PASS
Band12	3MHz	16QAM	23165	1RB#8	21.73	PASS
Band12	3MHz	QPSK	23165	1RB#14	22.22	PASS
Band12	3MHz	16QAM	23165	1RB#14	22.15	PASS
Band12	3MHz	QPSK	23165	8RB#0	21.80	PASS
Band12	3MHz	16QAM	23165	8RB#0	20.71	PASS
Band12	3MHz	QPSK	23165	8RB#4	21.66	PASS
Band12	3MHz	16QAM	23165	8RB#4	20.73	PASS
Band12	3MHz	QPSK	23165	8RB#7	21.92	PASS
Band12	3MHz	16QAM	23165	8RB#7	21.01	PASS
Band12	3MHz	QPSK	23165	15RB#0	21.57	PASS
Band12	3MHz	16QAM	23165	15RB#0	20.59	PASS
Band12	5MHz	QPSK	23035	1RB#0	22.33	PASS
Band12	5MHz	16QAM	23035	1RB#0	21.14	PASS
Band12	5MHz	QPSK	23035	1RB#12	22.26	PASS
Band12	5MHz	16QAM	23035	1RB#12	21.22	PASS
Band12	5MHz	QPSK	23035	1RB#24	22.25	PASS
Band12	5MHz	16QAM	23035	1RB#24	21.16	PASS
Band12	5MHz	QPSK	23035	12RB#0	21.82	PASS
Band12	5MHz	16QAM	23035	12RB#0	20.66	PASS
Band12	5MHz	QPSK	23035	12RB#6	21.91	PASS
Band12	5MHz	16QAM	23035	12RB#6	20.78	PASS
Band12	5MHz	QPSK	23035	12RB#13	21.72	PASS
Band12	5MHz	16QAM	23035	12RB#13	20.72	PASS
Band12	5MHz	QPSK	23035	25RB#0	21.69	PASS
Band12	5MHz	16QAM	23035	25RB#0	20.82	PASS
Band12	5MHz	QPSK	23095	1RB#0	22.20	PASS
Band12	5MHz	16QAM	23095	1RB#0	21.77	PASS
Band12	5MHz	QPSK	23095	1RB#12	22.04	PASS
Band12	5MHz	16QAM	23095	1RB#12	21.73	PASS
Band12	5MHz	QPSK	23095	1RB#24	22.21	PASS
Band12	5MHz	16QAM	23095	1RB#24	21.79	PASS
Band12	5MHz	QPSK	23095	12RB#0	21.70	PASS

Band12	5MHz	16QAM	23095	12RB#0	20.71	PASS
Band12	5MHz	QPSK	23095	12RB#6	21.71	PASS
Band12	5MHz	16QAM	23095	12RB#6	20.71	PASS
Band12	5MHz	QPSK	23095	12RB#13	21.63	PASS
Band12	5MHz	16QAM	23095	12RB#13	21.11	PASS
Band12	5MHz	QPSK	23095	25RB#0	21.57	PASS
Band12	5MHz	16QAM	23095	25RB#0	21.07	PASS
Band12	5MHz	QPSK	23155	1RB#0	22.10	PASS
Band12	5MHz	16QAM	23155	1RB#0	21.60	PASS
Band12	5MHz	QPSK	23155	1RB#12	22.18	PASS
Band12	5MHz	16QAM	23155	1RB#12	21.49	PASS
Band12	5MHz	QPSK	23155	1RB#24	22.20	PASS
Band12	5MHz	16QAM	23155	1RB#24	21.61	PASS
Band12	5MHz	QPSK	23155	12RB#0	22.04	PASS
Band12	5MHz	16QAM	23155	12RB#0	20.89	PASS
Band12	5MHz	QPSK	23155	12RB#6	22.01	PASS
Band12	5MHz	16QAM	23155	12RB#6	20.96	PASS
Band12	5MHz	QPSK	23155	12RB#13	21.82	PASS
Band12	5MHz	16QAM	23155	12RB#13	20.72	PASS
Band12	5MHz	QPSK	23155	25RB#0	21.75	PASS
Band12	5MHz	16QAM	23155	25RB#0	20.84	PASS
Band12	10MHz	QPSK	23060	1RB#0	22.21	PASS
Band12	10MHz	16QAM	23060	1RB#0	21.72	PASS
Band12	10MHz	QPSK	23060	1RB#24	22.10	PASS
Band12	10MHz	16QAM	23060	1RB#24	21.73	PASS
Band12	10MHz	QPSK	23060	1RB#49	22.01	PASS
Band12	10MHz	16QAM	23060	1RB#49	21.61	PASS
Band12	10MHz	QPSK	23060	25RB#0	21.77	PASS
Band12	10MHz	16QAM	23060	25RB#0	20.47	PASS
Band12	10MHz	QPSK	23060	25RB#12	21.68	PASS
Band12	10MHz	16QAM	23060	25RB#12	20.47	PASS
Band12	10MHz	QPSK	23060	25RB#25	21.64	PASS
Band12	10MHz	16QAM	23060	25RB#25	20.76	PASS
Band12	10MHz	QPSK	23060	50RB#0	21.61	PASS
Band12	10MHz	16QAM	23060	50RB#0	21.03	PASS
Band12	10MHz	QPSK	23095	1RB#0	22.16	PASS
Band12	10MHz	16QAM	23095	1RB#0	21.39	PASS
Band12	10MHz	QPSK	23095	1RB#24	22.12	PASS
Band12	10MHz	16QAM	23095	1RB#24	21.39	PASS
Band12	10MHz	QPSK	23095	1RB#49	22.10	PASS
Band12	10MHz	16QAM	23095	1RB#49	21.77	PASS
Band12	10MHz	QPSK	23095	25RB#0	21.68	PASS

Band12	10MHz	16QAM	23095	25RB#0	20.76	PASS
Band12	10MHz	QPSK	23095	25RB#12	21.70	PASS
Band12	10MHz	16QAM	23095	25RB#12	20.79	PASS
Band12	10MHz	QPSK	23095	25RB#25	21.66	PASS
Band12	10MHz	16QAM	23095	25RB#25	21.20	PASS
Band12	10MHz	QPSK	23095	50RB#0	21.60	PASS
Band12	10MHz	16QAM	23095	50RB#0	21.09	PASS
Band12	10MHz	QPSK	23130	1RB#0	22.15	PASS
Band12	10MHz	16QAM	23130	1RB#0	22.12	PASS
Band12	10MHz	QPSK	23130	1RB#24	22.05	PASS
Band12	10MHz	16QAM	23130	1RB#24	22.06	PASS
Band12	10MHz	QPSK	23130	1RB#49	22.15	PASS
Band12	10MHz	16QAM	23130	1RB#49	22.44	PASS
Band12	10MHz	QPSK	23130	25RB#0	21.54	PASS
Band12	10MHz	16QAM	23130	25RB#0	21.12	PASS
Band12	10MHz	QPSK	23130	25RB#12	21.60	PASS
Band12	10MHz	16QAM	23130	25RB#12	21.14	PASS
Band12	10MHz	QPSK	23130	25RB#25	21.81	PASS
Band12	10MHz	16QAM	23130	25RB#25	20.86	PASS
Band12	10MHz	QPSK	23130	50RB#0	21.66	PASS
Band12	10MHz	16QAM	23130	50RB#0	21.06	PASS

FDD-LTE Band 13:

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Verdict
Band13	5MHz	QPSK	23205	1RB#0	22.18	PASS
Band13	5MHz	16QAM	23205	1RB#0	20.90	PASS
Band13	5MHz	QPSK	23205	1RB#12	22.14	PASS
Band13	5MHz	16QAM	23205	1RB#12	20.85	PASS
Band13	5MHz	QPSK	23205	1RB#24	22.05	PASS
Band13	5MHz	16QAM	23205	1RB#24	20.72	PASS
Band13	5MHz	QPSK	23205	12RB#0	21.32	PASS
Band13	5MHz	16QAM	23205	12RB#0	20.13	PASS
Band13	5MHz	QPSK	23205	12RB#6	21.31	PASS
Band13	5MHz	16QAM	23205	12RB#6	20.14	PASS
Band13	5MHz	QPSK	23205	12RB#13	21.13	PASS
Band13	5MHz	16QAM	23205	12RB#13	20.25	PASS
Band13	5MHz	QPSK	23205	25RB#0	21.19	PASS
Band13	5MHz	16QAM	23205	25RB#0	20.32	PASS
Band13	5MHz	QPSK	23230	1RB#0	22.21	PASS
Band13	5MHz	16QAM	23230	1RB#0	20.62	PASS

Band13	5MHz	QPSK	23230	1RB#12	22.17	PASS
Band13	5MHz	16QAM	23230	1RB#12	20.58	PASS
Band13	5MHz	QPSK	23230	1RB#24	22.22	PASS
Band13	5MHz	16QAM	23230	1RB#24	20.64	PASS
Band13	5MHz	QPSK	23230	12RB#0	21.09	PASS
Band13	5MHz	16QAM	23230	12RB#0	20.27	PASS
Band13	5MHz	QPSK	23230	12RB#6	21.11	PASS
Band13	5MHz	16QAM	23230	12RB#6	20.29	PASS
Band13	5MHz	QPSK	23230	12RB#13	21.28	PASS
Band13	5MHz	16QAM	23230	12RB#13	20.29	PASS
Band13	5MHz	QPSK	23230	25RB#0	21.10	PASS
Band13	5MHz	16QAM	23230	25RB#0	20.51	PASS
Band13	5MHz	QPSK	23255	1RB#0	22.11	PASS
Band13	5MHz	16QAM	23255	1RB#0	21.18	PASS
Band13	5MHz	QPSK	23255	1RB#12	22.23	PASS
Band13	5MHz	16QAM	23255	1RB#12	21.27	PASS
Band13	5MHz	QPSK	23255	1RB#24	22.21	PASS
Band13	5MHz	16QAM	23255	1RB#24	21.25	PASS
Band13	5MHz	QPSK	23255	12RB#0	21.30	PASS
Band13	5MHz	16QAM	23255	12RB#0	20.38	PASS
Band13	5MHz	QPSK	23255	12RB#6	21.31	PASS
Band13	5MHz	16QAM	23255	12RB#6	20.33	PASS
Band13	5MHz	QPSK	23255	12RB#13	21.23	PASS
Band13	5MHz	16QAM	23255	12RB#13	20.54	PASS
Band13	5MHz	QPSK	23255	25RB#0	21.18	PASS
Band13	5MHz	16QAM	23255	25RB#0	20.29	PASS
Band13	10MHz	QPSK	23230	1RB#0	22.25	PASS
Band13	10MHz	16QAM	23230	1RB#0	21.26	PASS
Band13	10MHz	QPSK	23230	1RB#24	22.05	PASS
Band13	10MHz	16QAM	23230	1RB#24	21.09	PASS
Band13	10MHz	QPSK	23230	1RB#49	22.15	PASS
Band13	10MHz	16QAM	23230	1RB#49	21.19	PASS
Band13	10MHz	QPSK	23230	25RB#0	21.14	PASS
Band13	10MHz	16QAM	23230	25RB#0	20.34	PASS
Band13	10MHz	QPSK	23230	25RB#12	21.15	PASS
Band13	10MHz	16QAM	23230	25RB#12	20.35	PASS
Band13	10MHz	QPSK	23230	25RB#25	21.27	PASS
Band13	10MHz	16QAM	23230	25RB#25	20.15	PASS
Band13	10MHz	QPSK	23230	50RB#0	21.23	PASS
Band13	10MHz	16QAM	23230	50RB#0	20.45	PASS

FDD-LTE Band 17:

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Verdict
Band17	5MHz	QPSK	23755	1RB#0	22.10	PASS
Band17	5MHz	16QAM	23755	1RB#0	22.13	PASS
Band17	5MHz	QPSK	23755	1RB#12	22.10	PASS
Band17	5MHz	16QAM	23755	1RB#12	22.08	PASS
Band17	5MHz	QPSK	23755	1RB#24	22.19	PASS
Band17	5MHz	16QAM	23755	1RB#24	22.10	PASS
Band17	5MHz	QPSK	23755	12RB#0	22.12	PASS
Band17	5MHz	16QAM	23755	12RB#0	22.11	PASS
Band17	5MHz	QPSK	23755	12RB#6	22.16	PASS
Band17	5MHz	16QAM	23755	12RB#6	22.15	PASS
Band17	5MHz	QPSK	23755	12RB#13	22.15	PASS
Band17	5MHz	16QAM	23755	12RB#13	22.15	PASS
Band17	5MHz	QPSK	23755	25RB#0	22.15	PASS
Band17	5MHz	16QAM	23755	25RB#0	22.14	PASS
Band17	5MHz	QPSK	23790	1RB#0	22.08	PASS
Band17	5MHz	16QAM	23790	1RB#0	21.71	PASS
Band17	5MHz	QPSK	23790	1RB#12	22.18	PASS
Band17	5MHz	16QAM	23790	1RB#12	21.72	PASS
Band17	5MHz	QPSK	23790	1RB#24	22.13	PASS
Band17	5MHz	16QAM	23790	1RB#24	22.05	PASS
Band17	5MHz	QPSK	23790	12RB#0	21.52	PASS
Band17	5MHz	16QAM	23790	12RB#0	21.09	PASS
Band17	5MHz	QPSK	23790	12RB#6	21.63	PASS
Band17	5MHz	16QAM	23790	12RB#6	21.06	PASS
Band17	5MHz	QPSK	23790	12RB#13	21.99	PASS
Band17	5MHz	16QAM	23790	12RB#13	21.05	PASS
Band17	5MHz	QPSK	23790	25RB#0	21.64	PASS
Band17	5MHz	16QAM	23790	25RB#0	21.05	PASS
Band17	5MHz	QPSK	23825	1RB#0	22.10	PASS
Band17	5MHz	16QAM	23825	1RB#0	21.54	PASS
Band17	5MHz	QPSK	23825	1RB#12	22.20	PASS
Band17	5MHz	16QAM	23825	1RB#12	21.42	PASS
Band17	5MHz	QPSK	23825	1RB#24	22.19	PASS
Band17	5MHz	16QAM	23825	1RB#24	21.62	PASS
Band17	5MHz	QPSK	23825	12RB#0	21.92	PASS
Band17	5MHz	16QAM	23825	12RB#0	20.92	PASS
Band17	5MHz	QPSK	23825	12RB#6	22.04	PASS
Band17	5MHz	16QAM	23825	12RB#6	20.94	PASS
Band17	5MHz	QPSK	23825	12RB#13	21.79	PASS

Band17	5MHz	16QAM	23825	12RB#13	20.74	PASS
Band17	5MHz	QPSK	23825	25RB#0	21.83	PASS
Band17	5MHz	16QAM	23825	25RB#0	20.85	PASS
Band17	10MHz	QPSK	23780	1RB#0	22.15	PASS
Band17	10MHz	16QAM	23780	1RB#0	21.72	PASS
Band17	10MHz	QPSK	23780	1RB#24	22.04	PASS
Band17	10MHz	16QAM	23780	1RB#24	21.71	PASS
Band17	10MHz	QPSK	23780	1RB#49	22.14	PASS
Band17	10MHz	16QAM	23780	1RB#49	21.74	PASS
Band17	10MHz	QPSK	23780	25RB#0	21.66	PASS
Band17	10MHz	16QAM	23780	25RB#0	20.70	PASS
Band17	10MHz	QPSK	23780	25RB#12	21.69	PASS
Band17	10MHz	16QAM	23780	25RB#12	20.64	PASS
Band17	10MHz	QPSK	23780	25RB#25	21.91	PASS
Band17	10MHz	16QAM	23780	25RB#25	20.98	PASS
Band17	10MHz	QPSK	23780	50RB#0	21.53	PASS
Band17	10MHz	16QAM	23780	50RB#0	21.02	PASS
Band17	10MHz	QPSK	23790	1RB#0	22.19	PASS
Band17	10MHz	16QAM	23790	1RB#0	21.43	PASS
Band17	10MHz	QPSK	23790	1RB#24	22.14	PASS
Band17	10MHz	16QAM	23790	1RB#24	21.44	PASS
Band17	10MHz	QPSK	23790	1RB#49	22.20	PASS
Band17	10MHz	16QAM	23790	1RB#49	21.47	PASS
Band17	10MHz	QPSK	23790	25RB#0	21.61	PASS
Band17	10MHz	16QAM	23790	25RB#0	21.14	PASS
Band17	10MHz	QPSK	23790	25RB#12	21.60	PASS
Band17	10MHz	16QAM	23790	25RB#12	21.15	PASS
Band17	10MHz	QPSK	23790	25RB#25	22.08	PASS
Band17	10MHz	16QAM	23790	25RB#25	21.11	PASS
Band17	10MHz	QPSK	23790	50RB#0	21.72	PASS
Band17	10MHz	16QAM	23790	50RB#0	21.13	PASS
Band17	10MHz	QPSK	23800	1RB#0	22.25	PASS
Band17	10MHz	16QAM	23800	1RB#0	22.15	PASS
Band17	10MHz	QPSK	23800	1RB#24	22.20	PASS
Band17	10MHz	16QAM	23800	1RB#24	22.06	PASS
Band17	10MHz	QPSK	23800	1RB#49	22.20	PASS
Band17	10MHz	16QAM	23800	1RB#49	22.44	PASS
Band17	10MHz	QPSK	23800	25RB#0	21.56	PASS
Band17	10MHz	16QAM	23800	25RB#0	21.12	PASS
Band17	10MHz	QPSK	23800	25RB#12	21.61	PASS
Band17	10MHz	16QAM	23800	25RB#12	21.13	PASS
Band17	10MHz	QPSK	23800	25RB#25	21.86	PASS

Band17	10MHz	16QAM	23800	25RB#25	20.86	PASS
Band17	10MHz	QPSK	23800	50RB#0	21.65	PASS
Band17	10MHz	16QAM	23800	50RB#0	21.05	PASS

FDD-LTE Band 66:

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Verdict
Band66	1.4MHz	QPSK	131979	1RB#0	21.92	PASS
Band66	1.4MHz	16QAM	131979	1RB#0	22.05	PASS
Band66	1.4MHz	QPSK	131979	1RB#2	21.82	PASS
Band66	1.4MHz	16QAM	131979	1RB#2	22.07	PASS
Band66	1.4MHz	QPSK	131979	1RB#5	21.84	PASS
Band66	1.4MHz	16QAM	131979	1RB#5	21.96	PASS
Band66	1.4MHz	QPSK	131979	3RB#0	21.90	PASS
Band66	1.4MHz	16QAM	131979	3RB#0	21.19	PASS
Band66	1.4MHz	QPSK	131979	3RB#1	21.88	PASS
Band66	1.4MHz	16QAM	131979	3RB#1	21.20	PASS
Band66	1.4MHz	QPSK	131979	3RB#3	21.88	PASS
Band66	1.4MHz	16QAM	131979	3RB#3	21.20	PASS
Band66	1.4MHz	QPSK	131979	6RB#0	21.39	PASS
Band66	1.4MHz	16QAM	131979	6RB#0	20.76	PASS
Band66	1.4MHz	QPSK	132322	1RB#0	21.89	PASS
Band66	1.4MHz	16QAM	132322	1RB#0	21.76	PASS
Band66	1.4MHz	QPSK	132322	1RB#2	21.91	PASS
Band66	1.4MHz	16QAM	132322	1RB#2	21.79	PASS
Band66	1.4MHz	QPSK	132322	1RB#5	21.82	PASS
Band66	1.4MHz	16QAM	132322	1RB#5	21.82	PASS
Band66	1.4MHz	QPSK	132322	3RB#0	21.90	PASS
Band66	1.4MHz	16QAM	132322	3RB#0	20.83	PASS
Band66	1.4MHz	QPSK	132322	3RB#1	21.84	PASS
Band66	1.4MHz	16QAM	132322	3RB#1	20.84	PASS
Band66	1.4MHz	QPSK	132322	3RB#3	21.82	PASS
Band66	1.4MHz	16QAM	132322	3RB#3	20.75	PASS
Band66	1.4MHz	QPSK	132322	6RB#0	21.37	PASS
Band66	1.4MHz	16QAM	132322	6RB#0	20.42	PASS
Band66	1.4MHz	QPSK	132665	1RB#0	21.88	PASS
Band66	1.4MHz	16QAM	132665	1RB#0	20.70	PASS
Band66	1.4MHz	QPSK	132665	1RB#2	21.81	PASS
Band66	1.4MHz	16QAM	132665	1RB#2	20.64	PASS
Band66	1.4MHz	QPSK	132665	1RB#5	21.82	PASS
Band66	1.4MHz	16QAM	132665	1RB#5	20.70	PASS
Band66	1.4MHz	QPSK	132665	3RB#0	21.82	PASS

Band66	1.4MHz	16QAM	132665	3RB#0	21.13	PASS
Band66	1.4MHz	QPSK	132665	3RB#1	21.80	PASS
Band66	1.4MHz	16QAM	132665	3RB#1	21.18	PASS
Band66	1.4MHz	QPSK	132665	3RB#3	21.78	PASS
Band66	1.4MHz	16QAM	132665	3RB#3	21.19	PASS
Band66	1.4MHz	QPSK	132665	6RB#0	21.42	PASS
Band66	1.4MHz	16QAM	132665	6RB#0	20.35	PASS
Band66	3MHz	QPSK	131987	1RB#0	21.84	PASS
Band66	3MHz	16QAM	131987	1RB#0	21.30	PASS
Band66	3MHz	QPSK	131987	1RB#8	21.83	PASS
Band66	3MHz	16QAM	131987	1RB#8	21.20	PASS
Band66	3MHz	QPSK	131987	1RB#14	21.86	PASS
Band66	3MHz	16QAM	131987	1RB#14	21.24	PASS
Band66	3MHz	QPSK	131987	8RB#0	21.42	PASS
Band66	3MHz	16QAM	131987	8RB#0	20.64	PASS
Band66	3MHz	QPSK	131987	8RB#4	21.37	PASS
Band66	3MHz	16QAM	131987	8RB#4	20.68	PASS
Band66	3MHz	QPSK	131987	8RB#7	21.39	PASS
Band66	3MHz	16QAM	131987	8RB#7	20.72	PASS
Band66	3MHz	QPSK	131987	15RB#0	21.35	PASS
Band66	3MHz	16QAM	131987	15RB#0	20.54	PASS
Band66	3MHz	QPSK	132322	1RB#0	21.83	PASS
Band66	3MHz	16QAM	132322	1RB#0	21.08	PASS
Band66	3MHz	QPSK	132322	1RB#8	21.82	PASS
Band66	3MHz	16QAM	132322	1RB#8	20.99	PASS
Band66	3MHz	QPSK	132322	1RB#14	21.76	PASS
Band66	3MHz	16QAM	132322	1RB#14	21.03	PASS
Band66	3MHz	QPSK	132322	8RB#0	21.42	PASS
Band66	3MHz	16QAM	132322	8RB#0	20.57	PASS
Band66	3MHz	QPSK	132322	8RB#4	21.43	PASS
Band66	3MHz	16QAM	132322	8RB#4	20.58	PASS
Band66	3MHz	QPSK	132322	8RB#7	21.39	PASS
Band66	3MHz	16QAM	132322	8RB#7	20.54	PASS
Band66	3MHz	QPSK	132322	15RB#0	21.42	PASS
Band66	3MHz	16QAM	132322	15RB#0	20.58	PASS
Band66	3MHz	QPSK	132657	1RB#0	21.92	PASS
Band66	3MHz	16QAM	132657	1RB#0	20.68	PASS
Band66	3MHz	QPSK	132657	1RB#8	21.86	PASS
Band66	3MHz	16QAM	132657	1RB#8	20.70	PASS
Band66	3MHz	QPSK	132657	1RB#14	21.86	PASS
Band66	3MHz	16QAM	132657	1RB#14	20.63	PASS
Band66	3MHz	QPSK	132657	8RB#0	21.35	PASS

Band66	3MHz	16QAM	132657	8RB#0	20.59	PASS
Band66	3MHz	QPSK	132657	8RB#4	21.36	PASS
Band66	3MHz	16QAM	132657	8RB#4	20.57	PASS
Band66	3MHz	QPSK	132657	8RB#7	21.22	PASS
Band66	3MHz	16QAM	132657	8RB#7	20.56	PASS
Band66	3MHz	QPSK	132657	15RB#0	21.29	PASS
Band66	3MHz	16QAM	132657	15RB#0	20.31	PASS
Band66	5MHz	QPSK	131997	1RB#0	21.96	PASS
Band66	5MHz	16QAM	131997	1RB#0	20.95	PASS
Band66	5MHz	QPSK	131997	1RB#12	21.99	PASS
Band66	5MHz	16QAM	131997	1RB#12	20.92	PASS
Band66	5MHz	QPSK	131997	1RB#24	22.00	PASS
Band66	5MHz	16QAM	131997	1RB#24	21.04	PASS
Band66	5MHz	QPSK	131997	12RB#0	21.46	PASS
Band66	5MHz	16QAM	131997	12RB#0	20.55	PASS
Band66	5MHz	QPSK	131997	12RB#6	21.46	PASS
Band66	5MHz	16QAM	131997	12RB#6	20.55	PASS
Band66	5MHz	QPSK	131997	12RB#13	21.52	PASS
Band66	5MHz	16QAM	131997	12RB#13	20.47	PASS
Band66	5MHz	QPSK	131997	25RB#0	21.50	PASS
Band66	5MHz	16QAM	131997	25RB#0	20.62	PASS
Band66	5MHz	QPSK	132322	1RB#0	21.88	PASS
Band66	5MHz	16QAM	132322	1RB#0	20.89	PASS
Band66	5MHz	QPSK	132322	1RB#12	21.90	PASS
Band66	5MHz	16QAM	132322	1RB#12	20.79	PASS
Band66	5MHz	QPSK	132322	1RB#24	21.81	PASS
Band66	5MHz	16QAM	132322	1RB#24	20.79	PASS
Band66	5MHz	QPSK	132322	12RB#0	21.32	PASS
Band66	5MHz	16QAM	132322	12RB#0	20.42	PASS
Band66	5MHz	QPSK	132322	12RB#6	21.33	PASS
Band66	5MHz	16QAM	132322	12RB#6	20.30	PASS
Band66	5MHz	QPSK	132322	12RB#13	21.25	PASS
Band66	5MHz	16QAM	132322	12RB#13	20.38	PASS
Band66	5MHz	QPSK	132322	25RB#0	21.30	PASS
Band66	5MHz	16QAM	132322	25RB#0	20.47	PASS
Band66	5MHz	QPSK	132647	1RB#0	21.79	PASS
Band66	5MHz	16QAM	132647	1RB#0	20.82	PASS
Band66	5MHz	QPSK	132647	1RB#12	21.77	PASS
Band66	5MHz	16QAM	132647	1RB#12	20.79	PASS
Band66	5MHz	QPSK	132647	1RB#24	21.81	PASS
Band66	5MHz	16QAM	132647	1RB#24	20.81	PASS
Band66	5MHz	QPSK	132647	12RB#0	21.31	PASS

Band66	5MHz	16QAM	132647	12RB#0	20.33	PASS
Band66	5MHz	QPSK	132647	12RB#6	21.33	PASS
Band66	5MHz	16QAM	132647	12RB#6	20.35	PASS
Band66	5MHz	QPSK	132647	12RB#13	21.30	PASS
Band66	5MHz	16QAM	132647	12RB#13	20.35	PASS
Band66	5MHz	QPSK	132647	25RB#0	21.23	PASS
Band66	5MHz	16QAM	132647	25RB#0	20.49	PASS
Band66	10MHz	QPSK	132022	1RB#0	21.91	PASS
Band66	10MHz	16QAM	132022	1RB#0	21.48	PASS
Band66	10MHz	QPSK	132022	1RB#24	21.91	PASS
Band66	10MHz	16QAM	132022	1RB#24	21.51	PASS
Band66	10MHz	QPSK	132022	1RB#49	21.96	PASS
Band66	10MHz	16QAM	132022	1RB#49	21.48	PASS
Band66	10MHz	QPSK	132022	25RB#0	21.56	PASS
Band66	10MHz	16QAM	132022	25RB#0	20.50	PASS
Band66	10MHz	QPSK	132022	25RB#12	21.59	PASS
Band66	10MHz	16QAM	132022	25RB#12	20.50	PASS
Band66	10MHz	QPSK	132022	25RB#25	21.56	PASS
Band66	10MHz	16QAM	132022	25RB#25	20.57	PASS
Band66	10MHz	QPSK	132022	50RB#0	21.51	PASS
Band66	10MHz	16QAM	132022	50RB#0	20.58	PASS
Band66	10MHz	QPSK	132322	1RB#0	21.85	PASS
Band66	10MHz	16QAM	132322	1RB#0	21.43	PASS
Band66	10MHz	QPSK	132322	1RB#24	21.77	PASS
Band66	10MHz	16QAM	132322	1RB#24	21.35	PASS
Band66	10MHz	QPSK	132322	1RB#49	21.82	PASS
Band66	10MHz	16QAM	132322	1RB#49	21.40	PASS
Band66	10MHz	QPSK	132322	25RB#0	21.35	PASS
Band66	10MHz	16QAM	132322	25RB#0	20.39	PASS
Band66	10MHz	QPSK	132322	25RB#12	21.33	PASS
Band66	10MHz	16QAM	132322	25RB#12	20.40	PASS
Band66	10MHz	QPSK	132322	25RB#25	21.44	PASS
Band66	10MHz	16QAM	132322	25RB#25	20.42	PASS
Band66	10MHz	QPSK	132322	50RB#0	21.39	PASS
Band66	10MHz	16QAM	132322	50RB#0	20.39	PASS
Band66	10MHz	QPSK	132622	1RB#0	21.78	PASS
Band66	10MHz	16QAM	132622	1RB#0	21.38	PASS
Band66	10MHz	QPSK	132622	1RB#24	21.70	PASS
Band66	10MHz	16QAM	132622	1RB#24	21.32	PASS
Band66	10MHz	QPSK	132622	1RB#49	21.65	PASS
Band66	10MHz	16QAM	132622	1RB#49	21.26	PASS
Band66	10MHz	QPSK	132622	25RB#0	21.36	PASS

Band66	10MHz	16QAM	132622	25RB#0	20.32	PASS
Band66	10MHz	QPSK	132622	25RB#12	21.27	PASS
Band66	10MHz	16QAM	132622	25RB#12	20.34	PASS
Band66	10MHz	QPSK	132622	25RB#25	21.20	PASS
Band66	10MHz	16QAM	132622	25RB#25	20.26	PASS
Band66	10MHz	QPSK	132622	50RB#0	21.35	PASS
Band66	10MHz	16QAM	132622	50RB#0	20.32	PASS
Band66	15MHz	QPSK	132047	1RB#0	21.99	PASS
Band66	15MHz	16QAM	132047	1RB#0	21.57	PASS
Band66	15MHz	QPSK	132047	1RB#38	21.96	PASS
Band66	15MHz	16QAM	132047	1RB#38	21.53	PASS
Band66	15MHz	QPSK	132047	1RB#74	21.92	PASS
Band66	15MHz	16QAM	132047	1RB#74	21.50	PASS
Band66	15MHz	QPSK	132047	38RB#0	21.46	PASS
Band66	15MHz	16QAM	132047	38RB#0	21.58	PASS
Band66	15MHz	QPSK	132047	38RB#18	21.58	PASS
Band66	15MHz	16QAM	132047	38RB#18	21.58	PASS
Band66	15MHz	QPSK	132047	38RB#37	21.59	PASS
Band66	15MHz	16QAM	132047	38RB#37	21.58	PASS
Band66	15MHz	QPSK	132047	75RB#0	21.59	PASS
Band66	15MHz	16QAM	132047	75RB#0	20.54	PASS
Band66	15MHz	QPSK	132322	1RB#0	21.93	PASS
Band66	15MHz	16QAM	132322	1RB#0	21.45	PASS
Band66	15MHz	QPSK	132322	1RB#38	21.83	PASS
Band66	15MHz	16QAM	132322	1RB#38	21.39	PASS
Band66	15MHz	QPSK	132322	1RB#74	21.83	PASS
Band66	15MHz	16QAM	132322	1RB#74	21.41	PASS
Band66	15MHz	QPSK	132322	38RB#0	21.42	PASS
Band66	15MHz	16QAM	132322	38RB#0	21.42	PASS
Band66	15MHz	QPSK	132322	38RB#18	21.42	PASS
Band66	15MHz	16QAM	132322	38RB#18	21.42	PASS
Band66	15MHz	QPSK	132322	38RB#37	21.42	PASS
Band66	15MHz	16QAM	132322	38RB#37	21.42	PASS
Band66	15MHz	QPSK	132322	75RB#0	21.42	PASS
Band66	15MHz	16QAM	132322	75RB#0	20.40	PASS
Band66	15MHz	QPSK	132597	1RB#0	21.78	PASS
Band66	15MHz	16QAM	132597	1RB#0	21.39	PASS
Band66	15MHz	QPSK	132597	1RB#38	21.66	PASS
Band66	15MHz	16QAM	132597	1RB#38	21.25	PASS
Band66	15MHz	QPSK	132597	1RB#74	21.58	PASS
Band66	15MHz	16QAM	132597	1RB#74	21.19	PASS
Band66	15MHz	QPSK	132597	38RB#0	21.30	PASS

Band66	15MHz	16QAM	132597	38RB#0	21.31	PASS
Band66	15MHz	QPSK	132597	38RB#18	21.31	PASS
Band66	15MHz	16QAM	132597	38RB#18	21.31	PASS
Band66	15MHz	QPSK	132597	38RB#37	21.32	PASS
Band66	15MHz	16QAM	132597	38RB#37	21.32	PASS
Band66	15MHz	QPSK	132597	75RB#0	21.32	PASS
Band66	15MHz	16QAM	132597	75RB#0	20.28	PASS
Band66	20MHz	QPSK	132072	1RB#0	22.23	PASS
Band66	20MHz	16QAM	132072	1RB#0	21.43	PASS
Band66	20MHz	QPSK	132072	1RB#49	22.17	PASS
Band66	20MHz	16QAM	132072	1RB#49	21.34	PASS
Band66	20MHz	QPSK	132072	1RB#99	22.11	PASS
Band66	20MHz	16QAM	132072	1RB#99	21.30	PASS
Band66	20MHz	QPSK	132072	50RB#0	21.59	PASS
Band66	20MHz	16QAM	132072	50RB#0	20.71	PASS
Band66	20MHz	QPSK	132072	50RB#25	21.61	PASS
Band66	20MHz	16QAM	132072	50RB#25	20.71	PASS
Band66	20MHz	QPSK	132072	50RB#50	21.46	PASS
Band66	20MHz	16QAM	132072	50RB#50	20.70	PASS
Band66	20MHz	QPSK	132072	100RB#0	21.46	PASS
Band66	20MHz	16QAM	132072	100RB#0	20.53	PASS
Band66	20MHz	QPSK	132322	1RB#0	22.04	PASS
Band66	20MHz	16QAM	132322	1RB#0	22.07	PASS
Band66	20MHz	QPSK	132322	1RB#49	21.96	PASS
Band66	20MHz	16QAM	132322	1RB#49	21.86	PASS
Band66	20MHz	QPSK	132322	1RB#99	21.98	PASS
Band66	20MHz	16QAM	132322	1RB#99	21.87	PASS
Band66	20MHz	QPSK	132322	50RB#0	21.42	PASS
Band66	20MHz	16QAM	132322	50RB#0	20.58	PASS
Band66	20MHz	QPSK	132322	50RB#25	21.44	PASS
Band66	20MHz	16QAM	132322	50RB#25	20.66	PASS
Band66	20MHz	QPSK	132322	50RB#50	21.47	PASS
Band66	20MHz	16QAM	132322	50RB#50	20.52	PASS
Band66	20MHz	QPSK	132322	100RB#0	21.44	PASS
Band66	20MHz	16QAM	132322	100RB#0	20.57	PASS
Band66	20MHz	QPSK	132572	1RB#0	21.93	PASS
Band66	20MHz	16QAM	132572	1RB#0	21.09	PASS
Band66	20MHz	QPSK	132572	1RB#49	21.87	PASS
Band66	20MHz	16QAM	132572	1RB#49	21.08	PASS
Band66	20MHz	QPSK	132572	1RB#99	21.80	PASS
Band66	20MHz	16QAM	132572	1RB#99	20.96	PASS
Band66	20MHz	QPSK	132572	50RB#0	21.38	PASS

Band66	20MHz	16QAM	132572	50RB#0	20.53	PASS
Band66	20MHz	QPSK	132572	50RB#25	21.16	PASS
Band66	20MHz	16QAM	132572	50RB#25	20.47	PASS
Band66	20MHz	QPSK	132572	50RB#50	21.17	PASS
Band66	20MHz	16QAM	132572	50RB#50	20.29	PASS
Band66	20MHz	QPSK	132572	100RB#0	21.22	PASS
Band66	20MHz	16QAM	132572	100RB#0	20.14	PASS

Remark:

1. Per KDB941225 D05 v02r05, start with the largest channel bandwidth then measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle, and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. 6 When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.
2. Per KDB941225 D05 v02r05, the procedures required for 1 RB allocation in 5.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.
3. Per KDB941225 D05 v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations, and the highest reported SAR for 1 RB and 50% RB allocation in 5.2.1 and 5.2.2 are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB941225 D05 v02r05, for each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in 5.2.1, 5.2.2, and 5.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

WLAN(2.4GHz)					
Test Mode	Data Rate	Channel	Frequency (MHz)	Conducted Power (dBm)	Tune-up power (dBm)
802.11b	11Mbps	CH 01	2412	15.42	16.0
		CH 06	2437	15.72	16.0
		CH 11	2462	15.45	16.0
802.11g	54Mbps	CH 01	2412	14.76	15.0
		CH 06	2437	14.28	15.0
		CH 11	2462	14.16	15.0
802.11n-HT20	MCS7	CH 01	2412	13.81	14.0
		CH 06	2437	13.24	14.0
		CH 11	2462	13.10	14.0
802.11n-HT40	MCS7	CH 03	2422	12.16	13.0
		CH 06	2437	12.05	13.0
		CH 09	2452	12.05	13.0

WLAN(5.2GHz)				
Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Tune-up power (dBm)
802.11a	CH 36	5180	14.87	15.0
	CH 40	5200	14.63	15.0
	CH 48	5240	14.38	15.0
802.11n-HT20	CH 36	5180	13.90	14.0
	CH 40	5200	13.54	14.0
	CH 48	5240	13.28	14.0
802.11n-HT40	CH 38	5190	13.17	14.0
	CH 46	5230	12.70	14.0
802.11ac-VHT20	CH 36	5180	13.97	14.0
	CH 40	5200	13.81	14.0
	CH 48	5240	13.14	14.0
802.11ac-VHT40	CH 38	5190	13.33	14.0
	CH 46	5230	12.64	14.0
802.11ac-VHT80	CH 42	5210	12.73	14.0

WLAN(5.3GHz)				
Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Tune-up power (dBm)
802.11a	CH 52	5260	15.20	15.5
	CH 56	5280	15.25	15.5
	CH 64	5320	14.81	15.5
802.11n-HT20	CH 52	5260	14.19	14.5
	CH 56	5280	14.28	14.5
	CH 64	5320	13.84	14.5
802.11n-HT40	CH 54	5270	13.66	14.0
	CH 62	5310	13.43	14.0
802.11ac-VHT20	CH 52	5260	13.85	14.5
	CH 56	5280	13.81	14.5
	CH 64	5320	13.48	14.5
802.11ac-VHT40	CH 54	5270	13.39	14.0
	CH 62	5310	13.02	14.0
802.11ac-VHT80	CH 58	5290	13.22	14.0

WLAN(5.6GHz)				
Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Tune-up power (dBm)
802.11a	CH 100	5500	14.70	15.0
	CH 120	5600	14.31	15.0
	CH 140	5700	13.55	15.0
802.11n-HT20	CH 100	5500	13.75	14.0
	CH 120	5600	13.21	14.0
	CH 140	5700	12.50	14.0
802.11n-HT40	CH 102	5510	12.98	13.0
	CH 118	5590	12.71	13.0
	CH 134	5670	12.28	13.0
802.11ac-VHT20	CH 100	5500	13.80	14.0
	CH 120	5600	13.04	14.0
	CH 140	5700	12.75	14.0
802.11ac-VHT40	CH 102	5510	12.98	13.0
	CH 118	5590	12.71	13.0
	CH 134	5670	12.08	13.0
802.11ac-VHT80	CH 106	5530	12.36	13.0
	CH 122	5610	12.56	13.0

WLAN(5.8GHz)				
Test Mode	Channel	Frequency (MHz)	Conducted Power (dBm)	Tune-up power (dBm)
802.11a	CH 149	5745	13.31	13.5
	CH 157	5785	13.12	13.5
	CH 165	5825	13.34	13.5
802.11n-HT20	CH 149	5745	12.31	12.5
	CH 157	5785	12.18	12.5
	CH 165	5825	12.33	12.5
802.11n-HT40	CH 151	5755	11.63	12.0
	CH 159	5795	11.58	12.0
802.11ac-VHT20	CH 149	5745	12.89	13.0
	CH 157	5785	12.49	13.0
	CH 165	5825	12.40	13.0
802.11ac-VHT40	CH 151	5755	12.15	13.0
	CH 159	5795	11.77	13.0
802.11ac-VHT80	CH 155	5775	11.42	12.0

Remark:

1. Per KDB 248227 D01 v02r02, for 802.11b DSSS SAR measurements, DSSS SAR procedure applies to fixed exposure test position and initial test position procedure applies to multiple exposure test positions.
2. Per KDB 248227 D01 v02r02, For 802.11b DSSS SAR measurements ,when the reported SAR of the highest measured maximum output power channel (see 3.1) for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration. When the reported SAR is > 0.8 W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel; i.e., all channels require testing.
3. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
4. Per KDB 248227 D01 v02r02, When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined by applying the following steps sequentially.
 - 1) The largest channel bandwidth configuration is selected among the multiple configurations in a frequency band with the same specified maximum output power.
 - 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
 - 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
 - 4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n.

Bluetooth - Maximum Average Power				
Test Mode	Data Rate	Frequency (MHz)	Conducted Power(dBm)	Tune-up power (dBm)
GFSK	1Mbps	2402	1.68	3.0
		2441	1.37	3.0
		2480	1.83	3.0
$\pi/4$ DQPSK	2Mbps	2402	2.57	3.0
		2441	2.30	3.0
		2480	2.51	3.0
8DPSK	3Mbps	2402	2.88	3.0
		2441	2.54	3.0
		2480	2.76	3.0

Bluetooth - Maximum Average Power					
Test Mode	Data Rate	Channel	Frequency (MHz)	Conducted Power(dBm)	Tune-up power (dBm)
BLE	1Mbps	CH 00	2402	3.19	4.0
		CH 19	2440	2.96	4.0
		CH 39	2480	3.46	4.0
	2Mbps	CH 00	2402	3.40	4.0
		CH 19	2440	3.21	4.0
		CH 39	2480	3.67	4.0

Remark:

Bluetooth maximum output power is 3.67dBm and Maximum Tune-Up output power is 4.0dBm. Per KDB 447498 D01 V06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Bluetooth:

Tune-Up Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	Result	Limit
4.0	2.51	5	2.48	0.791	3

The exclusion threshold is $0.791 < 3$, therefore, the RF exposure evaluation is not required.

9.2 Test Results for Standalone SAR Test

Head SAR

GSM850 – Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	GSM	Right Cheek	190	836.6	32.21	32.5	1.069	0.063	0.067
	GSM	Right Tilted	190	836.6	32.21	32.5	1.069	0.058	0.062
1.	GSM	Left Cheek	190	836.6	32.21	32.5	1.069	0.074	0.079
	GSM	Left Tilted	190	836.6	32.21	32.5	1.069	0.065	0.069

GPRS850 – Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	GPRS_2TX	Right Cheek	190	836.6	30.05	30.5	1.109	0.080	0.089
	GPRS_2TX	Right Tilted	190	836.6	30.05	30.5	1.109	0.073	0.081
2.	GPRS_2TX	Left Cheek	190	836.6	30.05	30.5	1.109	0.100	0.111
	GPRS_2TX	Left Tilted	190	836.6	30.05	30.5	1.109	0.086	0.095

GSM1900 – Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
3.	GSM	Right Cheek	512	1850.2	28.42	28.5	1.019	0.048	0.049
	GSM	Right Tilted	512	1850.2	28.42	28.5	1.019	0.043	0.044
	GSM	Left Cheek	512	1850.2	28.42	28.5	1.019	0.029	0.030
	GSM	Left Tilted	512	1850.2	28.42	28.5	1.019	0.025	0.025

GPRS1900 – Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
4.	GPRS_3TX	Right Cheek	512	1850.2	24.59	25.0	1.099	0.053	0.058
	GPRS_3TX	Right Tilted	512	1850.2	24.59	25.0	1.099	0.048	0.053
	GPRS_3TX	Left Cheek	512	1850.2	24.59	25.0	1.099	0.026	0.029
	GPRS_3TX	Left Tilted	512	1850.2	24.59	25.0	1.099	0.023	0.025

WCDMA Band 2 – Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
5.	RMC	Right Cheek	9262	1852.4	21.26	21.5	1.057	0.068	0.072
	RMC	Right Tilted	9262	1852.4	21.26	21.5	1.057	0.062	0.066
	RMC	Left Cheek	9262	1852.4	21.26	21.5	1.057	0.040	0.042
	RMC	Left Tilted	9262	1852.4	21.26	21.5	1.057	0.035	0.037

WCDMA Band 4 – Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
6.	RMC	Right Cheek	1312	1712.4	21.98	22.0	1.005	0.023	0.023
	RMC	Right Tilted	1312	1712.4	21.98	22.0	1.005	0.021	0.021
	RMC	Left Cheek	1312	1712.4	21.98	22.0	1.005	0.019	0.019
	RMC	Left Tilted	1312	1712.4	21.98	22.0	1.005	0.016	0.016

WCDMA Band 5 – Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
7.	RMC	Right Cheek	4132	826.4	22.26	22.5	1.057	0.059	0.062
	RMC	Right Tilted	4132	826.4	22.26	22.5	1.057	0.052	0.055
	RMC	Left Cheek	4132	826.4	22.26	22.5	1.057	0.059	0.062
	RMC	Left Tilted	4132	826.4	22.26	22.5	1.057	0.050	0.053

LTE Band 2– Head SAR Test								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
8.	QPSK 20MHz 1RB	Right Cheek	1880	21.43	22.0	1.140	0.123	0.140
	QPSK 20MHz 1RB	Right Tilted	1880	21.43	22.0	1.140	0.116	0.132
	QPSK 20MHz 1RB	Left Cheek	1880	21.43	22.0	1.140	0.057	0.065
	QPSK 20MHz 1RB	Left Tilted	1880	21.43	22.0	1.140	0.055	0.063
	QPSK 20MHz 50%RB	Right Cheek	1880	21.43	22.0	1.140	0.111	0.127
	QPSK 20MHz 50%RB	Right Tilted	1880	21.43	22.0	1.140	0.103	0.117
	QPSK 20MHz 50%RB	Left Cheek	1880	21.43	22.0	1.140	0.052	0.059
	QPSK 20MHz 50%RB	Left Tilted	1880	21.43	22.0	1.140	0.049	0.056

LTE Band 4– Head SAR Test								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
9.	QPSK 20MHz 1RB	Right Cheek	1745	21.77	22.0	1.054	0.041	0.043
	QPSK 20MHz 1RB	Right Tilted	1745	21.77	22.0	1.054	0.038	0.040
	QPSK 20MHz 1RB	Left Cheek	1745	21.77	22.0	1.054	0.035	0.037
	QPSK 20MHz 1RB	Left Tilted	1745	21.77	22.0	1.054	0.032	0.034
	QPSK 20MHz 50%RB	Right Cheek	1745	21.77	22.0	1.054	0.037	0.039
	QPSK 20MHz 50%RB	Right Tilted	1745	21.77	22.0	1.054	0.033	0.035
	QPSK 20MHz 50%RB	Left Cheek	1745	21.77	22.0	1.054	0.029	0.031
	QPSK 20MHz 50%RB	Left Tilted	1745	21.77	22.0	1.054	0.028	0.030

LTE Band 5– Head SAR Test								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
10.	16QAM 10MHz 1RB	Right Cheek	829	22.10	23.0	1.230	0.087	0.107
	16QAM 10MHz 1RB	Right Tilted	829	22.10	23.0	1.230	0.080	0.098
	16QAM 10MHz 1RB	Left Cheek	829	22.10	23.0	1.230	0.056	0.069
	16QAM 10MHz 1RB	Left Tilted	829	22.10	23.0	1.230	0.052	0.064
	16QAM 10MHz 50%RB	Right Cheek	829	22.10	23.0	1.230	0.078	0.096
	16QAM 10MHz 50%RB	Right Tilted	829	22.10	23.0	1.230	0.072	0.089
	16QAM 10MHz 50%RB	Left Cheek	829	22.10	23.0	1.230	0.045	0.055
	16QAM 10MHz 50%RB	Left Tilted	829	22.10	23.0	1.230	0.040	0.049

LTE Band 7– Head SAR Test								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
11.	16QAM 20MHz 1RB	Right Cheek	2535	20.85	21.0	1.035	0.031	0.032
	16QAM 20MHz 1RB	Right Tilted	2535	20.85	21.0	1.035	0.029	0.030
	16QAM 20MHz 1RB	Left Cheek	2535	20.85	21.0	1.035	0.016	0.017
	16QAM 20MHz 1RB	Left Tilted	2535	20.85	21.0	1.035	0.014	0.014
	16QAM 20MHz 50%RB	Right Cheek	2535	20.85	21.0	1.035	0.027	0.028
	16QAM 20MHz 50%RB	Right Tilted	2535	20.85	21.0	1.035	0.023	0.024
	16QAM 20MHz 50%RB	Left Cheek	2535	20.85	21.0	1.035	0.012	0.012
	16QAM 20MHz 50%RB	Left Tilted	2535	20.85	21.0	1.035	0.011	0.011

LTE Band 12– Head SAR Test								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
12.	16QAM 10MHz 1RB	Right Cheek	711	22.44	23.0	1.138	0.125	0.142
	16QAM 10MHz 1RB	Right Tilted	711	22.44	23.0	1.138	0.109	0.124
	16QAM 10MHz 1RB	Left Cheek	711	22.44	23.0	1.138	0.102	0.116
	16QAM 10MHz 1RB	Left Tilted	711	22.44	23.0	1.138	0.090	0.102
	16QAM 10MHz 50%RB	Right Cheek	711	22.44	23.0	1.138	0.112	0.127
	16QAM 10MHz 50%RB	Right Tilted	711	22.44	23.0	1.138	0.100	0.114
	16QAM 10MHz 50%RB	Left Cheek	711	22.44	23.0	1.138	0.089	0.101
	16QAM 10MHz 50%RB	Left Tilted	711	22.44	23.0	1.138	0.078	0.089

LTE Band 13– Head SAR Test								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
13.	QPSK 10MHz 1RB	Right Cheek	782	22.25	23.0	1.189	0.103	0.122
	QPSK 10MHz 1RB	Right Tilted	782	22.25	23.0	1.189	0.090	0.107
	QPSK 10MHz 1RB	Left Cheek	782	22.25	23.0	1.189	0.087	0.103
	QPSK 10MHz 1RB	Left Tilted	782	22.25	23.0	1.189	0.080	0.095
	QPSK 10MHz 50%RB	Right Cheek	782	22.25	23.0	1.189	0.088	0.105
	QPSK 10MHz 50%RB	Right Tilted	782	22.25	23.0	1.189	0.080	0.095
	QPSK 10MHz 50%RB	Left Cheek	782	22.25	23.0	1.189	0.075	0.089
	QPSK 10MHz 50%RB	Left Tilted	782	22.25	23.0	1.189	0.061	0.072

LTE Band 17– Head SAR Test								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
14.	16QAM 10MHz 1RB	Right Cheek	711	22.44	23.0	1.138	0.126	0.143
	16QAM 10MHz 1RB	Right Tilted	711	22.44	23.0	1.138	0.115	0.131
	16QAM 10MHz 1RB	Left Cheek	711	22.44	23.0	1.138	0.106	0.121
	16QAM 10MHz 1RB	Left Tilted	711	22.44	23.0	1.138	0.088	0.100
	16QAM 10MHz 50%RB	Right Cheek	711	22.44	23.0	1.138	0.110	0.125
	16QAM 10MHz 50%RB	Right Tilted	711	22.44	23.0	1.138	0.100	0.114
	16QAM 10MHz 50%RB	Left Cheek	711	22.44	23.0	1.138	0.099	0.113
	16QAM 10MHz 50%RB	Left Tilted	711	22.44	23.0	1.138	0.078	0.089

LTE Band 66– Head SAR Test								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
15.	QPSK 20MHz 1RB	Right Cheek	1720	22.23	23.0	1.194	0.034	0.041
	QPSK 20MHz 1RB	Right Tilted	1720	22.23	23.0	1.194	0.031	0.037
	QPSK 20MHz 1RB	Left Cheek	1720	22.23	23.0	1.194	0.029	0.035
	QPSK 20MHz 1RB	Left Tilted	1720	22.23	23.0	1.194	0.027	0.032
	QPSK 20MHz 50%RB	Right Cheek	1720	22.23	23.0	1.194	0.030	0.036
	QPSK 20MHz 50%RB	Right Tilted	1720	22.23	23.0	1.194	0.028	0.033
	QPSK 20MHz 50%RB	Left Cheek	1720	22.23	23.0	1.194	0.026	0.031
	QPSK 20MHz 50%RB	Left Tilted	1720	22.23	23.0	1.194	0.025	0.030

WLAN 2.4GHz – Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11b	Right Cheek	06	2437	15.72	16.0	1.067	0.054	0.058
	802.11b	Right Tilted	06	2437	15.72	16.0	1.067	0.044	0.047
16.	802.11b	Left Cheek	06	2437	15.72	16.0	1.067	0.160	0.171
	802.11b	Left Tilted	06	2437	15.72	16.0	1.067	0.151	0.161

WLAN 5.2GHz – Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11a	Right Cheek	36	5180	14.87	15.0	1.030	0.219	0.226
	802.11a	Right Tilted	36	5180	14.87	15.0	1.030	0.202	0.208
17.	802.11a	Left Cheek	36	5180	14.87	15.0	1.030	0.541	0.557
	802.11a	Left Tilted	36	5180	14.87	15.0	1.030	0.508	0.523

WLAN 5.3GHz – Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11a	Right Cheek	56	5280	15.25	15.5	1.059	0.234	0.248
	802.11a	Right Tilted	56	5280	15.25	15.5	1.059	0.222	0.235
18.	802.11a	Left Cheek	56	5280	15.25	15.5	1.059	0.539	0.571
	802.11a	Left Tilted	56	5280	15.25	15.5	1.059	0.498	0.528

WLAN 5.6GHz– Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11a	Right Cheek	100	5500	14.70	15.0	1.072	0.287	0.308
	802.11a	Right Tilted	100	5500	14.70	15.0	1.072	0.268	0.287
19.	802.11a	Left Cheek	100	5500	14.70	15.0	1.072	0.553	0.593
	802.11a	Left Tilted	100	5500	14.70	15.0	1.072	0.512	0.549

WLAN 5.8GHz– Head SAR Test									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11a	Right Cheek	165	5825	13.34	13.5	1.038	0.170	0.176
	802.11a	Right Tilted	165	5825	13.34	13.5	1.038	0.164	0.170
20.	802.11a	Left Cheek	165	5825	13.34	13.5	1.038	0.494	0.513
	802.11a	Left Tilted	165	5825	13.34	13.5	1.038	0.473	0.491

Remark: Per KDB 447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

Body-worn SAR

GSM850 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
21.	GSM	Back Face	190	836.6	32.21	32.5	1.069	0.143	0.153
	GSM	Front Face	190	836.6	32.21	32.5	1.069	0.041	0.044

GSM1900 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
22.	GSM	Back Face	512	1850.2	28.42	28.5	1.019	0.288	0.293
	GSM	Front Face	512	1850.2	28.42	28.5	1.019	0.222	0.226

WCDMA Band 2 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
23.	RMC 12.2k	Back Face	9262	1852.4	21.26	21.5	1.057	0.378	0.399
	RMC 12.2k	Front Face	9262	1852.4	21.26	21.5	1.057	0.257	0.272

WCDMA Band 4– Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
24.	RMC 12.2k	Back Face	1312	1712.4	21.98	22.0	1.005	0.139	0.140
	RMC 12.2k	Front Face	1312	1712.4	21.98	22.0	1.005	0.079	0.079

WCDMA Band 5 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
25.	RMC 12.2k	Back Face	4132	826.4	22.26	22.5	1.057	0.109	0.115
	RMC 12.2k	Front Face	4132	826.4	22.26	22.5	1.057	0.037	0.039

LTE Band 2–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
26.	QPSK 20MHz 1RB	Back Face	1880	21.43	22.0	1.140	0.461	0.526
	QPSK 20MHz 1RB	Front Face	1880	21.43	22.0	1.140	0.332	0.379
	QPSK 20MHz 50%RB	Back Face	1880	21.43	22.0	1.140	0.437	0.498
	QPSK 20MHz 50%RB	Front Face	1880	21.43	22.0	1.140	0.224	0.255

LTE Band 4–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
27.	QPSK 20MHz 1RB	Back Face	1745	21.77	22.0	1.054	0.151	0.159
	QPSK 20MHz 1RB	Front Face	1745	21.77	22.0	1.054	0.089	0.094
	QPSK 20MHz 50%RB	Back Face	1745	21.77	22.0	1.054	0.136	0.143
	QPSK 20MHz 50%RB	Front Face	1745	21.77	22.0	1.054	0.078	0.082

LTE Band 5–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
28.	16QAM 10MHz 1RB	Back Face	829	22.10	23.0	1.230	0.104	0.128
	16QAM 10MHz 1RB	Front Face	829	22.10	23.0	1.230	0.025	0.031
	16QAM 10MHz 50%RB	Back Face	829	22.10	23.0	1.230	0.089	0.109
	16QAM 10MHz 50%RB	Front Face	829	22.10	23.0	1.230	0.020	0.025

LTE Band 7–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
29.	16QAM 20MHz 1RB	Back Face	2535	20.85	21.0	1.035	0.247	0.256
	16QAM 20MHz 1RB	Front Face	2535	20.85	21.0	1.035	0.095	0.098
	16QAM 20MHz 50%RB	Back Face	2535	20.85	21.0	1.035	0.228	0.236
	16QAM 20MHz 50%RB	Front Face	2535	20.85	21.0	1.035	0.083	0.086

LTE Band 12–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
30.	16QAM 10MHz 1RB	Back Face	711	22.44	23.0	1.138	0.224	0.255
	16QAM 10MHz 1RB	Front Face	711	22.44	23.0	1.138	0.134	0.152
	16QAM 10MHz 50%RB	Back Face	711	22.44	23.0	1.138	0.206	0.234
	16QAM 10MHz 50%RB	Front Face	711	22.44	23.0	1.138	0.110	0.125

LTE Band 13–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
31.	QPSK 10MHz 1RB	Back Face	782	22.25	23.0	1.189	0.130	0.155
	QPSK 10MHz 1RB	Front Face	782	22.25	23.0	1.189	0.095	0.113
	QPSK 10MHz 50%RB	Back Face	782	22.25	23.0	1.189	0.102	0.121
	QPSK 10MHz 50%RB	Front Face	782	22.25	23.0	1.189	0.087	0.103

LTE Band 17–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
32.	16QAM 10MHz 1RB	Back Face	711	22.44	23.0	1.138	0.219	0.249
	16QAM 10MHz 1RB	Front Face	711	22.44	23.0	1.138	0.133	0.151
	16QAM 10MHz 50%RB	Back Face	711	22.44	23.0	1.138	0.200	0.228
	16QAM 10MHz 50%RB	Front Face	711	22.44	23.0	1.138	0.112	0.127

LTE Band 66–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
33.	QPSK 20MHz 1RB	Back Face	1720	22.23	23.0	1.194	0.148	0.177
	QPSK 20MHz 1RB	Front Face	1720	22.23	23.0	1.194	0.051	0.061
	QPSK 20MHz 50%RB	Back Face	1720	22.23	23.0	1.194	0.135	0.161
	QPSK 20MHz 50%RB	Front Face	1720	22.23	23.0	1.194	0.043	0.051

WLAN 2.4GHz –Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11b	Back Face	06	2437	15.72	16.0	1.067	0.023	0.025
34.	802.11b	Front Face	06	2437	15.72	16.0	1.067	0.036	0.038

WLAN 5.2GHz –Body SAR Test(Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11a	Back Face	36	5180	14.87	15.0	1.030	0.068	0.070
35.	802.11a	Front Face	36	5180	14.87	15.0	1.030	0.081	0.083

WLAN 5.3GHz –Body SAR Test(Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11a	Back Face	56	5280	15.25	15.5	1.059	0.059	0.062
36.	802.11a	Front Face	56	5280	15.25	15.5	1.059	0.079	0.084

WLAN 5.6GHz–Body SAR Test(Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11a	Back Face	100	5500	14.70	15.0	1.072	0.076	0.081
37.	802.11a	Front Face	100	5500	14.70	15.0	1.072	0.091	0.098

WLAN 5.8GHz –Body SAR Test(Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11a	Back Face	165	5825	13.34	13.5	1.038	0.065	0.067
38.	802.11a	Front Face	165	5825	13.34	13.5	1.038	0.083	0.086

Hotspot SAR

GSM850 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
39.	GPRS_2TX	Back Face	190	836.6	30.05	30.5	1.109	0.178	0.197
	GPRS_2TX	Front Face	190	836.6	30.05	30.5	1.109	0.061	0.068
	GPRS_2TX	Right Side	190	836.6	30.05	30.5	1.109	0.030	0.033
	GPRS_2TX	Left Side	190	836.6	30.05	30.5	1.109	0.020	0.022
	GPRS_2TX	Bottom Side	190	836.6	30.05	30.5	1.109	0.033	0.037

GSM1900 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	GPRS_3TX	Back Face	512	1850.2	24.59	25.0	1.099	0.301	0.331
	GPRS_3TX	Front Face	512	1850.2	24.59	25.0	1.099	0.241	0.265
	GPRS_3TX	Right Side	512	1850.2	24.59	25.0	1.099	0.053	0.058
	GPRS_3TX	Left Side	512	1850.2	24.59	25.0	1.099	0.042	0.046
40.	GPRS_3TX	Bottom Side	512	1850.2	24.59	25.0	1.099	0.378	0.415

WCDMA Band 2 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	RMC 12.2k	Back Face	9262	1852.4	21.26	21.5	1.057	0.378	0.399
	RMC 12.2k	Front Face	9262	1852.4	21.26	21.5	1.057	0.257	0.272
	RMC 12.2k	Right Side	9262	1852.4	21.26	21.5	1.057	0.148	0.156
	RMC 12.2k	Left Side	9262	1852.4	21.26	21.5	1.057	0.017	0.018
41.	RMC 12.2k	Bottom Side	9262	1852.4	21.26	21.5	1.057	0.549	0.580

WCDMA Band 4 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	RMC 12.2k	Back Face	1312	1712.4	21.98	22.0	1.005	0.139	0.140
	RMC 12.2k	Front Face	1312	1712.4	21.98	22.0	1.005	0.079	0.079
	RMC 12.2k	Right Side	1312	1712.4	21.98	22.0	1.005	0.036	0.036
	RMC 12.2k	Left Side	1312	1712.4	21.98	22.0	1.005	0.014	0.014
42.	RMC 12.2k	Bottom Side	1312	1712.4	21.98	22.0	1.005	0.202	0.203

WCDMA Band 5 – Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
43.	RMC 12.2k	Back Face	4132	826.4	22.26	22.5	1.057	0.109	0.115
	RMC 12.2k	Front Face	4132	826.4	22.26	22.5	1.057	0.037	0.039
	RMC 12.2k	Right Side	4132	826.4	22.26	22.5	1.057	0.025	0.026
	RMC 12.2k	Left Side	4132	826.4	22.26	22.5	1.057	0.017	0.018
	RMC 12.2k	Bottom Side	4132	826.4	22.26	22.5	1.057	0.020	0.021

LTE Band 2–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
	QPSK 20MHz 1RB	Back Face	1880	21.43	22.0	1.140	0.461	0.526
	QPSK 20MHz 1RB	Front Face	1880	21.43	22.0	1.140	0.332	0.379
	QPSK 20MHz 1RB	Right Side	1880	21.43	22.0	1.140	0.069	0.079
	QPSK 20MHz 1RB	Left Side	1880	21.43	22.0	1.140	0.043	0.049
44.	QPSK 20MHz 1RB	Bottom Side	1880	21.43	22.0	1.140	0.600	0.684
	QPSK 20MHz 50%RB	Back Face	1880	21.43	22.0	1.140	0.437	0.498
	QPSK 20MHz 50%RB	Front Face	1880	21.43	22.0	1.140	0.224	0.255
	QPSK 20MHz 50%RB	Right Side	1880	21.43	22.0	1.140	0.064	0.073
	QPSK 20MHz 50%RB	Left Side	1880	21.43	22.0	1.140	0.041	0.047
	QPSK 20MHz 50%RB	Bottom Side	1880	21.43	22.0	1.140	0.582	0.664

LTE Band 4–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
	QPSK 20MHz 1RB	Back Face	1745	21.77	22.0	1.054	0.151	0.159
	QPSK 20MHz 1RB	Front Face	1745	21.77	22.0	1.054	0.089	0.094
	QPSK 20MHz 1RB	Right Side	1745	21.77	22.0	1.054	0.039	0.041
	QPSK 20MHz 1RB	Left Side	1745	21.77	22.0	1.054	0.030	0.032
45.	QPSK 20MHz 1RB	Bottom Side	1745	21.77	22.0	1.054	0.213	0.225
	QPSK 20MHz 50%RB	Back Face	1745	21.77	22.0	1.054	0.136	0.143
	QPSK 20MHz 50%RB	Front Face	1745	21.77	22.0	1.054	0.078	0.082
	QPSK 20MHz 50%RB	Right Side	1745	21.77	22.0	1.054	0.035	0.037
	QPSK 20MHz 50%RB	Left Side	1745	21.77	22.0	1.054	0.028	0.030
	QPSK 20MHz 50%RB	Bottom Side	1745	21.77	22.0	1.054	0.198	0.209

LTE Band 5–Body SAR Test (Gap: 10mm)								
P I o t N o.	Mode	Test Position	Frequ ency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
46.	16QAM 10MHz 1RB	Back Face	829	22.10	23.0	1.230	0.104	0.128
	16QAM 10MHz 1RB	Front Face	829	22.10	23.0	1.230	0.025	0.031
	16QAM 10MHz 1RB	Right Side	829	22.10	23.0	1.230	0.022	0.027
	16QAM 10MHz 1RB	Left Side	829	22.10	23.0	1.230	0.017	0.021
	16QAM 10MHz 1RB	Bottom Side	829	22.10	23.0	1.230	0.020	0.025
	16QAM 10MHz 50%RB	Back Face	829	22.10	23.0	1.230	0.089	0.109
	16QAM 10MHz 50%RB	Front Face	829	22.10	23.0	1.230	0.020	0.025
	16QAM 10MHz 50%RB	Right Side	829	22.10	23.0	1.230	0.018	0.022
	16QAM 10MHz 50%RB	Left Side	829	22.10	23.0	1.230	0.015	0.018
	16QAM 10MHz 50%RB	Bottom Side	829	22.10	23.0	1.230	0.017	0.021

LTE Band 7–Body SAR Test (Gap: 10mm)								
P I o t N o.	Mode	Test Position	Frequ ency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
47.	16QAM 20MHz 1RB	Back Face	2535	20.85	21.0	1.035	0.247	0.256
	16QAM 20MHz 1RB	Front Face	2535	20.85	21.0	1.035	0.095	0.098
	16QAM 20MHz 1RB	Right Side	2535	20.85	21.0	1.035	0.187	0.194
	16QAM 20MHz 1RB	Left Side	2535	20.85	21.0	1.035	0.074	0.077
	16QAM 20MHz 1RB	Bottom Side	2535	20.85	21.0	1.035	0.161	0.167
	16QAM 20MHz 50%RB	Back Face	2535	20.85	21.0	1.035	0.228	0.236
	16QAM 20MHz 50%RB	Front Face	2535	20.85	21.0	1.035	0.083	0.086
	16QAM 20MHz 50%RB	Right Side	2535	20.85	21.0	1.035	0.179	0.185
	16QAM 20MHz 50%RB	Left Side	2535	20.85	21.0	1.035	0.071	0.073
	16QAM 20MHz 50%RB	Bottom Side	2535	20.85	21.0	1.035	0.149	0.154

LTE Band 12–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
48.	16QAM 10MHz 1RB	Back Face	711	22.44	23.0	1.138	0.224	0.255
	16QAM 10MHz 1RB	Front Face	711	22.44	23.0	1.138	0.134	0.152
	16QAM 10MHz 1RB	Right Side	711	22.44	23.0	1.138	0.120	0.137
	16QAM 10MHz 1RB	Left Side	711	22.44	23.0	1.138	0.065	0.074
	16QAM 10MHz 1RB	Bottom Side	711	22.44	23.0	1.138	0.131	0.149
	16QAM 10MHz 50%RB	Back Face	711	22.44	23.0	1.138	0.206	0.234
	16QAM 10MHz 50%RB	Front Face	711	22.44	23.0	1.138	0.110	0.125
	16QAM 10MHz 50%RB	Right Side	711	22.44	23.0	1.138	0.116	0.132
	16QAM 10MHz 50%RB	Left Side	711	22.44	23.0	1.138	0.059	0.067
	16QAM 10MHz 50%RB	Bottom Side	711	22.44	23.0	1.138	0.125	0.142

LTE Band 13–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
49.	QPSK 10MHz 1RB	Back Face	782	22.25	23.0	1.189	0.130	0.155
	QPSK 10MHz 1RB	Front Face	782	22.25	23.0	1.189	0.095	0.113
	QPSK 10MHz 1RB	Right Side	782	22.25	23.0	1.189	0.087	0.103
	QPSK 10MHz 1RB	Left Side	782	22.25	23.0	1.189	0.063	0.075
	QPSK 10MHz 1RB	Bottom Side	782	22.25	23.0	1.189	0.079	0.094
	QPSK 10MHz 50%RB	Back Face	782	22.25	23.0	1.189	0.102	0.121
	QPSK 10MHz 50%RB	Front Face	782	22.25	23.0	1.189	0.087	0.103
	QPSK 10MHz 50%RB	Right Side	782	22.25	23.0	1.189	0.072	0.086
	QPSK 10MHz 50%RB	Left Side	782	22.25	23.0	1.189	0.059	0.070
	QPSK 10MHz 50%RB	Bottom Side	782	22.25	23.0	1.189	0.063	0.075

LTE Band 17–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
50.	16QAM 10MHz 1RB	Back Face	711	22.44	23.0	1.138	0.219	0.249
	16QAM 10MHz 1RB	Front Face	711	22.44	23.0	1.138	0.133	0.151
	16QAM 10MHz 1RB	Right Side	711	22.44	23.0	1.138	0.112	0.127
	16QAM 10MHz 1RB	Left Side	711	22.44	23.0	1.138	0.069	0.078
	16QAM 10MHz 1RB	Bottom Side	711	22.44	23.0	1.138	0.073	0.083
	16QAM 10MHz 50%RB	Back Face	711	22.44	23.0	1.138	0.200	0.228
	16QAM 10MHz 50%RB	Front Face	711	22.44	23.0	1.138	0.112	0.127
	16QAM 10MHz 50%RB	Right Side	711	22.44	23.0	1.138	0.102	0.116
	16QAM 10MHz 50%RB	Left Side	711	22.44	23.0	1.138	0.058	0.066
	16QAM 10MHz 50%RB	Bottom Side	711	22.44	23.0	1.138	0.063	0.072

LTE Band 66–Body SAR Test (Gap: 10mm)								
Plot No.	Mode	Test Position	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR 1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
	QPSK 20MHz 1RB	Back Face	1720	22.23	23.0	1.194	0.148	0.177
	QPSK 20MHz 1RB	Front Face	1720	22.23	23.0	1.194	0.051	0.061
	QPSK 20MHz 1RB	Right Side	1720	22.23	23.0	1.194	0.030	0.036
	QPSK 20MHz 1RB	Left Side	1720	22.23	23.0	1.194	0.023	0.027
51.	QPSK 20MHz 1RB	Bottom Side	1720	22.23	23.0	1.194	0.216	0.258
	QPSK 20MHz 50%RB	Back Face	1720	22.23	23.0	1.194	0.135	0.161
	QPSK 20MHz 50%RB	Front Face	1720	22.23	23.0	1.194	0.043	0.051
	QPSK 20MHz 50%RB	Right Side	1720	22.23	23.0	1.194	0.027	0.032
	QPSK 20MHz 50%RB	Left Side	1720	22.23	23.0	1.194	0.022	0.026
	QPSK 20MHz 50%RB	Bottom Side	1720	22.23	23.0	1.194	0.202	0.241

WLAN 2.4GHz –Body SAR Test (Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11b	Back Face	06	2437	15.72	16.0	1.067	0.023	0.025
52.	802.11b	Front Face	06	2437	15.72	16.0	1.067	0.036	0.038
	802.11b	Right Side	06	2437	15.72	16.0	1.067	0.019	0.020
	802.11b	Top Side	06	2437	15.72	16.0	1.067	0.021	0.022

WLAN 5.2GHz –Body SAR Test(Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11a	Back Face	36	5180	14.87	15.0	1.030	0.068	0.070
	802.11a	Front Face	36	5180	14.87	15.0	1.030	0.081	0.083
	802.11a	Right Side	36	5180	14.87	15.0	1.030	0.071	0.073
53.	802.11a	Top Side	36	5180	14.87	15.0	1.030	0.175	0.180

WLAN 5.8GHz –Body SAR Test(Gap: 10mm)									
Plot No.	Mode	Test Position	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	802.11a	Back Face	165	5825	13.34	13.5	1.038	0.065	0.067
	802.11a	Front Face	165	5825	13.34	13.5	1.038	0.083	0.086
	802.11a	Right Side	165	5825	13.34	13.5	1.038	0.072	0.075
54.	802.11a	Top Side	165	5825	13.34	13.5	1.038	0.179	0.186

Remark: Per KDB 447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

9.3 Simultaneous Multi-band Transmission SAR Analysis

List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Head SAR	Body SAR
1	GSM(Voice/Data) + WLAN(2.4GHz)(Data)	Yes	Yes
2	WCDMA (Voice/Data)+ WLAN(2.4GHz)(Data)	Yes	Yes
3	LTE(Data) + WLAN(2.4GHz)(Data)	Yes	Yes
4	GSM(Voice/Data) + WLAN(5GHz)(Data)	Yes	Yes
5	WCDMA (Voice/Data)+ WLAN(5GHz)(Data)	Yes	Yes
6	LTE(Data) + WLAN(5GHz)(Data)	Yes	Yes
7	GSM(Voice/Data) + Bluetooth(Data)	Yes	Yes
8	WCDMA (Voice/Data) + Bluetooth(Data)	Yes	Yes
9	LTE(Data) + Bluetooth(Data)	Yes	Yes

Remark:

1. GSM, WCDMA and LTE share the same antenna, and cannot transmit simultaneously.
2. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
3. According to the KDB 447498 D01 v06, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x]$
W/kg for test separation distances ≤ 50 mm;

where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.

For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 v06 as below:

Bluetooth:

Tune-Up Power (dBm)	Max. Power (mW)	Distance (mm)	Frequency (GHz)	X	SAR(1g) 5mm	SAR(1g) 10mm
4.0	2.51	5/10	2.480	7.5	0.105	0.053

4. The maximum SAR summation is calculated based on the same configuration and test position.

Head SAR**WWAN and WLAN**

	WWAN		WLAN(2.4GHz)	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM	0.089	0.058	0.147
Right Tilted	GSM	0.081	0.047	0.128
Left Cheek	GSM	0.111	0.171	0.282
Left Tilted	GSM	0.095	0.161	0.256
Right Cheek	WCDMA	0.072	0.058	0.130
Right Tilted	WCDMA	0.066	0.047	0.113
Left Cheek	WCDMA	0.062	0.171	0.233
Left Tilted	WCDMA	0.053	0.161	0.214
Right Cheek	LTE	0.143	0.058	0.201
Right Tilted	LTE	0.132	0.047	0.179
Left Cheek	LTE	0.121	0.171	0.292
Left Tilted	LTE	0.102	0.161	0.263

WWAN and WLAN

	WWAN		WLAN(5GHz)	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM	0.089	0.308	0.397
Right Tilted	GSM	0.081	0.287	0.368
Left Cheek	GSM	0.111	0.593	0.704
Left Tilted	GSM	0.095	0.549	0.644
Right Cheek	WCDMA	0.072	0.308	0.380
Right Tilted	WCDMA	0.066	0.287	0.353
Left Cheek	WCDMA	0.062	0.593	0.655
Left Tilted	WCDMA	0.053	0.549	0.602
Right Cheek	LTE	0.143	0.308	0.451
Right Tilted	LTE	0.132	0.287	0.419
Left Cheek	LTE	0.121	0.593	0.714
Left Tilted	LTE	0.102	0.549	0.651

Note:

WWAN + Bluetooth test result less than the WWAN + WLAN (2.4GHz/5GHz) test result, so the WWAN + Bluetooth test result is not show in the test report.

Body-worn SAR**WWAN and WLAN**

	WWAN		WLAN(2.4GHz)	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM	0.293	0.025	0.318
Front	GSM	0.226	0.038	0.264
Back	WCDMA	0.399	0.025	0.424
Front	WCDMA	0.272	0.038	0.310
Back	LTE	0.526	0.025	0.551
Front	LTE	0.379	0.038	0.417

WWAN and WLAN

	WWAN		WLAN(5GHz)	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM	0.293	0.081	0.374
Front	GSM	0.226	0.098	0.324
Back	WCDMA	0.399	0.081	0.480
Front	WCDMA	0.272	0.098	0.370
Back	LTE	0.526	0.081	0.607
Front	LTE	0.379	0.098	0.477

Note:

WWAN + Bluetooth test result less than the WWAN + WLAN (2.4GHz/5GHz) test result, so the WWAN + Bluetooth test result is not show in the test report.

Hotspot SAR**WWAN and WLAN**

	WWAN		WLAN(2.4GHz)	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM	0.331	0.025	0.356
Front	GSM	0.265	0.038	0.303
Right side	GSM	0.058	0.020	0.078
Left side	GSM	0.046	--	0.046
Bottom side	GSM	0.415	--	0.415
Top side	GSM	--	0.022	0.022
Back	WCDMA	0.399	0.025	0.424
Front	WCDMA	0.272	0.038	0.310
Right side	WCDMA	0.156	0.020	0.176
Left side	WCDMA	0.018	--	0.018
Bottom side	WCDMA	0.580	--	0.580
Top side	WCDMA	--	0.022	0.022
Back	LTE	0.526	0.025	0.551
Front	LTE	0.379	0.038	0.417
Right side	LTE	0.194	0.020	0.214
Left side	LTE	0.078	--	0.078
Bottom side	LTE	0.684	--	0.684
Top side	LTE	--	0.022	0.022

WWAN and WLAN

	WWAN		WLAN(5GHz)	Summed SAR (W/kg)
Position	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Back	GSM	0.331	0.070	0.401
Front	GSM	0.265	0.086	0.351
Right side	GSM	0.058	0.075	0.133
Left side	GSM	0.046	--	0.046
Bottom side	GSM	0.415	--	0.415
Top side	GSM	--	0.186	0.186
Back	WCDMA	0.399	0.070	0.469
Front	WCDMA	0.272	0.086	0.358
Right side	WCDMA	0.156	0.075	0.231
Left side	WCDMA	0.018	--	0.018
Bottom side	WCDMA	0.580	--	0.580
Top side	WCDMA	--	0.186	0.186
Back	LTE	0.526	0.070	0.596
Front	LTE	0.379	0.086	0.465
Right side	LTE	0.194	0.075	0.269
Left side	LTE	0.078	--	0.078
Bottom side	LTE	0.684	--	0.684
Top side	LTE	--	0.186	0.186

Note:

WWAN + Bluetooth test result less than the WWAN + WLAN (2.4GHz/5GHz) test result, so the WWAN + Bluetooth test result is not show in the test report.

10. Measurement Uncertainty

10.1 Uncertainty for SAR Test

Input quantity X_i (source of uncertainty)	Ref.	Prob. Dist PDF_i	Unc. $a(x_i)$	Div. q_i	$u(x_i) =$ $a(x_i)/q_i$	c_i (1 g; 10 g)	$u(y) = c_i \cdot u(x_i)$	v_i or v_{eff}
Measurement System errors								
Probe calibration	8.4.1.1	N	7.00	2	3.5	1	3.5	∞
Probe calibration drift	8.4.1.2	R	0	$\sqrt{3}$	0	1	0	∞
Probe linearity and detection limit	8.4.1.3	R	5.00	$\sqrt{3}$	2.89	1	2.89	∞
Broadband signal	8.4.1.4	R	0	$\sqrt{3}$	0	1	0	∞
Probe isotropy	8.4.1.5	R	2.50	$\sqrt{3}$	1.44	1	1.44	∞
Other probe and data acquisition errors	8.4.1.6	N	0.02	1	0.02	1	0.02	∞
RF ambient and noise	8.4.1.7	N	0	1	0	1	0	∞
Probe positioning errors	8.4.1.8	N	1.40	1	1.40	$2/TM$	0.70	
Data processing errors	8.4.1.9	N	0.05	1	0.05	1	0.05	∞
Phantom and device (DUT or validation antenna) errors								
Measurement of phantom conductivity(σ)	8.4.2.1	N	4.00	1	4.00	c_E, c_σ	4.00	∞
Temperature effects (medium)	8.4.2.2	R	2.50	$\sqrt{3}$	1.44	c_E, c_σ	1.44	∞
Shell permittivity	8.4.2.3	R	5.00	$\sqrt{3}$	2.88	See 8.4.2.3	2.88	∞
Distance between the radiating element of the DUT and the phantom medium	8.4.2.4	N	0.03	1	0.03	2	0.02	∞
Repeatability of positioning the DUT or source against the phantom	8.4.2.5	N	0.05	1	0.05	1	0.05	5
Device holder effects	8.4.2.6	N	5.00	1	5.00	1	5.00	
Effect of operating mode on probe sensitivity	8.4.2.7	R	0	$\sqrt{3}$	0	1	0	∞
Time-average SAR	8.4.2.8	R	0	$\sqrt{3}$	0	1	0	∞
Variation in SAR due to drift in output of DUT	8.4.2.9	N	5.00	1	5.00	1	5.00	
Validation antenna uncertainty (validation measurement only)	8.4.2.10	N	0	1	0	1	0	
Uncertainty in accepted power	8.4.2.11	N	0	1	0	1	0	

(validation measurement only)								
Corrections to the SAR result								
Phantom deviation from target (ϵ', σ)	8.4.3.1	N	0.05	1	0.05	1	0.05	
SAR scaling	8.4.3.2	R	2.00	$\sqrt{3}$	1.15	1	1.15	
Combined Standard Uncertainty		RSS			10.11		10.11	$v_{\text{eff}} =$
Expanded uncertainty, U		K=2			20.23		20.23	

Annex A. Plots of System Performance Check

MEASUREMENT 1

Type: Validation measurement (Fast, 75.00 %)
Date of measurement: 2024-08-10
Measurement duration: 7 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.27; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Validation plane
Device Position	Dipole
Band	CW750
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative Permittivity (real part)	41.081524
Conductivity (S/m)	0.872347
Power Variation (%)	1.178100
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=-2.00, Y=0.00

D. SAR 1g & 10g


SAR 10g (W/Kg)	1.430855
SAR 1g (W/Kg)	2.051374

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	2.8268	2.1542	1.6473	1.2759	1.0033



F. 3D Image



MEASUREMENT 2

Type: Validation measurement (Fast, 75.00 %)
Date of measurement: 2024-08-11
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.28; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative Permittivity (real part)	40.984892
Conductivity (S/m)	0.881475
Power Variation (%)	-1.847400
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=1.00, Y=0.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	1.527360
SAR 1g (W/Kg)	2.210386

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	3.0677	2.3224	1.7644	1.3585	1.0631



F. 3D Image



MEASUREMENT 3

Type: Validation measurement (Fast, 75.00 %)
Date of measurement: 2024-08-13
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative Permittivity (real part)	39.262144
Conductivity (S/m)	1.393848
Power Variation (%)	1.474200
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=1.00, Y=1.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	4.968858
SAR 1g (W/Kg)	9.623880

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	17.3936	10.4322	6.1187	3.6132	2.2066



F. 3D Image



MEASUREMENT 4

Type: Validation measurement (Fast, 75.00 %)
Date of measurement: 2024-08-15
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative Permittivity (real part)	40.942574
Conductivity (S/m)	1.424131
Power Variation (%)	-1.224700
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=0.00, Y=1.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	5.260825
SAR 1g (W/Kg)	10.222516

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	18.6940	11.1182	6.4717	3.8103	2.3414



F. 3D Image



MEASUREMENT 5

Type: Validation measurement (Fast, 75.00 %)
Date of measurement: 2024-08-17
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.62; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative Permittivity (real part)	38.513289
Conductivity (S/m)	1.764182
Power Variation (%)	1.475200
Ambient Temperature	22.5
Liquid Temperature	22.5

C. SAR Surface and Volume




Maximum location: X=7.00, Y=0.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	6.149024
SAR 1g (W/Kg)	13.746586

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	28.7959	15.1301	7.5430	3.7436	1.9810



F. 3D Image



MEASUREMENT 6

Type: Validation measurement (Fast, 75.00 %)
Date of measurement: 2024-08-19
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.50; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative Permittivity (real part)	39.824541
Conductivity (S/m)	1.924785
Power Variation (%)	1.344700
Ambient Temperature	22.5
Liquid Temperature	22.5

C. SAR Surface and Volume




Maximum location: X=3.00, Y=0.00

D. SAR 1g & 10g


SAR 10g (W/Kg)	6.553727
SAR 1g (W/Kg)	14.814545

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	31.1802	16.2650	8.0339	3.9472	2.0732



F. 3D Image



MEASUREMENT 7

Type: Validation measurement (Fast, 75.00 %)
Date of measurement: 2024-08-20
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.05; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative Permittivity (real part)	37.453547
Conductivity (S/m)	4.634561
Power Variation (%)	2.348510
Ambient Temperature	22.5
Liquid Temperature	22.5

C. SAR Surface and Volume




Maximum location: X=3.00, Y=0.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	5.214336
SAR 1g (W/Kg)	18.566732

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	63.694	35.714	18.361	8.6368	3.8326	1.6405	0.7180	0.3557	0.2183
	0	3	9						



F. 3D Image



MEASUREMENT 8

Type: Validation measurement (Fast, 75.00 %)
Date of measurement: 2024-08-20
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 0.99; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Dipole
Band	CW5400
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	5400.000000
Relative Permittivity (real part)	36.623765
Conductivity (S/m)	4.872471
Power Variation (%)	1.374500
Ambient Temperature	22.5
Liquid Temperature	22.5

C. SAR Surface and Volume




Maximum location: X=6.00, Y=0.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	5.463589
SAR 1g (W/Kg)	18.979345

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	62.945	36.057	19.161	9.4529	4.4747	2.0809	0.9976	0.5283	0.3243
	6	9	7						



F. 3D Image



MEASUREMENT 9

Type: Validation measurement (Fast, 75.00 %)
Date of measurement: 2024-08-21
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 0.96; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Dipole
Band	CW5600
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	5600.000000
Relative Permittivity (real part)	35.884172
Conductivity (S/m)	5.102584
Power Variation (%)	1.475731
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=5.00, Y=0.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	5.462480
SAR 1g (W/Kg)	19.007904

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	63.633	36.433	19.347	9.5356	4.5091	2.0948	1.0039	0.5323	0.3279
	5	9	5						



F. 3D Image



MEASUREMENT 10

Type: Validation measurement (Fast, 75.00 %)
Date of measurement: 2024-08-21
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 0.97; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	5800.000000
Relative Permittivity (real part)	34.743471
Conductivity (S/m)	5.242958
Power Variation (%)	-1.437500
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=6.00, Y=0.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	5.385932
SAR 1g (W/Kg)	18.087402

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	59.320	34.261	18.434	9.2545	4.4822	2.1439	1.0586	0.5728	0.3524
	3	7	7						



F. 3D Image



Annex B. Plots of SAR Measurement

MEASUREMENT 1

Type: Measurement (Complete)
Date of measurement: 2024-08-11
Measurement duration: 11 minutes 48 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.28; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Left head
Device Position	Cheek
Band	GSM850
Channels	Middle
Signal	TDMA (Crest factor: 8.0)

B. SAR Measurement Results

Frequency (MHz)	836.600000
Relative Permittivity (real part)	40.983224
Conductivity (S/m)	0.882458
Power Variation (%)	1.053600
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=-54.00, Y=-31.00

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.054174
SAR 1g (W/Kg)	0.074183

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1008	0.0774	0.0606	0.0491	0.0415



F. 3D Image



MEASUREMENT 2

Type: Measurement (Complete)
Date of measurement: 2024-08-11
Measurement duration: 11 minutes 48 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.28; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Left head
Device Position	Cheek
Band	GPRS850_2TX
Channels	Middle
Signal	Duty Cycle: 1:4

B. SAR Measurement Results

Frequency (MHz)	836.600000
Relative Permittivity (real part)	40.983224
Conductivity (S/m)	0.882458
Power Variation (%)	-0.289400
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=-55.00, Y=-24.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.073158
SAR 1g (W/Kg)	0.099938

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1763	0.1039	0.0782	0.0655	0.0527



F. 3D Image



MEASUREMENT 3

Type: Measurement (Complete)
Date of measurement: 2024-08-13
Measurement duration: 11 minutes 48 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.0)

B. SAR Measurement Results

Frequency (MHz)	1850.200000
Relative Permittivity (real part)	39.262245
Conductivity (S/m)	1.394181
Power Variation (%)	0.254800
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=-49.00, Y=-51.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.030504
SAR 1g (W/Kg)	0.048116

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1136	0.0507	0.0330	0.0268	0.0187



F. 3D Image



MEASUREMENT 4

Type: Measurement (Complete)
Date of measurement: 2024-08-13
Measurement duration: 11 minutes 48 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	GPRS1900_3TX
Channels	Low
Signal	Duty Cycle: 1:2.66

B. SAR Measurement Results

Frequency (MHz)	1850.200000
Relative Permittivity (real part)	39.262245
Conductivity (S/m)	1.394181
Power Variation (%)	-1.148700
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=-50.00, Y=-56.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.031728
SAR 1g (W/Kg)	0.052520

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.0817	0.0563	0.0386	0.0269	0.0191



F. 3D Image



MEASUREMENT 5

Type: Measurement (Complete)
Date of measurement: 2024-08-13
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	WCDMA1900_RMC
Channels	Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1852.400000
Relative Permittivity (real part)	39.262488
Conductivity (S/m)	1.393678
Power Variation (%)	0.822400
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=-49.00, Y=-55.00

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.041853
SAR 1g (W/Kg)	0.067568

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1022	0.0719	0.0507	0.0366	0.0272



F. 3D Image



MEASUREMENT 6

Type: Measurement (Complete)
Date of measurement: 2024-08-13
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	WCDMA1700_RMC
Channels	Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1712.400000
Relative Permittivity (real part)	39.261247
Conductivity (S/m)	1.394160
Power Variation (%)	0.864500
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=-48.00, Y=-56.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.014451
SAR 1g (W/Kg)	0.023367

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.0360	0.0251	0.0176	0.0126	0.0093



F. 3D Image



MEASUREMENT 7

Type: Measurement (Complete)
Date of measurement: 2024-08-11
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.28; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	WCDMA850_RMC
Channels	Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	826.400000
Relative Permittivity (real part)	40.984324
Conductivity (S/m)	0.882458
Power Variation (%)	-1.393800
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=-50.00, Y=-32.00
D. SAR 1g & 10g



SAR 10g (W/Kg)	0.044220
SAR 1g (W/Kg)	0.059338

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.0741	0.0619	0.0514	0.0424	0.0347



F. 3D Image

3D screen shot	Hot spot position
	

MEASUREMENT 8

Type: Measurement (Complete)
Date of measurement: 2024-08-15
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 2
Channels	QPSK, 20MHz, 1RB, Middle
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative Permittivity (real part)	39.111461
Conductivity (S/m)	1.423923
Power Variation (%)	-1.348500
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=-57.00, Y=-14.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.074268
SAR 1g (W/Kg)	0.123206

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1862	0.1322	0.0934	0.0666	0.0480



F. 3D Image



MEASUREMENT 9

Type: Measurement (Complete)
Date of measurement: 2024-08-13
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 4
Channels	QPSK, 20MHz, 1RB,High
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1745.000000
Relative Permittivity (real part)	39.261327
Conductivity (S/m)	1.392487
Power Variation (%)	1.085600
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=-56.00, Y=-8.00
D. SAR 1g & 10g



SAR 10g (W/Kg)	0.025123
SAR 1g (W/Kg)	0.041412

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1250	0.0438	0.0252	0.0209	0.0128



F. 3D Image

3D screen shot	Hot spot position
	

MEASUREMENT 10

Type: Measurement (Complete)
Date of measurement: 2024-08-11
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.28; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 5
Channels	16QAM 10MHz, 1RB, Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	829.000000
Relative Permittivity (real part)	40.983245
Conductivity (S/m)	0.882458
Power Variation (%)	-0.878500
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=-50.00, Y=-39.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.064215
SAR 1g (W/Kg)	0.086811

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1100	0.0908	0.0746	0.0612	0.0501



F. 3D Image



MEASUREMENT 11

Type: Measurement (Complete)
Date of measurement: 2024-08-19
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.50; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 7
Channels	16QAM, 20MHz, 1RB, Middle
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative Permittivity (real part)	39.823255
Conductivity (S/m)	1.923929
Power Variation (%)	1.174600
Ambient Temperature	22.5
Liquid Temperature	22.5

C. SAR Surface and Volume




Maximum location: X=-50.00, Y=-62.00
D. SAR 1g & 10g



SAR 10g (W/Kg)	0.015855
SAR 1g (W/Kg)	0.031389

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.0772	0.0335	0.0185	0.0123	0.0062



F. 3D Image

3D screen shot	Hot spot position
	

MEASUREMENT 12

Type: Measurement (Complete)
Date of measurement: 2024-08-10
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.27; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 12
Channels	16QAM, 10MHz, 1RB, High
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	711.000000
Relative Permittivity (real part)	41.084156
Conductivity (S/m)	0.871828
Power Variation (%)	-1.785400
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=-53.00, Y=-38.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.096266
SAR 1g (W/Kg)	0.124822

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1516	0.1273	0.1074	0.0913	0.0783



F. 3D Image



MEASUREMENT 13

Type: Measurement (Complete)
Date of measurement: 2024-08-10
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.27; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 13
Channels	QPSK, 10MHz, 1RB, Middle
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	782.000000
Relative Permittivity (real part)	41.084262
Conductivity (S/m)	0.871258
Power Variation (%)	0.149100
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=-50.00, Y=-38.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.076977
SAR 1g (W/Kg)	0.103467

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1338	0.1077	0.0873	0.0719	0.0601



F. 3D Image



MEASUREMENT 14

Type: Measurement (Complete)
Date of measurement: 2024-08-10
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.27; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 17
Channels	16QAM, 10MHz, 1RB, High
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	711.000000
Relative Permittivity (real part)	41.084156
Conductivity (S/m)	0.871828
Power Variation (%)	-1.025800
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=-53.00, Y=-38.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.097415
SAR 1g (W/Kg)	0.126337

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1519	0.1288	0.1093	0.0931	0.0794



F. 3D Image



MEASUREMENT 15

Type: Measurement (Complete)
Date of measurement: 2024-08-13
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Left head
Device Position	Cheek
Band	LTE Band 66
Channels	QPSK, 20MHz, 1RB, Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1720.000000
Relative Permittivity (real part)	39.263275
Conductivity (S/m)	1.392975
Power Variation (%)	0.189900
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=-57.00, Y=-7.00
D. SAR 1g & 10g



SAR 10g (W/Kg)	0.020405
SAR 1g (W/Kg)	0.033896

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.0909	0.0355	0.0204	0.0159	0.0104



F. 3D Image

3D screen shot	Hot spot position
	

MEASUREMENT 16

Type: Measurement (Complete)
Date of measurement: 2024-08-17
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.62; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Left head
Device Position	Cheek
Band	WiFi_802.11b
Channels	Middle
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative Permittivity (real part)	38.514231
Conductivity (S/m)	1.763875
Power Variation (%)	-1.963800
Ambient Temperature	22.5
Liquid Temperature	22.5

C. SAR Surface and Volume




Maximum location: X=-18.00, Y=18.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.074836
SAR 1g (W/Kg)	0.160285

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.3010	0.1780	0.1008	0.0552	0.0292



F. 3D Image



MEASUREMENT 17

Type: Measurement (Complete)
Date of measurement: 2024-08-20
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.05; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Left Head
Device Position	Cheek
Band	WiFi(5.2GHz)_802.11a
Channels	Low
Signal	Duty Cycle: 1:1

B. SAR Measurement Results

Frequency (MHz)	5180.000000
Relative Permittivity (real part)	37.453869
Conductivity (S/m)	4.631611
Power Variation (%)	-1.156800
Ambient Temperature	22.5
Liquid Temperature	22.5

C. SAR Surface and Volume




Maximum location: X=5.00, Y=23.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.216038
SAR 1g (W/Kg)	0.541469

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	0.9593	0.5374	0.2790	0.1401	0.0753	0.0481	0.0401	0.0433	0.0547



F. 3D Image



MEASUREMENT 18

Type: Measurement (Complete)
Date of measurement: 2024-08-20
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.05; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Left Head
Device Position	Cheek
Band	WiFi(5.3GHz)_802.11a
Channels	Middle
Signal	Duty Cycle: 1:1

B. SAR Measurement Results

Frequency (MHz)	5280.000000
Relative Permittivity (real part)	37.452283
Conductivity (S/m)	4.631926
Power Variation (%)	0.456800
Ambient Temperature	22.5
Liquid Temperature	22.5

C. SAR Surface and Volume




Maximum location: X=8.00, Y=24.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.166749
SAR 1g (W/Kg)	0.539240

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	1.0569	0.5173	0.2063	0.0665	0.0181	0.0064	0.0092	0.0104	0.0233



F. 3D Image



MEASUREMENT 19

Type: Measurement (Complete)
Date of measurement: 2024-08-21
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 0.96; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Left Head
Device Position	Cheek
Band	WiFi(5.6GHz)_802.11a
Channels	Low
Signal	Duty Cycle: 1:1

B. SAR Measurement Results

Frequency (MHz)	5500.000000
Relative Permittivity (real part)	35.883296
Conductivity (S/m)	5.101278
Power Variation (%)	-1.848600
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=6.00, Y=24.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.171536
SAR 1g (W/Kg)	0.553203

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	1.0910	0.5417	0.2261	0.0790	0.0245	0.0082	0.0050	0.0075	0.0157



F. 3D Image



MEASUREMENT 20

Type: Measurement (Complete)
Date of measurement: 2024-08-21
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 0.97; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=4mm dy=4mm dz=2mm
Phantom	Left Head
Device Position	Cheek
Band	WiFi(5.8GHz)_ 802.11a
Channels	Middle
Signal	Duty Cycle: 1:1

B. SAR Measurement Results

Frequency (MHz)	5825.000000
Relative Permittivity (real part)	34.742273
Conductivity (S/m)	5.243836
Power Variation (%)	-1.296800
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=8.00, Y=24.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.151929
SAR 1g (W/Kg)	0.494269

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00
SAR (W/Kg)	0.9723	0.4703	0.1861	0.0590	0.0155	0.0041	0.0025	0.0051	0.0135



F. 3D Image



MEASUREMENT 21

Type: Measurement (Complete)
Date of measurement: 2024-08-11
Measurement duration: 11 minutes 48 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.28; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Flat Plane
Device Position	Back
Band	GSM850
Channels	Middle
Signal	TDMA (Crest factor: 8.0)

B. SAR Measurement Results

Frequency (MHz)	836.600000
Relative Permittivity (real part)	40.983224
Conductivity (S/m)	0.882458
Power Variation (%)	0.747200
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=24.00, Y=8.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.083039
SAR 1g (W/Kg)	0.142971

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.3337	0.1505	0.0897	0.0638	0.0378



F. 3D Image



MEASUREMENT 22

Type: Measurement (Complete)
Date of measurement: 2024-08-13
Measurement duration: 11 minutes 48 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Flat Plane
Device Position	Back
Band	GSM1900
Channels	Low
Signal	TDMA (Crest factor: 8.0)

B. SAR Measurement Results

Frequency (MHz)	1850.200000
Relative Permittivity (real part)	39.262245
Conductivity (S/m)	1.394181
Power Variation (%)	2.178100
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=-3.00, Y=-16.00

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.156361
SAR 1g (W/Kg)	0.288077

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.4904	0.3135	0.1985	0.1276	0.0849



F. 3D Image



MEASUREMENT 23

Type: Measurement (Complete)
Date of measurement: 2024-08-13
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Flat Plane
Device Position	Back
Band	WCDMA1900_RMC
Channels	Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1852.400000
Relative Permittivity (real part)	39.262488
Conductivity (S/m)	1.393678
Power Variation (%)	-1.497500
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=5.00, Y=18.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.198049
SAR 1g (W/Kg)	0.377822

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.6541	0.4180	0.2626	0.1653	0.1055



F. 3D Image



MEASUREMENT 24

Type: Measurement (Complete)
Date of measurement: 2024-08-13
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Flat Plane
Device Position	Back
Band	WCDMA1700_RMC
Channels	Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1712.400000
Relative Permittivity (real part)	39.261247
Conductivity (S/m)	1.394160
Power Variation (%)	0.542300
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=6.00, Y=19.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.073256
SAR 1g (W/Kg)	0.138721

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.2345	0.1540	0.0999	0.0652	0.0431



F. 3D Image



MEASUREMENT 25/43

Type: Measurement (Complete)
Date of measurement: 2024-08-11
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.28; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Flat Plane
Device Position	Back
Band	WCDMA850_RMC
Channels	Low
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	826.400000
Relative Permittivity (real part)	40.984324
Conductivity (S/m)	0.882458
Power Variation (%)	-1.294800
Ambient Temperature	22.6
Liquid Temperature	22.6

C. SAR Surface and Volume




Maximum location: X=8.00, Y=15.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.063190
SAR 1g (W/Kg)	0.109229

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.1772	0.1179	0.0778	0.0519	0.0354



F. 3D Image



MEASUREMENT 26

Type: Measurement (Complete)
Date of measurement: 2024-08-15
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11


A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Flat Plane
Device Position	Back
Band	LTE Band 2
Channels	QPSK, 20MHz, 1RB, Middle
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative Permittivity (real part)	39.111461
Conductivity (S/m)	1.423923
Power Variation (%)	2.184700
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume




Maximum location: X=16.00, Y=24.00
D. SAR 1g & 10g


SAR 10g (W/Kg)	0.242121
SAR 1g (W/Kg)	0.461476

E. Z Axis Scan

Z (mm)	0.00	4.00	8.00	12.00	16.00
SAR (W/Kg)	0.8005	0.5113	0.3222	0.2047	0.1331



F. 3D Image



MEASUREMENT 27

Type: Measurement (Complete)
Date of measurement: 2024-08-13
Measurement duration: 12 minutes 3 seconds
E-field Probe: SSE2 - 3823-EPGO-435; ConvF: 1.37; Calibrated: 2024-07-11

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Phantom	Flat Plane
Device Position	Back
Band	LTE Band 4
Channels	QPSK, 20MHz, 1RB, High
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1745.000000
Relative Permittivity (real part)	39.261327
Conductivity (S/m)	1.392487
Power Variation (%)	-1.816400
Ambient Temperature	22.4
Liquid Temperature	22.4

C. SAR Surface and Volume

