

TEST REPORT

Reference No...... : WTF25X03065646W003
FCC ID..... : 2BH83-SIMPLE
Applicant..... : FULL TECHNOLOGY TRADE LIMITED
Address..... : RM 13,UNIT A1,2/F.,PHASE 1,KAISER ESTATE,NO.41 MAN YUE
STREET,HUNG HOM,KLN HONG KONG
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : Mobile Phone
Model No...... : SIMPLE
Standards..... : FCC Part 15.407
Date of Receipt sample..... : 2025-03-20
Date of Test..... : 2025-03-20 to 2025-03-30; 2025-04-05 to 2025-04-10
Date of Issue..... : 2025-04-10
Test Report Form No...... : WTX_Part 15_407W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.


Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Dashan Chen/Project Engineer

Approved by:



Silin Chen/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 TEST STANDARDS	6
1.3 TEST METHODOLOGY	6
1.4 TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING	6
1.5 EUT OPERATING DURING TEST	8
1.6 TEST FACILITY	8
1.7 EUT SETUP AND TEST MODE	9
1.8 MEASUREMENT UNCERTAINTY	10
1.9 TEST EQUIPMENT LIST AND DETAILS	11
2. SUMMARY OF TEST RESULTS	15
3. ANTENNA REQUIREMENT	16
3.1 STANDARD APPLICABLE	16
3.2 EVALUATION INFORMATION	16
4. AUTOMATICALLY DISCONTINUE TRANSMISSION	17
4.1 STANDARD APPLICABLE	17
4.2 SUMMARY OF TEST RESULTS	17
5. POWER SPECTRAL DENSITY	18
5.1 STANDARD APPLICABLE	18
5.2 TEST PROCEDURE	18
5.3 SUMMARY OF TEST RESULTS/PLOTS	19
6. EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	20
6.1 STANDARD APPLICABLE	20
6.2 TEST PROCEDURE	20
6.3 SUMMARY OF TEST RESULTS/PLOTS	22
7. MAXIMUM CONDUCTED OUTPUT POWER	23
7.1 STANDARD APPLICABLE	23
7.2 TEST PROCEDURE	23
7.3 SUMMARY OF TEST RESULTS/PLOTS	24
8. RADIATED SPURIOUS EMISSIONS	25
8.1 STANDARD APPLICABLE	25
8.2 TEST PROCEDURE	25
8.3 TEST RECEIVER SETUP	27
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION	27
8.5 SUMMARY OF TEST RESULTS/PLOTS	27
9. FREQUENCY STABILITY	118
9.1 STANDARD APPLICABLE	118
9.2 TEST PROCEDURE	118
9.3 SUMMARY OF TEST RESULTS/PLOTS	118
10. CONDUCTED EMISSIONS	119
10.1 TEST PROCEDURE	119
10.2 BASIC TEST SETUP BLOCK DIAGRAM	119
10.3 TEST RECEIVER SETUP	119
10.4 SUMMARY OF TEST RESULTS/PLOTS	119
APPENDIX SUMMARY	122
APPENDIX A	123
APPENDIX B	146
APPENDIX C	190
APPENDIX D	213

APPENDIX PHOTOGRAPHS 215

Report version

Version No.	Date of issue	Description
Rev.00	2025-04-10	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Mobile Phone
Trade Name:	Lifephone
Model No.:	SIMPLE
Adding Model(s):	/
Rated Voltage:	DC3.87V
Battery:	4900mAh
Adapter Model:	ONE Input:AC100-240V 50/60Hz 0.5A Output:DC5V3A/9V2A/12V1.5A
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11a, 802.11n(HT20), 802.11n-HT40, 802.11ac-VHT20, 802.11ac-VHT40,802.11ac-VHT80
Frequency Range:	5180-5240MHz, 5260-5320MHz 5500-5700MHz, 5745-5825MHz
Max. RF Output Power:	16.08dBm (Conducted)
Type of Modulation:	QPSK, 16QAM, 64QAM
Type of Antenna:	Integral Antenna
Antenna Gain:	-0.78dBi
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.407: General technical requirements.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

KDB789033 D02 v02r01: Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-Nii) Devices Part 15, Subparte.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, KDB789033 D02 v02r01. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Table for parameters of Test Software setting

Enter ***##83781##** into the calculator to enter the engineer mode, you can start to test. During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Mode	Test Frequency (MHz)												
	NCB: 20MHz												
	5180	5200	5240	5260	5300	5320	5500	5580	5700	5720	5745	5785	5825
802.11a 6Mbps	13	13	13	13	13	13	13	13	14	14	14	14	14
802.11n-HT20 MCS0	12	12	12	12	12	12	12	12	13	13	13	13	13
802.11ac-VHT20 MCS0	12	12	12	12	12	12	12	12	13	13	13	13	13
Mode	NCB: 40MHz												
	5190	5230	5270	5310	5510	5550	5670	5710	5755	5795			
802.11n-HT40 MCS0	11	11	11	11	10	10	12	12	12	12			
802.11ac-VHT40 MCS0	11	11	11	11	10	10	12	12	12	12			

Mode	NCB: 80MHz					
	5210	5290	5530	5610	5690	5775
802.11ac-VHT80 MCS0	10	10	10	10	10	11

1.5 EUT Operating during test

EUT was programmed to be in continuously transmitting mode. During the test, EUT operation to normal function and programs under Android were executed.

1.6 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.7 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11a	5180MHz,5200MHz,5240MHz,5260MHz,5280MHz,5320MHz,5500MHz,5600MHz,5700MHz,5745MHz, 5785MHz,5825MHz
TM2	802.11n-HT20	5180MHz,5200MHz,5240MHz,5260MHz,5280MHz,5320MHz,5500MHz,5600MHz,5700MHz,5745MHz, 5785MHz,5825MHz
TM3	802.11ac-VHT20	5180MHz,5200MHz,5240MHz,5260MHz,5280MHz,5320MHz,5500MHz,5600MHz,5700MHz,5745MHz, 5785MHz,5825MHz
TM4	802.11n-HT40	5190MHz,5230MHz,5270MHz,5310MHz,5510MHz,5590MHz,5670MHz,5755MHz,5795MHz
TM5	802.11ac-VHT40	5190MHz,5230MHz,5270MHz,5310MHz,5510MHz,5590MHz,5670MHz,5755MHz,5795MHz
TM6	802.11ac-VHT80	5210MHz,5290MHz,5530MHz,5610MHz,5775MHz
Note: 802.11ac-VHT20, 802.11ac-VHT40 covered by 802.11n-HT20 and 802.11n-HT40.		

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~75 %
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	1.0	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Earphone Cable	1.0	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	TianYi 100-14IBD	PF0F4ABV

1.8 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	0.57dB
Occupied Bandwidth	Conducted	0.015MHz
Power Spectral Density	Conducted	1.8dB
Conducted Spurious Emission	Conducted	2.17dB
Conducted Emissions	Conducted	9-150kHz, 3.74dB
		0.15-30MHz, 3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz, 4.52dB
		0.2-1GHz 5.56dB
		1-6GHz, 3.84dB
		6-18GHz, 3.92dB

1.9 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2025-02-23	2026-02-22
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2025-02-23	2026-02-22
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2025-02-23	2026-02-22
WTXE1004A 1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2025-02-23	2026-02-22
WTXE1103A 1003	Attenuator	Pasternack	PE4007-4	/	2025-02-23	2026-02-22
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2025-02-23	2026-02-22
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2025-02-23	2026-02-22
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22
WTXE1007A 1001	Amplifier	HP	8447F	2805A034 75	2025-02-23	2026-02-22
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2025-02-23	2026-02-22
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☐ Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2025-02-23	2026-02-22
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22
WTXE1065A 1001	Amplifier	C&D	PAP-1G18	2002	2025-02-23	2026-02-22
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2025-02-23	2026-02-22

WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2025-02-23	2026-02-22
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2025-02-23	2026-02-22
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2025-02-23	2026-02-22
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1007A 1002	Amplifier	HP	8447F	2944A038 69	2025-02-23	2026-02-22
WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☒ Chamber C: Above 1GHz						
WTXE1093A	EMI Test	Rohde &	ESIB 26	100401	2025-02-23	2026-02-22

1001	Receiver	Schwarz				
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2025-02-23	2026-02-22
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2024-12-08	2025-12-07
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2025-02-23	2026-02-22
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2025-02-23	2026-02-22
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2025-02-23	2026-02-22
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2025-02-23	2026-02-22
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2025-02-23	2026-02-22
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission A)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission B)	Farad	EZ-EMC	RA-03A1 (1.1.4.2)
EMI Test Software (Radiated Emission C)	Farad	EZ-EMC	RA-03A1-2 (1.1.4.2)
EMI Test Software (Conducted Emission Room 1#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3
EMI Test Software (Conducted Emission Room 2#)	Farad	EZ-EMC	3A1*CE-RE 1.1.4.3

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.405	Antenna Requirement	Compliant
15.407 (c)	Automatically Discontinue Transmission	Compliant
§15.207; §15.407(b)(6)	Conducted Emission	Compliant
§15.407(a)(1),(2)	Power Spectral Density	Compliant
§15.407(e)	Emission Bandwidth and Occupied Bandwidth	Compliant
§15.407(a)(1),(2)	Maximum Conducted Output Power	Compliant
§15.407(b)(1),(2),(3),(4)	Undesirable emission	Compliant
§15.205; §15.407(b)(1),(2),(3)	Radiated Emission	Compliant
§15.407(g)	Frequency Stability	Compliant
§15.407(h)	Dynamic Frequency Selection (DFS)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has an Integral antenna, fulfill the requirement of this section.

4. Automatically Discontinue Transmission

4.1 Standard Applicable

According to FCC Part 15.407(c), the device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

4.2 Summary of Test Results

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5. Power Spectral Density

5.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11 \text{ dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

5.2 Test Procedure

According to 789033 D02 v02r01 General UNII Test Procedures New Rules v02, the following is the measurement procedure.

For devices operating in the bands 5.15-5.25GHz, 5.25-5.35GHz, and 5.47-5.725GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85GHz, the rules specify a measurement bandwidth of 500kHz. Many spectrum analyzers do not have 500kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500kHz, "provided that the measured power is integrated over the full

reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1MHz, or 500kHz). If measurements are performed using a reduced resolution bandwidth ($< 1\text{MHz}$, or $< 500\text{kHz}$) and integrated over 1 MHz, or 500kHz bandwidth, the following adjustments to the procedures apply:

- a) Set $\text{RBW} \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $\text{VBW} \geq 3 \text{ RBW}$.
- c) If measurement bandwidth of Maximum PSD is specified in 500kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 500\text{kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/\text{RBW})$ to the measured result, whereas $\text{RBW} (< 1\text{MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100kHz for the sections 5.c) and 5.d) above, since $\text{RBW}=100\text{kHz}$ is available on nearly all spectrum analyzers.

5.3 Summary of Test Results/Plots

Please refer to Appendix A

6. Emission Bandwidth and Occupied Bandwidth

6.1 Standard Applicable

According to 15.407(a) and (e):

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(e) Within the 5.725-5.85GHz band, the minimum 6dB bandwidth of U-NII devices shall be at least 500kHz.

6.2 Test Procedure

According to 789033 D02 v02r0r section C&D, the following is the measurement procedure.

1. Emission Bandwidth (EBW)

a) Set RBW = approximately 1% of the emission bandwidth.

b) Set the VBW > RBW.

- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

2. Minimum Emission Bandwidth for the band 5.725-5.85GHz Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

D. 99 Percent Occupied Bandwidth

The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section II.G.3.d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the EBW to 789033 D02 v02r01 General UNII Test Procedures New Rules v01 define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section II.E. However, the EBW must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth:

- 1. Set center frequency to the nominal EUT channel center frequency.
- 2. Set span = 1.5 times to 5.0 times the OBW.
- 3. Set RBW = 1 % to 5 % of the OBW
- 4. Set VBW $\geq 3 \times$ RBW
- 5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- 6. Use the 99 % power bandwidth function of the instrument (if available).
- 7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency.

Reference No.: WTF25X03065646W003

The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6.3 Summary of Test Results/Plots

Please refer to Appendix B

7. Maximum Conducted Output Power

7.1 Standard Applicable

Section 15.407(a) Power limits:

(1) For the band 5.15-5.25GHz.

(iv) For mobile and portable client devices in the 5.15-5.25GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(2) For the 5.25-5.35GHz and 5.47-5.725GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250mW or $11\text{dBm} + 10 \log B$, where B is the 26dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

(3) For the band 5.725-5.85GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

7.2 Test Procedure

According to KDB789033 D02 v02r01 section E, the following is the measurement procedure.

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1MHz.
- (iii) Set VBW $\geq$ 3MHz.
- (iv) Number of points in sweep $\geq$ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that

narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq$ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

7.3 Summary of Test Results/Plots

Please refer to Appendix C

8. Radiated Spurious Emissions

8.1 Standard Applicable

According to §15.407(b), undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35GHz band: All emissions outside of the 5.15-5.35GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725GHz band: All emissions outside of the 5.47-5.725GHz band shall not exceed an e.i.r.p. of -27dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85GHz band:
 - (i) All emissions shall be limited to a level of -27dBm/MHz at 75MHz or more above or below the band edge increasing linearly to 10dBm/MHz at 25MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6dBm/MHz at 5MHz above or below the band edge, and from 5MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

According to §15.407(b)(6), Unwanted emissions below 1GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

According to §15.407(b)(7), The provisions of §15.205 apply to intentional radiators operating under this section.

789033 D02 v02r01 General UNII Test Procedures New Rules v01

If radiated measurements are performed, field strength is then converted to EIRP as follows:

$$\text{EIRP} = ((E \cdot d)^2) / 30$$

where:


- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.

8.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.407(b)(6) and FCC Part 15.209 Limit..

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



8.3 Test Receiver Setup

During the radiated emission test for above 1GHz, the test receiver was set with the following configurations:

For peak detector:

RBW = 1000kHz, VBW = 3000kHz, Sweep Time = Auto

For average detector:

RBW = 1000kHz, VBW = 10Hz, Sweep Time = Auto

8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.5 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


- Spurious Emission From 30MHz to 1GHz
- 5150-5250MHz

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.7406	30.07	-9.42	20.65	40.00	-19.35	-	-	peak
2	62.7432	28.67	-9.92	18.75	40.00	-21.25	-	-	peak
3	164.3129	30.84	-8.64	22.20	43.50	-21.30	-	-	peak
4	403.9335	29.34	-6.03	23.31	46.00	-22.69	-	-	peak
5	531.2910	30.70	-3.80	26.90	46.00	-19.10	-	-	peak
6	938.7139	32.22	2.72	34.94	46.00	-11.06	-	-	peak

802.11a			
Test Channel	5180MHz(Worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	37.3017	28.53	-9.90	18.63	40.00	-21.37	-	-	peak
2	58.8979	28.24	-9.43	18.81	40.00	-21.19	-	-	peak
3	156.4259	29.65	-8.58	21.07	43.50	-22.43	-	-	peak
4	363.5231	31.43	-6.79	24.64	46.00	-21.36	-	-	peak
5	586.2172	29.63	-2.48	27.15	46.00	-18.85	-	-	peak
6	972.2827	31.89	2.98	34.87	54.00	-19.13	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.4131	29.53	-9.05	20.48	40.00	-19.52	-	-	peak
2	79.1185	28.77	-12.84	15.93	40.00	-24.07	-	-	peak
3	163.1623	30.00	-8.58	21.42	43.50	-22.08	-	-	peak
4	307.1053	28.75	-7.60	21.15	46.00	-24.85	-	-	peak
5	468.1651	30.75	-4.89	25.86	46.00	-20.14	-	-	peak
6	765.6482	32.62	0.45	33.07	46.00	-12.93	-	-	peak

802.11n-HT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.0965	28.28	-9.79	18.49	40.00	-21.51	-	-	peak
2	58.8979	28.37	-9.43	18.94	40.00	-21.06	-	-	peak
3	155.3305	29.51	-8.62	20.89	43.50	-22.61	-	-	peak
4	363.5231	33.04	-6.79	26.25	46.00	-19.75	-	-	peak
5	594.5143	30.05	-2.23	27.82	46.00	-18.18	-	-	peak
6	1000.0000	31.57	3.04	34.61	54.00	-19.39	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	37.5648	28.34	-9.87	18.47	40.00	-21.53	-	-	peak
2	51.1756	28.94	-8.99	19.95	40.00	-20.05	-	-	peak
3	164.3129	31.44	-8.64	22.80	43.50	-20.70	-	-	peak
4	294.4260	29.30	-7.84	21.46	46.00	-24.54	-	-	peak
5	669.9523	29.59	-1.19	28.40	46.00	-17.60	-	-	peak
6	979.1392	32.39	3.00	35.39	54.00	-18.61	-	-	peak

802.11ac-VHT20			
Test Channel	5180MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	31.5126	28.91	-10.37	18.54	40.00	-21.46	-	-	peak
2	55.2883	28.45	-9.22	19.23	40.00	-20.77	-	-	peak
3	139.7909	29.51	-9.40	20.11	43.50	-23.39	-	-	peak
4	168.9970	28.68	-8.80	19.88	43.50	-23.62	-	-	peak
5	363.5231	31.27	-6.79	24.48	46.00	-21.52	-	-	peak
6	781.9606	30.99	0.71	31.70	46.00	-14.30	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.7406	30.38	-9.42	20.96	40.00	-19.04	-	-	peak
2	164.3129	30.86	-8.64	22.22	43.50	-21.28	-	-	peak
3	284.2607	28.59	-8.17	20.42	46.00	-25.58	-	-	peak
4	412.5395	29.45	-5.94	23.51	46.00	-22.49	-	-	peak
5	669.9523	30.48	-1.19	29.29	46.00	-16.71	-	-	peak
6	893.6557	31.56	1.84	33.40	46.00	-12.60	-	-	peak

802.11n-HT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.2625	28.48	-10.21	18.27	40.00	-21.73	-	-	peak
2	55.6781	28.44	-9.24	19.20	40.00	-20.80	-	-	peak
3	154.2428	29.15	-8.68	20.47	43.50	-23.03	-	-	peak
4	363.5230	32.10	-6.79	25.31	46.00	-20.69	-	-	peak
5	723.7930	33.14	-0.43	32.71	46.00	-13.29	-	-	peak
6	938.7139	31.86	2.72	34.58	46.00	-11.42	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	47.0371	29.29	-9.01	20.28	40.00	-19.72	-	-	peak
2	57.2654	27.94	-9.33	18.61	40.00	-21.39	-	-	peak
3	163.1623	30.06	-8.58	21.48	43.50	-22.02	-	-	peak
4	350.9722	29.86	-7.01	22.85	46.00	-23.15	-	-	peak
5	598.7067	29.67	-2.09	27.58	46.00	-18.42	-	-	peak
6	952.0001	31.87	2.95	34.82	46.00	-11.18	-	-	peak

802.11ac-VHT40			
Test Channel	5190MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	34.7705	28.02	-10.27	17.75	40.00	-22.25	-	-	peak
2	50.1080	28.49	-8.98	19.51	40.00	-20.49	-	-	peak
3	149.9676	29.66	-8.92	20.74	43.50	-22.76	-	-	peak
4	363.5231	33.18	-6.79	26.39	46.00	-19.61	-	-	peak
5	602.9287	29.70	-2.06	27.64	46.00	-18.36	-	-	peak
6	821.3871	31.30	0.98	32.28	46.00	-13.72	-	-	peak

802.11ac-VHT80			
Test Channel	5210MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.7406	30.77	-9.42	21.35	40.00	-18.65	-	-	peak
2	61.8676	28.38	-9.80	18.58	40.00	-21.42	-	-	peak
3	164.3129	31.22	-8.64	22.58	43.50	-20.92	-	-	peak
4	266.8395	29.75	-8.96	20.79	46.00	-25.21	-	-	peak
5	488.3263	30.26	-4.59	25.67	46.00	-20.33	-	-	peak
6	734.0373	34.72	-0.18	34.54	46.00	-11.46	-	-	peak


802.11ac-VHT80			
Test Channel	5210MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.7406	28.67	-9.42	19.25	40.00	-20.75	-	-	peak
2	64.5319	28.66	-10.14	18.52	40.00	-21.48	-	-	peak
3	171.3890	29.26	-8.98	20.28	43.50	-23.22	-	-	peak
4	363.5231	32.09	-6.79	25.30	46.00	-20.70	-	-	peak
5	607.1806	29.61	-2.07	27.54	46.00	-18.46	-	-	peak
6	833.0127	31.79	0.98	32.77	46.00	-13.23	-	-	peak


➤ 5250-5350MHz

802.11a			
Test Channel	5260MHz	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	44.1543	27.59	-8.39	19.20	40.00	-20.80	-	-	peak
2	74.2696	26.74	-11.20	15.54	40.00	-24.46	-	-	peak
3	162.0197	27.73	-7.69	20.04	43.50	-23.46	-	-	peak
4	334.1255	28.37	-6.18	22.19	46.00	-23.81	-	-	peak
5	478.1394	29.36	-3.97	25.39	46.00	-20.61	-	-	peak
6	781.9605	30.76	1.41	32.17	46.00	-13.83	-	-	peak

802.11a			
Test Channel	5260MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.9081	27.63	-8.93	18.70	40.00	-21.30	-	-	peak
2	56.4662	27.85	-8.56	19.29	40.00	-20.71	-	-	peak
3	148.9173	28.89	-8.07	20.82	43.50	-22.68	-	-	peak
4	363.5230	29.26	-5.89	23.37	46.00	-22.63	-	-	peak
5	586.2171	28.85	-1.69	27.16	46.00	-18.84	-	-	peak
6	821.3871	31.23	1.68	32.91	46.00	-13.09	-	-	peak

802.11n-HT20			
Test Channel	5260MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	44.4657	27.40	-8.36	19.04	40.00	-20.96	-	-	peak
2	73.7495	26.14	-11.10	15.04	40.00	-24.96	-	-	peak
3	165.4716	27.26	-7.87	19.39	43.50	-24.11	-	-	peak
4	311.4519	27.41	-6.58	20.83	46.00	-25.17	-	-	peak
5	550.2902	28.40	-2.98	25.42	46.00	-20.58	-	-	peak
6	919.1315	29.41	3.05	32.46	46.00	-13.54	-	-	peak

802.11n-HT20			
Test Channel	5260MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.7370	24.73	-8.85	15.88	40.00	-24.12	-	-	peak
2	54.1349	25.97	-8.42	17.55	40.00	-22.45	-	-	peak
3	129.3921	26.38	-9.29	17.09	43.50	-26.41	-	-	peak
4	280.2935	26.59	-7.43	19.16	46.00	-26.84	-	-	peak
5	520.2078	27.39	-3.14	24.25	46.00	-21.75	-	-	peak
6	906.3040	28.64	2.79	31.43	46.00	-14.57	-	-	peak

802.11ac-VHT20			
Test Channel	5260MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.7811	27.48	-9.20	18.28	40.00	-21.72	-	-	peak
2	101.8931	27.96	-12.43	15.53	43.50	-27.97	-	-	peak
3	159.7584	28.18	-7.69	20.49	43.50	-23.01	-	-	peak
4	320.3306	28.76	-6.39	22.37	46.00	-23.63	-	-	peak
5	505.7890	29.70	-3.43	26.27	46.00	-19.73	-	-	peak
6	844.8027	31.64	1.66	33.30	46.00	-12.70	-	-	peak

802.11ac-VHT20			
Test Channel	5260MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.3651	28.32	-8.99	19.33	40.00	-20.67	-	-	peak
2	74.2696	28.12	-11.20	16.92	40.00	-23.08	-	-	peak
3	165.4716	28.41	-7.87	20.54	43.50	-22.96	-	-	peak
4	338.8545	28.79	-6.20	22.59	46.00	-23.41	-	-	peak
5	452.0012	28.95	-4.11	24.84	46.00	-21.16	-	-	peak
6	689.0509	30.47	-0.34	30.13	46.00	-15.87	-	-	peak

802.11n-HT40			
Test Channel	5270MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.8451	28.23	-8.42	19.81	40.00	-20.19	-	-	peak
2	64.5318	26.27	-9.42	16.85	40.00	-23.15	-	-	peak
3	148.9173	27.46	-8.07	19.39	43.50	-24.11	-	-	peak
4	290.3168	28.16	-7.10	21.06	46.00	-24.94	-	-	peak
5	442.5721	29.73	-4.35	25.38	46.00	-20.62	-	-	peak
6	754.9627	28.93	0.98	29.91	46.00	-16.09	-	-	peak

802.11n-HT40			
Test Channel	5270MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	34.5269	24.06	-9.50	14.56	40.00	-25.44	-	-	peak
2	67.3108	23.82	-9.89	13.93	40.00	-26.07	-	-	peak
3	137.8398	24.66	-8.68	15.98	43.50	-27.52	-	-	peak
4	309.2709	25.67	-6.65	19.02	46.00	-26.98	-	-	peak
5	565.9775	27.64	-2.40	25.24	46.00	-20.76	-	-	peak
6	925.6131	28.51	3.19	31.70	46.00	-14.30	-	-	peak

802.11ac-VHT40			
Test Channel	5270MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.8451	26.77	-8.42	18.35	40.00	-21.65	-	-	peak
2	110.0818	27.69	-11.13	16.56	43.50	-26.94	-	-	peak
3	159.7584	28.26	-7.69	20.57	43.50	-22.93	-	-	peak
4	304.9547	27.69	-6.75	20.94	46.00	-25.06	-	-	peak
5	478.1394	29.08	-3.97	25.11	46.00	-20.89	-	-	peak
6	684.2258	28.86	-0.35	28.51	46.00	-17.49	-	-	peak

802.11ac-VHT40			
Test Channel	5270MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.8451	28.95	-8.42	20.53	40.00	-19.47	-	-	peak
2	129.3921	28.16	-9.29	18.87	43.50	-24.63	-	-	peak
3	255.8226	28.63	-8.57	20.06	46.00	-25.94	-	-	peak
4	415.4486	29.38	-5.01	24.37	46.00	-21.63	-	-	peak
5	637.7945	30.09	-0.98	29.11	46.00	-16.89	-	-	peak
6	899.9576	31.79	2.66	34.45	46.00	-11.55	-	-	peak

802.11ac-VHT80			
Test Channel	5290MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.0964	26.66	-9.02	17.64	40.00	-22.36	-	-	peak
2	75.8519	28.19	-11.53	16.66	40.00	-23.34	-	-	peak
3	162.0197	28.07	-7.69	20.38	43.50	-23.12	-	-	peak
4	282.2701	28.93	-7.36	21.57	46.00	-24.43	-	-	peak
5	495.2379	28.59	-3.65	24.94	46.00	-21.06	-	-	peak
6	651.3830	29.65	-0.58	29.07	46.00	-16.93	-	-	peak


802.11ac-VHT80			
Test Channel	5290MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	42.3313	25.98	-8.59	17.39	40.00	-22.61	-	-	peak
2	80.8041	27.72	-12.49	15.23	40.00	-24.77	-	-	peak
3	160.8851	26.88	-7.68	19.20	43.50	-24.30	-	-	peak
4	389.9874	28.13	-5.39	22.74	46.00	-23.26	-	-	peak
5	582.1121	28.80	-1.82	26.98	46.00	-19.02	-	-	peak
6	804.2522	28.33	1.71	30.04	46.00	-15.96	-	-	peak


➤ 5470-5725MHz

802.11a			
Test Channel	5500MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.7370	25.84	-8.85	16.99	40.00	-23.01	-	-	peak
2	72.7203	27.42	-10.89	16.53	40.00	-23.47	-	-	peak
3	162.0197	27.82	-7.69	20.13	43.50	-23.37	-	-	peak
4	329.4624	28.32	-6.22	22.10	46.00	-23.90	-	-	peak
5	445.6931	27.43	-4.26	23.17	46.00	-22.83	-	-	peak
6	679.4345	29.49	-0.39	29.10	46.00	-16.90	-	-	peak

802.11a			
Test Channel	5500MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.0964	28.26	-9.02	19.24	40.00	-20.76	-	-	peak
2	74.2696	28.53	-11.20	17.33	40.00	-22.67	-	-	peak
3	159.7584	28.50	-7.69	20.81	43.50	-22.69	-	-	peak
4	348.5144	29.08	-6.14	22.94	46.00	-23.06	-	-	peak
5	602.9287	29.03	-1.26	27.77	46.00	-18.23	-	-	peak
6	945.3336	30.71	3.60	34.31	46.00	-11.69	-	-	peak

802.11n-HT20			
Test Channel	5500MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	39.4587	25.53	-8.87	16.66	40.00	-23.34	-	-	peak
2	79.1185	27.52	-12.13	15.39	40.00	-24.61	-	-	peak
3	135.9162	27.41	-8.76	18.65	43.50	-24.85	-	-	peak
4	280.2935	27.20	-7.43	19.77	46.00	-26.23	-	-	peak
5	468.1650	28.52	-4.06	24.46	46.00	-21.54	-	-	peak
6	765.6482	29.92	1.15	31.07	46.00	-14.93	-	-	peak

802.11n-HT20			
Test Channel	5500MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	51.1755	25.94	-8.27	17.67	40.00	-22.33	-	-	peak
2	114.0183	25.09	-10.62	14.47	43.50	-29.03	-	-	peak
3	164.3129	25.71	-7.82	17.89	43.50	-25.61	-	-	peak
4	389.9874	26.62	-5.39	21.23	46.00	-24.77	-	-	peak
5	498.7302	26.71	-3.58	23.13	46.00	-22.87	-	-	peak
6	669.9523	28.21	-0.46	27.75	46.00	-18.25	-	-	peak

802.11ac-VHT20			
Test Channel	5500MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.0172	29.05	-8.81	20.24	40.00	-19.76	-	-	peak
2	68.7449	26.14	-10.19	15.95	40.00	-24.05	-	-	peak
3	170.1887	29.20	-8.04	21.16	43.50	-22.34	-	-	peak
4	334.1255	29.39	-6.18	23.21	46.00	-22.79	-	-	peak
5	655.9765	30.13	-0.56	29.57	46.00	-16.43	-	-	peak
6	906.3040	30.21	2.79	33.00	46.00	-13.00	-	-	peak

802.11ac-VHT20			
Test Channel	5500MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	37.3017	26.44	-9.13	17.31	40.00	-22.69	-	-	peak
2	60.1527	26.22	-8.86	17.36	40.00	-22.64	-	-	peak
3	148.9173	27.44	-8.07	19.37	43.50	-24.13	-	-	peak
4	268.7212	28.67	-8.03	20.64	46.00	-25.36	-	-	peak
5	412.5394	27.94	-5.05	22.89	46.00	-23.11	-	-	peak
6	856.7597	29.08	1.79	30.87	46.00	-15.13	-	-	peak

802.11n-HT40			
Test Channel	5510MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	42.6298	27.87	-8.55	19.32	40.00	-20.68	-	-	peak
2	65.4452	26.07	-9.54	16.53	40.00	-23.47	-	-	peak
3	156.4258	28.24	-7.74	20.50	43.50	-23.00	-	-	peak
4	320.3306	28.23	-6.39	21.84	46.00	-24.16	-	-	peak
5	509.3558	28.61	-3.36	25.25	46.00	-20.75	-	-	peak
6	875.0132	29.79	2.16	31.95	46.00	-14.05	-	-	peak

802.11n-HT40			
Test Channel	5510MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.3651	26.25	-8.99	17.26	40.00	-22.74	-	-	peak
2	65.4452	27.22	-9.54	17.68	40.00	-22.32	-	-	peak
3	148.9173	27.82	-8.07	19.75	43.50	-23.75	-	-	peak
4	324.8644	27.80	-6.28	21.52	46.00	-24.48	-	-	peak
5	498.7302	29.10	-3.58	25.52	46.00	-20.48	-	-	peak
6	887.3978	29.75	2.40	32.15	46.00	-13.85	-	-	peak

802.11ac-VHT40			
Test Channel	5510MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	42.9305	27.59	-8.52	19.07	40.00	-20.93	-	-	peak
2	69.2297	26.79	-10.27	16.52	40.00	-23.48	-	-	peak
3	159.7584	28.02	-7.69	20.33	43.50	-23.17	-	-	peak
4	353.4471	28.61	-6.07	22.54	46.00	-23.46	-	-	peak
5	655.9765	29.97	-0.56	29.41	46.00	-16.59	-	-	peak
6	958.7134	31.12	3.73	34.85	46.00	-11.15	-	-	peak

802.11ac-VHT40			
Test Channel	5510MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.7406	26.62	-8.67	17.95	40.00	-22.05	-	-	peak
2	104.0640	27.27	-12.08	15.19	43.50	-28.31	-	-	peak
3	163.1622	28.42	-7.74	20.68	43.50	-22.82	-	-	peak
4	313.6482	29.42	-6.54	22.88	46.00	-23.12	-	-	peak
5	461.6313	29.00	-4.08	24.92	46.00	-21.08	-	-	peak
6	893.6556	30.81	2.54	33.35	46.00	-12.65	-	-	peak

802.11ac-VHT80			
Test Channel	5530MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	43.2332	26.63	-8.48	18.15	40.00	-21.85	-	-	peak
2	71.2033	25.67	-10.62	15.05	40.00	-24.95	-	-	peak
3	157.5289	27.08	-7.73	19.35	43.50	-24.15	-	-	peak
4	311.4519	27.06	-6.58	20.48	46.00	-25.52	-	-	peak
5	573.9882	28.11	-2.09	26.02	46.00	-19.98	-	-	peak
6	945.3336	29.88	3.60	33.48	46.00	-12.52	-	-	peak


802.11ac-VHT80			
Test Channel	5530MHz(worst case)	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.1580	25.84	-8.72	17.12	40.00	-22.88	-	-	peak
2	58.8979	27.12	-8.71	18.41	40.00	-21.59	-	-	peak
3	154.2428	27.90	-7.84	20.06	43.50	-23.44	-	-	peak
4	346.0739	27.71	-6.15	21.56	46.00	-24.44	-	-	peak
5	505.7890	28.44	-3.43	25.01	46.00	-20.99	-	-	peak
6	754.9627	29.45	0.98	30.43	46.00	-15.57	-	-	peak


➤ 5725-5850MHz

802.11a			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.2994	28.17	-8.79	19.38	40.00	-20.62	-	-	peak
2	102.6117	27.53	-12.31	15.22	43.50	-28.28	-	-	peak
3	162.0197	27.64	-7.69	19.95	43.50	-23.55	-	-	peak
4	304.9547	28.61	-6.75	21.86	46.00	-24.14	-	-	peak
5	535.0376	29.61	-3.00	26.61	46.00	-19.39	-	-	peak
6	862.8015	29.75	1.91	31.66	46.00	-14.34	-	-	peak

802.11a			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.7333	26.72	-8.30	18.42	40.00	-21.58	-	-	peak
2	74.2696	29.80	-11.20	18.60	40.00	-21.40	-	-	peak
3	156.4258	27.66	-7.74	19.92	43.50	-23.58	-	-	peak
4	292.3642	28.39	-7.03	21.36	46.00	-24.64	-	-	peak
5	448.8361	28.30	-4.15	24.15	46.00	-21.85	-	-	peak
6	723.7930	29.19	0.27	29.46	46.00	-16.54	-	-	peak

802.11n-HT20			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.4483	27.82	-8.70	19.12	40.00	-20.88	-	-	peak
2	94.3135	28.24	-13.57	14.67	43.50	-28.83	-	-	peak
3	146.8391	28.86	-8.20	20.66	43.50	-22.84	-	-	peak
4	327.1553	27.77	-6.25	21.52	46.00	-24.48	-	-	peak
5	409.6506	28.23	-5.08	23.15	46.00	-22.85	-	-	peak
6	793.0281	30.13	1.59	31.72	46.00	-14.28	-	-	peak

802.11n-HT20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.6355	25.66	-8.96	16.70	40.00	-23.30	-	-	peak
2	65.4452	25.91	-9.54	16.37	40.00	-23.63	-	-	peak
3	156.4258	26.14	-7.74	18.40	43.50	-25.10	-	-	peak
4	336.4817	27.45	-6.20	21.25	46.00	-24.75	-	-	peak
5	495.2379	28.69	-3.65	25.04	46.00	-20.96	-	-	peak
6	952.0000	29.45	3.71	33.16	46.00	-12.84	-	-	peak

802.11ac-VHT20			
Test Channel	5745MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.9081	26.30	-8.93	17.37	40.00	-22.63	-	-	peak
2	101.1796	26.83	-12.57	14.26	43.50	-29.24	-	-	peak
3	148.9173	28.91	-8.07	20.84	43.50	-22.66	-	-	peak
4	324.8644	29.07	-6.28	22.79	46.00	-23.21	-	-	peak
5	509.3558	28.49	-3.36	25.13	46.00	-20.87	-	-	peak
6	793.0281	31.08	1.59	32.67	46.00	-13.33	-	-	peak

802.11ac-VHT20			
Test Channel	5745MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.5836	25.69	-8.77	16.92	40.00	-23.08	-	-	peak
2	60.1527	26.36	-8.86	17.50	40.00	-22.50	-	-	peak
3	159.7584	26.73	-7.69	19.04	43.50	-24.46	-	-	peak
4	315.8599	27.94	-6.48	21.46	46.00	-24.54	-	-	peak
5	523.8763	28.81	-3.06	25.75	46.00	-20.25	-	-	peak
6	804.2522	28.81	1.71	30.52	46.00	-15.48	-	-	peak

802.11n-HT40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	44.1543	29.81	-8.39	21.42	40.00	-18.58	-	-	peak
2	66.8395	27.24	-9.79	17.45	40.00	-22.55	-	-	peak
3	163.1622	28.95	-7.74	21.21	43.50	-22.29	-	-	peak
4	309.2709	28.48	-6.65	21.83	46.00	-24.17	-	-	peak
5	542.6103	29.89	-3.01	26.88	46.00	-19.12	-	-	peak
6	945.3336	30.37	3.60	33.97	46.00	-12.03	-	-	peak

802.11n-HT40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	37.3017	26.44	-9.13	17.31	40.00	-22.69	-	-	peak
2	49.7571	27.19	-8.26	18.93	40.00	-21.07	-	-	peak
3	137.8398	25.94	-8.68	17.26	43.50	-26.24	-	-	peak
4	264.9709	26.97	-8.24	18.73	46.00	-27.27	-	-	peak
5	433.3397	28.11	-4.64	23.47	46.00	-22.53	-	-	peak
6	739.2136	28.78	0.64	29.42	46.00	-16.58	-	-	peak

802.11ac-VHT40			
Test Channel	5755MHz(worst case)	Polarity:	Horizontal




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.2994	25.56	-8.79	16.77	40.00	-23.23	-	-	peak
2	60.1527	27.33	-8.86	18.47	40.00	-21.53	-	-	peak
3	111.6398	28.70	-10.95	17.75	43.50	-25.75	-	-	peak
4	254.0312	29.14	-8.62	20.52	46.00	-25.48	-	-	peak
5	452.0012	28.97	-4.11	24.86	46.00	-21.14	-	-	peak
6	815.6352	30.91	1.69	32.60	46.00	-13.40	-	-	peak

802.11ac-VHT40			
Test Channel	5755MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.2625	28.66	-9.43	19.23	40.00	-20.77	-	-	peak
2	56.4662	27.10	-8.56	18.54	40.00	-21.46	-	-	peak
3	148.9173	29.25	-8.07	21.18	43.50	-22.32	-	-	peak
4	276.3817	28.61	-7.61	21.00	46.00	-25.00	-	-	peak
5	415.4486	28.37	-5.01	23.36	46.00	-22.64	-	-	peak
6	749.6761	29.54	0.88	30.42	46.00	-15.58	-	-	peak

802.11ac-VHT80			
Test Channel	5775MHz(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	30.8552	24.81	-9.59	15.22	40.00	-24.78	-	-	peak
2	55.6781	28.89	-8.52	20.37	40.00	-19.63	-	-	peak
3	146.8391	26.65	-8.20	18.45	43.50	-25.05	-	-	peak
4	240.1442	28.20	-9.20	19.00	46.00	-27.00	-	-	peak
5	442.5721	27.91	-4.35	23.56	46.00	-22.44	-	-	peak
6	798.6204	28.51	1.69	30.20	46.00	-15.80	-	-	peak

802.11ac-VHT80			
Test Channel	5775MHz(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	33.5699	27.02	-9.55	17.47	40.00	-22.53	-	-	peak
2	65.9067	28.05	-9.62	18.43	40.00	-21.57	-	-	peak
3	155.3305	28.08	-7.77	20.31	43.50	-23.19	-	-	peak
4	309.2709	28.73	-6.65	22.08	46.00	-23.92	-	-	peak
5	458.3987	29.51	-4.09	25.42	46.00	-20.58	-	-	peak
6	765.6482	28.79	1.15	29.94	46.00	-16.06	-	-	peak

Remark: ‘-’Means’ the test Degree and Height are not recorded by the test software and only show the worst case in the test report.


➤ Spurious Emission above 1GHz

802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	74.34	-12.21	62.13	74.00	-11.87	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	48.92	-12.21	36.71	54.00	-17.29	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	75.02	-12.21	62.81	74.00	-11.19	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Vertical(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	48.41	-12.21	36.20	54.00	-17.80	-	-	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	74.45	-12.21	62.24	74.00	-11.76	-	-	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	49.27	-12.21	37.06	54.00	-16.94	-	-	AVG

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5147.395	80.56	-12.23	68.33	74.00	-5.67	-	-	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	49.14	-12.21	36.93	54.00	-17.07	-	-	AVG

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	84.51	-12.21	72.30	74.00	-1.70	-	-	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5147.395	49.66	-12.23	37.43	54.00	-16.57	-	-	AVG

802.11ac-VHT80- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5150.000	75.71	-12.21	63.50	74.00	-10.50	-	-	peak

802.11ac-VHT80- Restricted Bandedge			
Test Channel	band 5.15-5.25GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5146.092	47.17	-12.23	34.94	54.00	-19.06	-	-	AVG

802.11a- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5459.559	66.79	-10.61	56.18	74.00	-17.82	-	-	peak

802.11a- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5459.780	47.80	-10.61	37.19	54.00	-16.81	-	-	AVG

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5459.780	68.38	-10.61	57.77	74.00	-16.23	-	-	peak

802.11n-HT20- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5460.000	47.72	-10.61	37.11	54.00	-16.89	-	-	AVG

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5458.898	66.41	-10.61	55.80	74.00	-18.20	-	-	peak

802.11ac-VHT20- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5460.000	48.10	-10.61	37.49	54.00	-16.51	-	-	AVG

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5458.016	65.01	-10.62	54.39	74.00	-19.61	-	-	peak

802.11n-HT40- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5458.677	48.55	-10.61	37.94	54.00	-16.06	-	-	AVG

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5460.000	64.90	-10.61	54.29	74.00	-19.71	-	-	peak

802.11ac-VHT40- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5458.898	48.39	-10.61	37.78	54.00	-16.22	-	-	AVG

802.11ac-VHT80- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5460.000	58.62	-10.61	48.01	74.00	-25.99	-	-	peak

802.11ac-VHT80- Restricted Bandedge			
Test Channel	band 5.35-5.47GHz	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	5447.435	43.75	-10.67	33.08	54.00	-20.92	-	-	AVG

Note: The Restricted Bandedge was tested in Horizontal /Vertical and the worst case position data was reported.

Remark: ‘-’Means’ the test Degree and Height is not recorded by the test software and only show the worst case in the test report.

- For the frequency band 5.15-5.25GHz, 5.250-5.350GHz, 5.470-5.725GHz, 5.725-5.850GHz (802.11a)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5180MHz)							
10360	56.32	7.11	63.43	74	-10.57	H	PK
10360	40.28	7.11	47.39	54	-6.61	H	AV
10360	57.94	7.11	65.05	74	-8.95	V	PK
10360	38.29	7.11	45.40	54	-8.60	V	AV
Middle Channel (5200MHz)							
10400	58.19	7.22	65.41	74	-8.59	H	PK
10400	41.74	7.22	48.96	54	-5.04	H	AV
10400	57.54	7.22	64.76	74	-9.24	V	PK
10400	39.80	7.22	47.02	54	-6.98	V	AV
High Channel (5240MHz)							
10480	55.75	7.69	63.44	74	-10.56	H	PK
10480	38.35	7.69	46.04	54	-7.96	H	AV
10480	57.10	7.69	64.79	74	-9.21	V	PK
10480	39.84	7.69	47.53	54	-6.47	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5260MHz)							
10520	57.57	7.96	65.53	74	-8.47	H	PK
10520	41.25	7.96	49.21	54	-4.79	H	AV
10520	58.71	7.96	66.67	74	-7.33	V	PK
10520	41.16	7.96	49.12	54	-4.88	V	AV
Middle Channel (5280MHz)							
10560	57.72	8.02	65.74	74	-8.26	H	PK
10560	38.75	8.02	46.77	54	-7.23	H	AV
10560	58.83	8.02	66.85	74	-7.15	V	PK
10560	39.25	8.02	47.27	54	-6.73	V	AV
High Channel (5320MHz)							
10640	55.62	8.35	63.97	74	-10.03	H	PK
10640	38.57	8.35	46.92	54	-7.08	H	AV
10640	58.44	8.35	66.79	74	-7.21	V	PK
10640	38.34	8.35	46.69	54	-7.31	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5500MHz)							
11000	55.94	8.82	64.76	74	-9.24	H	PK
11000	38.36	8.82	47.18	54	-6.82	H	AV
11000	57.22	8.82	66.04	74	-7.96	V	PK
11000	41.12	8.82	49.94	54	-4.06	V	AV
Middle Channel (5600MHz)							
11200	57.53	8.92	66.45	74	-7.55	H	PK
11200	41.36	8.92	50.28	54	-3.72	H	AV
11200	55.35	8.92	64.27	74	-9.73	V	PK
11200	40.21	8.92	49.13	54	-4.87	V	AV
High Channel (5700MHz)							
11400	55.25	9.36	64.61	74	-9.39	H	PK
11400	41.37	9.36	50.73	54	-3.27	H	AV
11400	55.00	9.36	64.36	74	-9.64	V	PK
11400	38.96	9.36	48.32	54	-5.68	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	55.17	9.45	64.62	74	-9.38	H	PK
11490	40.83	9.45	50.28	54	-3.72	H	AV
11490	58.54	9.45	67.99	74	-6.01	V	PK
11490	41.18	9.45	50.63	54	-3.37	V	AV
Middle Channel (5785MHz)							
11570	55.04	9.62	64.66	74	-9.34	H	PK
11570	39.09	9.62	48.71	54	-5.29	H	AV
11570	56.32	9.62	65.94	74	-8.06	V	PK
11570	40.28	9.62	49.90	54	-4.10	V	AV
High Channel (5825MHz)							
11650	58.96	9.84	68.80	74	-5.20	H	PK
11650	39.54	9.84	49.38	54	-4.62	H	AV
11650	55.62	9.84	65.46	74	-8.54	V	PK
11650	41.40	9.84	51.24	54	-2.76	V	AV

➤ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-43.27	-27
Highest	Above 5350	-42.51	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5250-5350MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-42.47	-27
Highest	Above 5350	-41.76	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5470-5725MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-42.17	-27
Highest	Above 5725	-39.82	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-46.76	-27
	5650 to 5700	-33.64	-27 to -17
	5700 to 5720	-27.13	-17 to 15.6
	5720 to 5725	-17.27	15.6 to 27
Highest	5850 to 5855	-14.34	27 to 15.6
	5855 to 5875	-21.25	15.6 to -17
	5875 to 5925	-33.16	-17 to -27
	Above 5925	-38.22	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz, 5.250-5.350GHz, 5.470-5.725GHz, 5.725-5.850GHz (802.11n HT20)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5180MHz)							
10360	55.22	7.11	62.33	74	-11.67	H	PK
10360	38.88	7.11	45.99	54	-8.01	H	AV
10360	58.73	7.11	65.84	74	-8.16	V	PK
10360	40.63	7.11	47.74	54	-6.26	V	AV
Middle Channel (5200MHz)							
10400	55.71	7.22	62.93	74	-11.07	H	PK
10400	39.03	7.22	46.25	54	-7.75	H	AV
10400	57.67	7.22	64.89	74	-9.11	V	PK
10400	41.40	7.22	48.62	54	-5.38	V	AV
High Channel (5240MHz)							
10480	58.82	7.69	66.51	74	-7.49	H	PK
10480	41.79	7.69	49.48	54	-4.52	H	AV
10480	56.61	7.69	64.30	74	-9.70	V	PK
10480	40.62	7.69	48.31	54	-5.69	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5260MHz)							
10520	55.33	7.96	63.29	74	-10.71	H	PK
10520	40.57	7.96	48.53	54	-5.47	H	AV
10520	57.89	7.96	65.85	74	-8.15	V	PK
10520	38.25	7.96	46.21	54	-7.79	V	AV
Middle Channel (5280MHz)							
10560	57.01	8.02	65.03	74	-8.97	H	PK
10560	40.96	8.02	48.98	54	-5.02	H	AV
10560	55.37	8.02	63.39	74	-10.61	V	PK
10560	40.32	8.02	48.34	54	-5.66	V	AV
High Channel (5320MHz)							
10640	55.47	8.35	63.82	74	-10.18	H	PK
10640	38.75	8.35	47.10	54	-6.90	H	AV
10640	55.66	8.35	64.01	74	-9.99	V	PK
10640	40.72	8.35	49.07	54	-4.93	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5500MHz)							
11000	57.96	8.82	66.78	74	-7.22	H	PK
11000	38.04	8.82	46.86	54	-7.14	H	AV
11000	58.52	8.82	67.34	74	-6.66	V	PK
11000	40.89	8.82	49.71	54	-4.29	V	AV
Middle Channel (5600MHz)							
11200	56.31	8.92	65.23	74	-8.77	H	PK
11200	40.74	8.92	49.66	54	-4.34	H	AV
11200	58.63	8.92	67.55	74	-6.45	V	PK
11200	39.58	8.92	48.50	54	-5.50	V	AV
High Channel (5700MHz)							
11400	55.47	9.84	65.31	74	-8.69	H	PK
11400	39.50	9.84	49.34	54	-4.66	H	AV
11400	58.82	9.84	68.66	74	-5.34	V	PK
11400	39.28	9.84	49.12	54	-4.88	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	56.48	9.45	65.93	74	-8.07	H	PK
11490	38.04	9.45	47.49	54	-6.51	H	AV
11490	58.72	9.45	68.17	74	-5.83	V	PK
11490	40.19	9.45	49.64	54	-4.36	V	AV
Middle Channel (5785MHz)							
11570	58.70	9.62	68.32	74	-5.68	H	PK
11570	41.63	9.62	51.25	54	-2.75	H	AV
11570	55.54	9.62	65.16	74	-8.84	V	PK
11570	41.19	9.62	50.81	54	-3.19	V	AV
High Channel (5825MHz)							
11650	57.51	9.84	67.35	74	-6.65	H	PK
11650	38.10	9.84	47.94	54	-6.06	H	AV
11650	58.54	9.84	68.38	74	-5.62	V	PK
11650	40.79	9.84	50.63	54	-3.37	V	AV

➤ Out of Band edge 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-40.82	-27
Highest	Above 5350	-41.67	-27

Note: the data just list the worst cases

➤ Out of Band edge for 5250-5350MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-41.65	-27
Highest	Above 5350	-42.46	-27

Note: the data just list the worst cases

➤ Out of Band edge for 5470-5725MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-38.73	-27
Highest	Above 5725	-39.54	-27

Note: the data just list the worst cases

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-46.28	-27
	5650 to 5700	-33.16	-27 to -17
	5700 to 5720	-27.36	-17 to 15.6
	5720 to 5725	-17.72	15.6 to 27
Highest	5850 to 5855	-14.67	27 to 15.6
	5855 to 5875	-21.35	15.6 to -17
	5875 to 5925	-33.26	-17 to -27
	Above 5925	-38.15	-27

Note: the data just list the worst cases

- For the frequency band 5.15-5.25GHz, 5.250-5.350GHz, 5.470-5.725GHz, 5.725-5.850GHz (802.11ac-VHT20)
- Harmonics And Spurious Emissions

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5180MHz)							
10360	57.18	7.11	64.29	74	-9.71	H	PK
10360	40.78	7.11	47.89	54	-6.11	H	AV
10360	57.07	7.11	64.18	74	-9.82	V	PK
10360	40.16	7.11	47.27	54	-6.73	V	AV
Middle Channel (5200MHz)							
10400	56.20	7.22	63.42	74	-10.58	H	PK
10400	40.71	7.22	47.93	54	-6.07	H	AV
10400	56.46	7.22	63.68	74	-10.32	V	PK
10400	38.90	7.22	46.12	54	-7.88	V	AV
High Channel (5240MHz)							
10480	57.69	7.69	65.38	74	-8.62	H	PK
10480	41.66	7.69	49.35	54	-4.65	H	AV
10480	57.13	7.69	64.82	74	-9.18	V	PK
10480	40.76	7.69	48.45	54	-5.55	V	AV

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel (5260MHz)							
10520	56.77	7.96	64.73	74	-9.27	H	PK
10520	40.73	7.96	48.69	54	-5.31	H	AV
10520	55.88	7.96	63.84	74	-10.16	V	PK
10520	41.59	7.96	49.55	54	-4.45	V	AV
Middle Channel (5280MHz)							
10560	55.67	8.02	63.69	74	-10.31	H	PK
10560	38.24	8.02	46.26	54	-7.74	H	AV
10560	55.74	8.02	63.76	74	-10.24	V	PK
10560	40.92	8.02	48.94	54	-5.06	V	AV
High Channel (5320MHz)							
10640	57.19	8.35	65.54	74	-8.46	H	PK
10640	39.93	8.35	48.28	54	-5.72	H	AV
10640	55.04	8.35	63.39	74	-10.61	V	PK
10640	38.13	8.35	46.48	54	-7.52	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5500MHz)							
11000	58.83	8.82	67.65	74	-6.35	H	PK
11000	41.18	8.82	50.00	54	-4.00	H	AV
11000	55.82	8.82	64.64	74	-9.36	V	PK
11000	39.17	8.82	47.99	54	-6.01	V	AV
Middle Channel (5600MHz)							
11200	56.21	8.92	65.13	74	-8.87	H	PK
11200	38.30	8.92	47.22	54	-6.78	H	AV
11200	57.79	8.92	66.71	74	-7.29	V	PK
11200	41.13	8.92	50.05	54	-3.95	V	AV
High Channel (5700MHz)							
11400	55.25	9.84	65.09	74	-8.91	H	PK
11400	38.80	9.84	48.64	54	-5.36	H	AV
11400	57.21	9.84	67.05	74	-6.95	V	PK
11400	38.06	9.84	47.90	54	-6.10	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5745MHz)							
11490	57.71	9.45	67.16	74	-6.84	H	PK
11490	41.27	9.45	50.72	54	-3.28	H	AV
11490	55.52	9.45	64.97	74	-9.03	V	PK
11490	41.76	9.45	51.21	54	-2.79	V	AV
Middle Channel (5785MHz)							
11570	58.48	9.62	68.10	74	-5.90	H	PK
11570	40.07	9.62	49.69	54	-4.31	H	AV
11570	58.91	9.62	68.53	74	-5.47	V	PK
11570	39.85	9.62	49.47	54	-4.53	V	AV
High Channel (5825MHz)							
11650	57.46	9.84	67.30	74	-6.70	H	PK
11650	39.49	9.84	49.33	54	-4.67	H	AV
11650	56.30	9.84	66.14	74	-7.86	V	PK
11650	40.53	9.84	50.37	54	-3.63	V	AV

➤ Out of Band edge 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-40.27	-27
Highest	Above 5350	-41.34	-27

Note: the data just list the worst cases

➤ Out of Band edge for 5250-5350MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-41.57	-27
Highest	Above 5350	-42.62	-27

Note: the data just list the worst cases

➤ Out of Band edge for 5470-5725MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-38.73	-27
Highest	Above 5725	-39.29	-27

Note: the data just list the worst cases

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-46.75	-27
	5650 to 5700	-33.29	-27 to -17
	5700 to 5720	-27.60	-17 to 15.6
	5720 to 5725	-17.76	15.6 to 27
Highest	5850 to 5855	-14.52	27 to 15.6
	5855 to 5875	-21.34	15.6 to -17
	5875 to 5925	-33.25	-17 to -27
	Above 5925	-38.13	-27

Note: the data just list the worst cases

- For the frequency band 5.15-5.25GHz, 5.250-5.350GHz, 5.470-5.725GHz, 5.725-5.850GHz (802.11n HT40)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5190MHz)							
10380	57.11	7.89	65.00	74	-9.00	H	PK
10380	38.49	7.89	46.38	54	-7.62	H	AV
10380	56.62	7.89	64.51	74	-9.49	V	PK
10380	41.64	7.89	49.53	54	-4.47	V	AV
High Channel (5230MHz)							
10460	55.92	7.97	63.89	74	-10.11	H	PK
10460	41.62	7.97	49.59	54	-4.41	H	AV
10460	55.11	7.97	63.08	74	-10.92	V	PK
10460	39.83	7.97	47.80	54	-6.20	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5270MHz)							
10540	57.57	8.16	65.73	74	-8.27	H	PK
10540	38.27	8.16	46.43	54	-7.57	H	AV
10540	57.99	8.16	66.15	74	-7.85	V	PK
10540	38.36	8.16	46.52	54	-7.48	V	AV
High Channel (5310MHz)							
10620	56.87	8.57	65.44	74	-8.56	H	PK
10620	39.95	8.57	48.52	54	-5.48	H	AV
10620	55.10	8.57	63.67	74	-10.33	V	PK
10620	38.29	8.57	46.86	54	-7.14	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5510MHz)							
11020	56.86	9.16	66.02	74	-7.98	H	PK
11020	40.98	9.16	50.14	54	-3.86	H	AV
11020	58.85	9.16	68.01	74	-5.99	V	PK
11020	39.84	9.16	49.00	54	-5.00	V	AV
Middle Channel (5590MHz)							
11180	56.58	9.29	65.87	74	-8.13	H	PK
11180	38.64	9.29	47.93	54	-6.07	H	AV
11180	56.76	9.29	66.05	74	-7.95	V	PK
11180	39.03	9.29	48.32	54	-5.68	V	AV
High Channel (5670MHz)							
11340	58.11	9.43	67.54	74	-6.46	H	PK
11340	40.93	9.43	50.36	54	-3.64	H	AV
11340	58.85	9.43	68.28	74	-5.72	V	PK
11340	38.70	9.43	48.13	54	-5.87	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5755MHz)							
11510	56.41	9.45	65.86	74	-8.14	H	PK
11510	40.13	9.45	49.58	54	-4.42	H	AV
11510	55.74	9.45	65.19	74	-8.81	V	PK
11510	38.61	9.45	48.06	54	-5.94	V	AV
High Channel (5795MHz)							
11590	58.84	9.27	68.11	74	-5.89	H	PK
11590	41.42	9.27	50.69	54	-3.31	H	AV
11590	58.07	9.27	67.34	74	-6.66	V	PK
11590	41.89	9.27	51.16	54	-2.84	V	AV

➤ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-39.27	-27
Highest	Above 5350	-38.56	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5250-5350MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-37.81	-27
Highest	Above 5350	-38.24	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5470-5725MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-35.17	-27
Highest	Above 5725	-37.61	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5715	-41.72	-27
	5715 to 5725	-35.66	-17
Highest	5850 to 5860	-37.27	-17
	Above 5860	-38.35	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz, 5.250-5.350GHz, 5.470-5.725GHz, 5.725-5.850GHz (802.11ac-VHT40)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5190MHz)							
10380	55.98	7.89	63.87	74	-10.13	H	PK
10380	40.90	7.89	48.79	54	-5.21	H	AV
10380	56.83	7.89	64.72	74	-9.28	V	PK
10380	38.41	7.89	46.30	54	-7.70	V	AV
High Channel (5230MHz)							
10460	58.16	7.97	66.13	74	-7.87	H	PK
10460	40.81	7.97	48.78	54	-5.22	H	AV
10460	57.68	7.97	65.65	74	-8.35	V	PK
10460	40.42	7.97	48.39	54	-5.61	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5270MHz)							
10540	56.36	8.16	64.52	74	-9.48	H	PK
10540	41.70	8.16	49.86	54	-4.14	H	AV
10540	56.27	8.16	64.43	74	-9.57	V	PK
10540	41.43	8.16	49.59	54	-4.41	V	AV
High Channel (5310MHz)							
10620	56.44	8.57	65.01	74	-8.99	H	PK
10620	40.20	8.57	48.77	54	-5.23	H	AV
10620	57.54	8.57	66.11	74	-7.89	V	PK
10620	38.29	8.57	46.86	54	-7.14	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5510MHz)							
11020	58.23	9.16	67.39	74	-6.61	H	PK
11020	39.40	9.16	48.56	54	-5.44	H	AV
11020	57.28	9.16	66.44	74	-7.56	V	PK
11020	38.77	9.16	47.93	54	-6.07	V	AV
Middle Channel (5590MHz)							
11180	58.97	9.29	68.26	74	-5.74	H	PK
11180	39.10	9.29	48.39	54	-5.61	H	AV
11180	55.40	9.29	64.69	74	-9.31	V	PK
11180	38.86	9.29	48.15	54	-5.85	V	AV
High Channel (5670MHz)							
11340	58.59	9.43	68.02	74	-5.98	H	PK
11340	41.45	9.43	50.88	54	-3.12	H	AV
11340	56.53	9.43	65.96	74	-8.04	V	PK
11340	40.98	9.43	50.41	54	-3.59	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5755MHz)							
11510	58.62	9.45	68.07	74	-5.93	H	PK
11510	41.44	9.45	50.89	54	-3.11	H	AV
11510	55.92	9.45	65.37	74	-8.63	V	PK
11510	38.81	9.45	48.26	54	-5.74	V	AV
High Channel (5795MHz)							
11590	55.47	9.27	64.74	74	-9.26	H	PK
11590	39.46	9.27	48.73	54	-5.27	H	AV
11590	55.83	9.27	65.10	74	-8.90	V	PK
11590	38.45	9.27	47.72	54	-6.28	V	AV

➤ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-39.71	-27
Highest	Above 5350	-38.51	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5250-5350MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-37.16	-27
Highest	Above 5350	-38.75	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5470-5725MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-36.82	-27
Highest	Above 5725	-37.51	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-46.76	-27
	5650 to 5700	-33.25	-27 to -17
	5700 to 5720	-27.67	-17 to 15.6
	5720 to 5725	-17.51	15.6 to 27
Highest	5850 to 5855	-14.66	27 to 15.6
	5855 to 5875	-21.72	15.6 to -17
	5875 to 5925	-33.39	-17 to -27
	Above 5925	-38.74	-27
Note: the data just list the worst cases			

- For the frequency band 5.15-5.25GHz, 5.250-5.350GHz, 5.470-5.725GHz, 5.725-5.850GHz (802.11ac-VHT80)
- Harmonics And Spurious Emissions

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
5210MHz							
10420	58.53	7.53	66.06	74	-7.94	H	PK
10420	38.70	7.53	46.23	54	-7.77	H	AV
10420	58.04	7.53	65.57	74	-8.43	H	PK
10420	39.89	7.53	47.42	54	-6.58	H	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
5290MHz							
10580	56.11	7.95	64.06	74	-9.94	H	PK
10580	38.13	7.95	46.08	54	-7.92	H	AV
10580	57.84	7.95	65.79	74	-8.21	V	PK
10580	40.69	7.95	48.64	54	-5.36	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel (5530MHz)							
11060	58.89	9.42	68.31	74	-5.69	H	PK
11060	40.49	9.42	49.91	54	-4.09	H	AV
11060	57.56	9.42	66.98	74	-7.02	V	PK
11060	38.12	9.42	47.54	54	-6.46	V	AV
High Channel (5610MHz)							
11220	55.66	9.69	65.35	74	-8.65	H	PK
11220	40.15	9.69	49.84	54	-4.16	H	AV
11220	55.43	9.69	65.12	74	-8.88	V	PK
11220	38.26	9.69	47.95	54	-6.05	V	AV

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
5775MHz							
11550	56.76	9.93	66.69	74	-7.31	H	PK
11550	38.75	9.93	48.68	54	-5.32	H	AV
11550	56.57	9.93	66.50	74	-7.50	V	PK
11550	39.47	9.93	49.40	54	-4.60	V	AV

➤ Out of Band edge for 5150-5250MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-37.70	-27
Highest	Above 5350	-36.18	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5250-5350MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5150	-38.24	-27
Highest	Above 5350	-36.56	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5470-5725MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5470	-39.31	-27
Highest	Above 5725	-37.47	-27
Note: the data just list the worst cases			

➤ Out of Band edge for 5725-5850MHz

Test CH.	Test Segment	Result	Limit
	MHz	dBm/MHz	dBm/MHz
Lowest	Below 5650	-46.22	-27
	5650 to 5700	-33.51	-27 to -17
	5700 to 5720	-27.67	-17 to 15.6
	5720 to 5725	-17.25	15.6 to 27
Highest	5850 to 5855	-14.30	27 to 15.6
	5855 to 5875	-22.49	15.6 to -17
	5875 to 5925	-33.25	-17 to -27
	Above 5925	-38.61	-27
Note: the data just list the worst cases			

Note: Testing is carried out with frequency rang 9kHz to 40Ghz, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Frequency Stability

9.1 Standard Applicable

According to §15.407(g), manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

9.3 Summary of Test Results/Plots

Please refer to Appendix D


10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

10.2 Basic Test Setup Block Diagram




10.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150kHz
Stop Frequency.....	30MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth.....	9kHz
Quasi-Peak Adapter Mode.....	Normal


10.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1580	35.89	9.73	45.62	65.56	-19.94	QP
2	0.1580	22.66	9.73	32.39	55.56	-23.17	AVG
3	0.2660	20.49	9.62	30.11	51.24	-21.13	AVG
4	0.2700	35.27	9.62	44.89	61.12	-16.23	QP
5	0.4260	17.79	9.70	27.49	47.33	-19.84	AVG
6*	0.4380	32.70	9.71	42.41	57.10	-14.69	QP
7	0.9300	29.70	9.68	39.38	56.00	-16.62	QP
8	1.0100	15.96	9.67	25.63	46.00	-20.37	AVG
9	1.7500	27.88	9.63	37.51	56.00	-18.49	QP
10	1.9420	14.44	9.62	24.06	46.00	-21.94	AVG
11	8.1180	19.24	9.82	29.06	50.00	-20.94	AVG
12	8.1980	32.34	9.82	42.16	60.00	-17.84	QP

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1580	20.80	9.73	30.53	55.56	-25.03	AVG
2	0.1660	34.26	9.70	43.96	65.15	-21.19	QP
3	0.2660	33.54	9.62	43.16	61.24	-18.08	QP
4	0.2660	20.32	9.62	29.94	51.24	-21.30	AVG
5	0.5700	29.50	9.73	39.23	56.00	-16.77	QP
6	0.5980	16.08	9.72	25.80	46.00	-20.20	AVG
7	0.9820	32.17	9.67	41.84	56.00	-14.16	QP
8	0.9980	15.77	9.67	25.44	46.00	-20.56	AVG
9	1.8660	28.29	9.63	37.92	56.00	-18.08	QP
10	2.0380	14.61	9.62	24.23	46.00	-21.77	AVG
11*	7.9740	36.08	9.82	45.90	60.00	-14.10	QP
12	8.2620	21.15	9.83	30.98	50.00	-19.02	AVG

APPENDIX SUMMARY

Project No.	WTF25X03065646W	Test Engineer	Elin Su
Start date	2025/3/31	Finish date	2025/3/31
Temperature	24℃	Humidity	40%
RF specifications	U-NII		

APPENDIX	Description of Test Item	Result
A	Power Spectral Density	Compliant
B	Emission Bandwidth and Occupied Bandwidth	Compliant
C	Maximum Conducted Output Power	Compliant
D	Frequency Stability	Compliant

APPENDIX A


Power Spectral Density			
U-NII-1:5150-5250MHz			
Operating mode	Test Channel	Power Spectral Density dBm/MHz	Limit (dBm/MHz)
802.11a	5180	1.73	11
	5200	1.04	11
	5240	0.54	11
802.11n-HT20	5180	0.15	11
	5200	-0.22	11
	5240	-0.76	11
802.11n-HT40	5190	-4.09	11
	5230	-4.59	11
802.11ac-VHT20	5180	0.27	11
	5200	0.04	11
	5240	-0.44	11
802.11ac-VHT40	5190	-3.86	11
	5230	-4.46	11
802.11ac-VHT80	5210	-9.00	11

U-NII-2A: 5250-5350MHz			
Operating mode	Test Channel	Power Spectral Density dBm/MHz	Limit (dBm/MHz)
802.11a	5260	1.26	11
	5280	1.16	11
	5320	0.75	11
802.11n-HT20	5260	0.12	11
	5280	-0.07	11
	5320	-0.35	11
802.11n-HT40	5270	-4.44	11
	5310	-4.42	11
802.11ac-VHT20	5260	0.19	11
	5280	0.02	11
	5320	-0.14	11
802.11ac-VHT40	5270	-4.08	11
	5310	-3.87	11
802.11ac-VHT80	5290	-9.31	11


U-NII-2C: 5470-5725MHz			
Operating mode	Test Channel	Power Spectral Density dBm/MHz	Limit (dBm/MHz)
802.11a	5500	1.79	11
	5580	1.47	11
	5700	0.80	11
802.11n-HT20	5500	0.36	11
	5580	0.50	11
	5700	-0.30	11
802.11n-HT40	5510	-4.86	11
	5550	-4.94	11
	5670	-4.52	11
802.11ac-VHT20	5500	0.54	11
	5580	0.48	11
	5700	-0.20	11
802.11ac-VHT40	5510	-4.61	11
	5550	-4.69	11
	5670	-4.31	11
802.11ac-VHT80	5530	-9.05	11
	5610	-8.49	11

U-NII-3: 5725-5850MHz					
Operating mode	Test Channel	Power Spectral Density dBm/300kHz	Factor	Power Spectral Density* dBm/500kHz	Limit dBm/500kHz
802.11a	5745	-2.46	2.22	-0.24	30
	5785	-2.48	2.22	-0.26	30
	5825	-2.78	2.22	-0.56	30
802.11n-HT20	5745	-3.33	2.22	-1.11	30
	5785	-3.48	2.22	-1.26	30
	5825	-3.81	2.22	-1.59	30
802.11n HT40	5755	-7.02	2.22	-4.80	30
	5795	-6.85	2.22	-4.63	30
802.11ac-VHT20	5745	-3.13	2.22	-0.91	30
	5785	-3.31	2.22	-1.09	30
	5825	-3.61	2.22	-1.39	30
802.11ac-VHT40	5755	-7.24	2.22	-5.02	30
	5795	-7.35	2.22	-5.13	30
802.11ac-VHT80	5775	-11.51	2.22	-9.29	30
*Note: Maximum PSD=PSD(dBm/300kHz)+10log(500kHz/300kHz)=2.22					


5150-5250MHz






Date: 31.MAR.2025 14:59:21









Date: 31.MAR.2025 15:00:17




Date: 31.MAR.2025 15:00:39

802.11n-HT20-Low	 Date: 31.MAR.2025 15:01:27
802.11n-HT20-Middle	 Date: 31.MAR.2025 15:01:47
802.11n-HT20-High	 Date: 31.MAR.2025 15:02:05


802.11n-HT40-Low	 Date: 31.MAR.2025 15:02:43
802.11n-HT40-High	 Date: 31.MAR.2025 15:03:34
802.11ac-VHT20-Low	 Date: 31.MAR.2025 15:03:57

802.11ac-VHT20-Middle	 Date: 31.MAR.2025 15:04:26
802.11ac-VHT20-High	 Date: 31.MAR.2025 15:04:50
802.11ac-VHT40-Low	 Date: 31.MAR.2025 15:05:11




802.11ac-VHT40-High









802.11ac-VHT80-Low








5250-5350MHz

802.11a-Low	 Ref 20 dBm Att 30 dB RBW 1 MHz VBW 3 MHz Span 40 MHz Marker 1 [T1] 1.26 dBm 5.26384000 GHz Date: 31.MAR.2025 15:43:05
802.11a-Middle	 Ref 20 dBm Att 30 dB RBW 1 MHz VBW 3 MHz Span 40 MHz Marker 1 [T1] 1.16 dBm 5.27648000 GHz Date: 31.MAR.2025 15:43:47
802.11a-High	 Ref 20 dBm Att 30 dB RBW 1 MHz VBW 3 MHz Span 40 MHz Marker 1 [T1] 0.75 dBm 5.31632000 GHz Date: 31.MAR.2025 15:44:09




802.11n-HT20-Low	 Ref 20 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1] -0.12 dBm *VBW 3 MHz *SWT 1 s 5.263840000 GHz 20 Offset 1 dB Center 5.26 GHz 4 MHz/ Span 40 MHz Date: 31.MAR.2025 15:45:53
802.11n-HT20-Middle	 Ref 20 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1] -0.07 dBm *VBW 3 MHz *SWT 1 s 5.272880000 GHz 20 Offset 1 dB Center 5.28 GHz 4 MHz/ Span 40 MHz Date: 31.MAR.2025 15:46:33
802.11n-HT20-High	 Ref 20 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1] -0.35 dBm *VBW 3 MHz *SWT 1 s 5.316400000 GHz 20 Offset 1 dB Center 5.32 GHz 4 MHz/ Span 40 MHz Date: 31.MAR.2025 15:46:57




802.11n-HT40-Low	 Date: 31.MAR.2025 15:47:27
802.11n-HT40-High	 Date: 31.MAR.2025 15:47:50
802.11ac-VHT20-Low	 Date: 31.MAR.2025 15:48:14




802.11ac-VHT20-Middle	 Date: 31.MAR.2025 15:48:30
802.11ac-VHT20-High	 Date: 31.MAR.2025 15:49:15
802.11ac-VHT40-Low	 Date: 31.MAR.2025 15:49:40

802.11ac-VHT40-High	Ref 20 dBm Offset 1 dB RBW 1 MHz VBW 3 MHz SWT 1 s Marker 1 [T1] -3.97 dBm 5.293680000 GHz  Center 5.31 GHz 8 MHz/ Span 80 MHz Date: 31.MAR.2025 15:50:09
802.11ac-VHT80-Low	Ref 20 dBm Offset 1 dB RBW 1 MHz VBW 3 MHz SWT 1 s Marker 1 [T1] -9.31 dBm 5.277520000 GHz  Center 5.29 GHz 16 MHz/ Span 160 MHz Date: 31.MAR.2025 15:50:39

5470-5725MHz

802.11a-Low	 Date: 31.MAR.2025 16:26:40
802.11a-Middle	 Date: 31.MAR.2025 16:27:07
802.11a-High	 Date: 31.MAR.2025 16:27:30


802.11n-HT20-Low	 Date: 31.MAR.2025 16:28:03
802.11n-HT20-Middle	 Date: 31.MAR.2025 16:28:31
802.11n-HT20-High	 Date: 31.MAR.2025 16:29:32

802.11n-HT40-Low	 Ref 20 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1] -4.86 dBm *VSW 3 MHz *SWT 1 s 5.493520000 GHz 20 Offset 1 dB Center 5.51 GHz 8 MHz/ Span 80 MHz Date: 31.MAR.2025 16:30:14
802.11n-HT40-Middle	 Ref 20 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1] -4.94 dBm *VSW 3 MHz *SWT 1 s 5.606480000 GHz 20 Offset 1 dB Center 5.59 GHz 8 MHz/ Span 80 MHz Date: 31.MAR.2025 16:30:37
802.11n-HT40-High	 Ref 20 dBm *Att 30 dB *RBW 1 MHz Marker 1 [T1] -4.52 dBm *VSW 3 MHz *SWT 1 s 5.653680000 GHz 20 Offset 1 dB Center 5.67 GHz 8 MHz/ Span 80 MHz Date: 31.MAR.2025 16:31:13


802.11ac-VHT20-Low	Date: 31.MAR.2025 16:31:57
802.11ac-VHT20-Middle	Date: 31.MAR.2025 16:32:14
802.11ac-VHT20-High	Date: 31.MAR.2025 16:32:42

802.11ac-VHT40-Low	Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VBW: 3 MHz, SWT: 1 s, Marker 1 [T1]: -4.61 dBm, 5.49360000 GHz Date: 31.MAR.2025 16:33:40
802.11ac-VHT40-Middle	Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VBW: 3 MHz, SWT: 1 s, Marker 1 [T1]: -4.69 dBm, 5.50640000 GHz Date: 31.MAR.2025 16:33:58
802.11ac-VHT40-High	Ref: 20 dBm, Att: 30 dB, RBW: 1 MHz, VBW: 3 MHz, SWT: 1 s, Marker 1 [T1]: -4.31 dBm, 5.65320000 GHz Date: 31.MAR.2025 16:34:28




802.11ac-VHT80-Low









802.11ac-VHT80-High








5725-5850MHz

802.11a-Low	 Date: 31.MAR.2025 16:49:42
802.11a-Middle	 Date: 31.MAR.2025 16:50:02
802.11a-High	 Date: 31.MAR.2025 16:50:17

802.11n-HT20-Low	 Ref: 20 dBm, Att: 30 dB, RBW: 300 kHz, VSW: 1 MHz, SWT: 1 s, Marker 1 [T1]: -3.33 dBm, 5.752520000 GHz Center: 5.745 GHz, 4 MHz/, Span: 40 MHz Date: 31.MAR.2025 16:50:54
802.11n-HT20-Middle	 Ref: 20 dBm, Att: 30 dB, RBW: 300 kHz, VSW: 1 MHz, SWT: 1 s, Marker 1 [T1]: -3.48 dBm, 5.792520000 GHz Center: 5.785 GHz, 4 MHz/, Span: 40 MHz Date: 31.MAR.2025 16:51:12
802.11n-HT20-High	 Ref: 20 dBm, Att: 30 dB, RBW: 300 kHz, VSW: 1 MHz, SWT: 1 s, Marker 1 [T1]: -3.81 dBm, 5.832520000 GHz Center: 5.825 GHz, 4 MHz/, Span: 40 MHz Date: 31.MAR.2025 16:51:34

802.11n-HT40-Low	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -7.02 dBm *VSW 1 MHz *SWT 1 s 5.771320000 GHz 20 Offset 1 dB Center 5.755 GHz 8 MHz/ Span 80 MHz Date: 31.MAR.2025 16:52:38
802.11n-HT40-High	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -6.85 dBm *VSW 1 MHz *SWT 1 s 5.811320000 GHz 20 Offset 1 dB Center 5.795 GHz 8 MHz/ Span 80 MHz Date: 31.MAR.2025 16:52:55
802.11ac-VHT20-Low	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -3.13 dBm *VSW 1 MHz *SWT 1 s 5.752520000 GHz 20 Offset 1 dB Center 5.745 GHz 4 MHz/ Span 40 MHz Date: 31.MAR.2025 16:53:21

802.11ac-VHT20-Middle	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -3.31 dBm *VSW 1 MHz *SWT 1 s 5.782520000 GHz 20 Offset 1 dB Center 5.785 GHz 4 MHz/ Span 40 MHz Date: 31.MAR.2025 16:54:06
802.11ac-VHT20-High	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -3.61 dBm *VSW 1 MHz *SWT 1 s 5.832520000 GHz 20 Offset 1 dB Center 5.825 GHz 4 MHz/ Span 40 MHz Date: 31.MAR.2025 16:54:26
802.11ac-VHT40-Low	 Ref 20 dBm *Att 30 dB *RBW 300 kHz Marker 1 [T1] -7.24 dBm *VSW 1 MHz *SWT 1 s 5.767480000 GHz 20 Offset 1 dB Center 5.755 GHz 8 MHz/ Span 80 MHz Date: 31.MAR.2025 16:54:51

802.11ac-VHT40-High	Ref 20 dBm *Att 30 dB RBW 300 kHz Marker 1 [T1] VBW 1 MHz -7.35 dBm SWT 1 s 5.807480000 GHz  Center 5.795 GHz 8 MHz/ Span 80 MHz Date: 31.MAR.2025 16:55:12
802.11ac-VHT80-Low	Ref 20 dBm *Att 30 dB RBW 300 kHz Marker 1 [T1] VBW 1 MHz -11.51 dBm SWT 1 s 5.792600000 GHz  Center 5.775 GHz 16 MHz/ Span 160 MHz Date: 31.MAR.2025 16:55:38

APPENDIX B

Emission Bandwidth and Occupied Bandwidth

U-NII-1:5150-5250MHz				
Test Mode	Test Channel MHz	26 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz
802.11a	5180	23.30	17.30	Pass
	5200	22.20	17.30	Pass
	5240	24.50	17.20	Pass
802.11n-HT20	5180	26.10	18.10	Pass
	5200	26.00	18.10	Pass
	5240	27.10	18.00	Pass
802.11n-HT40	5190	40.20	36.80	Pass
	5230	41.20	36.80	Pass
802.11ac-VHT20	5180	20.70	17.90	Pass
	5200	20.40	17.90	Pass
	5240	20.40	18.00	Pass
802.11ac-VHT40	5190	39.60	36.80	Pass
	5230	40.00	36.80	Pass
802.11ac-VHT80	5210	86.80	76.00	Pass

U-NII-2A: 5250-5350MHz				
Test Mode	Test Channel MHz	26 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz
802.11a	5260	21.50	17.30	Pass
	5280	24.30	17.10	Pass
	5320	22.30	17.20	Pass
802.11n-HT20	5260	26.00	18.10	Pass
	5280	26.00	18.10	Pass
	5320	25.90	18.00	Pass
802.11n-HT40	5270	40.60	36.80	Pass
	5310	41.20	36.80	Pass
802.11ac-VHT20	5260	21.10	17.90	Pass
	5280	21.40	17.90	Pass
	5320	21.70	17.90	Pass
802.11ac-VHT40	5270	41.00	36.80	Pass
	5310	40.00	36.80	Pass
802.11ac-VHT80	5290	87.60	76.00	Pass

U-NII-2C: 5470-5725MHz				
Test Mode	Test Channel MHz	26 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz
802.11a	5500	20.20	17.20	Pass
	5580	21.50	17.10	Pass
	5700	22.10	17.00	Pass
802.11n-HT20	5500	26.70	18.00	Pass
	5580	27.20	18.10	Pass
	5700	25.60	18.00	Pass
802.11n-HT40	5510	40.40	37.00	Pass
	5550	40.20	36.80	Pass
	5670	40.40	36.80	Pass
802.11ac-VHT20	5500	20.70	17.80	Pass
	5580	20.70	18.00	Pass
	5700	20.70	18.00	Pass
802.11ac-VHT40	5510	40.00	36.80	Pass
	5550	40.00	36.80	Pass
	5670	40.40	36.80	Pass
802.11ac-VHT80	5530	88.80	76.00	Pass
	5610	86.00	76.00	Pass

U-NII-3: 5725-5850MHz				
Test Mode	Test Channel MHz	6 dB Bandwidth MHz	99% Bandwidth MHz	Limit MHz
802.11a	5745	16.50	17.30	≥500
	5785	16.50	17.20	≥500
	5825	16.60	17.20	≥500
802.11n-HT20	5745	17.60	18.10	≥500
	5785	17.50	18.10	≥500
	5825	17.50	18.10	≥500
802.11n-HT40	5755	36.60	37.40	≥500
	5795	36.40	37.40	≥500
802.11ac-VHT20	5745	17.60	18.00	≥500
	5785	17.50	18.10	≥500
	5825	17.50	18.00	≥500
802.11ac-VHT40	5755	36.60	37.20	≥500
	5795	36.60	37.20	≥500
802.11ac-VHT80	5775	76.00	75.60	≥500