

**User Manual**

**1. Product description**

Display

Antenna

Power switch

Microphone

Speaker

TF card slot

Charging port

**2. Charging method**

Charging method

**3. Product charging and installation method**

2.1 Installation method

2.2 Installation method

**4. App download**

1. Download "Search" "TuYa Smart" in the app store or scan the barcode QR code to download.

2. Register / Login

**5. Pair product with TuYa Smart App**

1. Pair product with TuYa Smart App (Bluetooth)

**6. Common functions**

1. Push notification settings

**7. Home management and device sharing**

1. Home management

2. Device sharing

**8. Display main page icons**

1. Pair product with TuYa Smart App (Bluetooth)

**9. Pair product with TuYa Smart App (Bluetooth)**

**10. Common functions**

**11. Home management and device sharing**

**12. Device sharing**

**13. Pair product with TuYa Smart App (Bluetooth)**

**14. Common functions**

**15. Home management and device sharing**

<div>14. Product parameters</div> <div>Camera</div> <table border="1"> <tr> <td>Power consumption</td><td>Working: 330mA</td></tr> <tr> <td>Temperature and humidity detection range</td><td>Temperature: -35℃~40℃ Humidity: 5%-95%RH</td></tr> <tr> <td>Rotation angle</td><td>Vertical 45° Horizontal 355°</td></tr> <tr> <td>IR</td><td>2K</td></tr> <tr> <td>Lens angle</td><td>100°</td></tr> <tr> <td>Night vision light source</td><td>940nm infrared lamp</td></tr> <tr> <td>Baby call</td><td>✓</td></tr> <tr> <td>Motion detection</td><td>Support region detection</td></tr> <tr> <td>Working temperature</td><td>-20℃~40℃</td></tr> <tr> <td>Working humidity</td><td>&lt;95%</td></tr> </table>	Power consumption	Working: 330mA	Temperature and humidity detection range	Temperature: -35℃~40℃ Humidity: 5%-95%RH	Rotation angle	Vertical 45° Horizontal 355°	IR	2K	Lens angle	100°	Night vision light source	940nm infrared lamp	Baby call	✓	Motion detection	Support region detection	Working temperature	-20℃~40℃	Working humidity	<95%	<div>14. FCC Statement</div> <table border="1"> <tr> <td>Battery charging voltage</td><td>DC 5V</td></tr> <tr> <td>Display size</td><td>5 inch</td></tr> <tr> <td>Working current</td><td>450mA</td></tr> <tr> <td>Two way intercom</td><td>✓</td></tr> <tr> <td>Working mode</td><td>Power saving mode Normal mode</td></tr> <tr> <td>Playback</td><td>✓</td></tr> <tr> <td>Screen resolution</td><td>1280*720</td></tr> <tr> <td>Working temperature</td><td>-20℃~40℃</td></tr> <tr> <td>TF card capacity</td><td>Maximum 128G</td></tr> <tr> <td>Battery capacity</td><td>3000mAh</td></tr> </table> <p>(This manual is valid for the product and accessories of the registration APP and registered by the factory. Factory continues to optimize the product and accessories, so the actual parameters may be slightly different from this.)</p> <p>If you have any questions, please contact our customer service.</p>	Battery charging voltage	DC 5V	Display size	5 inch	Working current	450mA	Two way intercom	✓	Working mode	Power saving mode Normal mode	Playback	✓	Screen resolution	1280*720	Working temperature	-20℃~40℃	TF card capacity	Maximum 128G	Battery capacity	3000mAh	<div>15. FCC Statement</div> <p>1. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:</p> <p>(1)The device may not cause harmful interference.</p> <p>(2)The device must accept any interference received, including interference that may cause undesired operation.</p> <p>2. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.</p> <p>Note: This equipment has been tested and found to comply with the limits for a class B digital device, as defined by Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.</p> <p>This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:</p> <ul style="list-style-type: none"> <li>• Reorient or relocate the receiving antenna.</li> <li>• Increase the separation between the equipment and receiver.</li> <li>• Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.</li> <li>• Consult the dealer or an experienced radio/TV technician for help.</li> </ul> <p>The device has been evaluated to meet general RF exposure requirements. The device can be used in portable exposure condition without restrictions. (For product: Baby monitor display)</p> <p>The device has been evaluated to meet general RF exposure requirements. The equipment should be installed and operated with a minimum distance of 20 cm between the radiator and your body. (For product: Baby monitor camera)</p>	<div>16. FCC Statement</div> <p>1. This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:</p> <p>(1)The device may not cause harmful interference.</p> <p>(2)The device must accept any interference received, including interference that may cause undesired operation.</p> <p>2. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.</p> <p>Note: This equipment has been tested and found to comply with the limits for a class B digital device, as defined by Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.</p> <p>This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:</p> <ul style="list-style-type: none"> <li>• Reorient or relocate the receiving antenna.</li> <li>• Increase the separation between the equipment and receiver.</li> <li>• Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.</li> <li>• Consult the dealer or an experienced radio/TV technician for help.</li> </ul> <p>The device has been evaluated to meet general RF exposure requirements. The device can be used in portable exposure condition without restrictions. (For product: Baby monitor display)</p> <p>The device has been evaluated to meet general RF exposure requirements. The equipment should be installed and operated with a minimum distance of 20 cm between the radiator and your body. (For product: Baby monitor camera)</p>
Power consumption	Working: 330mA																																										
Temperature and humidity detection range	Temperature: -35℃~40℃ Humidity: 5%-95%RH																																										
Rotation angle	Vertical 45° Horizontal 355°																																										
IR	2K																																										
Lens angle	100°																																										
Night vision light source	940nm infrared lamp																																										
Baby call	✓																																										
Motion detection	Support region detection																																										
Working temperature	-20℃~40℃																																										
Working humidity	<95%																																										
Battery charging voltage	DC 5V																																										
Display size	5 inch																																										
Working current	450mA																																										
Two way intercom	✓																																										
Working mode	Power saving mode Normal mode																																										
Playback	✓																																										
Screen resolution	1280*720																																										
Working temperature	-20℃~40℃																																										
TF card capacity	Maximum 128G																																										
Battery capacity	3000mAh																																										