



FCC AND ISED CERTIFICATION TEST REPORT

Applicant	:	Ultranik Intelligent Technology Co.Ltd
Address of Applicant	:	No.1 plant ,Tangbeiyuan village group, Dushi Village, Pingtan Town, Huiyang District, Huizhou , Guangdong ,China
Manufacturer	:	Ultranik Intelligent Technology Co.Ltd
Address of Manufacturer	:	No.1 plant ,Tangbeiyuan village group, Dushi Village, Pingtan Town, Huiyang District, Huizhou , Guangdong ,China
Equipment under Test	:	motion sensor
Model No.	:	UM01/FU, UM01
FCC ID	:	2BHEYUM01
IC	:	32731-UM01
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C. RSS-210 Issue 11 June 2024 ANSI C63.10:2013. RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021)
Report No.	:	DDT-RE24052715-1E01
Issue Date	:	2024/07/09
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	5
2.	General Test Information.....	6
2.1.	Description of EUT.....	6
2.2.	Accessories of EUT	6
2.3.	Assistant equipment used for test	6
2.4.	Block diagram of EUT configuration for test.....	6
2.5.	Deviations of test standard	7
2.6.	Test environment conditions.....	7
2.7.	Test laboratory	7
2.8.	Measurement uncertainty	8
3.	20dB Bandwidth and 99% Bandwidth	9
3.1.	Block diagram of test setup	9
3.2.	Limits.....	9
3.3.	Test procedure.....	9
3.4.	Test result	9
4.	Radiated Emission	10
4.1.	Test equipment	10
4.2.	Block diagram of test setup	11
4.3.	Limits.....	12
4.4.	Assistant equipment used for test	14
4.5.	Test procedure.....	14
4.6.	Test result	15
4.7.	Test data	17
5.	Power Line Conducted Emissions.....	21
5.1.	Test equipment	21
5.2.	Block diagram of test setup	21
5.3.	Limits.....	21
5.4.	Assistant equipment used for test	21
5.5.	Test procedure.....	22
5.6.	Test result	22
5.7.	Test data	23
6.	Test Setup Photograph.....	25
7.	Photos of the EUT	27

Test Report Declare

Applicant	:	Ultranik Intelligent Technology Co.Ltd
Address of Applicant	:	No.1 plant ,Tangbeiyuan village group, Dushi Village, Pingtan Town, Huiyang District, Huizhou , Guangdong ,China
Equipment under Test	:	motion sensor
Model No.	:	UM01/FU, UM01
Manufacturer	:	Ultranik Intelligent Technology Co.Ltd
Address of Manufacturer	:	No.1 plant ,Tangbeiyuan village group, Dushi Village, Pingtan Town, Huiyang District, Huizhou , Guangdong ,China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C.

RSS-210 Issue 11 June 2024

ANSI C63.10:2013.

RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021)

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24052715-1E01		
Date of Receipt:	2024/06/19	Date of Test:	2024/06/19~2024/07/09

Prepared By:

Tiger Mo/Engineer

Approved By:

Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/07/09	

1. Summary of Test Results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
20dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.215 ANSI C63.10:2013 RSS-210 Issue 11 RSS-Gen Issue 5	Pass
Radiated Emission	FCC Part 15: 15.205 FCC Part 15: 15.209 FCC Part 15: 15.249 ANSI C63.10:2013 RSS-210 Issue 11 RSS-Gen Issue 5	Pass
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10:2013 RSS-210 Issue 11 RSS-Gen Issue 5	Pass
Antenna requirement	FCC Part 15: 15.203 RSS-210 Issue 11 RSS-Gen Issue 5	Pass

Note: N/A is an abbreviation for Not Applicable.

2. General Test Information

2.1. Description of EUT

EUT Name	: motion sensor
Model Number	: UM01/FU, UM01
Difference of model number	: Above models are identical in schematic, appearance and structure, only the Model Number and Power Supply different for all the models, the UM01/FU Power Supply 120-277V, the UM01 Power Supply 120V therefore the test performed on the model UM01/FU.
EUT Function Description	: Please reference user manual of this device
Power Supply	: 120-277V, 50/60Hz
Operation frequency	: 5725MHz-5875MHz
Modulation	: Doppler
Antenna Gain	: Internal Antenna, maximum PK gain: 0 dBi

Note 1: EUT is the abbreviation of equipment under test.

Note 2: “☒” means to be chosen or applicable; “☐” means don’t to be chosen or not applicable; This note applies to entire report.

Note3: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.


2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
N/A	N/A	N/A	N/A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Serial No.	Other
Power cable	N/A	N/A	N/A	N/A

2.4. Block diagram of EUT configuration for test



2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to 106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118


2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz \leq f < 3.6 GHz); 1.38 dB (3.6 GHz \leq f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz \leq f < 3.6 GHz); 1.38 dB (3.6 GHz \leq f < 8 GHz)
Frequencies Stability	6.7×10^{-8} (Antenna couple method) 5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB (10 MHz \leq f < 3.6 GHz); 1.40 dB (3.6 GHz \leq f < 8 GHz) 1.66 dB (8 GHz \leq f < 26.5 GHz)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz) 4.40 dB (6 GHz - 18 GHz) 3.54 dB (18 GHz - 26 GHz) 4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz) 3.72dB (9KHz-150KHz)

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. 20dB Bandwidth and 99% Bandwidth

3.1. Block diagram of test setup



3.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

3.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, measure the 20 dB bandwidth of signal.

3.4. Test result



Mode	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)	Conclusion
Doppler	119.54	127.88	/	PASS


4. Radiated Emission

4.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2024/07/14
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200A	DDT-ZC01401	2024/09/20
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2024/07/11
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2025/09/18
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22

4.2. Block diagram of test setup





4.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dB(mV)/m (Peak) 54.0 dB(mV)/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit3m(dBuV/m)} = \text{Limit30m(dBuV/m)} + 40\log(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

4.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

4.5. Test procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.
- (2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According ANSI C63.10:2013 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

- (3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

- (a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)
- (b) Change work frequency or channel of device if practicable.
- (c) Change modulation type of device if practicable.
- (d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2013 clause 4.1.4.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 40 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) 30 MHz ~ 40 GHz: (Scan with all mode, the worst case is record and report)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with the worst mode.

4.6. Test result

PASS. (See below detailed test result)

Field Strength of the Fundamental Signal

Freq. [MHz]	Reading [dB μ V/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Detector	Polarity
5797.678	61.05	34.19	5.91	-39.98	61.17	94.00	32.83	PK	Horizontal
5797.560	58.00	34.19	5.91	-39.98	58.12	94.00	35.88	PK	Vertical
Result: Pass									

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

4.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-06-28

Tested By: Genliu

EUT: motion sensor

Model Number: UM01/FU

Test Mode: 5.8G radar


Power Supply: AC 120V/60Hz

Condition: Temp:21.9°C;Humi:60.0%

Test Site: DDT 3# Chamber

File Path: d:\ts\2024 report data\Q24052715-1E\FCC BELOW 1G\20240628-090623_H

Memo:



Data List										
NO.	Freq. [MHz]	Reading [dB μ V/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Detector	Polarity
1	31.399	40.76	10.28	3.77	-30.98	23.83	40.00	16.17	QP	Horizontal
2	54.445	36.7	12.48	3.92	-30.67	22.43	40.00	17.57	QP	Horizontal
3	119.991	26.78	10.00	4.33	-30.84	10.27	43.50	33.23	QP	Horizontal
4	294.599	39.65	12.74	5.20	-30.32	27.27	46.00	18.73	QP	Horizontal
5	441.505	24.3	16.01	5.78	-30.02	16.07	46.00	29.93	QP	Horizontal
6	584.033	30.39	18.44	6.31	-29.90	25.24	46.00	20.76	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-06-28

Tested By: Genliu

EUT: motion sensor

Model Number: UM01/FU

Test Mode: 5.8G radar


Power Supply: AC 120V/60Hz

Condition: Temp:21.9°C;Humi:60.0%

Test Site: DDT 3# Chamber

File Path: d:\ts\2024 report data\Q24052715-1E\FCC BELOW 1G\20240628-090704_V

Memo:



Data List											
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	AMP [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	38.668	27.59	11.47	3.81	-30.87	12.00	40.00	28.00	QP	Vertical	
2	44.928	27.81	13.19	3.85	-30.78	14.07	40.00	25.93	QP	Vertical	
3	71.971	37.78	9.60	4.03	-30.55	20.86	40.00	19.14	QP	Vertical	
4	119.991	33.02	10.00	4.33	-30.84	16.51	43.50	26.99	QP	Vertical	
5	197.818	28.8	10.48	4.75	-30.61	13.42	43.50	30.08	QP	Vertical	
6	486.361	40.96	16.42	5.95	-29.93	33.40	46.00	12.60	QP	Vertical	

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-06-28

Tested By: Genliu

EUT: motion sensor

Model Number: UM01/FU

Test Mode: 5.8G radar

Power Supply: AC 120V/60Hz


Condition: Temp:21.9°C;Humi:60.0%

Test Site: DDT 3# Chamber

File Path: d:\ts\2024 report data\Q24052715-1E\FCC ABOVE 1G\1

Memo:

Test Graph



Data List

N.O.	Freq. [MHz]	Reading [dB μ V/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Detector	Polarity
1	1136.000	45.65	24.72	3.10	-36.90	36.57	74.00	37.43	PK	Horizontal
2	1406.300	45.98	25.13	3.57	-36.93	37.75	74.00	36.25	PK	Horizontal
3	3789.700	46.69	30.66	5.09	-40.32	42.12	74.00	31.88	PK	Horizontal
4	4782.500	45.67	32.43	5.52	-40.16	43.46	74.00	30.54	PK	Horizontal
5	11157.500	41.60	39.24	8.23	-39.16	49.91	74.00	24.09	PK	Horizontal
6	15740.700	39.16	38.42	9.98	-39.20	48.36	74.00	25.64	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2024-06-28

Tested By: Genliu

EUT: motion sensor

Model Number: UM01/FU

Test Mode: 5.8G radar

Power Supply: AC 120V/60Hz


Condition: Temp:21.9°C;Humi:60.0%

Test Site: DDT 3# Chamber

File Path: d:\ts\2024 report data\Q24052715-1E\FCC ABOVE 1G\2

Memo:

Test Graph



Data List											
N.O.	Freq. [MHz]	Reading [dB μ V/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dB μ V/m]	Limit [dB μ V/m]	Margin [dB]	Detector	Polarity	
1	1056.100	46.39	24.41	2.97	-36.89	36.88	74.00	37.12	PK	Vertical	
2	1506.600	45.96	25.41	3.74	-36.95	38.16	74.00	35.84	PK	Vertical	
3	4138.200	45.94	31.18	5.13	-40.40	41.85	74.00	32.15	PK	Vertical	
4	4563.200	45.70	31.90	5.39	-40.24	42.75	74.00	31.25	PK	Vertical	
5	11392.100	41.83	39.29	8.38	-39.27	50.23	74.00	23.77	PK	Vertical	
6	15937.900	39.84	38.06	10.11	-39.32	48.69	74.00	25.31	PK	Vertical	

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

5. Power Line Conducted Emissions

5.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Two Line V-Network	R&S	ENV216	DDT-ZC02059	2024/07/11
EMI Test Receiver	R&S	ESCI/E3	DDT-ZC01297	2024/07/11
Δ-shaped artificial power network	SCHWARZBEC K	PVDC 8301	DDT-ZC03939	2025/03/31
Two Line V-Network	R&S	ENV216	DDT-ZC02056	2024/07/11
Conducted Radiated Software	Audix	E3	DDT-ZC00562	/
Three-phase artificial power network	SCHWARZBEC K	NSLK 8163	DDT-ZC01572	2024/07/11
RF Cable	Yuhu Technology	Z806-NJ-NJ-6M	DDT-ZC02004	2024/07/14
Pulse Limiter	SCHWARZBEC K	VTSD 9561	DDT-ZC02128	2024/07/14

5.2. Block diagram of test setup



5.3. Limits

Frequency	Quasi-Peak Level dB(mV)	Average Level dB(mV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

5.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

5.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

5.6. Test result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “—” means Peak detection; “—” means Average detection.


Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.

5.7. Test data

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 6# Shield Room	D:\2024 Report Date\Q24052715-1E\0626 CE.EM6
Test Date	: 2024-06-26	Tested By : Genliu
EUT	: motion sensor	Model Number : UM01/FU
Power Supply	: AC 120V/60Hz	Test Mode : 5.8G SRD mode
Condition	: Temp:21.5°C,Humi:51.8%	LISN : 2023 ENV 216 3#/NEUTRAL
Memo	:	

Data: 2



Item (Mark)	Freq. (MHz)	Read Level (dB μ V)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dB μ V)	Limit Line (dB μ V)	Over Limit (dB)	Detector	Phase
1	0.24	8.03	9.84	0.11	9.95	27.93	62.17	-34.24	QP	NEUTRAL
2	0.24	-7.54	9.84	0.11	9.95	12.36	52.17	-39.81	Average	NEUTRAL
3	0.61	-3.77	9.75	0.14	9.96	16.08	56.00	-39.92	QP	NEUTRAL
4	0.61	-10.03	9.75	0.14	9.96	9.82	46.00	-36.18	Average	NEUTRAL
5	0.83	20.41	9.98	0.19	9.97	40.55	56.00	-15.45	QP	NEUTRAL
6	0.83	-8.70	9.98	0.19	9.97	11.44	46.00	-34.56	Average	NEUTRAL
7	0.91	17.41	10.03	0.22	9.97	37.63	56.00	-18.37	QP	NEUTRAL
8	0.91	-7.84	10.03	0.22	9.97	12.38	46.00	-33.62	Average	NEUTRAL
9	1.23	3.27	9.55	0.25	9.98	23.05	56.00	-32.95	QP	NEUTRAL
10	1.23	-4.63	9.55	0.25	9.98	15.15	46.00	-30.85	Average	NEUTRAL
11	7.29	-0.74	9.80	0.28	10.03	19.37	60.00	-40.63	QP	NEUTRAL
12	7.29	-13.84	9.80	0.28	10.03	6.27	50.00	-43.73	Average	NEUTRAL

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 6# Shield Room **Tested By** : Genliu
Test Date : 2024-06-26 **Model Number** : UM01/FU
EUT : motion sensor **Test Mode** : 5.8G SRD mode
Power Supply : AC 120V/60Hz **LISN** : 2023 ENV 216 3#/LINE
Condition : Temp:21.5°C,Humi:51.8%
Memo :

Data: 4



Item (Mark)	Freq. (MHz)	Read Level (dB μ V)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dB μ V)	Limit Line (dB μ V)	Over Limit (dB)	Detector	Phase
1	0.15	29.92	9.80	0.10	9.94	49.76	65.74	-15.98	QP	LINE
2	0.15	0.86	9.80	0.10	9.94	20.70	55.74	-35.04	Average	LINE
3	0.68	18.36	9.59	0.14	9.96	38.05	56.00	-17.95	QP	LINE
4	0.68	-10.82	9.59	0.14	9.96	8.87	46.00	-37.13	Average	LINE
5	1.03	12.00	9.66	0.25	9.97	31.88	56.00	-24.12	QP	LINE
6	1.03	-12.90	9.66	0.25	9.97	6.98	46.00	-39.02	Average	LINE
7	2.00	7.62	9.86	0.26	9.99	27.73	56.00	-28.27	QP	LINE
8	2.00	-13.60	9.86	0.26	9.99	6.51	46.00	-39.49	Average	LINE
9	3.17	-2.20	9.62	0.27	10.01	17.70	56.00	-38.30	QP	LINE
10	3.17	-16.60	9.62	0.27	10.01	3.30	46.00	-42.70	Average	LINE
11	5.84	-5.22	9.78	0.27	10.02	14.85	60.00	-45.15	QP	LINE
12	5.84	-12.56	9.78	0.27	10.02	7.51	50.00	-42.49	Average	LINE

- Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

7. Photos of the EUT

Please refer to DDT-Q24052715-1E appendix I

-----End Report-----