

# Test Report

Verified code: 138075

Report No.: E20240527499701-3

Customer: Nanjing Mindray Bio-Medical Electronics Co., Ltd.

Address: 666 Middle Zhengfang Road, Jiangning, 211111 Nanjing, Jiangsu, China

Sample Name: Mobile Charging Station

Sample Model: MCSU-III

Receive Sample Date: 2024-06-13

Test Date: 2024-06-26 ~ 2024-06-26

Reference Document: CFR47 FCC Part 1: Subpart I Section 1.1310  
CFR47 FCC Part 1: Subpart I Section 1.1307

Test Result: Pass

Prepared by: Wen Wenwen  
Wen WenwenReviewed by: Wu Haoting  
Wu HaotingApproved by: Xiao Liang  
Xiao Liang

GRG METROLOGY &amp; TEST GROUP CO., LTD.

Issued Date: 2024-08-19

GRG METROLOGY &amp; TEST GROUP CO., LTD.

Address: No.163, Pingyun Road, West of Huangpu Avenue, Guangzhou, Guangdong, China  
Tel: (+86) 400-602-0999 FAX: (+86) 020-38698685 Web: <http://www.grgtest.com>

## Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. This testing report is only for scientific research, teaching, internal quality control, etc.

—Blank space below this page—

## TABLE OF CONTENTS

1. GENERAL DESCRIPTION OF EUT .....	5
1.1 APPLICANT .....	5
1.2 MANUFACTURER .....	5
1.3 FACTORY .....	5
1.4 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST .....	5
2. LABORATORY AND MEASUREMENT UNCERTAINTY .....	7
2.1 LABORATORY .....	7
2.2 MEASUREMENT UNCERTAINTY .....	7
3. TEST MODE AND SUPPORTIVE INSTRUMENTS .....	8
3.1 TEST MODE .....	8
3.2 LOCAL SUPPORTIVE INSTRUMENTS .....	8
3.3 CONFIGURATION OF SYSTEM UNDER TEST .....	8
4. LIST OF USED TEST EQUIPMENT AT GRGT .....	10
4.1 LIST OF USED TEST EQUIPMENT .....	10
5. TECHNICAL REQUIREMENTS SPECIFICATION .....	11
5.1 TEST LIMIT .....	11
5.2 TEST PROCEDURES .....	12
5.3 TEST RESULT .....	13
6. PHOTOGRAPHS OF TEST SET-UP .....	14
7. PHOTOGRAPHS OF THE EUT .....	14

—Blank space below this page—

**REPORT ISSUED HISTORY**

Report Version	Report No.	Description	Compile Date
1.0	E20240527499701-3	Original Issue	2024-07-10

—Blank space below this page—

## 1. GENERAL DESCRIPTION OF EUT

### 1.1 APPLICANT

Name: Nanjing Mindray Bio-Medical Electronics Co., Ltd.

Address: 666 Middle Zhengfang Road, Jiangning, 211111 Nanjing, Jiangsu, China

### 1.2 MANUFACTURER

Name: Nanjing Mindray Bio-Medical Electronics Co., Ltd.

Address: 666 Middle Zhengfang Road, Jiangning, 211111 Nanjing, Jiangsu, China

### 1.3 FACTORY

Name: Nanjing Mindray Bio-Medical Electronics Co., Ltd.

Address: 666 Middle Zhengfang Road, Jiangning, 211111 Nanjing, Jiangsu, China

## 1.4 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST

Product Name: Mobile Charging Station

Product Model: MCSU-III

Adding Model: /

Trade Name: **mindray**

Input: AC 100-240V, 50/60Hz, 0.3A Max

Adapter: Output: DC 5V 2.4A

Model: MANGO12SC-05B-MR

Working frequency: 110.6kHz ~ 114.4kHz, 176.6kHz ~ 206.9kHz

FCC ID: 2BHFC-MCS3

Antenna Type: Coil Antenna

Modulation type: AM

Sample submitting way:  Provided by customer  Sampling

Sample No: E20240527499701-0001

Temperature Range: +5°C ~ +40°C

Hardware version: 3.0

Software version: 0.0

Note:

The basic description of the EUT is provided by the applicant. This report is made Solely on the basis of such data and/or information. We accept no responsibility for the authenticity and completeness of the above data and information and the validity of the results and/or conclusions.

—Blank space below this page—

## 2. LABORATORY AND MEASUREMENT UNCERTAINTY

### 2.1 LABORATORY

The tests & measurements refer to this report were performed by Shenzhen EMC Laboratory of GRG METROLOGY & TEST group CO., LTD.

Add : No.1301 Guanguang Road Xinlan Community, Guanlan Street, Longhua District  
Shenzhen, 518110, People's Republic of China

P.C. : 518110

Tel : 0755-61180008

Fax : 0755-61180008

### 2.2 MEASUREMENT UNCERTAINTY

Parameter	Worst Case Uncertainty	Max. Uncertainty
E/H-Field Level Tester	12.6%	<30%

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95%.

This uncertainty represents an expanded uncertainty factor of  $k=2$ .

—Blank space below this page—

### 3. TEST MODE AND SUPPORTIVE INSTRUMENTS

#### 3.1 TEST MODE

Mode No.	Description of the modes
Mode 1	EUT charging mode + RX load(5W)
Mode 2	EUT charging mode + V07XXU RX load
Mode 3	EUT standby mode


Note: mode 1 working frequency is 110.6kHz ~ 114.4kHz, mode 2 working frequency is 176.6kHz ~ 206.9kHz, mode 3 working frequency is 176.6kHz.

#### 3.2 LOCAL SUPPORTIVE INSTRUMENTS


No.	Name of Equipment	Manufacturer	Model	Serial Number
A	Intelligent wireless charging full function test module Load	/	/	/
B	V07XXU RX load	Nanjing Mindray Bio-Medical Electronics Co., Ltd.	/	/

#### 3.3 CONFIGURATION OF SYSTEM UNDER TEST

Mode 1:



Mode 2:



Mode 3:

EUT

—Blank space below this page—

**4. LIST OF USED TEST EQUIPMENT AT GRGT****4.1 LIST OF USED TEST EQUIPMENT**

Name of equipment	Manufacturer	Model	Serial number	Calibration due
Long, medium and short wave electromagnetic field frequency selective analyzer	narda	EHP-200A	180ZX00611	2025-06-13

Note: The calibration interval of the test instruments is 12 months.

—Blank space below this page—

## 5. TECHNICAL REQUIREMENTS SPECIFICATION

### 5.1 TEST LIMIT

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(i) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
<b>(ii) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. \* = Plane-wave equivalent power density.

The EUT does comply with requirements of KDB 680106 D01.

1)The power transfer frequency is below 1 MHz.

Yes, the operating frequency of the device is 110.6kHz ~ 114.4kHz, 176.6kHz ~ 206.9kHz.

2)The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts..

Yes, the maximum output power of the primary coil is 5W.

3)A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact).

Yes, client device is placed directly in contact with the transmitter.

4)Only § 2.1091-Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions)..

Yes, the EUT is a mobile Wireless Charger.

5)The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.

Yes, the E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit.


6)For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested..

Yes, the EUT has only one RF coil, The test is run in maximum power mode. the E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit,

## 5.2 TEST PROCEDURES

Note: Measurements should be made from all sides and the top of EUT, with the 20cm measured from the center of the probe(s) to the edge of the device and the 20cm measured from the center of the probe(s) to the top of the device. Position A is the front of the EUT, position B is the rear of the EUT, position C is the left of the EUT, position D is the right of the EUT, position E is the top of the EUT.

—Blank space below this page—



### 5.3 TEST RESULT

Date of testing:	2024-06-26
Ambient temperature:	24.6 °C
Relative humidity:	53%RH
Ambient Pressure:	101.0kPa
Test by:	Qin tingting

H-Field Strength at 20 cm from the edges surrounding the EUT and 20cm from the top surface of the EUT.

EUT Test Mode	Measured H-Field Strength Values(A/m)					50% Limit(A/m)	Limit (A/m)	Result
	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E			
Mode 1	0.4985	0.3267	0.3581	0.3127	0.1420	0.815	1.63	Pass
Mode 2	0.1978	0.1292	0.1774	0.1092	0.0841	0.815	1.63	Pass
Mode 3	0.2983	0.1280	0.1286	0.1013	0.1026	0.815	1.63	Pass

E-Field Strength at 20 cm from the edges surrounding the EUT and 20cm from the top surface of the EUT.

EUT Test Mode	Measured E-Field Strength Values(V/m)					50% Limit(V/m)	Limit (V/m)	Result
	Test Position A	Test Position B	Test Position C	Test Position D	Test Position E			
Mode 1	1.8392	3.1031	1.0286	2.2272	0.8569	307	614	Pass
Mode 2	0.6278	0.6711	0.5539	0.7753	0.5636	307	614	Pass
Mode 3	0.4823	1.3786	1.0127	0.8624	0.4853	307	614	Pass

—Blank space below this page—

## **6. PHOTOGRAPHS OF TEST SET-UP**

Please refer to the attached document E20240527499701-test setup photo.

## **7. PHOTOGRAPHS OF THE EUT**

Please refer to the attached document E20240527499701-EUT photo.

----- End of Report -----