



# RF EXPOSURE EVALUATION REPORT

**FCC ID** : 2BHFNHESTIAA1  
**Equipment** : NTN Dongle  
**Brand Name** : APAL  
**Model Name** : Hestia A1  
**Applicant** : Creative5 Inc.  
7F, No.300, Sec. 1, Neihu Rd., Neihu Dist.  
Taipei City, 11493, Taiwan  
**Manufacturer** : Creative5 Inc.  
7F, No.300, Sec. 1, Neihu Rd., Neihu Dist.  
Taipei City, 11493, Taiwan  
**Standard** : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.

Approved by: Cona Huang / Deputy Manager



**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



## **Table of Contents**

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....	4
2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS .....	4
3. RF EXPOSURE LIMIT INTRODUCTION .....	5
4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION .....	6
4.1. Collocated Power Density Calculation.....	6



## History of this test report



## 1. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	NTN Dongle
Brand Name	APAL
Model Name	Hestia A1
FCC ID	2BHFNHESTIAA1
Wireless Technology and Frequency Range	NTN Band 23: 2000 MHz ~ 2020 MHz NTN Band 24: 1626.5 MHz ~ 1660.5 MHz NTN Band 255: 1626.5 MHz ~ 1660.5 MHz
Mode	BPSK, QPSK
HW Version	V1.0
EUT Stage	Identical Prototype

Reviewed by: Jason Wang

Report Producer: Carlie Tsai

## 2. Maximum RF average output power among production units

Mode		Maximum Average power(dBm)
NTN	Band 23	25
	Band 24	25
	Band 255	25



### 3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



## **4. Radio Frequency Radiation Exposure Evaluation**

### **4.1. Collocated Power Density Calculation**

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum PG (mW)	Power Density at 20cm (mW/cm^2)	Limit (mW/cm^2)
NTN Band 23	5.482	25.000	1117.378	0.222	1.000
NTN Band 24	2.998	25.000	630.667	0.126	1.000
NTN Band 255	2.998	25.000	630.667	0.126	1.000

### **Conclusion:**

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.