



Solutions

**FCC 47 CFR PART 15 SUBPART C
ISED RSS-247 ISSUE 3**

TEST REPORT

For

Wired Security Camera

FCC MODEL NUMBER: P320 Pro

**FCC SERIES MODEL NUMBER:
P320 XXX XXX (where X may be 0-9 A-Z a-z or blank)**

IC MODEL NUMBER: P320 Pro

PROJECT NUMBER: 4791739259.1

REPORT NUMBER: 4791739259.1-1

FCC ID: 2BHG-0235CADY

IC: 32743-0235CADY

ISSUE DATE: Jul. 04, 2025

Prepared for

KeyLife International Technology Limited

Prepared by

**UL-CCIC COMPANY LIMITED
No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China
Tel: +86 512-6808 6400
Fax: +86 512-6808 4099
Website: www.ul.com**

Form-ULID-008536-14 V5.0

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	07/04/2025	Initial Issue	

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	7
4.2. <i>MEASUREMENT UNCERTAINTY</i>	7
5. EQUIPMENT UNDER TEST	8
5.1. <i>DESCRIPTION OF EUT</i>	8
5.2. <i>MAXIMUM OUTPUT POWER</i>	9
5.3. <i>CHANNEL LIST</i>	9
5.4. <i>TEST CHANNEL CONFIGURATION</i>	9
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER</i>	9
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	10
5.7. <i>THE WORSE CASE CONFIGURATIONS</i>	10
5.8. <i>TEST ENVIRONMENT</i>	10
5.9. <i>DESCRIPTION OF TEST SETUP</i>	11
5.10. <i>MEASURING INSTRUMENT AND SOFTWARE USED</i>	13
6. MEASUREMENT METHODS	14
7. ANTENNA PORT TEST RESULTS	15
7.1. <i>ON TIME AND DUTY CYCLE</i>	15
7.2. <i>6 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH</i>	17
7.3. <i>CONDUCTED OUTPUT POWER</i>	25
7.4. <i>POWER SPECTRAL DENSITY</i>	27
7.5. <i>CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS</i>	32
8. RADIATED TEST RESULTS.....	47
8.1. <i>LIMITS AND PROCEDURE</i>	47
8.2. <i>TEST ENVIRONMENT</i>	54
8.3. <i>RESTRICTED BANDEDGE</i>	54
8.4. <i>SPURIOUS EMISSIONS</i>	63
9. AC POWER LINE CONDUCTED EMISSIONS	95
10. ANTENNA REQUIREMENTS.....	98

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: KeyLife International Technology Limited
Address: Workshop 7, 6th Floor Core 45, No. 43 Tsun Yip Street, Kowloon, HONG KONG

Manufacturer Information

Company Name: KeyLife International Technology Limited
Address: Workshop 7, 6th Floor Core 45, No. 43 Tsun Yip Street, Kowloon, HONG KONG

EUT Description

Product Name: Wired Security Camera
FCC Model Number: P320 Pro
FCC Series Model Number: P320 XXX XXX (where X may be 0-9 A-Z a-z or blank)
Model Difference: All the models have the same technical construction, including circuit diagram, PCB layout, components, and component layout. The only difference is the model numbers, which represent different platforms, countries, channels, functions, and configurations, and have no effect on EMC performance.
IC Model Number: P320 Pro
Sample Number: 8487508
Data of Receipt Sample: May. 21, 2025
Test Date: May. 21, 2025~ Jul. 04, 2025

APPLICABLE STANDARDS

STANDARD

TEST RESULTS

CFR 47 Part 15 Subpart C
ISED RSS-247 Issue 3
ISED RSS-GEN Issue 5

PASS

Summary of Test Results			
Clause	Test Items	FCC&ISED Rules	Test Results
1	6 dB Bandwidth and 99% Occupied Bandwidth	FCC 15.247 (a) (2) RSS-247 Clause 5.2 (a) RSS-Gen Clause 6.7	PASS
2	Conducted Power	FCC 15.247 (b) (3) RSS-247 Clause 5.4 (d) RSS-Gen Clause 6.12	PASS
3	Power Spectral Density	FCC 15.247 (e) RSS-247 Clause 5.2 (b)	PASS
4	Conducted Band edge And Spurious emission	FCC 15.247 (d) RSS-247 Clause 5.5 RSS-GEN Clause 6.13	PASS
5	Radiated Band edges and Spurious emission	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 6.13 RSS-GEN Clause 8.9 RSS-GEN Clause 8.10	PASS
6	Conducted Emission Test for AC Power Port	FCC 15.207 RSS-GEN Clause 8.8	PASS
7	Antenna Requirement	FCC 15.203 RSS-GEN Clause 6.8	PASS

Note:
The measurement result for the sample received is < Pass > according to < ANSI C63.10-2013, FCC CFR 47 Part 2, FCC CFR 47 Part 15C, RSS-GEN, RSS-247 > when < Simple Acceptance > decision rule is applied.

Prepared By:

Tom Tang

Tom Tang

Reviewed By:

Emily Wang

Emily Wang

Authorized By:

Kevin Shen

Kevin Shen

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, FCC 47 CFR Part 2, FCC 47 CFR Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 3 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p> <p>IC (IC Designation No.: 25056; CAB No.: CN0073) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.</p>
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.1dB
DTS Bandwidth	1.9%
Maximum Conducted Output Power	1.3dB
Maximum Power Spectral Density Level	1.5dB
Band-edge Compliance	1.9%
Unwanted Emissions in Non-restricted Freq Bands	9kHz-30MHz: ± 0.90 dB 30MHz-1GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.9 dB 12.75GHz-26.5GHz: ± 2.1 dB
Radiation Emission test (include Fundamental emission) (9kHz-30MHz)	3.4dB
Radiation Emission test (include Fundamental emission) (30MHz-1GHz)	3.4dB
Radiation Emission test (1GHz to 26GHz) (include Fundamental emission)	3.5dB (1GHz-18GHz) 3.9dB (18GHz-26.5GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

Equipment:	Wired Security Camera	
Model Name:	P320 Pro	
Technology:	Bluetooth - Low Energy	
Transmit Frequency Range:	2402 MHz ~ 2480 MHz	
Modulation:	GFSK	
Data Rate:	LE 1M	1 Mbps
	LE 2M	2 Mbps
Test Software of EUT:	SecureCRT (manufacturer declare)	
Antenna Type:	FPC Antenna	
Antenna Gain:	3.40 dBi	
	Note: This data is provided by customer and our lab isn't responsible for this data.	

5.2. MAXIMUM OUTPUT POWER

Bluetooth Mode	Frequency (MHz)	Channel Number	Max Output Power(dBm)
BLE 1M	2402-2480	0-39[40]	2.59
BLE 2M	2402-2480	0-39[40]	2.46

5.3. CHANNEL LIST

Channel	Frequency (MHz)						
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel		Frequency
GFSK	Low Channel	CH 0	2402MHz
	Middle Channel	CH 19	2440MHz
	High Channel	CH 39	2480MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		SecureCRT		
Modulation Type	Transmit Antenna Number	Test Channel		
		LCH	MCH	HCH
GFSK	1	default	default	default

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Ant.	Frequency (MHz)	Antenna Type	Antenna Gain (dBi)
1	2400-2483.5	FPC Antenna	3.40 dBi

Note: This data is provided by customer and our lab isn't responsible for this data.

Test Mode	Transmit and Receive Mode	Description
BLE 1M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.
BLE 2M	<input checked="" type="checkbox"/> 1TX, 1RX	Antenna1 can be used as transmitting/receiving antenna independently.

5.7. THE WORSE CASE CONFIGURATIONS

For BLE module, the product only supports 1 Mbps and 2 Mbps, both the two data rate were tested and the test result was recorded in this report.

5.8. TEST ENVIRONMENT

Environment Parameter	Selected Values During Tests	
Relative Humidity	55 ~ 65%	
Atmospheric Pressure:	101kPa	
Temperature	TN	23 ~ 28°C
Voltage:	VL	N/A
	VN	AC 120V
	VH	N/A

Note: VL= Lower Extreme Test Voltage

VN= Nominal Voltage

VH= Upper Extreme Test Voltage

TN= Normal Temperature

5.9. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Description
1	Laptop	ThinkPad	E590	/

I/O PORT


Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	USB-TTL	USB	100cm Length	/

ACCESSORY

Item	Accessory	Brand Name	Model Name	Description
1	AC/DC ADAPTOR	Dachuan	DCT24W120150US-A3	Input: 100-240V~, 50/60Hz 0.7A max Output: 12.0V=1.5A

TEST SETUP

The EUT can work in an engineer mode with a software through a laptop.

SETUP DIAGRAM FOR TESTS

5.10. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions Test (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI Test Receiver	R&S	ESR3	126700	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Two-Line V-Network	R&S	ENV216	126701	2023-11-25	2024-11-02	2025-11-01
Conducted Emissions Test (Software)							
Used	Description		Manufacturer	Name		Version	
<input checked="" type="checkbox"/>	Software for Conducted Emissions Test		R&S	EMC32		9.25.00	
Radiated Emissions Test (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	EMI test receiver	R&S	ESR7	222993	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	EMI test receiver	R&S	ESR26	126703	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Spectrum Analyzer	R&S	FSV3044	222992	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Receiver Antenna (9kHz-30MHz)	Schwarzbeck	FMZB 1513	155456	2021-06-03	2024-05-27	2027-05-26
<input checked="" type="checkbox"/>	Receiver Antenna (30MHz-1GHz)	Schwarzbeck	VULB 9168	171952	2021-07-05	2024-07-04	2027-07-03
<input checked="" type="checkbox"/>	Receiver Antenna (1GHz-18GHz)	R&S	HF907	126705	2022-02-28	2025-02-17	2028-02-16
<input checked="" type="checkbox"/>	Receiver Antenna (18GHz-26.5GHz)	Schwarzbeck	BBHA9170	126706	2022-02-28	2025-02-17	2028-02-16
<input checked="" type="checkbox"/>	Pre-amplification (To 18GHz)	Tonscned	TAP01018050	224539	2023-10-10	2024-10-10	2025-10-09
<input checked="" type="checkbox"/>	Pre-amplification (To 18GHz)	R&S	SCU-18D	134667	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Pre-amplification (To 26.5GHz)	R&S	SCU-26D	135391	2023-11-25	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	Band Reject Filter	Wainwright	WRCGV12-2375-2400-2485-2510-40SS	1	2023-12-18	2024-11-02	2025-11-01
<input checked="" type="checkbox"/>	High Pass Filter	COM-MW	ZBF13-3-18G-01	2	2023-12-18	2024-11-02	2025-11-01
Radiated Emissions Test (Software)							
Used	Description		Manufacturer	Name		Version	
<input checked="" type="checkbox"/>	Software for Radiated Emissions Test		Tonscend	JS32-RE		5.0.0.2	
Antenna Port Test (Instrument)							
Used	Equipment	Manufacturer	Model No.	Serial No.	Upper Last Cal.	Last Cal.	Next Cal.
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9010B	155368	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Power Meter	MWT	MW100-RFCB	221694	2024-03-23	2025-03-15	2026-03-14
<input checked="" type="checkbox"/>	Power Meter	Anritsu	MA24406A	12896	2024-03-23	2025-03-15	2026-03-14
Antenna Port Test (Software)							
Used	Description		Manufacturer	Name		Version	
<input checked="" type="checkbox"/>	Software for Antenna Port Test		Tonscend	JS1120-3 Test System		V3.2.22	

6. MEASUREMENT METHODS

No.	Test Item	KDB Name	Section
1	6 dB Bandwidth and 99% Occupied Bandwidth	KDB 558074 D01 15.247 Meas Guidance v05r02	8.2
2	Output Power	KDB 558074 D01 15.247 Meas Guidance v05r02	8.3.1.3 (11.9.1.3 PKPM1 Peak power meter method of ANSI C63.10)
3	Power Spectral Density	KDB 558074 D01 15.247 Meas Guidance v05r02	8.4 (11.10.2 Method PKPSD of ANSI C63.10)
4	Out-of-band emissions in non-restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.5
5	Out-of-band emissions in restricted bands	KDB 558074 D01 15.247 Meas Guidance v05r02	8.6
6	Band-edge	KDB 558074 D01 15.247 Meas Guidance v05r02	8.7
7	Conducted Emission Test for AC Power Port	ANSI C63.10-2013	6.2

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only

PROCEDURE

FCC KDB 558074 Zero-Span Spectrum Analyzer Method

TEST SETUP



TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

TEST RESULTS TABLE



Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (db)	1/T Minimum VBW (kHz)	Final VBW (kHz)
BLE 1M	2.12	2.50	0.8480	84.80%	1.18	0.47	0.5
BLE 2M	1.07	1.88	0.5691	56.91%	1.78	0.93	1.0

Note: 1) Duty Cycle Correction Factor=10log(1/x).

2) Where: x is Duty Cycle (Linear)

3) Where: T is On Time (transmit duration)

TEST GRAPHS



7.2. 6 dB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 47 CFR 15.247(a)(2) ISED RSS-247 5.2 (a)	6dB Bandwidth	>= 500kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99% Occupied Bandwidth	For reporting purposes only	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Frequency Span	Peak
Detector	For 6 dB Bandwidth: 100 kHz For 99% Occupied Bandwidth: 1% to 5% of the occupied bandwidth
RBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99% Occupied Bandwidth: $\geq 3 \times$ RBW
VBW	Max hold
Trace	Max hold
Sweep	Auto couple

- Use the 99% power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
- Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

TEST RESULTS TABLE



Test Mode	Test Channel	6dB bandwidth (MHz)	99% bandwidth (MHz)	Result
BLE 1M	LCH	0.676	1.0167	Pass
	MCH	0.676	1.0168	Pass
	HCH	0.672	1.0175	Pass
BLE 2M	LCH	1.248	2.0449	Pass
	MCH	1.256	2.0461	Pass
	HCH	1.252	2.0480	Pass



TEST GRAPHS

6dB Bandwidth


Test Mode	Test Channel	Verdict
BLE 1M	LCH	PASS
		


Test Mode	Test Channel	Verdict
BLE 1M	MCH	PASS
		








99% Bandwidth

Test Mode	Test Channel	Verdict
BLE 1M	LCH	PASS
 <p>LCH</p> <p>Test Mode: BLE 1M</p> <p>Test Channel: LCH</p> <p>Verdict: PASS</p> <p>Test Metrics:</p> <ul style="list-style-type: none"> Center Frequency: 2.40200000 GHz Span: 4.0000 MHz CF Step: 400.000 kHz Freq Offset: 0 Hz Occupied Bandwidth: 1.0167 MHz Total Power: 9.02 dBm Transmit Freq Error: -772 Hz dB Bandwidth: 1.263 MHz % of OBW Power: 99.00 % x dB: -26.00 dB 		

Test Mode	Test Channel	Verdict
BLE 1M	MCH	PASS
 <p>MCH</p> <p>Test Mode: BLE 1M</p> <p>Test Channel: MCH</p> <p>Verdict: PASS</p> <p>Test Metrics:</p> <ul style="list-style-type: none"> Center Frequency: 2.44000000 GHz Span: 4.0000 MHz CF Step: 400.000 kHz Freq Offset: 0 Hz Occupied Bandwidth: 1.0168 MHz Total Power: 9.17 dBm Transmit Freq Error: -1.886 kHz dB Bandwidth: 1.261 MHz % of OBW Power: 99.00 % x dB: -26.00 dB 		





7.3. CONDUCTED OUTPUT POWER

LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.247(b)(3) ISED RSS-247 5.4 (d) RSS-Gen Clause 6.12	Output Power	1 watt or 30dBm	2400-2483.5

TEST PROCEDURE

Place the EUT on the table and set it in the transmitting mode.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.


Measure the power of each channel.

PK Detector used for PK result.

TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

TEST SETUP



TEST RESULTS TABLE

Test Mode	Test Channel	Maximum Conducted Output Power (PK)		LIMIT
		dBm	dBm	
BLE 1M	LCH	2.40		30
	MCH	2.59		30
	HCH	2.21		30
BLE 2M	LCH	2.27		30
	MCH	2.46		30
	HCH	2.09		30

7.4. POWER SPECTRAL DENSITY

LIMITS

FCC Part15 (15.247), Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm/3 kHz	2400-2483.5

TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

TEST SETUP



TEST RESULTS TABLE

Test Mode	Test Channel	Maximum Peak power spectral density (dBm/30kHz)	Result
BLE 1M	LCH	-1.85	Pass
	MCH	-1.70	Pass
	HCH	-1.94	Pass
BLE 2M	LCH	-5.54	Pass
	MCH	-5.37	Pass
	HCH	-5.68	Pass

TEST GRAPHS


Test Mode	Test Channel	Verdict
BLE 1M	MCH	PASS
		

Test Mode	Test Channel	Verdict
BLE 1M	HCH	PASS
		

Test Mode	Test Channel	Verdict
BLE 2M	LCH	PASS
 <p>Detailed description: This screenshot shows a Keysight Spectrum Analyzer interface. The main display shows a spectrum plot with a single peak labeled '1'. The plot has a logarithmic y-axis ranging from -80 to 0 dB. The x-axis shows frequency in GHz. The center frequency is set to 2.4020000 GHz, with a span of 1.872 MHz and a video bandwidth of 100 kHz. The measurement is taken over a 2.00 ms sweep with 1001 points. The reference level is 10.00 dBm, and the offset is 8.15 dB. The signal power is -5.54 dBm. The right side of the screen displays a vertical stack of control buttons for frequency, center frequency, span, and other settings, with 'AUTO TUNE' highlighted.</p>		

Test Mode	Test Channel	Verdict
BLE 2M	MCH	PASS
 <p>Detailed description: This screenshot shows a Keysight Spectrum Analyzer interface for the MCH channel. The main display shows a spectrum plot with a single peak labeled '1'. The plot has a logarithmic y-axis ranging from -80 to 0 dB. The x-axis shows frequency in GHz. The center frequency is set to 2.4400000 GHz, with a span of 1.884 MHz and a video bandwidth of 100 kHz. The measurement is taken over a 2.00 ms sweep with 1001 points. The reference level is 10.00 dBm, and the offset is 8.23 dB. The signal power is -5.37 dBm. The right side of the screen displays a vertical stack of control buttons for frequency, center frequency, span, and other settings, with 'AUTO TUNE' highlighted.</p>		

Test Mode	Test Channel	Verdict
BLE 2M	HCH	PASS
		

7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

LIMITS

FCC Part15 (15.247), Subpart C		
Section	Test Item	Limit
FCC §15.247 (d) RSS-247 Clause 5.5 RSS-GEN Clause 6.13	Conducted Bandedge and Spurious Emissions	20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to FCC KDB 558074, connect the UUT to the spectrum analyser and use the following settings:


Center Frequency	The centre frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum PSD level.

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
measurement points	\geq span/RBW
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.

TEST SETUP



Form-ULID-008536-14 V5.0

TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V

PART 1: REFERENCE LEVEL MEASUREMENT

TEST RESULTS TABLE


Test Mode	Test Channel	Result[dBm]
BLE 1M	LCH	2.06
	MCH	2.22
	HCH	1.86
BLE 2M	LCH	0.91
	MCH	1.03
	HCH	0.68

TEST GRAPHS









PART 2: CONDUCTED BANDEDGE**TEST RESULTS TABLE**

Test Mode	Test Channel	Result	Verdict
BLE 1M	LCH	Refer to the Test Graph	PASS
	HCH	Refer to the Test Graph	PASS
BLE 2M	LCH	Refer to the Test Graph	PASS
	HCH	Refer to the Test Graph	PASS

TEST GRAPHS

Test Mode	Test Channel	Verdict
BLE 1M	LCH	PASS

Spectrum Analyzer 1
Swept SA

KEYSIGHT Input: RF Coupling: DC
RL: Align. Auto

Input Z: 50 Ω Corrections: Off
Preamp: Off

#Affen: 30 dB PNO: Fast
Gate: Off

#Avg Type: Power (RMS) 1, 2, 3, 4, 5, 6
Avg Hold: 200/200

IF Gain: Low Sig Track: Off

Trig: Free Run

PPPPPP

Frequency
Center Frequency: 2.352600000 GHz
Span: 105.000000 MHz
Sweep Span: Zero Span
Full Span
Start Freq: 2.300000000 GHz
Stop Freq: 2.405600000 GHz
AUTO TUNE
CF Step: 10.500000 MHz
Auto
Man
Freq Offset: 0 Hz
X Axis Scale: Log
Lin
Signal Track (Span Zoom)

1 Spectrum
Ref Lvl Offset: 8.15 dB
Ref Level: 20.00 dBm
Mkr5: 2.303 570 GHz, -50.05 dBm
Scale/Div: 10 dB
Start: 2.30000 GHz, Stop: 2.40500 GHz
#Video BW: 300 kHz, Sweep: 10.1 ms (1001 pts)
#Res BW: 100 kHz

5 Marker Table

Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.400 000 GHz	-50.72 dBm		
2	N	1	f	2.390 000 GHz	-51.95 dBm		
3	N	1	f	2.310 000 GHz	-54.60 dBm		
4	N	1	f	2.303 570 GHz	-50.05 dBm		
5	N	1	f	2.303 570 GHz	-50.05 dBm		
6							

Jun 26, 2025 8:05:15 PM

Test Mode	Test Channel	Verdict
BLE 1M	HCH	PASS

Spectrum Analyzer 1
Swept SA

KEYSIGHT Input: RF Coupling: DC
RL: Align. Auto
Freq Ref: Int (S)

Input Z: 50 Ω Corrections: Off
Preamp: Off
PNO: Fast
Gate: Off
IF Gain: Low
Sig Track: Off

#Aver: 30 dB
#Avg Type: Power (RMS)
Avg Hold: 200/200
Trig: Free Run

M: W W W W W
P: P P P P P

1 Spectrum
Scale/Div 10 dB
Ref Lvl Offset 8.23 dB
Ref Level 20.00 dBm
Mkr4 2.49168 GHz
-50.99 dBm



Start 2.47000 GHz #Video BW 300 kHz Stop 2.55000 GHz
#Res BW 100 kHz Sweep 7.67 ms (1001 pts)

5 Marker Table

Mode	Trace	Scale	X	Y	Function	Function Width	Function Value
1	N	1	f	2.48350 GHz	-54.07 dBm		
2	N	1	f	2.50000 GHz	-54.40 dBm		
3	N	1	f	2.49168 GHz	-50.99 dBm		
4	N	1	f	2.49168 GHz	-50.99 dBm		
5							
6							

Frequency: 2.51000000 GHz
Span: 80.0000000 MHz
Sweep Span: Zero Span
Full Span
Start Freq: 2.47000000 GHz
Stop Freq: 2.55000000 GHz
AUTO TUNE
CF Step: 8.000000 MHz
Auto: Man
Freq Offset: 0 Hz
X Axis Scale: Log
Signal Track (Span Zoom)

Jun 26, 2025 8:10:25 PM




PART 3: CONDUCTED SPURIOUS EMISSION**TEST RESULTS TABLE**



Test Mode	Test Channel	Result	Verdict
BLE 1M	LCH	Refer to the Test Graph	PASS
	MCH	Refer to the Test Graph	PASS
	HCH	Refer to the Test Graph	PASS
BLE 2M	LCH	Refer to the Test Graph	PASS
	MCH	Refer to the Test Graph	PASS
	HCH	Refer to the Test Graph	PASS

TEST GRAPHS


Test Mode	Channel	Verdict
BLE 1M	LCH	PASS




Test Mode	Channel	Verdict
BLE 1M	MCH	PASS





Test Mode	Channel	Verdict
BLE 1M	HCH	PASS





Test Mode	Channel	Verdict
BLE 2M	LCH	PASS



Test Mode	Channel	Verdict
BLE 2M	MCH	PASS



Test Mode	Channel	Verdict
BLE 2M	HCH	PASS



8. RADIATED TEST RESULTS

8.1. LIMITS AND PROCEDURE

LIMITS

Please refer to FCC §15.205 and §15.209, ISED RSS-247 Clause 5.5, ISED RSS-GEN Clause 8.9&6.13 (Transmitter)

Radiation Disturbance Test Limit for ISED (9kHz-1GHz)

Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength (μ V/m at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (μ A/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

Please refer to FCC KDB 558074

Radiation Disturbance Test Limit for FCC (Class B) (9kHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

Radiation Disturbance Test Limit for FCC (Above 1G)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

Restricted bands of operation


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

RBW	200 Hz (From 9kHz to 0.15MHz) / 9kHz (From 0.15MHz to 30MHz)
VBW	200 Hz (From 9kHz to 0.15MHz) / 9kHz (From 0.15MHz to 30MHz)
Sweep	Auto
Detector	Peak/QP/Average
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. For the actual test configuration, please refer to the related item in this test report
(Photographs of the Test Configuration)
8. The limits in FCC 47 CFR, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y - 51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1G




The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12 mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

Above 1G




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK:3 MHz AVG: See note6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 12mm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz, the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements; and 1 MHz resolution bandwidth with video bandwidth $\geq 1/T$ but not less than the setting list in section 7.1 when use peak detector, max hold to be run for at least $[50 * (1/\text{Duty Cycle})]$ traces for average measurements. For the Duty Cycle need to refer the results in section 7.1.
7. For the actual test configuration, please refer to the related item in this test report (Photographs of the Test Configuration)

X axis, Y axis, Z axis positions:



Note: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

8.2. TEST ENVIRONMENT

Temperature	22°C	Relative Humidity	56%
Atmosphere Pressure	101kPa	Test Voltage	AC 120V


8.3. RESTRICTED BANDEDGE

TEST RESULT TABLE

Test Mode	Channel	Puw(dBm)	Verdict
BLE 1M	LCH	<Limit	PASS
	HCH	<Limit	PASS
BLE 2M	LCH	<Limit	PASS
	HCH	<Limit	PASS

TEST GRAPHS

Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Horizontal	PASS




PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]				
1	2365.0894	37.16	13.60	50.76	74.00	-23.24	Horizontal
2	2390.0000	35.65	13.72	49.37	74.00	-24.63	Horizontal

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Test Mode	Channel	Polarization	Verdict
BLE 1M	LCH	Vertical	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2361.6202	37.27	13.55	50.82	74.00	-23.18	Vertical
2	2390.0000	34.49	13.72	48.21	74.00	-25.79	Vertical

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

Test Mode	Channel	Polarization	Verdict
BLE 1M	HCH	Horizontal	PASS


PK Result:

No.	Frequency	Reading Level	Correct Factor	Result	Limit	Margin	Remark
	[MHz]	[dBuV/m]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
1	2483.5000	34.95	14.12	49.07	74.00	-24.93	Horizontal
2	2515.6595	36.51	14.47	50.98	74.00	-23.02	Horizontal

Note: 1. Peak result: Peak detector, RBW: 1 MHz, VBW: 3 MHz.
2. Average result: Peak detector, RBW: 1 MHz, VBW: 1/T MHz (refer to clause 7.1.).
3. Measurement = Reading Level + Correct Factor.
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.