

Autel Digital Power Co., Ltd.

MPE ASSESSMENT REPORT

REPORT TYPE:

FCC MPE Assessment Report

MODEL:

Maxi UW19L002, Maxi UW19C002
Maxi UW19LJ02, Maxi UW19CJ02
Maxi UW19LB02, Maxi UW19L0N2
Maxi UW19CON2, Maxi UW19LJN2
Maxi UW19CJN2, Maxi UW19LBN2

REPORT NUMBER:

241000094SHA-002

ISSUE DATE:

November 1, 2024

DOCUMENT CONTROL NUMBER:

TTRFFCCMPE-01_V1 © 2018 Intertek





Total Quality. Assured.

TEST REPORT

Intertek Testing Services Shanghai
Building No.86, 1198 Qinzhou Road (North)
Caohejing Development Zone
Shanghai 200233, China

Telephone: 86 21 6127 8200
www.intertek.com

Report no.: 241000094SHA-002

Applicant: Autel Digital Power Co., Ltd.
Floors 1, 2, 3 and 6, Caihong Keji Building 36 Hi-tech North Six Road
Songpingshan Community, Xili Sub-district Nanshan District,
Shenzhen, Guangdong 518057, China

Manufacturer: Autel Digital Power Co., Ltd.
Floors 1, 2, 3 and 6, Caihong Keji Building 36 Hi-tech North Six Road
Songpingshan Community, Xili Sub-district Nanshan District,
Shenzhen, Guangdong 518057, China

Factory1: Autel Digital Power Co., Ltd. Guangming Branch
Rooms 101 and 501, Building 2, Huaxing Optoelectronics Industrial
Park, Dongkeng Community, Fenghuang Street, Guangming District,
Shenzhen City, Guangdong Province, China

Factory2: Autel Viet Nam New Energy Technology Company Limited
Factory B&C, Lot IN3-11*B, VSIP Hai Phong Township, Industrial &
Service Park, in Dinh Vu-Cat Hai Economic Zone, Lap Le Commune
Thuy Nguyen District, Hai Phong City 04300, Vietnam

FCC ID: 2BHGJ-MAXCHG80A

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06

FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

PREPARED BY:

Project Engineer
Scout Gong

REVIEWED BY:

Reviewer
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT**Revision History**

Report No.	Version	Description	Issued Date
230800707SHA-002	Rev. 01	Initial issue of report	July 17, 2024
241000094SHA-002	Rev. 01	Two optional power modules are added. The optional power modules were equipped with the model Maxi UW19L0002, and both new types were tested. The test data were listed in this report.	November 1, 2024

TEST REPORT**1 GENERAL INFORMATION****1.1 Description of Equipment Under Test (EUT)**

Product name:	EV Charger
Type/Model:	Maxi UW19L002, Maxi UW19C002, Maxi UW19LJ02, Maxi UW19CJ02, Maxi UW19LB02, Maxi UW19L0N2, Maxi UW19C0N2, Maxi UW19LJN2, Maxi UW19CJN2, Maxi UW19LBN2
Description of EUT:	<p>The EUT covered in the report is an EV charger. RFID card reader is incorporated in model for process control. There are 10 models, the difference among all the models is listed in appendix II. Here is the certificate information of the wireless modules which EUT equipped. Model Maxi UW19L002 was tested as representative.</p> <p>For WIFI/Bluetooth module, FCC ID: XMR202102FC21</p> <p>For Wi-sun module, FCC ID: 2BFLD-S9</p> <p>For LTE module, FCC ID: XMR2023EG915QNA</p>
Rating:	Input/Output Rating: 208/240V AC, 50/60Hz, 80A
EUT type:	<input checked="" type="checkbox"/> Tabletop <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Serial numbers:	A241014-24-001
Sample received date:	October 14, 2024
Date of test:	October 14, 2024 – November 1, 2024

1.2 Technical Specification

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna:	PCB antenna

TEST REPORT**1.3 Description of Test Facility**

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road (North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

TEST REPORT**2 MPE Assessment****Test result: PASS****2.1 MPE Assessment Limit****Mobile device exposure for standalone operations:**

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: Limit for 13.56MHz is 60.77 V/m

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0**

TEST REPORT

2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm^2

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 241000094SHA-001: 60.80 dBuV/m at 3m

$$@20\text{cm} = @3\text{m} + 40 \times \log (3/0.2) = 107.84 \text{ dBuV/m} = 0.25 \text{ V/m} < 60.77 \text{ V/m}$$

The power for WIFI/Bluetooth module refers to certificate of FCC ID: XMR202102FC21

The power for Wi-sun module refers to certificate of FCC ID: 2BFLD-S9

The power for LTE module refers to certificate of FCC ID: XMR2023EG915QNA

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent the worst case in terms of the exposure levels.

Wi-Fi 2.4G, Wi-Fi 5G, Bluetooth, LTE and Wi-sun can transmit simultaneously, here listed the maximum RF exposure according to the modules' certificated reports.

Module FCC Cert.	Frequency Range	P		G		R cm	S mW/cm^2	Limits mW/cm^2
		MHz	dBm	dB _i	Numeric			
XMR202102F C21	Wi-Fi 2.4G 802.11b	19.0	79.433	5.16	3.28	20.00	0.052	1.0000
	Wi-Fi 5G 802.11a	17.0	50.119	4.48	2.81	20.00	0.032	1.0000
	Bluetooth	15.0	31.623	3.00	2.00	20.00	0.013	1.0000
2BFLD-S9	902.2-927.8MHz	18.0	63.10	2.20	1.66	20.00	0.020	0.6000
XMR2023EG9 15QNA	LTE Band 2	25.0	316.22	1.43	1.39	20.00	0.0874	1.0000
	LTE Band 4	25.0	316.22	1.54	1.43	20.00	0.0897	1.0000
	LTE Band 5	25.0	316.22	2.21	1.66	20.00	0.1046	0.5498
	LTE Band 12	25.0	316.22	2.00	1.58	20.00	0.0997	0.4665
	LTE Band 13	25.0	316.22	2.10	1.62	20.00	0.1020	0.5197
	LTE Band 66	25.0	316.22	1.68	1.47	20.00	0.0926	1.0000

Note: 1 mW/cm^2 from 1.310 Table 1.

RFID, Wi-Fi 2.4G, Wi-Fi 5G, Bluetooth, LTE and Wi-can transmit simultaneously, so the maximum rate of MPE is:

$$0.25/60.77 + 0.052/1 + 0.032/1 + 0.013/1 + 0.02/1 + 0.1046/0.5498 = 0.311 < 1.000$$

Therefore, the MPE requirement is deemed to be satisfied without test.

TEST REPORT

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.

TEST REPORT

Appendix II: Model Difference

Model	Maxi UW19L002	Maxi UW19C002	Maxi UW19LJ02	Maxi UW19CJ02	Maxi UW19LB02
Input/Output rating	208/240V AC 50/60Hz, 80A				
With or without LCD	With	With	Without	Without	Without
Connector Type	J1772	J1772	J1772	J1772	J1772
Charging Cable Length	7.5m (25ft)	6m (18ft)	7.5m (25ft)	6m (18ft)	7.5m (25ft)
4G Function	Support	Support	Support	Support	Not Support
Model	Maxi UW19L0N2	Maxi UW19C0N2	Maxi UW19LJN2	Maxi UW19CJN2	Maxi UW19LBN2
Input/Output rating	208/240V AC 50/60Hz, 80A				
With or without LCD	With	With	Without	Without	Without
Connector Type	NACS	NACS	NACS	NACS	NACS
Charging Cable Length	7.5m (25ft)	6m (18ft)	7.5m (25ft)	6m (18ft)	7.5m (25ft)
4G Function	Support	Support	Support	Support	Not Support

****END*****