

12/5/2024

AMC Schweiz Alfa Metalcraft Corp. AG  
Buonaserstrasse 30  
6343 Rotkreuz  
Schweiz

Dear Alex Baenninger,

Enclosed is the MPE test report for testing of the AMC Schweiz Alfa Metalcraft Corp. AG, Audiotherm A0024 tested to the requirements of FCC Part 2.1091

Thank you for using the services of Eurofins E&E North America. If you have any questions regarding these results or if MET can be of further service to you, please do feel free to contact me.

Sincerely,



Nancy LaBrecque  
Documentation Department  
Eurofins Electrical and Electronic Testing NA, Inc.

Reference: WIRA132133-MPE\_R1



Certificates and reports shall not be reproduced except in full, without the written permission of Eurofins E&E North America. While use of the A2LA logo in this report reflects MET accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.

Eurofins MET Laboratories Inc. (Eurofins E&E North America) is part of the Eurofins Electrical & Electronics (E&E) global compliance network.

**RF Exposure Criteria  
Test Report  
Using Maximum Permissible Exposure (MPE) Calculations**

for the

**AMC Schweiz Alfa Metalcraft Corp. AG**  
Audiotherm A0024

**Tested under**

**FCC Part 2.1091**

**Report: WIRA132133-MPE\_R1**

12/5/2024



Bryan Taylor, Wireless Team Lead  
Electromagnetic Compatibility Lab



Nancy LaBrecque  
Documentation Department

**Engineering Statement:** The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Part 15.247 under normal use and maintenance.



Matthew Hinojosa  
EMC Manager, Austin Electromagnetic Compatibility Lab

## Report Status Sheet

Revision	Report Date	Reason for Revision
0	10/1/2024	Initial Issue.
1	12/5/2024	Reviewer Comments

## Table of Contents

<b>1.0 Requirements Summary.....</b>	<b>8</b>
<b>2.0 Equipment Configuration .....</b>	<b>9</b>
<b>2.1 Overview.....</b>	<b>9</b>
<b>2.2 Test Site .....</b>	<b>10</b>
<b>2.3 References.....</b>	<b>10</b>
<b>2.4 Description of Test Sample.....</b>	<b>11</b>
<b>2.5 Mode of Operation.....</b>	<b>11</b>
<b>2.6 Modifications .....</b>	<b>11</b>
<b>2.6.1 Modifications to EUT .....</b>	<b>11</b>
<b>2.6.2 Modifications to Test Standard.....</b>	<b>11</b>
<b>2.7 Disposition of EUT .....</b>	<b>11</b>

## List of Tables

Table 1. Summary of Test Results .....	8
Table 2. EUT Summary Table .....	9
Table 3. References .....	10
Table 7. Test Channels Utilized .....	11

## List of Terms and Abbreviations

<b>AC</b>	Alternating Current
<b>ACF</b>	Antenna Correction Factor
<b>Cal</b>	Calibration
<i>d</i>	Measurement Distance
<b>dB</b>	Decibels
<b>dB<math>\mu</math>A</b>	Decibels above one microamp
<b>dB<math>\mu</math>V</b>	Decibels above one microvolt
<b>dB<math>\mu</math>A/m</b>	Decibels above one microamp per meter
<b>dB<math>\mu</math>V/m</b>	Decibels above one microvolt per meter
<b>DC</b>	Direct Current
<b>E</b>	Electric Field
<b>DSL</b>	Digital Subscriber Line
<b>ESD</b>	Electrostatic Discharge
<b>EUT</b>	Equipment Under Test
<i>f</i>	Frequency
<b>CISPR</b>	Comite International Special des Perturbations Radioelectriques (International Special Committee on Radio Interference)
<b>GRP</b>	Ground Reference Plane
<b>H</b>	Magnetic Field
<b>HCP</b>	Horizontal Coupling Plane
<b>Hz</b>	Hertz
<b>IEC</b>	International Electrotechnical Commission
<b>kHz</b>	kiloHertz
<b>kPa</b>	kiloPascal
<b>kV</b>	kilovolt
<b>LISN</b>	Line Impedance Stabilization Network
<b>MHz</b>	MegaHertz
<b><math>\mu</math>H</b>	microHenry
<b><math>\mu</math>F</b>	microFarad
<b><math>\mu</math>s</b>	microseconds
<b>PRF</b>	Pulse Repetition Frequency
<b>RF</b>	Radio Frequency
<b>RMS</b>	Root-Mean-Square
<b>V/m</b>	Volts per meter
<b>VCP</b>	Vertical Coupling Plane

## 1.0 Requirements Summary

Page Number	Test Name	Result
12	FCC Part 2.1091 MPE Limits (For General Public Exposure)	Compliant

**Table 1. Summary of Test Results**

## 2.0 Equipment Configuration

### 2.1 Overview

Eurofins MET Labs was contracted by AMC Schweiz Alfa Metalcraft Corp. AG to perform testing on the Audiotherm A0024, under AMC Schweiz Alfa Metalcraft Corp. AG's purchase order number 4500921562.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the AMC Schweiz Alfa Metalcraft Corp. AG Audiotherm A0024.

The results obtained relate only to the item(s) tested.

<b>Product Name:</b>	Audiotherm A0024	
<b>Model(s) Tested:</b>	Audiotherm A0024	
<b>FCCID:</b>	2BHIHA0024	
<b>EUT Specifications:</b>	Primary Power: 1.8 – 3.0VDC	
	Type of Modulations:	GFSK
	Equipment Code:	DTS
	Peak RF Output Power:	2.05dBm
	EUT Frequency Ranges:	2402MHz – 2480MHz
	Antenna Gain <sup>1</sup> :	-2.6dBi
<b>Analysis:</b>	The results obtained relate only to the item(s) tested.	
<b>Environmental Test Conditions:</b>	Temperature: 15-35° C	
	Relative Humidity: 30-60%	
	Barometric Pressure: 860-1060 mbar	
<b>Evaluated by:</b>	Bryan Taylor, Sergio Gutierrez	
<b>Report Date(s):</b>	6/25/2024 through 6/29/2024	

**Table 2. EUT Summary Table**

<sup>1</sup> The antenna gain information was provided by AMC Schweiz Alfa Metalcraft Corp. AG and may affect compliance.

## 2.2 Test Site

All testing was performed at Eurofins E&E North America, Austin, TX. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

## 2.3 References

FCC Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.
-----------------	---

**Table 3. References**

## 2.4 Description of Test Sample

The Audiotherm is mounted on a pan lid reading the themperatur from the pan and alarm acoustically the cook, when temperature has to be changed or cooking time is gone. In addition it can control the cooking plate via BLE. With an App you can load recepies on the Audiotherm.

## 2.5 Mode of Operation

The Nordic nRF Connect software was used to interface with the test sample and force it to transmit on low, mid, and high channels at maximum output power.

Transmit Band	Modulation	Channel Frequencies Tested	Test Tool Power Setting
2400 – 2483.5MHz	BLE (GFSK)	2402MHz / 2440MHz / 2480MHz	8

**Table 4. Test Channels Utilized**

## 2.6 Modifications

### 2.6.1 Modifications to EUT

No modifications were made to the EUT.

### 2.6.2 Modifications to Test Standard

No modifications were made to the test standard.

## 2.7 Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to AMC Schweiz Alfa Metalcraft Corp. AG upon completion of testing.

## 2.8 FCC Exposure Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. \* = Plane-wave equivalent power density.

**Test Procedure:**

An MPE evaluation for was performed in order to show that the device was compliant with the general population exposure limits. The maximum power density was calculated for each transmitter band at a separation distance of 20cm using the maximum declared output power including tune up tolerance.

For each transmitter the maximum RF exposure at a 20 cm distance using the formula:

$$ConductedPower_{mW} = 10^{\frac{ConductedPower(dBm)}{10}}$$

$$PowerDensity = \frac{ConductedPower_{mW} \times Ant.Gain}{4\pi \times (20_{cm})^2}$$

For transmitters that could operate simultaneously, the MPE to limit ratio for each was calculated and then summed. If the sum of the MPE to limit ratios was less than 1, that specific combination of transmitters was deemed to comply.

**Test Results:**

The Audiotherm A0024 was **compliant** with FCC Part 2.1091. The calculated maximum power density at 20cm distance was equal to or less than the required limits for general population exposure for FCC Part 2.1091.

**Test Data:**

Duty Cycle	100 (%)		Declared Max Cond. Power (Inc. Tolerance) (dBm)	Duty Cycle Adjusted Cond. Output Power (dBm)	Antenna Gain (dB)	MPE Value (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Margin to Limit (mW/cm <sup>2</sup> )
Separation Dist.	20 (cm)							
Operating Mode	Frequency (MHz)	Declared Max Cond. Power (Inc. Tolerance) (dBm)	Duty Cycle Adjusted Cond. Output Power (dBm)	Antenna Gain (dB)	MPE Value (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )	Margin to Limit (mW/cm <sup>2</sup> )	
BLE	2402	3	3.00	-2.6	0.0002	1.0000	0.9998	

FCC MPE Data

**Test Engineer(s):** Bryan Taylor

**Test Date(s):** 6/26/2024