



# TEST REPORT

**Product Name** : Tablet PC  
**Brand Name** : Wishtel  
**Model** : T808  
**Series Model** : N/A  
**FCC ID** : 2BHIY-IRAT808  
**Applicant** : **Wishtel Pvt Ltd**  
**Address** : 4, Champaklal Industrial Estate, Sion East, Mumbai, MH - 400022  
**Manufacturer** : **Wishtel Pvt Ltd**  
**Address** : 4, Champaklal Industrial Estate, Sion East, Mumbai, MH - 400022  
**Standard(s)** : FCC CFR Title 47 Part 15 Subpart C Section 15.247  
**Date of Receipt** : July 08, 2024  
**Date of Test** : July 08, 2024 ~ July 22, 2024  
**Issued Date** : July 22, 2024

**Issued By:** **Guangdong Asia Hongke Test Technology Limited**  
B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street,  
Bao'an District, Shenzhen, Guangdong, China  
Tel.: +86 0755-230967639      Fax.: +86 0755-230967639

**Reviewed by:**

Leon Yi

Leon.yi

**Approved by:**

Sean She

Sean She



Note: This device has been tested and found to comply with the standard(s) listed, this test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory. This report shall not be reproduced except in full, without the written approval of Guangdong Asia Hongke Test Technology Limited. If there is a need to alter or revise this document, the right belongs to Guangdong Asia Hongke Test Technology Limited, and it should give a prior written notice of the revision document. This test report must not be used by the client to claim product endorsement.

**Guangdong Asia Hongke Test Technology Limited**

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.

**Report Revise Record**

Report Version	Issued Date	Notes
M1	July 22, 2024	Initial Release

## Contents

<b>1 TEST SUMMARY .....</b>	<b>4</b>
1.1 TEST STANDARDS .....	4
1.2 TEST SUMMARY .....	4
1.3 TEST FACILITY .....	5
1.4 MEASUREMENT UNCERTAINTY .....	5
<b>2 GENGGENERAL INFORMATION .....</b>	<b>6</b>
2.1 ENVIRONMENTAL CONDITIONS .....	6
2.2 GENERAL DESCRIPTION OF EUT .....	6
2.3 DESCRIPTION OF TEST MODES AND TEST FREQUENCY .....	7
2.4 SPECIAL ACCESSORIES .....	8
2.5 EQUIPMENT LIST FOR THE TEST .....	8
<b>3 TEST CONDITIONS AND RESULTS .....</b>	<b>9</b>
3.1 CONDUCTED EMISSIONS TEST .....	9
3.2 RADIATED EMISSIONS AND BAND EDGE .....	12
3.3 MAXIMUM PEAK CONDUCTED OUTPUT POWER .....	19
3.4 POWER SPECTRAL DENSITY .....	20
3.5 6dB BANDWIDTH .....	21
3.6 OUT-OF-BAND EMISSIONS .....	22
3.7 ANTENNA REQUIREMENT .....	23
<b>4 TEST SETUP PHOTOGRAPHS OF EUT .....</b>	<b>24</b>
<b>5 EXTERNAL PHOTOGRAPHS OF EUT .....</b>	<b>24</b>
<b>6 INTERNAL PHOTOGRAPHS OF EUT .....</b>	<b>24</b>

# 1 TEST SUMMARY

## 1.1 Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10: 2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spreda Spectrum System, and Hybrid System Devices Operating Under Section 15.247 of the FCC Rules

## 1.2 Test Summary

Test Item	Section in RSS-47	Result
Antenna requirement	§15.203	Pass
On Time and Duty Cycle	/	/
AC Power Line Conducted Emission	§ 15.207(a)	Pass
Conducted Peak Output Power	§15.247 (b)(3)	Pass
Channel Bandwidth	§15.247 (a)(2)	Pass
Power Spectral Density	§15.247 (e)	Pass
Transmitter Radiated Spurious Emission	§15.205/15.209	Pass
Restricted Bands	§15.205/15.209	PASS
Conducted Unwanted emissions and Bandedge	§15.205, §15.247(d)	Pass

## 1.3 Test Facility

### Test Laboratory:

#### Guangdong Asia Hongke Test Technology Limited

B1/F, Building 11, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

The test facility is recognized, certified or accredited by the following organizations:

#### FCC-Registration No.: 251906 Designation Number: CN1376

Guangdong Asia Hongke Test Technology Limited has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

#### IC —Registration No.: 31737 CAB identifier: CN0165

The 3m Semi-anechoic chamber of Guangdong Asia Hongke Test Technology Limited has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 31737

#### A2LA-Lab Cert. No.: 7133.01

Guangdong Asia Hongke Test Technology Limited has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

## 1.4 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Guangdong Asia Hongke Test Technology Limited's quality system according to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Asia Hongke laboratory is reported:

Test	Measurement Uncertainty	Notes
Power Line Conducted Emission	150KHz~30MHz $\pm 1.20$ dB	(1)
Radiated Emission	9KHz~30Hz $\pm 3.10$ dB	(1)
Radiated Emission	9KHz~1GHz $\pm 3.75$ dB	(1)
Radiated Emission	1GHz~18GHz $\pm 3.88$ dB	(1)
Radiated Emission	18GHz-40GHz $\pm 3.88$ dB	(1)
RF power, conducted	30MHz~6GHz $\pm 0.16$ dB	(1)
RF power density, conducted	$\pm 0.24$ dB	(1)
Spurious emissions, conducted	$\pm 0.21$ dB	(1)
Temperature	$\pm 1$ °C	(1)
Humidity	$\pm 3$ %	(1)
DC and low frequency voltages	$\pm 1.5$ %	(1)
Time	$\pm 2$ %	(1)
Duty cycle	$\pm 2$ %	(1)

The report uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty Multiplied by a coverage factor of  $k=2$  , providing a level of confidence of approximately 95%

## 2 GENERAL INFORMATION

### 2.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

### 2.2 General Description of EUT

Product Name:	Tablet PC
Model/Type reference:	T808
Serial Model:	N/A
Power Supply:	DC 3.8V from battery 4000mAh
Adapter Information:	Model: AS1201A-0502000USU Input: 100-240V~50/60Hz 0.35A Max Output: 5.0V=2000mA
Hardware Version:	N/A
Software Version:	N/A
Sample(s) Status:	AiTDG-240708005-1(Normal sample) AiTDG-240708005-2(Engineer sample)

#### Bluetooth LE:

Supported type:	Bluetooth LE 1M
Modulation:	GFSK
Operation frequency:	2402MHz to 2480MHz
Channel number:	40
Channel separation:	2MHz
Antenna type:	FPC antenna
Antenna gain:	1.19 dBi

#### Remark:

The above DUT's information was declared by manufacturer. For more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

## 2.3 Description of Test Modes and Test Frequency

There are 40 channels provided to the EUT and Channel 00/19/39 were selected to test.

### Operation Frequency List:

Channel	Frequency (MHz)
<b>00</b>	<b>2402</b>
02	2404
03	2406
:	:
<b>19</b>	<b>2440</b>
:	:
37	2476
38	2478
<b>39</b>	<b>2480</b>

Note: The line display in grey were the channel selected for testing

Exploratory testing was performed under each mode combination test channel; only the final measurement of the worst combination was made and recorded in this report.

Test case	Exploratory measurement			Final measurement Recorded In Report		
	Mode	Date rate	Channel	Mode	Date rate	Channel
Maximum output power	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest
Power spectral density	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest
-6dB bandwidth	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest
Conducted Spurious Emissions	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest
Conducted Band edge	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest
Radiated Band edge	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest
Radiated Emissions Above 1GHz	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest
Radiated Emissions Below 1GHz	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	LE 1M	<input checked="" type="checkbox"/> Middle
Conducted Emissions 9KHz-30 MHz	GFSK	LE 1M	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	LE 1M	<input checked="" type="checkbox"/> Middle

### Power setting during the test:

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

### Power Parameters:

Test Software Version	#*#3646633#*#*		
Frequency	2402MHz	2440MHz	2480MHz
BLE_1M	default	default	default

## 2.4 Special Accessories

Follow auxiliary equipment(s) test with EUT that provided by the manufacturer or laboratory is listed as follow:

Description	Manufacturer	Model	Serial No.	Provided by	Other
/	/	/	/	/	/
/	/	/	/	/	/

## 2.5 Equipment List for the Test

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	Spectrum Analyzer	R&S	FSV40	101470	2023.09.08	2024.09.07
2	Spectrum Analyzer	Keysight	N9020A	MY51280643	2023.09.08	2024.09.07
3	EMI Measuring Receiver	R&S	ESR	101660	2023.09.08	2024.09.07
4	Low Noise Pre-Amplifier	HP	HP8447E	1937A01855	2023.09.08	2024.09.07
5	Low Noise Pre-Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2023.09.08	2024.09.07
6	Passive Loop	ETS	6512	00165355	2022.09.04	2024.09.03
7	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9160	9160-3206	2021.08.29	2024.08.28
8	Broadband Horn Antenna	SCHWARZBECK	BBHA9120D	452	2021.08.29	2024.08.28
9	SHF-EHF Horn Antenna 15-40GHz	SCHWARZBECK	BBHA9170	BBHA9170367d	2021.08.29	2024.08.28
10	EMI Measuring Receiver	R&S	ESR	101160	2023.09.13	2024.09.12
11	LISN	SCHWARZBECK	NNLK 8129	8130179	2023.10.29	2024.10.28
12	Pulse Limiter	R&S	ESH3-Z2	102789	2023.09.13	2024.09.12
13	Pro.Temp&Humi.chamber	MENTEK	MHP-150-1C	MAA08112501	2023.09.08	2024.09.07
14	RF Automatic Test system	MW	MW100-RFCB	21033016	2023.09.08	2024.09.07
15	Signal Generator	Agilent	N5182A	MY50143009	2023.09.08	2024.09.07
16	Wideband Radio communication tester	R&S	CMW500	1201.0002K50	2023.09.08	2024.09.07
17	RF Automatic Test system	MW	MW100-RFCB	21033016	2023.09.08	2024.09.07
18	DC power supply	ZHAOXIN	RXN-305D-2	28070002559	N/A	N/A
19	RE Software	EZ	EZ-EMC_RE	Ver.AIT-03A	N/A	N/A
20	CE Software	EZ	EZ-EMC_CE	Ver.AIT-03A	N/A	N/A
21	RF Software	MW	MTS 8310	2.0.0.0	N/A	N/A
22	temporary antenna connector(Note)	NTS	R001	N/A	N/A	N/A

Note: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

### 3 TEST CONDITIONS AND RESULTS


#### 3.1 Conducted Emissions Test

##### LIMIT

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.

##### TEST CONFIGURATION




##### TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

## TEST RESULTS

Remark: Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:




Remark: Correct Factor = Insertion loss of LISN + Cable loss + Insertion loss of Pulse Limiter;

Measurement Result = Reading Level +Correct Factor;

Margin = Measurement Result- Limit

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1675	44.89	10.67	55.56	65.08	-9.52	QP
2	0.1723	25.10	10.67	35.77	54.85	-19.08	AVG
3	0.2130	22.12	10.70	32.82	53.09	-20.27	AVG
4	0.2940	39.30	10.70	50.00	60.41	-10.41	QP
5	0.2983	21.16	10.70	31.86	50.29	-18.43	AVG
6	0.3390	39.27	10.70	49.97	59.23	-9.26	QP
7	0.3390	22.11	10.70	32.81	49.23	-16.42	AVG
8	0.3840	36.09	10.69	46.78	58.19	-11.41	QP
9	0.5100	33.90	10.69	44.59	56.00	-11.41	QP
10	0.5955	33.19	10.69	43.88	56.00	-12.12	QP
11	0.6990	19.30	10.68	29.98	46.00	-16.02	AVG
12	1.3650	18.26	10.69	28.95	46.00	-17.05	AVG



Remark: Correct Factor = Insertion loss of LISN + Cable loss + Insertion loss of Pulse Limiter;  
Measurement Result = Reading Level +Correct Factor;

Margin = Measurement Result- Limit

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark	
							QP	AVG
1	0.1680	37.60	10.67	48.27	65.06	-16.79	QP	
2	0.1723	21.83	10.67	32.50	54.85	-22.35	AVG	
3	0.2265	34.51	10.69	45.20	62.58	-17.38	QP	
4	0.2802	22.36	10.69	33.05	50.81	-17.76	AVG	
5	0.3030	32.61	10.69	43.30	60.16	-16.86	QP	
6	0.3165	21.21	10.69	31.90	49.80	-17.90	AVG	
7	0.6180	31.25	10.68	41.93	56.00	-14.07	QP	
8	0.6360	19.09	10.67	29.76	46.00	-16.24	AVG	
9	0.8160	16.76	10.65	27.41	46.00	-18.59	AVG	
10	0.9330	29.80	10.65	40.45	56.00	-15.55	QP	
11	2.1929	14.57	10.78	25.35	46.00	-20.65	AVG	
12	2.3685	28.30	10.78	39.08	56.00	-16.92	QP	

## 3.2 Radiated Emissions and Band Edge

### Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB $\mu$ V/m)	Radiated ( $\mu$ V/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

### TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



**(C) Radiated Emission Test Set-Up, Frequency above 1000MHz**



**Test Procedure**

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antenna	1


7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

**TEST RESULTS**


Remark:

1. For below 1GHz testing recorded worst at BLE 1M middle channel.
2. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and The emission levels from 9kHz to 30MHz are attenuated 20dB below the limit and not recorded in report.

**For 30MHz-1GHz**

**Remark:**

Emission Level = Reading + Factor;  
Factor = Antenna Factor + Cable Loss – Pre-amplifier;  
Margin= Emission Level - Limit.

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	42.0066	34.18	-16.54	17.64	40.00	-22.36	QP
2	128.5630	38.12	-17.81	20.31	43.50	-23.19	QP
3	161.4742	39.31	-16.59	22.72	43.50	-20.78	QP
4 *	327.8873	50.71	-16.17	34.54	46.00	-11.46	QP
5	368.1116	49.03	-15.29	33.74	46.00	-12.26	QP
6	935.5463	35.84	-3.90	31.94	46.00	-14.06	QP



For 1GHz to 25GHz

**BLE 1M GFSK (above 1GHz)**

Frequency(MHz):		2402		Polarity:	Horizontal	
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor	Emission Level (dB $\mu$ V/m)	Limits	Margin	Detector Type
4804	46.65	5.06	51.71	74	-22.29	PEAK
4804	37.53	5.06	42.59	54	-11.41	AVG
7206	43.25	7.03	50.28	74	-23.72	PEAK
7206	31.94	7.03	38.97	54	-15.03	AVG

Frequency(MHz):		2402		Polarity:	VERTICAL	
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor	Emission Level (dB $\mu$ V/m)	Limits	Margin	Detector Type
4804	47.56	5.06	52.62	74	-21.38	PEAK
4804	35.49	5.06	40.55	54	-13.45	AVG
7206	45.58	7.03	52.61	74	-21.39	PEAK
7206	31.34	7.03	38.37	54	-15.63	AVG

Frequency(MHz):		2440		Polarity:	Horizontal	
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor	Emission Level (dB $\mu$ V/m)	Limits	Margin	Detector Type
4880	48.29	5.14	53.43	74	-20.57	PEAK
4880	34.88	5.14	40.02	54	-13.98	AVG
7320	43.24	7.52	50.76	74	-23.24	PEAK
7320	30.83	7.52	38.35	54	-15.65	AVG

Frequency(MHz):		2440		Polarity:	VERTICAL	
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor	Emission Level (dB $\mu$ V/m)	Limits	Margin	Detector Type
4880	48.18	5.14	53.32	74	-20.68	PEAK
4880	36.48	5.14	41.62	54	-12.38	AVG
7320	43.58	7.52	51.10	74	-22.90	PEAK
7320	29.55	7.52	37.07	54	-16.93	AVG

Frequency(MHz):		2480		Polarity:	Horizontal	
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB $\mu$ V)	(dB/m)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	
4960	46.17	5.22	51.39	74	-22.61	PEAK
4960	37.86	5.22	43.08	54	-10.92	AVG
7440	46.13	8.06	54.19	74	-19.81	PEAK
7440	30.99	8.06	39.05	54	-14.95	AVG

Frequency(MHz):		2480		Polarity:	VERTICAL	
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dB $\mu$ V)	(dB/m)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	
4960	45.34	5.22	50.56	74	-23.44	PEAK
4960	36.25	5.22	41.47	54	-12.53	AVG
7440	45.16	8.06	53.22	74	-20.78	PEAK
7440	30.90	8.06	38.96	54	-15.04	AVG

**REMARKS:**

1. Emission level (dB $\mu$ V/m) = Reading (dB $\mu$ V)+ Factor (dB/m)
2. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Emission level- Limit value.
4. -- Mean the PK detector measured value is below average limit.
5. Other emission levels are attenuated 20dB below the limit and not recorded in report.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

**Radiation Restricted band**
**BLE 1M GFSK**

Frequency(MHz):		2402		Polarity:	Horizontal	
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB/m)	Emission Level (dB $\mu$ V/m)	Limits	Margin (dB)	Detector Type
2385.63	40.42	-5.64	34.78	74	-39.22	peak
2390	39.52	-5.72	33.8	74	-40.2	peak
2400	40.75	-5.61	35.14	74	-38.86	peak

Frequency(MHz):		2402		Polarity:	Vertical	
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB/m)	Emission Level (dB $\mu$ V/m)	Limits	Margin (dB)	Detector Type
2386.15	40.77	-5.72	35.05	74	-38.95	peak
2390	39.23	-5.94	33.29	74	-40.71	peak
2400	40.74	-5.65	35.09	74	-38.91	peak

Frequency(MHz):		2480		Polarity:	Horizontal	
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB/m)	Emission Level (dB $\mu$ V/m)	Limits	Margin (dB)	Detector Type
2483.5	38.19	-5.29	32.9	74	-41.1	peak
2483.64	39.08	-4.59	34.49	74	-39.51	peak

Frequency(MHz):		2408		Polarity:	Vertical	
Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB/m)	Emission Level (dB $\mu$ V/m)	Limits	Margin (dB)	Detector Type
2483.5	36.77	-5.15	31.62	74	-42.38	peak
2485.07	37.77	-4.71	33.06	74	-40.94	peak

**REMARKS:**

1. Emission level (dB $\mu$ V/m) = Reading (dB $\mu$ V)+ Factor (dB/m)
2. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Emission level- Limit value.
4. Other emission levels are attenuated 20dB below the limit and not recorded in report.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

### 3.3 Maximum Peak Conducted Output Power

#### Limit


The Maximum Peak Output Power Measurement is 30dBm.

#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer. The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq 3 \times$  RBW
- c) Set span  $\geq 3 \times$  RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

#### Test Configuration



#### Test Results

**Pass**       **Not Applicable**

Note:

For test data, please refer to Appendix RF test data for BLE.

## 3.4 Power Spectral Density


### Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW  $\geq$  3 kHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

### Test Configuration



### Test Results

Pass       Not Applicable

Note:

For test data, please refer to Appendix RF test data for BLE.

### 3.5 6dB Bandwidth


#### Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

#### Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. Measured the 6dB bandwidth by related function of the spectrum analyzer.

#### Test Configuration



#### Test Results

**Pass**       **Not Applicable**

Note:

For test data, please refer to Appendix RF test data for BLE.

## 3.6 Out-of-band Emissions


### Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

### Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

### Test Configuration



### Test Results

Pass       Not Applicable

Note:

For test data, please refer to Appendix RF test data for BLE.

## 3.7 Antenna Requirement

### Standard Applicable

#### **For intentional device, according to FCC 47 CFR Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

#### **FCC CFR Title 47 Part 15 Subpart C Section 15.247(b) (4):**

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### Test Result

The maximum gain of antenna was 1.19dBi with impedance  $50\Omega$ .

## 4 Test Setup Photographs of EUT

Please refer to separated files for Test Setup Photos of the EUT.

## 5 External Photographs of EUT

Please refer to separated files for External Photos of the EUT.

## 6 Internal Photographs of EUT

Please refer to separated files for Internal Photos of the EUT.

\*\*\*\*\* End of Report \*\*\*\*\*