



FCC TEST REPORT

FCC ID: 2BHJ3-EC-Q01S

On Behalf of

Shenzhen Xinyusheng Technology Co., Ltd.

Security Camera

Model No.: EC-Q01S-01W

Prepared for : Shenzhen Xinyusheng Technology Co., Ltd.
302, No.1 Building, Jindiweixin Technology Park, No.11 Baolong
Address : 1st Road, Baolong Community, Baolong Street, Longgang Dist.,
Shenzhen, China

Prepared By : Shenzhen PSI Testing Co., Ltd.
Address : 1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road,
Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number : psi2406044-C01-R07
Date of Receipt : June 12, 2024
Date of Test : June 13, 2024-June 20, 2024
Date of Report : June 21, 2024
Version Number : V0

TABLE OF CONTENTS

Description	Page
1. Summary Of Standards And Results -----	6
1.1. Description of Standards and Results -----	6
2. General Information -----	7
2.1. Description of Device (EUT) -----	7
2.2. Accessories of Device (EUT) -----	8
2.3. Tested Supporting System Details-----	8
2.4. Block Diagram of Connection Between EUT and Simulators -----	8
2.5. Test Mode Description -----	9
2.6. Test Conditions -----	10
2.7. Test Facility-----	10
2.8. Measurement Uncertainty -----	10
2.9. Test Equipment List -----	11
3. Spurious Emission -----	12
3.1. Test Limits -----	12
3.2. Block Diagram of Test setup -----	13
3.3. Test Procedure -----	14
3.4. Test Results -----	15
4. Power Line Conducted Emission -----	23
4.1. Test Limits -----	23
4.2. Test Procedure -----	23
4.3. Test Setup -----	23
4.4. Test Results -----	24
5. Out-of-band Emissions -----	27
5.1. Test Limits -----	27
5.2. Test Procedure -----	27
5.3. Test Setup -----	27
5.4. Test Results -----	27
6. Conducted Maximum Output Power -----	43
6.1. Test limits -----	43
6.2. Test Procedure -----	43
6.3. Test Setup -----	43
6.4. Test Results -----	44
7. Peak Power Spectral Density -----	45
7.1. Test limits -----	45
7.2. Test Procedure -----	45
7.3. Test Setup -----	45
7.4. Test Results -----	46
8. Bandwidth -----	51
8.1. Test limits -----	51
8.2. Test Procedure -----	51
8.3. Test Setup -----	51
8.4. Test Results -----	51
9. Band Edge Test -----	62
9.1. Block Diagram of Test Setup-----	62
9.2. Test Limit-----	62
9.3. Test Procedure -----	62
9.4. Test Results -----	63
10. Antenna Requirement -----	66
10.1. Standard Requirement -----	66
10.2. Antenna Connected Construction -----	66
10.3. Results -----	66
11. Photos of test setup -----	67

12. Photos of EUT ----- 67

TEST REPORT DECLARATION

Applicant : Shenzhen Xinyusheng Technology Co., Ltd.
Address : 302, No.1 Building, Jindiweixin Technology Park, No.11 Baolong 1st Road,
Baolong Community, Baolong Street, Longgang Dist., Shenzhen, China
Manufacturer : Shenzhen Xinyusheng Technology Co., Ltd.
Address : 302, No.1 Building, Jindiweixin Technology Park, No.11 Baolong 1st Road,
Baolong Community, Baolong Street, Longgang Dist., Shenzhen, China
EUT Description : Security Camera
(A) Model No. : EC-Q01S-01W
(B) Trademark : N/A

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10-2013

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C limits both conducted and radiated emissions. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....:

Jensen Wang
Test Engineer

Jensen Wang

Approved by (name + signature).....:

Simple Guan
Project Manager

Simple Guan

Date of issue.....:

June 21, 2024

Revision History

Revision	Issue Date	Revisions	Revised By
V0	June 21, 2024	Initial released Issue	Jensen Wang



1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Radiated Spurious Emission	FCC Part 15: 15.209 FCC Part 15: 15.205	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d)	P
Power Line Conducted Emissions	FCC Part 15: 15.207	P
6dB Bandwidth	FCC PART 15:15.247(a)(2)	P
Output Power	FCC Part 15: 15.247(b)(3)	P
Out-of-band Emissions	FCC Part 15: 15.247(d)	P
Power Spectral Density	FCC PART 15:15.247(e)	P
Antenna Requirement	FCC Part 15: 15.203	P
Note: 1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable. 4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty.		

2. General Information

2.1. Description of Device (EUT)

Product Name : Security Camera
Model : EC-Q01S-01W
Diff : N/A
Test Voltage : AC 120V/60Hz

Radio technology	: 2.4G WiFi
Operation frequency	: 2412MHz-2462MHz for IEEE 802.11 b, g, n/HT20
Channel No.	: 802.11b/802.11g/802.11n(HT20)
Modulation type	: IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n:OFDM(64QAM, 16QAM, QPSK, BPSK)
Antenna Type	: Internal antenna, Maximum Gain is 2.24dBi.
Software version	: V1.0
Hardware version	: V1.0
Note	: Antenna information is provided by applicant. Testing lab is not responsible for the accuracy of the information.

2.2. Accessories of Device (EUT)


Accessories : Power adapter
Manufacturer : Shenzhen Xinyusheng Technology Co., Ltd.
Model : HL-608
Rating : INPUT :100-240V, 50/60Hz 0.35A
OUTPUT :5V $\overline{=}$ 1.5A

Accessories : USB Cable
Manufacturer : Shenzhen Xinyusheng Technology Co., Ltd.
Model : N/A
Rating : N/A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	N/A	N/A	N/A	N/A

2.4. Block Diagram of Connection Between EUT and Simulators



2.5. Test Mode Description

Keeping TX			
Mode	Data rate (Mbps)	Channel	Frequency(MHz)
IEEE 802.11 b	1	Low :CH1	2412
	1	Middle: CH6	2437
	1	High: CH11	2462
IEEE 802.11 g	6	Low :CH1	2412
	6	Middle: CH6	2437
	6	High: CH11	2462
IEEE 802.11 n/HT20	6.5	Low :CH1	2412
	6.5	Middle: CH6	2437
	6.5	High: CH11	2462
Note: According exploratory test, EUT will have maximum output power in those data rate. So those data rate were used for all test.			

Channel list:					
For IEEE 802.11b, g, n/HT20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
CH1	2412	CH5	2432	CH9	2452
CH2	2417	CH6	2437	CH10	2457
CH3	2422	CH7	2442	CH11	2462
CH4	2427	CH8	2447		

2.6. Test Conditions

Items	Required
Temperature range:	15-35℃
Humidity range:	25-75%
Pressure range:	86-106kPa

2.7. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission

Registration Number: 916281

2.8. Measurement Uncertainty

(95% confidence levels, k=2)

Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	2.17dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	2.74dB(Polarize: V)
	2.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 18GHz)	4.29dB(Polarize: V)
	4.82dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	48.24KHz
Uncertainty for conducted RF Power	0.41dB
Uncertainty for Power Spectral Density	0.39 dB

2.9. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2022.12.20	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2023.12.19	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2023.12.19	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2023.12.19	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2023.04.03	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2022.12.26	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2023.12.19	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2022.12.26	2 Year
9.	Amplifier	SKET	LAPA_01G1 8G-45dB	SK20220329 01	/	2023.12.19	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2022.12.25	2 Year
11.	Amplifier	SKET	LNPA_0118 G-45	SK20200108 01	/	2023.12.19	1 Year
12.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02 -1111533-Fz	/	2023.12.19	1 Year
13.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2023.12.19	1 Year
14.	Temp. & Humid Chamber	Auchno	9606	/	/	2023.12.19	1 Year
15.	Regulated DC Power Supply	Xinouhua	ADC120V10 A	2022112516 38		2023.12.19	1 Year

For Test Software Information

Item	Software Name	Manufacturer	Version
RE	EZ EMC	Farad	PSI-3A1
CE	EZ EMC	Farad	PSI-3A1
RF	RTS	TACHOY	V1.0.0

3. Spurious Emission

3.1. Test Limits

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)


15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	


Note 1: The peak limit is 20 dB higher than the average limit

3.2. Block Diagram of Test setup


3.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



3.2.2 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



3.2.3 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



3.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

Test setup information:

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHz~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

3.4. Test Results


We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.
Detailed information please see the following page.

From 9KHz to 30MHz:	
Test Date : 2024.06.14	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : IEEE 802.11b mode	
Test Results : PASS	
Note:	The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.




From 30MHz to 1000MHz:	
Test Date : 2024.06.14	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : IEEE 802.11b mode	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of IEEE 802.11b mode, Channel 2412MHz was listed in this report.



Polarization: Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	46.4826	21.19	13.36	34.55	40.00	-5.45	QP
2	59.9376	19.83	12.16	31.99	40.00	-8.01	QP
3 *	72.0211	26.24	10.56	36.80	40.00	-3.20	QP
4	96.2250	30.02	9.22	39.24	43.50	-4.26	QP
5	243.4839	20.47	12.05	32.52	46.00	-13.48	QP
6	400.0810	23.34	16.19	39.53	46.00	-6.47	QP


Level = Reading + Factor Margin = Level - Limit

Polarization: Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	46.5437	22.88	13.35	36.23	40.00	-3.77	QP
2	58.9475	21.86	12.26	34.12	40.00	-5.88	QP
3	66.2371	24.60	11.49	36.09	40.00	-3.91	QP
4 *	77.2873	27.82	9.16	36.98	40.00	-3.02	QP
5	96.4784	30.92	9.24	40.16	43.50	-3.34	QP
6	145.4780	23.08	12.94	36.02	43.50	-7.48	QP

Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:	
Test Date : 2024.06.14	Temperature : 26℃
Test Engineer : Jensen Wang	Humidity : 54%
Test Mode : WIFI mode	
Test Results : PASS	
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.



Test Mode : IEEE 802.11b TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4824	V	85.09	-27.27	57.82	74.00	-16.18	Peak
2	4824	V	65.50	-27.27	38.23	54.00	-15.77	Avg
3	7236	--	--	--	--	--	--	--
4	9648	--	--	--	--	--	--	--
5	4824	H	82.17	-27.27	54.90	74.00	-19.10	Peak
6	4824	H	72.49	-27.27	45.22	54.00	-8.78	Avg
7	7236	--	--	--	--	--	--	--
8	9648	--	--	--	--	--	--	--
Test Mode : IEEE 802.11b TX Mid								
1	4874	V	86.82	-27.79	59.03	74.00	-14.97	Peak
2	4874	V	64.11	-27.79	36.32	54.00	-17.68	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	83.19	-27.79	55.40	74.00	-18.60	Peak
6	4874	H	73.46	-27.79	45.67	54.00	-8.33	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11b TX High								
1	4924	V	84.14	-28.30	55.84	74.00	-18.16	Peak
2	4924	V	68.93	-28.30	40.63	54.00	-13.37	Avg
3	7386	--	--	--	--	--	--	--
4	9848	--	--	--	--	--	--	--
5	4924	H	83.69	-28.30	55.39	74.00	-18.61	Peak
6	4924	H	70.32	-28.30	42.02	54.00	-11.98	Avg
7	7386	--	--	--	--	--	--	--
8	9848	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

Test Mode : IEEE 802.11g TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4824	V	83.70	-27.27	56.43	74.00	-17.57	Peak
2	4824	V	65.18	-27.27	37.91	54.00	-16.09	Avg
3	7236	--	--	--	--	--	--	--
4	9648	--	--	--	--	--	--	--
5	4824	H	82.09	-27.27	54.82	74.00	-19.18	Peak
6	4824	H	73.21	-27.27	45.94	54.00	-8.06	Avg
7	7236	--	--	--	--	--	--	--
8	9648	--	--	--	--	--	--	--
Test Mode : IEEE 802.11g TX Mid								
1	4874	V	87.39	-27.79	59.60	74.00	-14.40	Peak
2	4874	V	65.07	-27.79	37.28	54.00	-16.72	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	83.16	-27.79	55.37	74.00	-18.63	Peak
6	4874	H	71.13	-27.79	43.34	54.00	-10.66	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11g TX High								
1	4924	V	84.03	-28.30	55.73	74.00	-18.27	Peak
2	4924	V	67.58	-28.30	39.28	54.00	-14.72	Avg
3	7386	--	--	--	--	--	--	--
4	9848	--	--	--	--	--	--	--
5	4924	H	80.24	-28.30	51.94	74.00	-22.06	Peak
6	4924	H	72.20	-28.30	43.90	54.00	-10.10	Avg
7	7386	--	--	--	--	--	--	--
8	9848	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

Test Mode : IEEE 802.11n/HT20 TX Low								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	4824	V	85.00	-27.27	57.73	74.00	-16.27	Peak
2	4824	V	66.55	-27.27	39.28	54.00	-14.72	Avg
3	7236	--	--	--	--	--	--	--
4	9648	--	--	--	--	--	--	--
5	4824	H	83.01	-27.27	55.74	74.00	-18.26	Peak
6	4824	H	71.24	-27.27	43.97	54.00	-10.03	Avg
7	7236	--	--	--	--	--	--	--
8	9648	--	--	--	--	--	--	--
Test Mode : IEEE 802.11n/HT20 TX Mid								
1	4874	V	85.14	-27.79	57.35	74.00	-16.65	Peak
2	4874	V	66.01	-27.79	38.22	54.00	-15.78	Avg
3	7311	--	--	--	--	--	--	--
4	9748	--	--	--	--	--	--	--
5	4874	H	81.56	-27.79	53.77	74.00	-20.23	Peak
6	4874	H	71.30	-27.79	43.51	54.00	-10.49	Avg
7	7311	--	--	--	--	--	--	--
8	9748	--	--	--	--	--	--	--
Test Mode : IEEE 802.11n/HT20 TX High								
1	4924	V	84.66	-28.30	56.36	74.00	-17.64	Peak
2	4924	V	68.54	-28.30	40.24	54.00	-13.76	Avg
3	7386	--	--	--	--	--	--	--
4	9848	--	--	--	--	--	--	--
5	4924	H	82.49	-28.30	54.19	74.00	-19.81	Peak
6	4924	H	71.18	-28.30	42.88	54.00	-11.12	Avg
7	7386	--	--	--	--	--	--	--
8	9848	--	--	--	--	--	--	--
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit.								

4. Power Line Conducted Emission

4.1. Test Limits

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.


4.2. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs.

Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10:2013 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9 kHz.

4.3. Test Setup



4.4. Test Results

Test Date	: 2024.06.17	Temperature	: 26℃
Test Engineer	: Jensen Wang	Humidity	: 54%
Test Mode	: WIFI mode		
Test Results	: PASS		

Note: 1. The test results are listed in next pages.


2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out.

3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

4. All modes have been tested, and only worst data of b mode, Channel 2412MHz (AC 120V/ 60Hz) was listed in this report.




Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1660	48.21	9.94	58.15	65.16	-7.01	QP	P
2	0.1660	38.69	9.94	48.63	55.16	-6.53	AVG	P
3	0.2020	47.23	9.95	57.18	63.53	-6.35	QP	P
4	0.2020	34.82	9.95	44.77	53.53	-8.76	AVG	P
5	0.4686	40.07	9.82	49.89	56.54	-6.65	QP	P
6	0.4686	30.00	9.82	39.82	46.54	-6.72	AVG	P
7	1.1340	40.13	9.41	49.54	56.00	-6.46	QP	P
8	1.1340	29.42	9.41	38.83	46.00	-7.17	AVG	P
9	1.2860	41.20	9.40	50.60	56.00	-5.40	QP	P
10 *	1.2860	31.34	9.40	40.74	46.00	-5.26	AVG	P
11	1.4020	41.18	9.40	50.58	56.00	-5.42	QP	P
12	1.4020	27.91	9.40	37.31	46.00	-8.69	AVG	P

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1500	52.68	9.77	62.45	66.00	-3.55	QP	P
2	0.1500	42.69	9.77	52.46	56.00	-3.54	AVG	P
3 *	0.1685	51.79	9.87	61.66	65.03	-3.37	QP	P
4	0.1685	34.53	9.87	44.40	55.03	-10.63	AVG	P
5	1.1060	33.48	9.48	42.96	56.00	-13.04	QP	P
6	1.1060	24.67	9.48	34.15	46.00	-11.85	AVG	P
7	1.4380	34.04	9.40	43.44	56.00	-12.56	QP	P
8	1.4380	24.84	9.40	34.24	46.00	-11.76	AVG	P
9	1.7580	38.42	9.32	47.74	56.00	-8.26	QP	P
10	1.7580	24.19	9.32	33.51	46.00	-12.49	AVG	P
11	2.4500	37.12	9.39	46.51	56.00	-9.49	QP	P
12	2.4500	20.21	9.39	29.60	46.00	-16.40	AVG	P

Note: Level = Reading + Factor Margin = Level - Limit

5. Out-of-band Emissions


5.1. Test Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in FCC Part 15.209(a) is not required.

5.2. Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.


5.3. Test Setup




5.4. Test Results


PASS.

The test results are listed in next pages.


Band Edge: Pass.




1_Reference_Level_NVNT_ANT1_802_11g_2412




2_Bandedge_NVNT_ANT1_802_11g_2412




1_Reference_Level_NVNT_ANT1_802_11g_2462




2_Bandedge_NVNT_ANT1_802_11g_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412



2_Bandedge_NVNT_ANT1_802_11n(HT20)_2412





1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462




2_Bandedge_NVNT_ANT1_802_11n(HT20)_2462





Conducted spurious emission: Pass.**1_Reference_Level_NVNT_ANT1_802_11b_2412****2_Spurious_Emission_NVNT_ANT1_802_11b_2412**

1_Reference_Level_NVNT_ANT1_802_11b_2437




2_Spurious_Emission_NVNT_ANT1_802_11b_2437







1_Reference_Level_NVNT_ANT1_802_11g_2412




2_Spurious_Emission_NVNT_ANT1_802_11g_2412




1_Reference_Level_NVNT_ANT1_802_11g_2437




2_Spurious_Emission_NVNT_ANT1_802_11g_2437






1_Reference_Level_NVNT_ANT1_802_11g_2462




2_Spurious_Emission_NVNT_ANT1_802_11g_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412**2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2412**



1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462



2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2462



6. Conducted Maximum Output Power

6.1. Test limits

Please refer RSS-247 & FCC PART 15: 15.247.

Regulation 15.247(b) The limit of Maximum Peak Output Power Measurement is 1 W(30dBm)


6.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

- 1 Place the EUT on the table and set it in transmitting mode.
- 2 Connected the EUT's antenna port to peak power meter by 20dB attenuator.
- 3 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

6.3. Test Setup



6.4. Test Results

Condition	Antenna	Modulation	Frequency (MHz)	Detector	Conducted Power(dBm)	Duty factor(dB)	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	Peak	14.37	N/A	14.37	30	Pass
NVNT	ANT1	802.11b	2437.00	Peak	14.67	N/A	14.67	30	Pass
NVNT	ANT1	802.11b	2462.00	Peak	14.08	N/A	14.08	30	Pass
NVNT	ANT1	802.11g	2412.00	Peak	19.03	N/A	19.03	30	Pass
NVNT	ANT1	802.11g	2437.00	Peak	19.55	N/A	19.55	30	Pass
NVNT	ANT1	802.11g	2462.00	Peak	14.25	N/A	14.25	30	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	Peak	14.25	N/A	14.25	30	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	Peak	14.81	N/A	14.81	30	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	Peak	14.14	N/A	14.14	30	Pass

Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty factor(dB)
NVNT	ANT1	802.11b	2412.00	100	0.00
NVNT	ANT1	802.11b	2437.00	100	0.00
NVNT	ANT1	802.11b	2462.00	100	0.00
NVNT	ANT1	802.11g	2412.00	100	0.00
NVNT	ANT1	802.11g	2437.00	100	0.00
NVNT	ANT1	802.11g	2462.00	100	0.00
NVNT	ANT1	802.11n(HT20)	2412.00	100	0.00
NVNT	ANT1	802.11n(HT20)	2437.00	100	0.00
NVNT	ANT1	802.11n(HT20)	2462.00	100	0.00

7. Peak Power Spectral Density

7.1. Test limits

7.1.1 Please refer RSS-247 & FCC PART 15: 15.247.

7.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

7.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

7.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02

7.2.1 Place the EUT on the table and set it in transmitting mode.


7.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3 Set the spectrum analyzer as $RBW = 100\text{kHz}$ (Set the RBW to: $3\text{ kHz} \leq RBW \leq 100\text{ kHz}$), $VBW = 300\text{kHz}$ (Set the $VBW \geq 3 \times RBW$), $\text{span} \geq 1.5 \times \text{DTS bandwidth}$, detail see the test plot.

7.2.4 Record the max reading.


7.2.5 Repeat the above procedure until the measurements for all frequencies are completed.



7.3. Test Setup







7.4. Test Results



Condition	Modulation	Frequency (MHz)	PSD(dBm/30kHz)	RB factor(dB)	PSD(dBm/3kHz)	limit(dBm/3kHz)	Result
NVNT	802.11b	2412.00	-0.60	-10.00	-10.60	8	Pass
NVNT	802.11b	2437.00	-0.44	-10.00	-10.44	8	Pass
NVNT	802.11b	2462.00	-0.77	-10.00	-10.77	8	Pass
NVNT	802.11g	2412.00	-3.97	-10.00	-13.97	8	Pass
NVNT	802.11g	2437.00	-2.74	-10.00	-12.74	8	Pass
NVNT	802.11g	2462.00	-8.53	-10.00	-18.53	8	Pass
NVNT	802.11n(HT20)	2412.00	-7.96	-10.00	-17.96	8	Pass
NVNT	802.11n(HT20)	2437.00	-7.43	-10.00	-17.43	8	Pass
NVNT	802.11n(HT20)	2462.00	-8.15	-10.00	-18.15	8	Pass











8. Bandwidth

8.1. Test limits

Please refer RSS-247 & FCC PART 15: 15.247

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.

8.2. Test Procedure

Details see the KDB558074 D01 Meas Guidance v05r02



- a) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- b) The test receiver set RBW = 100kHz, VBW $\geq$ 3*RBW =300kHz,, Peak Detector, Sweep time set auto, detail see the test plot.



8.3. Test Setup







8.4. Test Results


Condition	Antenna	Modulation	Frequency (MHz)	-6dB BW(MHz)	limit(kHz)	Result
NVNT	ANT1	802.11b	2412.00	8.09	500	Pass
NVNT	ANT1	802.11b	2437.00	8.09	500	Pass
NVNT	ANT1	802.11b	2462.00	8.10	500	Pass
NVNT	ANT1	802.11g	2412.00	15.15	500	Pass
NVNT	ANT1	802.11g	2437.00	15.14	500	Pass
NVNT	ANT1	802.11g	2462.00	15.16	500	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	15.15	500	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	15.14	500	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	15.16	500	Pass




















Condition	Antenna	Modulation	Frequency (MHz)	99%BW(MHz)
NVNT	ANT1	802.11b	2412.00	12.830
NVNT	ANT1	802.11b	2437.00	12.844
NVNT	ANT1	802.11b	2462.00	13.031
NVNT	ANT1	802.11g	2412.00	17.077
NVNT	ANT1	802.11g	2437.00	17.046
NVNT	ANT1	802.11g	2462.00	17.077
NVNT	ANT1	802.11n(HT20)	2412.00	18.007
NVNT	ANT1	802.11n(HT20)	2437.00	17.946
NVNT	ANT1	802.11n(HT20)	2462.00	18.072












9. Band Edge Test

9.1. Block Diagram of Test Setup



9.2. Test Limit

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

9.3. Test Procedure

Refer to ANSI C 63.10, Clause 6.10.

All restriction band and non- restriction band have been tested, only worse case is reported.

Details see the KDB558074 D01 Meas Guidance v05r02

9.3.1 Put the EUT on a 1.5m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission

9.3.2 Check the spurious emissions out of band.

9.3.3 RBW 1MHz, VBW 3MHz, peak detector for peak value, RBW 1MHz, VBW 10Hz, RMS detector for AV value.

9.4. Test Results

Test Date : 2024.06.15					Temperature : 26℃			
Test Engineer : Jensen Wang					Humidity : 54%			
Test Results : PASS								
Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11b TX 2412MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	71.43	-21.62	49.81	74.00	-24.19	Peak
2	2390	H	--	-21.62	--	54.00	--	Avg
3	2400	H	76.00	-26.08	49.92	74.00	-24.08	Peak
4	2400	H	--	-26.08	--	54.00	--	Avg
1	2390	V	67.67	-21.62	46.05	74.00	-27.95	Peak
2	2390	V	--	-21.62	--	54.00	--	Avg
3	2400	V	76.26	-26.08	50.18	74.00	-23.82	Peak
4	2400	V	--	-26.08	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11b TX 2462MHz								
1	2483.5	H	75.13	-25.84	49.29	74.00	-24.71	Peak
2	2483.5	H	--	-25.84	--	54.00	--	Avg
1	2483.5	V	72.79	-25.84	46.95	74.00	-27.05	Peak
2	2483.5	V	--	-25.84	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11g TX 2412MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	73.78	-21.62	52.16	74.00	-21.84	Peak
2	2390	H	--	-21.62	--	54.00	--	Avg
3	2400	H	76.15	-26.08	50.07	74.00	-23.93	Peak
4	2400	H	--	-26.08	--	54.00	--	Avg
1	2390	V	67.87	-21.62	46.25	74.00	-27.75	Peak
2	2390	V	--	-21.62	--	54.00	--	Avg
3	2400	V	79.14	-26.08	53.06	74.00	-20.94	Peak
4	2400	V	--	-26.08	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11g TX 2462MHz								
1	2483.5	H	76.85	-25.84	51.01	74.00	-22.99	Peak
2	2483.5	H	--	-25.84	--	54.00	--	Avg
1	2483.5	V	74.96	-25.84	49.12	74.00	-24.88	Peak
2	2483.5	V	--	-25.84	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Frequency Range : 2310MHz~2410MHz								
Test Mode : IEEE 802.11n/HT20 TX 2412MHz								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	71.53	-21.62	49.91	74.00	-24.09	Peak
2	2390	H	--	-21.62	--	54.00	--	Avg
3	2400	H	75.24	-26.08	49.16	74.00	-24.84	Peak
4	2400	H	--	-26.08	--	54.00	--	Avg
1	2390	V	70.61	-21.62	48.99	74.00	-25.01	Peak
2	2390	V	--	-21.62	--	54.00	--	Avg
3	2400	V	77.11	-26.08	51.03	74.00	-22.97	Peak
4	2400	V	--	-26.08	--	54.00	--	Avg
Frequency Range : 2450MHz~2550MHz								
Test Mode : IEEE 802.11n/HT20 TX 2462MHz								
1	2483.5	H	73.79	-25.84	47.95	74.00	-26.05	Peak
2	2483.5	H	--	-25.84	--	54.00	--	Avg
1	2483.5	V	73.81	-25.84	47.97	74.00	-26.03	Peak
2	2483.5	V	--	-25.84	--	54.00	--	Avg
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.							

10. Antenna Requirement

10.1. Standard Requirement


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2. Antenna Connected Construction

The antenna connector is unique antenna and no consideration of replacement. Please see EUT photo for details.

10.3. Results

The EUT antenna is internal antenna. a. It complies with the standard requirement.



11. Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

12. Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

----- END OF REPORT-----

