

MPE Calculation / RF Exposure

Product: LTE-V2X-OB

Applicant: Ettifos Co.

Model: ETF-PRO-OC02

Address: 405, 41, Beolmal-ro 50beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, South Korea

FCC ID: 2BHJL-ETF-PRO-OC02

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310 is listed in below table. According to FCC §1.1310: the criteria listed in the following tables shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Prediction Prediction of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

Classification The antenna of this product is at least 20 cm away from the body of the user. So this product is classified as mobile device.

Frequency (GHz)	Max. Tune up EIRP		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
	(dBm)	(mW)			
5.915	24	251.19	20	0.04997	1

Note1) The Max. Tune up EIRP value includes an antenna gain of 9dBi.

Note2) The EUT does not support transmit MIMO.

Results: Compliant

This confirms compliance to the required radio frequency radiation exposure limit of 1.0 mW/cm² at 20 cm operation.