

RF Exposure evaluation

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance v06

FCC Part 2 §2.1091

FCC ID: 2BHJP-CXZ502

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
BT	Antenna 0	PCB Antenna	2402MHz-2480MHz	-2.23dBi
5.2G Wifi	Antenna 0	PCB Antenna	5180MHz~5240MHz	3.08dBi
5.8G Wifi	Antenna 0	PCB Antenna	5725MHz~5850MHz	5.12dBi

5. Manufacturing Tolerance

BT GFSK(Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	4.0	4.0	3.0
Tolerance ±(dB)	1.0	1.0	1.0
BT π /4 DQPSK (Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	6.0	6.0	6.0
Tolerance ±(dB)	1.0	1.0	1.0
BT 8DPSK (Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	7.0	7.0	6.0
Tolerance ±(dB)	1.0	1.0	1.0
BT LE GFSK(Peak)			
Channel	Channel 00	Channel 39	Channel 78
Target (dBm)	4.0	4.0	4.0
Tolerance ±(dB)	1.0	1.0	1.0

5.2G WLAN

IEEE 802.11A (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	12.0	12.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n20 (Average)			
Frequency (MHz)	5180	5200	5240
Target (dBm)	12.0	12.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n40 (Average)			
Frequency (MHz)	5190	/	5230
Target (dBm)	10.0	/	10.0
Tolerance $\pm$ (dB)	1.0	/	1.0

5.8G WLAN

IEEE 802.11A (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	11.0	10.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n20 (Average)			
Frequency (MHz)	5745	5785	5825
Target (dBm)	11.0	10.0	8.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n40 (Average)			
Frequency (MHz)	5755	/	5795
Target (dBm)	8.0	/	7.0
Tolerance $\pm$ (dB)	1.0	/	1.0

6. Evaluation Results for Standalone

6.1 Standalone MPE

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
BT	8.0	6.3096	-2.23	0.5984	0.0008	1.0000
BLE	5.0	3.1623	-2.23	0.5984	0.0004	1.0000
5.2GWIFI	14.0	25.1189	3.08	2.0324	0.0102	1.0000
5.8GWIFI	12.0	15.8489	5.12	3.2509	0.0103	1.0000

Remark:

1. Output power (Peak) including turn-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer.

7. Simultaneous MPE Result

The product's Bluetooth and wifi use the same RF module and the same antenna, there is no need to consider synchronous transmission issues.

8. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

