





FCC Test Report

Report No.: AGC15705241026FR01

FCC ID : 2BHJX-ATS50GR2424

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: REMOTE

BRAND NAME : N/A

MODEL NAME : DR-ATS50G, DR-STP51G, DR-UHG50G,

DR-UHG51G

APPLICANT: Shenzhen Ameta Technology Co., Ltd.

DATE OF ISSUE : Jul. 23, 2025

STANDARD(S) : FCC Part 15 Subpart C §15.249

REPORT VERSION: V1.0

Attestation Of Global Conce (Shenzhen) Co., Ltd



Page 2 of 44


Report Revise Record

| Report Version | Revise Time | Issued Date | Valid Version | Notes | |
|----------------|-------------|---------------|---------------|-----------------|--|
| V1.0 | / | Jul. 23, 2025 | Valid | Initial Release | |



Table of Contents

| 1. General Information | 4 |
|---|----|
| 2. Product Information | 5 |
| 2.1 Product Technical Description | 5 |
| 2.2 Test Frequency List | 6 |
| 2.3 Related Submittal(S) / Grant (S) | 7 |
| 2.4 Test Methodology | 7 |
| 2.5 Antenna Requirement | 7 |
| 3. Test Environment | 8 |
| 3.1 Address of the Test Laboratory | 8 |
| 3.2 Test Facility | 8 |
| 3.3 Environmental Conditions | 9 |
| 3.4 Measurement Uncertainty | 9 |
| 3.5 List of Equipment Use | 10 |
| 4.System Test Configuration | 12 |
| 4.1 EUT Configuration | 12 |
| 4.2 EUT Exercise | 12 |
| 4.3 Configuration of Tested System | 12 |
| 4.4 Equipment Used In Tested System | 13 |
| 4.5 Summary of Test Results | 14 |
| 5. Description of Test Modes | 15 |
| 6. Duty Cycle Measurement | 16 |
| 7. 20dB Bandwidth Measurement | 17 |
| 7.1 Provisions Applicable | 17 |
| 7.2 Measurement Procedure | 17 |
| 7.3 Measurement Setup (Block Diagram of Configuration) | 17 |
| 7.4 Measurement Results | 18 |
| 8. Field Strength of Fundamental and Radiated Spurious Emission | 20 |
| 8.1 Measurement Limit | 20 |
| 8.2 Measurement Procedure | 21 |
| 8.3 Measurement Setup (Block Diagram of Configuration) | 24 |
| 8.4 Measurement Result | 25 |
| 9. AC Power Line Conducted Emission | 39 |
| 9.1 Measurement Limit | 39 |
| 9.2 Measurement Setup (Block Diagram of Configuration) | 39 |
| 9.3 Preliminary Procedure of Line Conducted Emission Test | 40 |
| 9.4 Final Procedure of Line Conducted Emission Test | 40 |
| 9.5 Measurement Result | 40 |
| Appendix I: Photographs of Test Setup | 43 |
| Appendix II: Photographs of Test EUT | 43 |





1. General Information

| Shenzhen Ameta Technology Co., Ltd. |
|---|
| 501, BLDG4, Pingshan MinQi Technology Park, No.65 Lishan Road, Pingshan Community, Taoyuan Street, Nanshan District, Shenzhen, Guangdong, China |
| Shenzhen Ameta Technology Co., Ltd. |
| 501, BLDG4, Pingshan MinQi Technology Park, No.65 Lishan Road, Pingshan Community, Taoyuan Street, Nanshan District, Shenzhen, Guangdong, China |
| Shenzhen Ameta Technology Co., Ltd. |
| 501, BLDG4, Pingshan MinQi Technology Park, No.65 Lishan Road, Pingshan Community, Taoyuan Street, Nanshan District, Shenzhen, Guangdong, China |
| REMOTE |
| N/A |
| DR-ATS50G |
| DR-STP50G, DR-STP51G, DR-UHG50G, DR-UHG51G |
| All the same except for the model names. |
| Nov. 11, 2024 |
| Apr. 08, 2025~May 07, 2025 |
| No any deviation from the test method |
| Normal |
| Pass |
| AGCER-FCC-NTX-V1 |
| |

Note: The test results of this report relate only to the tested sample identified in this report.

| Prepared By | Coliti | |
|-------------|-----------------------------------|---------------|
| | Cici Li (Project Engineer) | Jul. 23, 2025 |
| Reviewed By | Bibo zhang | |
| | Bibo Zhang (Reviewer) | Jul. 23, 2025 |
| Approved By | Angole Li | |
| | Angela Li (Authorized Officer) | Jul. 23, 2025 |



Page 5 of 44

2. Product Information

2.1 Product Technical Description

| Equipment Specification | Low Power Short Range Equipment |
|-------------------------------|--|
| Frequency Band | 2400MHz-2483.5MHz |
| Operation Frequency Range | 2410MHz-2470MHz |
| Modulation Type | GFSK |
| Number of channels | 65 |
| Channel Separation | 1MHz |
| Field Strength of Fundamental | 83.38µV/m (Peak) |
| Hardware Version | v2.0 |
| Software Version | V1.0 |
| Antenna Designation | Wire Antenna |
| Antenna Gain | 4.6dBi |
| Power Supply | DC 3.7V by battery or DC 5V by adapter |



2.2 Test Frequency List

| Channel No. | Frequency (GHz) | Channel No. | Frequency (GHz) | Channel No. | Frequency (GHz) |
|-------------|--------------------|-------------|--------------------|-------------|--------------------|
| 01 | 2.410 | 22 | 2.431 | 43 | 2.452 |
| 02 | 2.411 | 23 | 2.432 | 44 | 2.453 |
| 03 | 2.412 | 24 | 2.433 | 45 | 2.454 |
| 04 | 2.413 | 25 | 2.434 | 46 | 2.455 |
| 05 | 2.414 | 26 | 2.435 | 47 | 2.456 |
| 06 | 2.415 | 27 | 2.436 | 48 | 2.457 |
| 07 | 2.416 | 28 | 2.437 | 49 | 2.458 |
| 08 | 2.417 | 29 | 2.438 | 50 | 2.459 |
| 09 | 2.418 | 30 | 2.439 | 51 | 2.460 |
| 10 | 2.419 | 31 | 2.440 | 52 | 2.461 |
| 11 | 2.420 | 32 | 2.441 | 53 | 2.462 |
| 12 | 2.421 | 33 | 2.442 | 54 | 2.463 |
| 13 | 2.422 | 34 | 2.443 | 55 | 2.464 |
| 14 | 2.423 | 35 | 2.444 | 56 | 2.465 |
| 15 | 2.424 | 36 | 2.445 | 57 | 2.466 |
| 16 | 2.425 | 37 | 2.446 | 58 | 2.467 |
| 17 | 2.426 | 38 | 2.447 | 59 | 2.468 |
| 18 | 2.427 | 39 | 2.448 | 60 | 2.469 |
| 19 | 2.428 | 40 | 2.449 | 61 | 2.470 |
| 20 | 2.429 | 41 | 2.450 | | |
| 21 | 2.430 | 42 | 2.451 | | |



Page 7 of 44

2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2BHJX-ATS50GR2424**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

| No. | o. Identity Document Title | | | |
|-----|----------------------------|---|--|--|
| 1 | FCC 47 CFR Part 2 | Frequency allocations and radio treaty matters; general rules and regulations | | |
| 2 | FCC 47 CFR Part 15 | Radio Frequency Devices | | |
| 3 | ANSI C63.10-2013 | American National Standard for Testing Unlicensed Wireless Devices | | |

2.5 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 4.6 dBi.



Page 8 of 44

3. Test Environment

3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.






3.3 Environmental Conditions

| | Normal Conditions |
|-------------------------|--------------------|
| Temperature range (℃) | 15 - 35 |
| Relative humidity range | 20 % - 75 % |
| Pressure range (kPa) | 86 - 106 |
| Power supply | DC 3.7V by battery |

3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%

| Item | Measurement Uncertainty |
|---|----------------------------|
| Uncertainty of Conducted Emission for AC Port | $U_c = \pm 2.9 \text{ dB}$ |
| Uncertainty of Radiated Emission below 1GHz | $U_c = \pm 3.9 \text{ dB}$ |
| Uncertainty of Radiated Emission above 1GHz | $U_c = \pm 4.9 \text{ dB}$ |
| Uncertainty of total RF power, conducted | $U_c = \pm 0.8 \text{ dB}$ |
| Uncertainty of RF power density, conducted | $U_c = \pm 2.6 \text{ dB}$ |
| Uncertainty of spurious emissions, conducted | $U_c = \pm 2 \%$ |
| Uncertainty of Occupied Channel Bandwidth | $U_c = \pm 2 \%$ |






3.5 List of Equipment Use

| • F | RF Conducted Test System | | | | | | | | |
|-------------|--------------------------|------------------------|---------------|---------------|------------|------------------------------|------------------------------|--|--|
| Used | Equipment No. | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) | | |
| \boxtimes | AGC-ER-E036 | Spectrum Analyzer | Agilent | N9020A | MY49100060 | 2024-05-24 | 2025-05-23 | | |
| \boxtimes | AGC-ER-A007 | 6dB Fixed Attenuator | Mini circuits | BW-S6-2W263A+ | N/A | 2025-01-30 | 2026-01-29 | | |
| \boxtimes | N/A | RF Connection Cable | N/A | 1# | N/A | Each time | N/A | | |
| | N/A | RF Connection Cable | N/A | 2# | N/A | Each time | N/A | | |

| • F | Radiated Spurious Emission | | | | | | | |
|-------------|----------------------------|----------------------------------|--------------|------------|------------|------------------------------|------------------------------|--|
| Used | Equipment No. | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) | |
| \boxtimes | AGC-EM-E046 | EMI Test Receiver | R&S | ESCI | 10096 | 2025-01-14 | 2026-01-13 | |
| | AGC-EM-E116 | EMI Test Receiver | R&S | ESCI | 100034 | 2024-05-24 | 2025-05-23 | |
| | AGC-EM-E061 | Spectrum Analyzer | Agilent | N9010A | MY53470504 | 2024-05-28 | 2025-05-27 | |
| \boxtimes | AGC-EM-E086 | Loop Antenna | ZHINAN | ZN30900C | 18051 | 2024-03-05 | 2026-03-04 | |
| \boxtimes | AGC-EM-E001 | Wideband Antenna | SCHWARZBECK | VULB9168 | D69250 | 2025-03-14 | 2027-03-13 | |
| | AGC-EM-E029 | Broadband Ridged Horn Antenna | ETS | 3117 | 00034609 | 2025-03-27 | 2026-03-26 | |
| \boxtimes | AGC-EM-E082 | Horn Antenna | SCHWARZBECK | BBHA 9170 | #768 | 2023-09-24 | 2025-09-23 | |
| \boxtimes | AGC-EM-E146 | Pre-amplifier | ETS | 3117-PA | 00246148 | 2024-07-24 | 2026-07-23 | |
| \boxtimes | AGC-EM-A119 | 2.4G Filter | SongYi | N/A | N/A | 2024-05-23 | 2025-05-22 | |
| | AGC-EM-A138 | 6dB Attenuator | Eeatsheep | LM-XX-6-5W | N/A | 2023-06-09 | 2025-06-08 | |
| | AGC-EM-A139 | 6dB Attenuator | Eeatsheep | LM-XX-6-5W | N/A | 2023-06-09 | 2025-06-08 | |

| A | AC Power Line Conducted Emission | | | | | | | | |
|---------------------|----------------------------------|-------------------|--------------|------------|------------|------------------------------|------------------------------|--|--|
| Used | Equipment No. | Test Equipment | Manufacturer | Model No. | Serial No. | Last Cal. Date (YY-MM-DD) | Next Cal. Date (YY-MM-DD) | | |
| \boxtimes | AGC-EM-E116 | EMI Test Receiver | R&S | ESCI | 100034 | 2024-05-24 | 2025-05-23 | | |
| \boxtimes | AGC-EM-E023 | AMN | R&S | 100086 | ESH2-Z5 | 2024-05-28 | 2025-05-27 | | |
| \boxtimes | AGC-EM-A130 | 6dB Attenuator | Eeatsheep | LM-XX-6-5W | DC-6GZ | 2023-06-09 | 2025-06-08 | | |





| • Te | Test Software | | | | | | | |
|-------------|---------------|---------------------|---------------------|----------------------|---------|--|--|--|
| Used | Equipment No. | Model No. | Version Information | | | | | |
| \boxtimes | AGC-EM-S001 | CE Test System | R&S | ES-K1 | V1.71 | | | |
| \boxtimes | AGC-EM-S003 | RE Test System | FARA | EZ-EMC | VRA-03A | | | |
| \boxtimes | AGC-ER-S012 | BT/WIFI Test System | Tonscend | JS1120-2 | 2.6 | | | |
| \boxtimes | AGC-EM-S011 | RSE Test System | Tonscend | TS+-Ver2.1(JS36-RSE) | 4.0.0.0 | | | |



4.System Test Configuration

4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:





Page 13 of 44

4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

| N | lo. | Equipment | Model No. | Manufacturer | Specification Information | Cable |
|---|-----|-----------|-----------|--------------|--|--------------------|
| , | 1 | Adapter | Huawei | HW-200440C00 | Input(AC):100V-240V 50/60Hz 2.4A Output(DC):USB-C(5V/3A;9V/3A;10V/4A;11V/ 6A;12V/3A;15V/3A;20V4.4A) USB-A(5V/2A;10V/4A;11V/6A;20V/4.4A) | 1.0m unshielded |

☐ Test Accessories Come From The Manufacturer

| No. | Equipment | Model No. | Manufacturer | Specification Information | Cable |
|-----|-----------|-----------|--------------|---------------------------|-------|
| 1 | | | | | |



Page 14 of 44

4.5 Summary of Test Results

| Item | FCC Rules Description of Test | | Result |
|------|--|----------------------------------|--------|
| 1 | §15.203 | Antenna Equipment | Pass |
| 2 | §15.249(a) Field Strength of Fundamental | | Pass |
| 3 | §15.209&§15.249(d) | Radiated Emission& Band Edge | Pass |
| 4 | §15.205 | Restricted Bands of Operation | Pass |
| 5 | §15.215 | 20dB Bandwidth | Pass |
| 6 | §15.207 | AC Power Line Conducted Emission | Pass |




Page 15 of 44

5. Description of Test Modes

| Summary Table of Test Cases | | | | |
|---------------------------------|--|--|--|--|
| Test Item | Equipment type / Modulation | | | |
| rest item | Short Distance and Low Power Consumption/ GFSK | | | |
| | Mode 1: Normal Transmission on channel 01 (Battery powered or AC/DC adapter) | | | |
| Radiated & Conducted Test Cases | Mode 2: Normal Transmission on channel 31 (Battery powered or AC/DC adapter) | | | |
| | Mode 3: Normal Transmission on channel 61 (Battery powered or AC/DC adapter) | | | |
| AC Conducted Emission | 2.4G play+Battery + USB Cable (Charging from AC Adapter) | | | |

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- The battery is full-charged during the test.
- 3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
- The fixed-frequency transmission of the prototype is debugged through the buttons or software declared by the manufacturer.
- The manufacturer of RF external cable claims that the cable loss is 0.5dB, and the cable loss and attenuator have been compensated into the Corrections Configuration of measuring equipment.
- 7. Input correction factor includes external cable loss and attenuator amplitude compensation. The formula is: Input compensation coefficient (dB) = Cable Loss (dB) + Attenuator attenuation value (dB)






6. Duty Cycle Measurement

The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

| Operating mode | T(µs) | Duty Cycle (%) | Duty Cycle Factor (dB) | 1/ T Minimum VBW (kHz) |
|----------------|-------|-------------------|---------------------------|---------------------------|
| GFSK_2410MHz | 1680 | 16.78 | 7.75 | 0.60 |
| GFSK_2440MHz | 1680 | 16.78 | 7.75 | 0.60 |
| GFSK_2470MHz | 1680 | 16.78 | 7.75 | 0.60 |

Remark: Duty Cycle factor = 10 * log (1/ Duty cycle)

The test plots as follows:



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 17 of 44

7. 20dB Bandwidth Measurement


7.1 Provisions Applicable

N/A

7.2 Measurement Procedure

- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss
 was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 30 kHz. Set the Video bandwidth (VBW) = 100 kHz. In order to make an accurate measurement.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 5. Measure and record the results in the test report.

7.3 Measurement Setup (Block Diagram of Configuration)







7.4 Measurement Results

| Test Data of Occupied Bandwidth and -20dB Bandwidth | | | | | | | |
|---|-------------------------|--------------------------|-----------------------------|-----------------|--------------|--|--|
| Test Mode | Test Frequency (MHz) | Occupied Bandwidth (MHz) | -20dB Bandwidth (MHz) | Limits (MHz) | Pass or Fail | | |
| GFSK | 2410 | 3.6214 | 3.452 | N/A | Pass | | |
| | 2440 | 4.0898 | 3.973 | N/A | Pass | | |
| | 2470 | 4.4185 | 4.949 | N/A | Pass | | |

Test Graphs of Occupied Bandwidth and -20 Bandwidth







Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 20 of 44

8. Field Strength of Fundamental and Radiated Spurious Emission

8.1 Measurement Limit

15.249 Limit in the below table has to be followed:

| Francisco Danas | Field Strength of Fundamental | Field Strength of Harmonics |
|-----------------|-------------------------------|-----------------------------|
| Frequency Range | (millivolts/meter) | (microvolts/meter) |
| 900-928MHz | 50 | 500 |
| 2400-2483.5MHz | 50 | 500 |
| 5725-5875MHz | 50 | 500 |
| 24.0-24.25GHz | 250 | 2500 |

15.209 Limit in the below table has to be followed:

| Frequency Range | Distance | Field Strengths Limit | | | |
|-----------------|----------|--|----------|--|--|
| (MHz) | Meters | μV/m | dB(μV)/m | | |
| 0.009 ~ 0.490 | 300 | 2400/F(kHz) | | | |
| 0.490 ~ 1.705 | 30 | 24000/F(kHz) | | | |
| 1.705 ~ 30 | 30 | 30 | | | |
| 30 ~ 88 | 3 | 100 | 40.0 | | |
| 88 ~ 216 | 3 | 150 | 43.5 | | |
| 216 ~ 960 | 3 | 200 | 46.0 | | |
| 960 ~ 1000 | 3 | 500 | 54.0 | | |
| Above 1000 | 3 | Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average) | | | |

Remark:

- 1) Emission level dB μ V = 20 log Emission level μ V/m.
- 2) The smaller limit shall apply at the cross point between two frequency bands.
- Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.



Page 21 of 44

8.2 Measurement Procedure

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



Page 22 of 44

■ The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting | | | |
|-----------------------|---|--|--|--|
| Start ~Stop Frequency | 9kHz~150kHz/RB 200Hz for QP | | | |
| Start ~Stop Frequency | 150kHz~30MHz/RB 9kHz for QP | | | |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120kHz for QP | | | |
| Start ~Stop Frequency | 1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average | | | |

| Receiver Parameter | Setting | | |
|-----------------------|--------------------------------|--|--|
| Start ~Stop Frequency | 9kHz~150kHz/RB 200Hz for QP | | |
| Start ~Stop Frequency | 150kHz~30MHz/RB 9kHz for QP | | |
| Start ~Stop Frequency | 30MHz~1000MHz/RB 120kHz for QP | | |

- The following is the test setup of Field Strength of Fundamental:
 - > Peak detection: RBW is greater than the main frequency OBW, VBW=50MHz / Sweep=AUTO
 - Average detection: RBW is greater than the main frequency OBW, VBW=50MHz / Sweep=AUTO
- The following is the test setup of Band Edge:

The EUT operates at transmitting mode. The operate channel is tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.

- Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - Peak detection: RBW=1MHz, VBW=3MHz / Sweep=AUTO
 - Average detection: RBW=1MHz; VBW=1/T / Sweep=AUTO (Duty cycle is less than 98%)
 - Average detection: RBW=1MHz; VBW=3M / Sweep=AUTO
 - Other procedures refer to clause 7.2.



Report No.: AGC15705241026FR01 Page 23 of 44

Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize


Average Measurements above 1GHz (Method VB)

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW setting requirements are as follows:
- 4. If the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10 Hz.
- 5. If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.
- 6. Detector = Peak
- 7. Sweep time = auto
- 8. Trace mode = max hold
- 8. Trace was allowed to stabilize




8.3 Measurement Setup (Block Diagram of Configuration)


Radiated Emission Test Setup 9KHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 25 of 44

8.4 Measurement Result

Field Strength of Fundamental

| EUT Name | | REMOTE I | | Model Name | Model Name | | DR-ATS50G | |
|--------------------|-------------------------------|---------------------------|---------------------------|----------------------------|-------------------|------------------|------------|--|
| Temperature | | 22.5°C | | Relative Humid | Relative Humidity | | 57.6% | |
| Pressure | | 960hPa | | Test Voltage | | DC 3.7V b | y battery | |
| Test Mode | | Mode 1/2/3 | | Antenna Polar | ity | Horizontal | / Vertical | |
| | | | Pea | k Value | | | | |
| Frequency (MHz) | Measured Level@3m (dBµV/m) | | Correction Factor dB/m | Field Strength (dBµV/m) | | it @3m sµV/m) | Polarity | |
| 2410 | | 93.18 | -10.06 | 83.12 | 11 | 14.00 | Horizontal | |
| 2410 | | 82.50 | -10.06 | 72.44 | 11 | 14.00 | Vertical | |
| 2440 | | 92.37 | -10.21 | 82.16 | 114.00 | | Horizontal | |
| 2440 | | 81.71 | -10.21 | 71.50 | 114.00 | | Vertical | |
| 2470 | 93.97 | | -10.59 | 83.38 | 114.00 | | Horizontal | |
| 2470 | | 84.62 | -10.59 | 74.03 | 114.00 | | Vertical | |
| | | | Avera | ge Value | | | | |
| Frequency (MHz) | Meas | ured Level@3m (dBµV/m) | Correction Factor dB/m | Field Strength (dBµV/m) | | it @3m sµV/m) | Polarity | |
| 2410 | | 88.18 | -10.06 | 78.12 | 94.00 | | Horizontal | |
| 2410 | | 77.48 | -10.06 | 67.42 | 94.00 | | Vertical | |
| 2440 | 86.77 | | -10.21 | 76.56 | 94.00 | | Horizontal | |
| 2440 | 76.44 | | -10.21 | 66.23 | 9 | 4.00 | Vertical | |
| 2470 | 88.64 | | -10.59 | 78.05 | 94.00 | | Horizontal | |
| 2470 | | 77.93 | -10.59 | 67.34 | 9 | 4.00 | Vertical | |

RESULT: Pass


Note: Corr. Factor= Antenna Factor (dB/m) + Cable Loss (dB)




Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20dB below the permissible value need not be reported.

| Radiated Emission Test Results at 30MHz-1GHz | | | | | | | |
|--|--------|-------------------|--------------------|--|--|--|--|
| EUT Name | REMOTE | Model Name | DR-ATS50G | | | | |
| Temperature | 22.5℃ | Relative Humidity | 57.6% | | | | |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery | | | | |
| Test Mode | Mode 1 | Antenna Polarity | Horizontal | | | | |




| Final I | Data List | | | | | | | |
|---------|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|------------|
| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
| 1 | 60.07 | 21.97 | 17.86 | 40.00 | 18.03 | 100 | 110 | Horizontal |
| 2 | 102.75 | 21.98 | 16.93 | 43.50 | 21.52 | 100 | 140 | Horizontal |
| 3 | 159.98 | 21.49 | 17.81 | 43.50 | 22.01 | 100 | 100 | Horizontal |
| 4 | 459.71 | 28.74 | 24.69 | 46.00 | 17.26 | 100 | 200 | Horizontal |
| 5 | 616.85 | 30.62 | 25.58 | 46.00 | 15.38 | 100 | 180 | Horizontal |
| 6 | 860.32 | 35.23 | 30.00 | 46.00 | 10.77 | 100 | 130 | Horizontal |





| Radiated Emission Test Results at 30MHz-1GHz | | | | | | | |
|--|--------|-------------------|--------------------|--|--|--|--|
| EUT NameREMOTEModel NameDR-ATS50G | | | | | | | |
| Temperature | 22.5℃ | Relative Humidity | 57.6% | | | | |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery | | | | |
| Test Mode | Mode 1 | Antenna Polarity | Vertical | | | | |



Final Data List

| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|-------------|--------------|----------|
| 1 | 68.8 | 26.79 | 15.04 | 40.00 | 13.21 | 100 | 150 | Vertical |
| 2 | 141.55 | 27.06 | 16.13 | 43.50 | 16.44 | 100 | 200 | Vertical |
| 3 | 234.67 | 22.44 | 15.03 | 46.00 | 23.56 | 100 | 80 | Vertical |
| 4 | 463.59 | 28.40 | 23.86 | 46.00 | 17.60 | 100 | 230 | Vertical |
| 5 | 619.76 | 30.56 | 25.90 | 46.00 | 15.44 | 100 | 100 | Vertical |
| 6 | 900.09 | 35.66 | 30.27 | 46.00 | 10.34 | 100 | 120 | Vertical |

RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.



Page 28 of 44

Radiated Emissions Test Results for Above 1GHz

| EUT Name | REMOTE | Model Name | DR-ATS50G |
|-------------|--------|-------------------|--------------------|
| Temperature | 22.5℃ | Relative Humidity | 57.6% |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery |
| Test Mode | Mode 1 | Antenna Polarity | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type | |
|-----------|---------------|--------|----------------|----------|--------|--------------|--|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | - Value Type | |
| 4820.000 | 46.56 | 0.08 | 46.64 | 74 | -27.36 | peak | |
| 4820.000 | 37.64 | 0.08 | 37.72 | 54 | -16.28 | AVG | |
| 7230.000 | 41.87 | 2.21 | 44.08 | 74 | -29.92 | peak | |
| 7230.000 | 32.14 | 2.21 | 34.35 | 54 | -19.65 | AVG | |
| | | | | | | | |
| | | | | | | | |

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

| EUT Name | REMOTE | Model Name | DR-ATS50G |
|-------------|--------|-------------------------|--------------------|
| Temperature | 22.5℃ | Relative Humidity 57.6% | |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery |
| Test Mode | Mode 1 | Antenna Polarity | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Tree |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | Value Type |
| 4820.000 | 46.80 | 0.08 | 46.88 | 74 | -27.12 | peak |
| 4820.000 | 37.82 | 0.08 | 37.90 | 54 | -16.10 | AVG |
| 7230.000 | 41.02 | 2.21 | 43.23 | 74 | -30.77 | peak |
| 7230.000 | 32.96 | 2.21 | 35.17 | 54 | -18.83 | AVG |
| | | | | | | |
| | | | | | | |

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 29 of 44

Radiated Emissions Test Results for Above 1GHz

| EUT Name | REMOTE | Model Name | DR-ATS50G |
|-------------|--------|-------------------|--------------------|
| Temperature | 22.5℃ | Relative Humidity | 57.6% |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery |
| Test Mode | Mode 2 | Antenna Polarity | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | Value Type |
| 4880.000 | 46.38 | 0.08 | 46.46 | 74 | -27.54 | peak |
| 4880.000 | 37.32 | 0.08 | 37.40 | 54 | -16.60 | AVG |
| 7320.000 | 41.46 | 2.21 | 43.67 | 74 | -30.33 | peak |
| 7320.000 | 32.43 | 2.21 | 34.64 | 54 | -19.36 | AVG |
| | | | | | | |
| | | | | | | |

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| EUT Name | REMOTE | Model Name | DR-ATS50G |
|-------------|--------|-------------------|--------------------|
| Temperature | 22.5℃ | Relative Humidity | 57.6% |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery |
| Test Mode | Mode 2 | Antenna Polarity | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type | |
|-----------|---------------|--------|----------------|----------|--------|------------|--|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type | |
| 4880.000 | 46.60 | 0.08 | 46.68 | 74 | -27.32 | peak | |
| 4880.000 | 37.75 | 80.0 | 37.83 | 54 | -16.17 | AVG | |
| 7320.000 | 41.41 | 2.21 | 43.62 | 74 | -30.38 | peak | |
| 7320.000 | 32.58 | 2.21 | 34.79 | 54 | -19.21 | AVG | |
| | | | | | | | |
| | | | | | | | |
| Remark: | | | | | | | |

RESULT: Pass



Page 30 of 44

Radiated Emissions Test Results for Above 1GHz

| EUT Name | REMOTE | Model Name | DR-ATS50G |
|-------------|--------|-------------------|--------------------|
| Temperature | 22.5℃ | Relative Humidity | 57.6% |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery |
| Test Mode | Mode 3 | Antenna Polarity | Horizontal |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4940.000 | 46.88 | 80.0 | 46.96 | 74 | -27.04 | peak |
| 4940.000 | 37.63 | 80.0 | 37.71 | 54 | -16.29 | AVG |
| 7410.000 | 41.51 | 2.21 | 43.72 | 74 | -30.28 | peak |
| 7410.000 | 32.54 | 2.21 | 34.75 | 54 | -19.25 | AVG |
| | | | | | | |
| | | | | | | |

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

| EUT Name | REMOTE | Model Name | DR-ATS50G |
|-------------|--------|-------------------|--------------------|
| Temperature | 22.5℃ | Relative Humidity | 57.6% |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery |
| Test Mode | Mode 3 | Antenna Polarity | Vertical |

| Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Value Type |
|-----------|---------------|--------|----------------|----------|--------|------------|
| (MHz) | (dBµV) | (dB) | (dBµV/m) | (dBµV/m) | (dB) | value Type |
| 4940.000 | 46.54 | 0.08 | 46.62 | 74 | -27.38 | peak |
| 4940.000 | 37.88 | 0.08 | 37.96 | 54 | -16.04 | AVG |
| 7410.000 | 41.28 | 2.21 | 43.49 | 74 | -30.51 | peak |
| 7410.000 | 32.76 | 2.21 | 34.97 | 54 | -19.03 | AVG |
| | | | | | | |
| | | | | | | |


Remark

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass

Note:

- The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.







Band Edge Emission Test Results for Restricted Bands

| EUT Name | REMOTE | Model Name | DR-ATS50G |
|-------------|--------|-------------------|--------------------|
| Temperature | 22.5℃ | Relative Humidity | 57.6% |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery |
| Test Mode | Mode 1 | Antenna Polarity | Horizontal |

Test Graph for Peak Measurement




| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|------------|
| 1 | 2390 | 49.95 | 34.40 | 74.00 | 24.05 | 150 | 101 | Horizontal |
| 2 | 2402.012012 | 52.06 | 34.43 | 74.00 | 21.94 | 150 | 245 | Horizontal |
| 3 | 2410.3003 | 82.81 | 34.46 | 114.00 | 31.39 | 150 | 253 | Horizontal |






Test Graph for Average Measurement



| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-----------------------|----------------|-------------------|----------------|----------------|--------------|------------|
| 1 | 2390 | 37.83 | 34.40 | 54.00 | 16.17 | 150 | 353 | Horizontal |
| 2 | 2402.012012 | 41.53 | 34.43 | 54.00 | 12.47 | 150 | 245 | Horizontal |
| 3 | 2410.06006 | 77.80 | 34.46 | 94.00 | 16.20 | 150 | 254 | Horizontal |

RESULT: Pass







Band Edge Emission Test Results for Restricted Bands

| EUT Name | REMOTE | Model Name | DR-ATS50G |
|-------------|--------|-------------------|--------------------|
| Temperature | 22.5℃ | Relative Humidity | 57.6% |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery |
| Test Mode | Mode 1 | Antenna Polarity | Vertical |

Test Graph for Peak Measurement




| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|----------|
| 1 | 2390 | 48.94 | 34.40 | 74.00 | 25.06 | 150 | 336 | Vertical |
| 2 | 2402.012012 | 50.16 | 34.43 | 74.00 | 23.84 | 150 | 91 | Vertical |
| 3 | 2410.3003 | 71.81 | 34.46 | 114.00 | 42.19 | 150 | 91 | Vertical |






Test Graph for Average Measurement



| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|----------|
| 1 | 2390 | 37.75 | 34.40 | 54.00 | 16.25 | 150 | 56 | Vertical |
| 2 | 2402.012012 | 39.01 | 34.43 | 54.00 | 14.99 | 150 | 78 | Vertical |
| 3 | 2410 | 66.10 | 34.46 | 94.00 | 27.90 | 150 | 86 | Vertical |

RESULT: Pass






Band Edge Emission Test Results for Restricted Bands

| EUT Name | REMOTE | Model Name | DR-ATS50G |
|-------------|--------|-------------------|--------------------|
| Temperature | 22.5℃ | Relative Humidity | 57.6% |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery |
| Test Mode | Mode 3 | Antenna Polarity | Horizontal |


Test Graph for Peak Measurement



| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|------------|
| 1 | 2469.72973 | 82.36 | 34.63 | 114.00 | 31.64 | 150 | 239 | Horizontal |
| 2 | 2483.533534 | 68.74 | 34.66 | 74.00 | 5.26 | 150 | 49 | Horizontal |




Test Graph for Average Measurement



| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|------------|
| 1 | 2470.08008 | 77.54 | 34.63 | 94.00 | 16.46 | 150 | 238 | Horizontal |
| 2 | 2483.533534 | 40.57 | 34.66 | 54.00 | 13.43 | 150 | 86 | Horizontal |

RESULT: Pass







Band Edge Emission Test Results for Restricted Bands

| EUT Name | REMOTE | Model Name | DR-ATS50G |
|-------------|--------|-------------------|--------------------|
| Temperature | 22.5℃ | Relative Humidity | 57.6% |
| Pressure | 960hPa | Test Voltage | DC 3.7V by battery |
| Test Mode | Mode 3 | Antenna Polarity | Vertical |

Test Graph for Peak Measurement




| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|----------|
| 1 | 2470.29029 | 73.00 | 34.63 | 114.00 | 41.00 | 150 | 198 | Vertical |
| 2 | 2483.533534 | 57.59 | 34.66 | 74.00 | 16.41 | 150 | 198 | Vertical |





Test Graph for Average Measurement



| NO. | Freq. [MHz] | Level [dBµV/m] | Factor [dB] | Limit [dBµV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|----------|
| 1 | 2470.045045 | 67.20 | 34.63 | 94.00 | 26.80 | 150 | 194 | Vertical |
| 2 | 2483.533534 | 40.04 | 34.66 | 54.00 | 13.96 | 150 | 30 | Vertical |

RESULT: Pass

Note:

- 1) Factor=Antenna Factor + Cable loss Amplifier gain. Field Strength=Factor + Reading level
- 2) The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μ V) to represent the Amplitude. Use the F dB(μ V/m) to represent the Field Strength. So A=F.



9. AC Power Line Conducted Emission


9.1 Measurement Limit

| Eraguanav | Maximum RF Line Voltage | | | | |
|---------------|-------------------------|----------------|--|--|--|
| Frequency | Q.P. (dBµV) | Average (dBµV) | | | |
| 150kHz~500kHz | 66-56 | 56-46 | | | |
| 500kHz~5MHz | 56 | 46 | | | |
| 5MHz~30MHz | 60 | 50 | | | |

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

9.2 Measurement Setup (Block Diagram of Configuration)





Page 40 of 44

9.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


9.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

9.5 Measurement Result







MEASUREMENT RESULT: "agc fin"

| 2025/4/28 | 21:32 | 2 | | | | | |
|-----------|-------|-------|--------|-------|--------|----------|------|
| Frequen | су | Level | Transd | Limit | Margin | Detector | Line |
| M | Hz | dΒμV | dB | dΒμV | dB | | |
| | | | | | | | |

| 0.810000 | 32.00 | 6.2 | 56 | 24.0 | QP | L1 |
|----------|-------|-----|----|------|----|-----|
| 1.058000 | 32.80 | 6.2 | 56 | 23.2 | QP | L1 |
| 1.078000 | 32.70 | 6.2 | 56 | 23.3 | QP | L1 |
| 1.182000 | 33.10 | 6.2 | 56 | 22.9 | QP | L1 |
| 1.306000 | 32.90 | 6.2 | 56 | 23.1 | QP | L1 |
| 1.314000 | 33.20 | 6.2 | 56 | 22.8 | OP | I.1 |


MEASUREMENT RESULT: "agc fin2"

2025/4/28 21:33

| , | | | | | | |
|--|--|---------------------------------|----------------------------|--|----------------------------|----------------------------|
| Frequency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line |
| 0.338000 0.490000 0.778000 0.898000 1.230000 1.698000 | 26.90 27.80 28.60 25.50 26.10 23.50 | 6.1 6.2 6.2 6.2 6.2 | 49 46 46 46 46 | 22.4 18.4 17.4 20.5 19.9 22.5 | AV AV AV AV AV | L1 L1 L1 L1 L1 |
| | | | | | | |

RESULT: Pass






MEASUREMENT RESULT: "agc_fin"

| 2025/4/28 21 | :37 | | | | | |
|--------------|-------|--------|-------|--------|----------|------|
| Frequency | Level | Transd | Limit | Margin | Detector | Line |
| MHz | dBuV | dB | dΒμV | dB | | |
| | | | | | | |
| 0.510000 | 32.30 | 6.2 | 56 | 23.7 | QP | N |
| 0.810000 | 32.70 | 6.2 | 56 | 23.3 | QP | N |
| 0.822000 | 32.90 | 6.2 | 56 | 23.1 | QP | N |
| 0.930000 | 33.20 | 6.2 | 56 | 22.8 | QP | N |
| 1.158000 | 33.70 | 6.2 | 56 | 22.3 | QP | N |
| 1.194000 | 33.80 | 6.2 | 56 | 22.2 | QP | N |

MEASUREMENT RESULT: "agc fin2"

| 2025/4 | /28 21:3 | 7 | | | | | |
|--------|---------------|---------------|--------------|---------------|--------------|----------|------|
| Fre | quency MHz | Level dBµV | Transd dB | Limit dBµV | Margin dB | Detector | Line |
| 0. | 306000 | 27.30 | 6.1 | 50 | 22.8 | AV | N |
| 0. | 778000 | 28.80 | 6.2 | 46 | 17.2 | AV | N |
| 1. | 214000 | 26.20 | 6.2 | 46 | 19.8 | AV | N |
| 2. | 166000 | 21.10 | 6.3 | 46 | 24.9 | AV | N |
| 27. | 610000 | 14.80 | 8.2 | 50 | 35.2 | AV | N |
| 29. | 170000 | 14.60 | 8.3 | 50 | 35.4 | AV | N |
| | | | | | | | |

RESULT: PASS





Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC15705241026AP01

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC15705241026AP02



Page 44 of 44

Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

----End of Report----