











ANT 2:

Conducted Emissions

U-NII 1 and U-NII 3:

TestMode	Freq(MHz)	FreqRange [MHz]	Max. Fre [MHz]	Max. Level [dBm]	Limit [dBm]	Verdict
11a	5180	30~5140	2434.77	-63.83	≤-27	PASS
		5360~27000	25262.31	-57.95	≤-27	PASS
	5220	30~5140	2437.83	-63.55	≤-27	PASS
		5360~27000	25271.69	-58.35	≤-27	PASS
	5240	30~5140	2436.13	-63.3	≤-27	PASS
		5360~27000	26650.87	-57.33	≤-27	PASS
	5745	30~5650	5223.07	-52.77	≤-27	PASS
		5925~27000	26810.33	-57.63	≤-27	PASS
	5785	30~5650	5228.31	-56.46	≤-27	PASS
		5925~27000	26204.77	-58.38	≤-27	PASS
802.11n(HT20)	5180	30~5140	3121.55	-67.39	≤-27	PASS
		5360~27000	26951.67	-58.05	≤-27	PASS
	5220	30~5140	2437.15	-64.84	≤-27	PASS
		5360~27000	26536.18	-57.63	≤-27	PASS
	5240	30~5140	2436.81	-64.03	≤-27	PASS
		5360~27000	26119.25	-56.9	≤-27	PASS
	5745	30~5650	2438.92	-64.6	≤-27	PASS
		5925~27000	25280.28	-57.86	≤-27	PASS
	5785	30~5650	2437.61	-64.43	≤-27	PASS
		5925~27000	25055.48	-57.42	≤-27	PASS
802.11n(HT40)	5190	30~5140	3178.78	-67.35	≤-27	PASS
		5360~27000	24350.54	-57.52	≤-27	PASS
	5230	30~5140	2439.02	-63.37	≤-27	PASS
		5360~27000	26997.11	-57.33	≤-27	PASS
	5755	30~5650	3159.22	-67.8	≤-27	PASS
		5925~27000	26877.06	-57.79	≤-27	PASS
	5795	30~5650	2436.11	-63.31	≤-27	PASS
		5925~27000	26519.49	-57.81	≤-27	PASS
802.11ac(HT20)	5180	30~5140	2638.48	-65.97	≤-27	PASS
		5360~27000	26962.49	-57.55	≤-27	PASS
	5220	30~5140	3030.08	-67.29	≤-27	PASS
		5360~27000	25711.7	-57.52	≤-27	PASS
	5240	30~5140	2436.81	-64.1	≤-27	PASS
		5360~27000	25342.38	-57.82	≤-27	PASS
	5745	30~5650	2439.67	-63.62	≤-27	PASS
		5925~27000	25857.74	-58.14	≤-27	PASS
	5785	30~5650	3171.77	-67.57	≤-27	PASS
		5925~27000	26187.91	-57.48	≤-27	PASS
802.11ac(HT40)	5190	30~5140	3040.3	-67.22	≤-27	PASS
		5360~27000	26982.69	-58.2	≤-27	PASS
	5230	30~5140	2439.54	-64.01	≤-27	PASS
		5360~27000	26158.2	-57.04	≤-27	PASS
	5755	30~5650	2436.3	-63.62	≤-27	PASS
		5925~27000	26614.33	-57.51	≤-27	PASS
	5795	30~5650	2676.83	-67.68	≤-27	PASS
		5925~27000	26652.26	-58.2	≤-27	PASS
802.11ac(HT80)	5210	30~5140	2438.51	-63.7	≤-27	PASS
		5360~27000	26797.31	-57.83	≤-27	PASS
	5775	30~5650	5218.38	-52.45	≤-27	PASS
		5925~27000	26606.6	-57.99	≤-27	PASS
802.11ax(HT20)	5180	30~5140	2434.77	-64.77	≤-27	PASS
		5360~27000	26206.53	-57.98	≤-27	PASS
	5220	30~5140	2435.96	-64.08	≤-27	PASS

	5240	5360~27000	26174.07	-57.39	≤-27	PASS
		30~5140	3148.29	-66.76	≤-27	PASS
		5360~27000	26935.8	-56.96	≤-27	PASS
	5745	30~5650	5214.45	-58.65	≤-27	PASS
		5925~27000	26285.56	-57.04	≤-27	PASS
	5785	30~5650	5214.45	-52.09	≤-27	PASS
		5925~27000	26190.72	-57.21	≤-27	PASS
	5825	30~5650	2437.8	-64.48	≤-27	PASS
5925~27000		26584.82	-57.61	≤-27	PASS	
802.11ax(HT40)	5190	30~5140	2602.37	-67.35	≤-27	PASS
		5360~27000	26375.33	-57.34	≤-27	PASS
	5230	30~5140	3163.11	-67.36	≤-27	PASS
		5360~27000	26023.31	-58.56	≤-27	PASS
	5755	30~5650	5185.98	-62.24	≤-27	PASS
		5925~27000	25261.31	-58.12	≤-27	PASS
	5795	30~5650	3157.34	-67.51	≤-27	PASS
		5925~27000	26579.2	-58.51	≤-27	PASS
802.11ax(HT80)	5210	30~5140	2439.88	-63.33	≤-27	PASS
		5360~27000	26689.83	-58.07	≤-27	PASS
	5775	30~5650	5211.45	-58.02	≤-27	PASS
		5925~27000	26855.29	-57.98	≤-27	PASS



























