

TEST REPORT

Reference No...... : WTD25D02042371W002
FCC ID : 2BHP6-PBW16
Applicant..... : SM TEK GROUP INC
Address..... : 132 32ND ST STE #402 BROOKLYN NY 11232 United States
Manufacturer : SM TEK GROUP INC
Address : 132 32ND ST STE #402 BROOKLYN NY 11232 United States
Product..... : Power bank
Model(s) : WM-PBW16-GY, WM-PBW16-BK, WM-PBW16-WH, PBW16-BK, PBW16-GY, PBW16-WH, PBW6-GY, PBW6-WH, PBW6-BK, PBW6
Standards..... : FCC 47CFR 15.209
Date of Receipt sample : 2025-07-04
Date of Test : 2025-07-11 to 2025-07-16
Date of Issue..... : 2025-07-30
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

Estel Qian

Estel Qian / Project Engineer

Approved by:



Deval Qin / Designated Reviewer

2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	2
3 REVISION HISTORY	3
4 GENERAL INFORMATION	4
4.1 GENERAL DESCRIPTION OF E.U.T.	4
4.2 DETAILS OF E.U.T.	4
4.3 TEST FACILITY	5
4.4 SUBCONTRACTED	5
4.5 ABNORMALITIES FROM STANDARD CONDITIONS	5
4.6 TEST MODE	6
5 TEST SUMMARY	7
6 EQUIPMENT USED DURING TEST	8
6.1 EQUIPMENTS LIST	8
6.2 DESCRIPTION OF SUPPORT UNITS	9
6.3 MEASUREMENT UNCERTAINTY	9
6.4 TEST EQUIPMENT CALIBRATION	9
7 RADIATED SPURIOUS EMISSIONS	10
7.1 EUT OPERATION	10
7.2 TEST SETUP	11
7.3 SPECTRUM ANALYZER SETUP	12
7.4 TEST PROCEDURE	12
7.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	12
7.6 SUMMARY OF TEST RESULTS	13
8 BANDWIDTH MEASUREMENT	21
8.1 TEST PROCEDURE	21
8.2 TEST RESULT	21
9 ANTENNA REQUIREMENT	23
10 RF EXPOSURE	23
11 PHOTOGRAPHS OF TEST SETUP AND EUT	23

3 Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD25D02042371W002	2025-07-04	2025-07-11 to 2025-07-16	2025-07-30	Original	-	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	Power bank
Model(s):	WM-PBW16-GY, WM-PBW16-BK, WM-PBW16-WH, PBW16-BK, PBW16-GY, PBW16-WH, PBW6-GY, PBW6-WH, PBW6-BK, PBW6
Model Description:	Only the model names are different. Model WM-PBW16-GY was tested in the report.
Test Sample No.:	1-1/1
Frequency Range:	115-325kHz
Antenna installation:	Inductive loop coil Antenna
Hardware Version:	N/A
Software Version:	N/A

4.2 Details of E.U.T.

Ratings:	Input: DC 9V/2A, 12V/1.5A, 5V/3A(MAX) Output: 15W/3.5W/2.5W(MAX) Type-C Output: 5VDC/3A, 9VDC/2.22A, 20W MAX
Battery:	Battery Capacity: 3.7V, 20000MAh, 74Wh Rated Capacity: 12900mAh(5V/3A)

4.3 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

4.4 Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

4.5 Abnormalities from Standard Conditions

None.

4.6 Test Mode

Test Mode	Descriptions
TM1	Standby mode, EUT alone powered by AC/DC adapter
TM2	2.5W output, iWatch only (The battery capacity is less than 5%)
TM3	3.5W output, AirPods only (The battery capacity is less than 5%)
TM4	15W output, iPhone only (The battery capacity is less than 5%)
TM5	3 in 1 charge, iWatch+ AirPods+ iPhone charge together (The battery capacity is less than 5%)

Note:

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

5 Test Summary

Test Items	Test Requirement	Result
Conducted Emission	47CFR part 15§15.207	N/A ¹
Radiated Emission	47CFR part 15§15.209	PASS
20dB Bandwidth	47CFR part 15§15.215	PASS
Antenna Requirement	47CFR part 15§15.203	PASS
RF Exposure	FCC CFR 47 part1§1.1310 KDB 680106 D01 v03	PASS
Note: Pass=Compliance; NC=Not Compliance; NT=Not Tested; N/A=Not Applicable		

Note:

¹ When the EUT is charged through AC Main, the wireless charge does not work. Not applicable to the test.

6 Equipment Used during Test

6.1 Equipments List

3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2025-04-19	2026-04-18
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2024-11-04	2025-11-03
3	Active Loop Antenna	Com-Power Corp.	AL-130R	10160007	2025-04-21	2026-04-20
4	Amplifier	ANRITSU	MH648A	M43381	2025-04-19	2026-04-18
5	Cable	HUBER+SUHNER	CBL2	525178	2025-04-19	2026-04-18
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Signal Analyzer (9k~26.5GHz)	Agilent	N9010A	MY50520207	2025-04-19	2026-04-18
2	Spectrum Analyzer	R&S	FSP40	100501	2024-07-18	2025-07-17

Test Software:

Test Item	Software name	Software version
Radiated Emission(3m)	EZ-EMC	EZ-EMC(RA-03A1-1)

6.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
iPhone	Apple	MQ8T2LL/A	/
iWatch	Apple	A1758	/
Wireless Charging Case	Apple	A2083	/

6.3 Measurement Uncertainty

Parameter	Uncertainty
Conducted Emission	± 3.64 dB (AC mains 150KHz~30MHz)
Radiated Spurious Emissions	± 5.08 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)
Radio Frequency	$\pm 1 \times 10^{-7}$ Hz
RF Power	± 0.42 dB
RF Power Density	± 0.7 dB
Conducted Spurious Emissions	± 2.76 dB (9kHz~26500MHz)
Confidence interval: 95%. Confidence factor: k=2	

6.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P. R. China.

7 Radiated Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209

Test Method: ANSI C63.10-2020+A1-2024

Test Result: PASS

Measurement Distance: 3m

Limit:

FCC Part15 Paragraph 15.209

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	$\mu\text{V/m}$	Distance (m)	$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100**	3	100	$20\log^{(100)}$
88 ~ 216	150**	3	150	$20\log^{(150)}$
216 ~ 960	200**	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

In the emission table above, the tighter limit applies at the band edges.

Note:

According to §15.209(d), the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

According to §15.31(f)(2):

3m Measurement level ($\text{dB}\mu\text{V/m}$) = 300m Measurement level ($\text{dB}\mu\text{V/m}$) + $40\log(300/3)$ ($\text{dB}\mu\text{V/m}$).

7.1 EUT Operation

Operating Environment:

Temperature: 25.8 °C

Humidity: 52.6 % RH


Atmospheric Pressure: 101.2kPa

EUT Operation: Refer to section 4.6.


Only the worst-case transmitting mode were record in the report.

7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10-2020+A1-2024.
The test setup for emission measurement below 30MHz.



The test setup for emission measurement above 30MHz and up to 1 000MHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth..... 10kHz
 Resolution Bandwidth..... 10kHz

Above 30MHz

Sweep Speed Auto
 Video Bandwidth..... 300kHz
 Resolution Bandwidth..... 100kHz

7.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane, EUT is set 3m away from the receiving antenna, which is 1.0m above ground plane (Height of the centre of the loop above the GRP of the SAC is 1 m).
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And each emission was to be maximized by changing the polarization of receiving antenna both vertical coaxial and vertical coplanar.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes (X, Y, Z) position (X denotes lying on the table, Y denotes side stand and Z denotes vertical stand). After pre-test, it was found that the worse radiation emission was get at the Z position. So the data shown was the Z position only.

Note:

Although these test were performed other than open area test site, adequate comparison measurements were confirmed against 300m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788 D01.

7.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

7.6 Summary of Test Results


All test mode were tested, and only the worst-case (TM5) are shown in the report.

Test Frequency: 9kHz ~ 150kHz


Antenna Orientation: Parallel



Antenna Orientation: Perpendicular




Antenna Orientation: Ground parallel




Test Frequency: 150kHz ~ 30MHz


Antenna Orientation: Parallel



Antenna Orientation: Perpendicular




Antenna Orientation: Ground parallel




Test Frequency: 30MHz ~ 1000MHz

Antenna Polarization: Vertical



Antenna Polarization: Horizontal



8 Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.215

Test Method: ANSI C63.10-2020+A1-2024


8.1 Test Procedure

- 1 The transmitter shall be operated at its maximum carrier power measured under normal test conditions;
2. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.
3. The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW), video bandwidth (VBW) is set to approximately 3 times of the RBW.
4. Measured the spectrum width with power higher than 20dB below carrier.


8.2 Test Result

Test Mode	Test Channel (kHz)	20dB Bandwidth Emission(kHz)
TM2	127.654	0.262
TM3	127.660	0.344
TM4	324.708	0.270


Test result plot please refer to next page:



Date: 15.JUL.2025 15:25:48



Date: 15.JUL.2025 10:49:43



Date: 15.JUL.2025 10:59:20

9 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of a unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated inside the device and is not considered for replacement.

Antenna location: Refer to Appendix (Internal Photos).

10 RF Exposure

Note: Please refer to RF Exposure test report: WTD25D02042371W003.

11 Photographs of test setup and EUT

Note: Please refer to appendix: Appendix-WM-PBW16-GY-Photos.

===== End of Report =====