

TEST REPORT

Job No. : GPEM2405000392EC
Test Report No. : F690501-RF-EMC002469_1
Applicant : SM LNS
Product Name : Cradle(ETEE Hybrid Toothbrush)
Model Name : SM-ETEE100
Standards : FCC Part 15 Subpart B
FCC ID : 2BHRF-SM-ETEE100
Date of Receipt : May 24, 2024
Date of Test : May 30, 2024 ~ June 7, 2024
Date of Issue : July 31, 2024
Test Result : Complied

- 1) This test report does not assure KOLAS accreditation.
2) The results of this test report are effective only to the items tested.
3) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.

	Tested by (Name, signature)	Approved by (Name, signature)
Affirmation	DoHyeon Lee 	Paul Kang 

SGS Korea Co., Ltd. Gunpo Laboratory

4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, 15807, KOREA

Remarks :

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Contents

1. Test Laboratory.....	4
1.1 General information.....	4
2. General Information of E.U.T.	5
2.1 Applicant Information	5
2.2 General Information of E.U.T.	5
2.3 Configurations of E.U.T	5
3. E.U.T. Operation and Test Configuration	6
3.1 Peripheral Equipments.....	6
3.2 Cable List.....	6
3.3 Operating Modes and Conditions	6
3.4 Test System Layout	6
3.5 Modifications to the test items during testing	7
4. Test Results.....	8
4.1 Summary	8
4.2 Note	8
5. Emission Test	9
5.1 Test Method and Limits	9
5.2 Test Limits.....	9
5.3 Conducted Emission	11
5.3.1 Test Equipments.....	11
5.3.2 Environment Conditions.....	11
5.3.3 Test Results.....	12
5.4 Radiated Emission	14
5.4.1 Test Equipments.....	14
5.4.2 Environment Conditions.....	14
5.4.3 Test Result	15
Appendix A: Measurement Uncertainty	18



Revision History

Revision	Report Number	Description
0	F690501-RF-EMC002469	Initial
1	F690501-RF-EMC002469_1	FCC ID changed.

1. Test Laboratory

1.1 General information

Name	SGS Korea Co., Ltd.		
- Branch Site	4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Republic of Korea		
	Tel. 82 31 428 5700		Fax. 82 31 427 5370
- Branch Site-3	35, Giheungdanji-ro 121beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea		
	Tel. 82 31 548 0710		Fax. 82 31 548 0719
- Branch Site-4	12, Dongtansandan 10-gil, Hwaseong-si, Gyeonggi-do, 18487, Republic of Korea		
	Tel. 82 31 8007 5302		Fax. 82 31 427 2370
Website	http://www.sgsgroup.kr/ee		

SGS Korea Co., Ltd. has been accredited by the agencies listed in the following table;

Accreditation	Accreditation bodies	Accreditation No.
KC	MSIT- RRA	KR0150
FCC	FCC (MRA)	
IC	IC (MRA)	
Vietnam-MIC	Vietnam-MIC	
Japan EMI	VCCI	C-14102, T-11156, R-13662, G-20037
KOLAS	KATS - KOLAS	Testing No.123
CBTL	IECEE	TL 146
SDPPI	SDPPI	-

2. General Information of E.U.T.

2.1 Applicant Information

Applicant	SM LNS
Applicant Address	501, 33, Gangnam-daero 112-gil, Gangnam-gu, Seoul, Republic of Korea
Manufacturer	SM LNS
Manufacturer Address	501, 33, Gangnam-daero 112-gil, Gangnam-gu, Seoul, Republic of Korea

2.2 General Information of E.U.T.

Classification	Description
Product Name	Cradle(ETEE Hybrid Toothbrush)
Model Name	SM-ETEE100
Alt. Model Name	-
Model Differences	-
Serial No.	-
EMI Classification	Class B
Internal Clock Frequency	16 MHz
Rated Power	5 Vd.c.
Tested Power	Operating : 5 Vd.c. Charging : 120 V~, 60 Hz
F/W Version	2.0
S/W Version	3.1
Port	USB A-Type
Components	Toothbrush Body, Charging Cradle, Toothbrush Head(3 type)
Function	Electric Toothbrush

2.3 Configurations of E.U.T

Description	Model	Serial No.	Manufacturer	Note
Main Board	GY-H1 REV:V3	-	-	-
Battery	14650-1100mAh	-	Shenzhen Shenchao New Energy Technology Co.,Ltd	-
Motor	-	-	-	-
Cradle Board	JGY-H1 charg REV2	-	-	-
Cradle_Coil	-	-	-	-

3. E.U.T. Operation and Test Configuration

3.1 Peripheral Equipments

Description	Model	Serial No.	Manufacturer	Note.
Travel Adapter	EP-TA200	R37KC8JBX41SE3	SAMSUNG	-


3.2 Cable List

Start		END		Cable Spec.		Used core
Name	I/O Port	Name	I/O Port	Length (m)	Shield	
01, 02 Mode						
EUT	-	-	-	-	-	-
03 Mode						
EUT	-	Charging Cradle (EUT)	-	-	-	-
Charging Cradle (EUT)	USB A-Type	Travel Adapter	USB A-Type	0.8	Unshielded	-

3.3 Operating Modes and Conditions

Operating mode	Operating condition
01 EM Wave + Hard	Operating state in EM wave + Hard.
02 EM Wave + Massage	Operating state in EM wave + Massage.
03 Wireless Charging	Wireless charging state through AC Adapter.

3.4 Test System Layout



3.5 Modifications to the test items during testing

- ☒ No modifications done during testing
- ☐ Modification done during testing (see details below)

No.	Description of modification (if any)
1	
2	

4. Test Results

4.1 Summary

Test Items	Standards	Test Results
Conducted Emission	FCC Part 15 Subpart B Section 15.107 ANSI C63.4a:2017	Complied
Radiated Emission	FCC Part 15 Subpart B Section 15.109 ANSI C63.4a:2017	Complied

4.2 Note

- 1 Test Methods of all test items are performed according to the basic standard in subclause 4.1.
- 2

Emission Test

5.1 Test Method and Limits

Test Items	Measuring Frequency Range	RBW	Measuring Distance
Conducted Emission	0.15 MHz - 30 MHz	9 kHz	-
Radiated Emission	30 MHz - 1 GHz	120 kHz	10 m or 3 m
	Above 1 GHz	1 MHz	3 m

5.2 Test Limits

Frequency Range	Limits(dBμV)		Class
	Quasi-peak	CISPR-Average	
0.15 MHz - 0.5 MHz	79	66	Class A
0.5 MHz - 30 MHz	73	60	
0.15 MHz - 0.5 MHz	66 to 56 ^{Note1}	56 to 46 ^{Note1}	Class B
0.5 MHz - 5 MHz	56	46	
5 MHz - 30 MHz	60	50	

[Table 2.1 Conducted Emission Limits]

Frequency Range	Limits(dBμV/m)	Class
	Quasi-peak	
30 MHz - 88 MHz	39.0	Class A (10 m method)
88 MHz - 216 MHz	43.5	
216 MHz - 960 MHz	46.4	
960 MHz - 1 GHz	49.5	
30 MHz - 88 MHz	40.0	Class B (3 m method)
88 MHz - 216 MHz	43.5	
216 MHz - 960 MHz	46.0	
960 MHz - 1 GHz	54.0	

[Table 2.2 Radiated Emission Limits below 1 GHz_For FCC Part 15 Subpart B]

Frequency Range	Limits(dBμV/m)	Class
	Quasi-peak	
30 MHz - 88 MHz	40.0	Class A (10 m method)
88 MHz - 216 MHz	43.5	
216 MHz - 230 MHz	46.4	
230 MHz - 960 MHz	47.0	
960 MHz - 1 GHz	49.5	

30 MHz - 88 MHz	50.0	Class A (3 m method)
88 MHz - 216 MHz	54.0	
216 MHz - 230 MHz	56.9	
230 MHz - 960 MHz	57.0	
960 MHz - 1 GHz	60.0	
30 MHz - 88 MHz	30.0	Class B (10 m method)
88 MHz - 216 MHz	33.1	
216 MHz - 230 MHz	35.6	
230 MHz - 960 MHz	37.0	
960 MHz - 1 GHz	43.5	
30 MHz - 88 MHz	40.0	Class B (3 m method)
88 MHz - 216 MHz	43.5	
216 MHz - 230 MHz	46.0	
230 MHz - 960 MHz	47.0	
960 MHz - 1 GHz	54.0	

[Table 2.3 Radiated Emission Limits below 1 GHz_For ICES-003 Issue 7 : 2020]

Frequency Range	Limits(dBμV)		Class
	Quasi-peak	CISPR-Average	
Above 1 GHz	79.5	59.5	Class A
	74.0	54.0	Class B

[Table 2.4 Radiated Emission Limits Above 1 GHz_For FCC Part 15 Subpart B ^{Note2}]

Frequency Range	Limits(dBμV)		Class
	Quasi-peak	CISPR-Average	
Above 1 GHz	80.0	60.0	Class A
	74.0	54.0	Class B

[Table 2.5 Radiated Emission Limits Above 1 GHz_For ICES-003 Issue 7 : 2020]

Note 1. The lower limit shall apply at the transition frequencies. The limit decreases linearly with the logarithm of that frequency.

Note 2. The limits of class A equipment is extrapolated using an extrapolation factor of 20 dB/decade because it was measured at 3 m distance not 10 m distance.

5.3 Conducted Emission

5.3.1 Test Equipments

Description	Model No.	Manufacturer	Serial No	Cal Due. Date
Two-Line V-Network	ENV216	R & S	100190	2025-05-23
Test Receiver	ESCI 7	R & S	100911	2025-02-26

Note. Measuring software is below


- Branch Site : EMC32(V10.60.20) from R&S
- Branch Site-3 : EMC32(V10.40.10) from R&S
- Branch Site-4 : EMC32(V10.40.00) from R&S

5.3.2 Environment Conditions

Test Site	Shield Room in Branch site
Temperature	(Minimum 22.0, Maximum 22.5) °C
Humidity	(Minimum 49.0, Maximum 50.1) % R.H.
Atmospheric Pressure	(Minimum 101.0, Maximum 101.0) kPa
Test Date	2024-06-07

5.3.3 Test Results


Live Line_03 Mode



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.190	---	33.17	54.04	20.87	15 000.0	9.000	L1	OFF	9.7
0.190	37.26	---	64.04	26.77	15 000.0	9.000	L1	OFF	9.7
0.378	---	35.50	48.32	12.83	15 000.0	9.000	L1	OFF	9.7
0.378	39.39	---	58.32	18.93	15 000.0	9.000	L1	OFF	9.7
0.714	---	26.19	46.00	19.81	15 000.0	9.000	L1	OFF	9.7
0.714	30.89	---	56.00	25.11	15 000.0	9.000	L1	OFF	9.7
1.318	---	22.08	46.00	23.92	15 000.0	9.000	L1	OFF	9.8
1.318	28.19	---	56.00	27.81	15 000.0	9.000	L1	OFF	9.8
2.634	---	17.46	46.00	28.54	15 000.0	9.000	L1	OFF	9.9
2.634	24.66	---	56.00	31.34	15 000.0	9.000	L1	OFF	9.9
11.746	---	20.84	50.00	29.16	15 000.0	9.000	L1	OFF	10.4
11.746	28.83	---	60.00	31.17	15 000.0	9.000	L1	OFF	10.4

Neutral Line_03 Mode



Final Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.190	---	29.63	54.04	24.40	15 000.0	9.000	N	OFF	9.6
0.190	31.98	---	64.04	32.05	15 000.0	9.000	N	OFF	9.6
0.374	---	29.99	48.41	18.43	15 000.0	9.000	N	OFF	9.7
0.374	33.69	---	58.41	24.72	15 000.0	9.000	N	OFF	9.7
0.718	---	21.89	46.00	24.11	15 000.0	9.000	N	OFF	9.7
0.718	28.64	---	56.00	27.36	15 000.0	9.000	N	OFF	9.7
1.318	---	19.19	46.00	26.81	15 000.0	9.000	N	OFF	9.8
1.318	23.14	---	56.00	32.86	15 000.0	9.000	N	OFF	9.8
1.890	---	14.25	46.00	31.75	15 000.0	9.000	N	OFF	9.8
1.890	18.91	---	56.00	37.09	15 000.0	9.000	N	OFF	9.8
11.962	---	18.70	50.00	31.30	15 000.0	9.000	N	OFF	10.5
11.962	24.08	---	60.00	35.92	15 000.0	9.000	N	OFF	10.5

Note. Measurement Uncertainty : See Appendix A

- Line (L1) : Live Line of AC Power
- Margin = Limit – Quasi Peak or CAverage

- Line (N) : Neutral Line of AC Power
- Corr. = LISN Factor + Cable loss + Pulse Limiter factor

Ex) In case

Freq ; 0.5 Mhz, level ; 30 dB(µV), CL ; 0.2 dB, LISN ; 9.5 dB, P/L: 9.8 dB

Result = Level + CL + LISN + P/L

$$= 30 + 0.2 + 9.5 + 9.8$$

$$= 49.5$$

Margin = Limit – Result

$$= 79 - 49.5$$

$$= 29.5$$

5.4 Radiated Emission

5.4.1 Test Equipments

Equipment	Model	Manufacturer	Serial No	Cal Due. Date
Hybrid Antenna	VULB9163	SCHWARZBECK	01126	2025-02-26
AMPLIFIER	317	SONOMA	243246	2024-12-08
EMI TEST RECEIVER	ESU40	R&S	100075	2025-01-17
RF Cable(CA-04)	-	-	-	2024-10-03
RF Cable(CA-06)	MWX221-NMSNMS (4m)	RF ONE	J023142	2024-10-03
RF Cable(CA-08)	PL520-NMNM-10M (10m)	RF ONE	0200324001	2024-10-03

Note. Measuring software is below


- Branch Site : ELECTRA(V5.02.0) from R&S
- Branch Site-3 : EMC32(V10.40.10) from R&S
- Branch Site-4 : EMC32(V10.40.10) from R&S

5.4.2 Environment Conditions

Test Site	10 m SEMI-ANECHOIC CHAMBER in Branch site-3
Temperature	(Minimum 22.0, Maximum 23.0) °C
Humidity	(Minimum 33.0, Maximum 34.0) % R.H.
Atmospheric Pressure	(Minimum 101.3, Maximum 101.4) kPa
Test Date	2024-05-30

5.4.3 Test Result


01 Mode



Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
31.358	12.79	40.00	27.21	15 000.0	120.000	200.0	H	62.0	-20.2
106.339	12.09	43.50	31.41	15 000.0	120.000	200.0	V	267.0	-17.5
321.194	16.63	46.00	29.37	15 000.0	120.000	100.0	V	24.0	-13.0
614.619	23.86	46.00	22.14	15 000.0	120.000	100.0	V	0.0	-5.7
836.070	25.86	46.00	20.14	15 000.0	120.000	100.0	H	282.0	-3.7
891.360	33.86	46.00	12.14	15 000.0	120.000	200.0	V	83.0	-2.7


02 Mode



Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
141.550	8.51	43.50	34.99	15 000.0	120.000	100.0	H	310.0	-21.0
161.823	22.07	43.50	21.43	15 000.0	120.000	100.0	H	74.0	-20.0
181.999	24.29	43.50	19.21	15 000.0	120.000	100.0	H	275.0	-19.1
202.272	12.05	43.50	31.45	15 000.0	120.000	100.0	H	275.0	-17.5
222.545	12.96	46.00	33.04	15 000.0	120.000	100.0	H	301.0	-16.6
890.972	35.10	46.00	10.90	15 000.0	120.000	200.0	V	82.0	-2.7

03 Mode



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
82.477	27.20	40.00	12.80	15 000.0	120.000	100.0	V	38.0	-22.0
84.611	27.11	40.00	12.89	15 000.0	120.000	100.0	V	38.0	-21.3
120.889	21.19	43.50	22.31	15 000.0	120.000	100.0	V	0.0	-19.6
123.120	21.75	43.50	21.75	15 000.0	120.000	100.0	V	309.0	-20.0
156.391	23.70	43.50	19.80	15 000.0	120.000	100.0	V	272.0	-20.4
891.166	35.12	46.00	10.88	15 000.0	120.000	200.0	V	44.0	-2.7

Note. Measurement Uncertainty: See Appendix A

- POL H = Horizontal
- POL V = Vertical
- Margin = Limit – Quasi Peak
- Corr. = Antenna Factor + Cable loss – Amplifier Gain

Ex) In case

Freq ; 100 MHz, level ; 30 dB(µV/m), AF ; 10 dB/m, CL ; 4 dB, Amp ; 25 dB

Result = Level + AF + CL – Amp

$$= 30 + 10 + 4 - 25$$

$$= 19$$

Margin = Limit – Result

$$= 43.5 - 19$$

$$= 24.5$$

Appendix A: Measurement Uncertainty

Test Method		Measurement Uncertainty
Conducted Emission	ENV216	3.1 dB (The confidential level is 95 %, $k=2$)
	ESH2-Z5	2.8 dB (The confidential level is 95 %, $k=2$)
	ESH3-Z6	3.0 dB (The confidential level is 95 %, $k=2$)
Conducted Emission - Signal	ISN T800	5.3 dB (The confidential level is 95 %, $k=2$)
	ISNT8-Cat6	5.4 dB (The confidential level is 95 %, $k=2$)
	ISN S751	7.1 dB (The confidential level is 95 %, $k=2$)
Disturbance Voltage at Antenna Terminal		2.2 dB (The confidential level is 95 %, $k=2$)
Radiated Emission	9 kHz - 30 MHz	Horizontal 3.6 dB (The confidential level is 95 %, $k=2$)
		Vertical 3.6 dB (The confidential level is 95 %, $k=2$)
	30 MHz - 1 000 MHz	Horizontal 4.6 dB (The confidential level is 95 %, $k=2$)
		Vertical 4.9 dB (The confidential level is 95 %, $k=2$)
	1 GHz - 18 GHz	Horizontal 3.9 dB (The confidential level is 95 %, $k=2$)
		Vertical 3.8 dB (The confidential level is 95 %, $k=2$)

Table A.1 Measurement Uncertainty of Branch Site

Test Method		Measurement Uncertainty	
Conducted Emission	ENV216	3.2 dB	(The confidential level is 95 %, $k=2$)
	ESH3-Z6	3.2 dB	(The confidential level is 95 %, $k=2$)
	ESH2-Z5	3.0 dB	(The confidential level is 95 %, $k=2$)
	NNLK8129	3.0 dB	(The confidential level is 95 %, $k=2$)
Conducted Emission - Signal		ISN T800	5.5 dB (The confidential level is 95 %, $k=2$)
		ISN ST08	6.6 dB (The confidential level is 95 %, $k=2$)
Radiated Emission	9 kHz - 30 MHz	Horizontal	3.3 dB (The confidential level is 95 %, $k=2$)
		Vertical	3.3 dB (The confidential level is 95 %, $k=2$)
	30 MHz - 1 000 MHz	Horizontal	4.3 dB (The confidential level is 95 %, $k=2$)
		Vertical	4.6 dB (The confidential level is 95 %, $k=2$)
	1 GHz - 18 GHz	Horizontal	3.9 dB (The confidential level is 95 %, $k=2$)
		Vertical	4.0 dB (The confidential level is 95 %, $k=2$)

Table A.2 Measurement Uncertainty of Branch Site-3

Test Method		Measurement Uncertainty	
Conducted Emission	ENV216	3.5 dB	(The confidential level is 95 %, $k=2$)
	ESH2-Z5	3.3 dB	(The confidential level is 95 %, $k=2$)
	ESH3-Z6	3.3 dB	(The confidential level is 95 %, $k=2$)
	NNLK8129	3.4 dB	(The confidential level is 95 %, $k=2$)
Conducted Emission - Signal	ISN T800	5.6 dB	(The confidential level is 95 %, $k=2$)
	ISN ST08	5.5 dB	(The confidential level is 95 %, $k=2$)
Radiated Emission	9 kHz - 30 MHz (Triple Loop Ant.)	3.7 dB	(The confidential level is 95 %, $k=2$)
	9 kHz - 30 MHz (Loop Ant.)	Horizontal	4.2 dB (The confidential level is 95 %, $k=2$)
		Vertical	4.2 dB (The confidential level is 95 %, $k=2$)
	30 MHz - 1 000 MHz	Horizontal	4.8 dB (The confidential level is 95 %, $k=2$)
		Vertical	5.2 dB (The confidential level is 95 %, $k=2$)
	1 GHz - 18 GHz	Horizontal	4.5 dB (The confidential level is 95 %, $k=2$)
		Vertical	4.5 dB (The confidential level is 95 %, $k=2$)

Table A.3 Measurement Uncertainty of Branch Site-4

- End of Test Report -