

# Shanghai Medconn Medical Technology Co., Ltd.

## RF TEST REPORT

**Report Type:**  
FCC Part 15.225 RF report

**Model:**  
MQ-8000, MQ-8000PT

**REPORT NUMBER:**  
2412B0311SHA-001

**ISSUE DATE:**  
December 10, 2024

**DOCUMENT CONTROL NUMBER:**  
TTRF15.225\_V1 © 2018 Intertek



**Applicant:** Shanghai Medconn Medical Technology Co., Ltd.  
No.1018 WeiChang Road, ShanYang, JinShan District, Shanghai, China

**Manufacturer:** Shanghai Medconn Medical Technology Co., Ltd.  
No.1018 WeiChang Road, ShanYang, JinShan District, Shanghai, China

**Factory:** Shanghai Medconn Medical Technology Co., Ltd.  
Rm 1001-1003, 1F, East of Building4 & 2F, East of Building4, No. 1018  
Weichang Road, Shanyang Town, Jinshan District, Shanghai, China


**FCC ID:** **2BHV21501**

**SUMMARY:**

The equipment complies with the requirements according to the following standard(s) or Specification:

**47CFR Part 15 (2023):** Radio Frequency Devices (Subpart C)

**ANSI C63.10 (2020):** American National Standard of Procedures for Compliance Testing of Unlicensed  
Wireless Devices

**PREPARED BY:**

---

Project Engineer  
Alexander Li**REVIEWED BY:**

---

Reviewer  
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**TEST REPORT****Content**

<b>REVISION HISTORY.....</b>	<b>5</b>
<b>MEASUREMENT RESULT SUMMARY .....</b>	<b>6</b>
<b>1 GENERAL INFORMATION .....</b>	<b>7</b>
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) .....	7
1.2 TECHNICAL SPECIFICATION.....	7
1.3 DESCRIPTION OF TEST FACILITY.....	8
<b>2 TEST SPECIFICATIONS.....</b>	<b>9</b>
2.1 STANDARDS OR SPECIFICATION .....	9
2.2 MODE OF OPERATION DURING THE TEST.....	9
2.3 TEST SOFTWARE LIST .....	9
2.4 TEST PERIPHERALS LIST.....	9
2.5 TEST ENVIRONMENT CONDITION:.....	9
2.6 INSTRUMENT LIST .....	10
2.7 MEASUREMENT UNCERTAINTY.....	11
<b>3 FUNDAMENTAL EMISSION .....</b>	<b>12</b>
3.1 LIMIT .....	12
3.2 MEASUREMENT PROCEDURE .....	12
3.3 TEST CONFIGURATION .....	13
3.4 TEST RESULTS OF FUNDAMENTAL EMISSIONS .....	14
<b>4 SPURIOUS EMISSION .....</b>	<b>15</b>
4.1 LIMIT .....	15
4.2 MEASUREMENT PROCEDURE .....	15
4.3 TEST RESULTS OF RADIATED EMISSIONS .....	17
<b>5 FREQUENCY STABILITY (TEMPERATURE VARIATION).....</b>	<b>21</b>
5.1 TEST LIMIT .....	21
5.2 TEST CONFIGURATION .....	21
5.3 TEST PROCEDURE AND TEST SETUP .....	22
5.4 TEST PROTOCOL.....	22
<b>6 FREQUENCY STABILITY (VOLTAGE VARIATION) .....</b>	<b>23</b>
6.1 TEST LIMIT .....	23
6.2 TEST CONFIGURATION .....	23
6.3 TEST PROCEDURE AND TEST SETUP .....	23
6.4 TEST PROTOCOL.....	24
<b>7 CONDUCTED EMISSIONS .....</b>	<b>25</b>
7.1 LIMIT .....	25
7.2 TEST CONFIGURATION .....	25
7.3 MEASUREMENT PROCEDURE .....	26
7.4 TEST RESULTS OF CONDUCTED EMISSIONS.....	27
<b>8 20DB BANDWIDTH .....</b>	<b>29</b>
8.1 LIMIT.....	29
8.2 TEST CONFIGURATION .....	29
8.3 TEST PROCEDURE AND TEST SET UP .....	30
8.4 TEST PROTOCOL .....	31

**TEST REPORT**

<b>9 ANTENNA REQUIREMENT.....</b>	<b>32</b>
-----------------------------------	-----------

**TEST REPORT****Revision History**

Report No.	Version	Description	Issued Date
2412B0311SHA-001	Rev. 01	Initial issue of report	December 10, 2024

**TEST REPORT****Measurement result summary**

TEST ITEM	FCC REFERENCE	RESULT
Fundamental emission	15.225(a) (b) (c)	Pass
Spurious emission	15.225(d)	Pass
Frequency stability	15.225(e)	Pass
Conducted emissions	15.207	Pass
99% and 20dB Bandwidth	15.215(c)	Pass
Antenna requirement	15.203	Pass

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

**TEST REPORT****1 GENERAL INFORMATION****1.1 Description of Equipment Under Test (EUT)**

Product name:	Glycated Hemoglobin Analyzer
Type/Model:	MQ-8000, MQ-8000PT
Description of EUT:	The EUT is a Glycated Hemoglobin Analyzer with NFC function, both models are identical except the appearance color. After review, model MQ-8000 was selected to perform all tests.
Rating:	100-240V~, 50/60Hz, 180VA
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Serial numbers:	A241020-11-001
Sample received date:	November 13, 2024
Date of test:	November 13, 2024 to December 10, 2024

**1.2 Technical Specification**

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna:	PCB antenna

**TEST REPORT****1.3 Description of Test Facility**

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No.: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

**TEST REPORT****2 TEST SPECIFICATIONS****2.1 Standards or specification**

47CFR Part 15 (2023)  
ANSI C63.10 (2020)

**2.2 Mode of operation during the test**

While testing, the internal modulation and continuously transmission was applied.

**2.3 Test software list**

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

**2.4 Test peripherals list**

Item No	Description	Band and Model	S/No
1	--	--	--

**2.5 Test environment condition:**

Test items	Temperature	Humidity
Radiated emission	25°C	53% RH
Power line conducted emission	24°C	53% RH

**TEST REPORT**
**2.6 Instrument list**

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESR7	EC 6194	2025-02-27
<input checked="" type="checkbox"/>	A.M.N.	R&S	ESH2-Z5	EC 3119	2025-11-19
<input checked="" type="checkbox"/>	Attenuator	Hua Xiang	Ts5-10db-6g	EC 6194-1	2025-12-07
<input checked="" type="checkbox"/>	Shielded room	Zhongyu	-	EC 2838	2025-01-11
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Test Receiver	R&S	ESIB 26	EC 3045	2025-08-22
<input checked="" type="checkbox"/>	Active loop antenna	Schwarzbeck	FMZB1519	EC 5345	2025-09-24
<input checked="" type="checkbox"/>	Bilog Antenna	TESEQ	CBL 6112B	EC 6411	2025-09-12
<input checked="" type="checkbox"/>	Pre-amplifier	Tonscend	tap01018050	EC 6432-1	2025-12-07
<input checked="" type="checkbox"/>	Horn antenna	Tonscend	bha9120d	EC 6432-2	2025-02-15
<input checked="" type="checkbox"/>	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2026-09-12
<input checked="" type="checkbox"/>	Semi-anechoic chamber	Albatross project	-	EC 3048	2025-01-11
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input type="checkbox"/>	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2025-03-07
<input type="checkbox"/>	Vector Signal Generator	Agilent	N5182B	EC 5175	2025-03-07
<input type="checkbox"/>	Universal Radio Communication Tester	R&S	CMW500	EC5944	2025-03-07
<input type="checkbox"/>	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2025-03-07
<input type="checkbox"/>	Mobile Test System	Litepoint	Iqxel	EC 5176	2025-01-11
<input type="checkbox"/>	Test Receiver	R&S	ESCI 7	EC 4501	2025-03-09
<input type="checkbox"/>	Climate chamber	GWS	MT3065	EC 6021	2025-03-06
<input checked="" type="checkbox"/>	Spectrum Analyzer	Keysight	N9030B	EC 6078	2025-06-15
<input type="checkbox"/>	Universal Radio Communication Tester	R&S	CMW500	EC 6209	2025-01-30
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
<input checked="" type="checkbox"/>	Thermo-Hygrograph	Testo	175h1	EC 6640	2025-08-28
<input checked="" type="checkbox"/>	Thermo-Hygrograph	Testo	175h1	EC 6641	2025-08-28
<input checked="" type="checkbox"/>	Pressure meter	YM3	Shanghai Mengde	EC 4620	2025-08-16

**TEST REPORT****2.7 Measurement uncertainty**

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	± 0.74dB
Power spectrum density	± 0.74dB
Radiated Emissions in restricted frequency bands below 1GHz	± 4.90dB
Radiated Emissions in restricted frequency bands above 1GHz	± 5.02dB
Emission outside the frequency band	± 2.89dB
Power line conducted emission	± 3.19dB
Occupied bandwidth	± 0.84 × 10 <sup>-7</sup>

**TEST REPORT****3 Fundamental Emission****Test result:** Pass**3.1 Limit**


Frequencies (MHz)	Limit at 30m (dBuV/m)	Limit at 3m (dBuV/m)
13.110 – 13.410	40.50	80.50
13.410 – 13.553	50.50	90.50
13.553 – 13.567	84.00	124.00
13.567 – 13.710	50.50	90.50
13.710 – 14.010	40.50	80.50

**3.2 Measurement Procedure**

- a) The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to PK Detect Function and Specified Bandwidth with Maximum Hold Mode.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

**TEST REPORT****3.3 Test Configuration**

**TEST REPORT**
**3.4 Test Results of Fundamental Emissions**

Note: X axis as the worst case was recorded.



Antenna Polarization	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin	Detector
X	13.56	45.7	20.5	124.00	78.3	PK
Y	13.56	40.6	20.5	124.00	83.4	PK

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.  
 2. Corrected Reading = Original Receiver Reading + Correct Factor  
 3. Margin = Limit - Corrected Reading

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,  
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,  
 Limit = 40.00dBuV/m.  
 Then Correct Factor =  $30.20 + 2.00 - 32.00 = 0.20$ dB/m;  
 Corrected Reading =  $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$ ;  
 Margin =  $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$ .

**TEST REPORT****4 Spurious Emission****Test result:** Pass**4.1 Limit**

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**4.2 Measurement Procedure****For Radiated emission below 30MHz:**

- f) The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- g) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- h) Both X and Y axes of the antenna are set to make the measurement.
- i) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- j) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

**NOTE:**

2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

**For Radiated emission above 30MHz:**

- a) The EUT was placed on a 0.8m plank above the ground at a 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

**TEST REPORT**

- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


**Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. All modes of operation were evaluated and the worst-case emissions were reported


**TEST REPORT****4.3 Test Results of Radiated Emissions**

The EUT has been tested in all two orthogonal planes, it has the worst case when it is in horizontal position for both below 30MHz & above 30MHz.

**Test Curve for below 30MHz:**





Y axis



**TEST REPORT****Test data below 30MHz:**

Frequency	Limit (dBuV/m)	Corrected Reading (dBuV/m)	Margin	Detector	Polarity
9.848kHz	127.7	59.4	68.3	PK	X
23.976kHz	120.0	51.4	68.6	PK	X
47.146kHz	114.1	51.8	62.3	PK	X
568.738kHz	72.5	55.4	17.1	PK	X
9.848kHz	127.7	67.1	60.6	PK	X
45.168kHz	114.5	55.2	59.3	PK	Y
269.639kHz	99.0	53.6	45.4	PK	Y
508.918kHz	73.5	57.1	16.4	PK	Y
7.448MHz	69.5	43.5	26.0	PK	Y
9.848kHz	127.7	67.1	60.6	PK	Y

Note: the point six is the wanted signal.

**TEST REPORT****Test Curve for 30MHz to 1GHz:**

**TEST REPORT**
**Test data from 30MHz to 1000MHz:**

Antenna Polarization	Frequency	Limit (dBuV/m)	Corrected Reading (dBuV/m)	Margin	Detector
H	122.732MHz	43.50	35.09	8.41	PK
H	187.722MHz	43.50	36.19	7.31	PK
H	205.861MHz	43.50	38.25	5.25	PK
H	263.576MHz	46.00	40.34	5.66	PK
H	517.231MHz	46.00	36.60	9.40	PK
H	711.231MHz	46.00	39.94	6.06	PK
V	59.779MHz	40.00	36.15	3.85	PK
V	115.457MHz	43.50	36.80	6.70	PK
V	122.732MHz	43.50	41.95	1.55	PK
V	135.924MHz	43.50	41.99	1.51	PK
V	264.837MHz	46.00	40.91	5.09	PK
V	517.231MHz	46.00	40.22	5.78	PK

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.  
 2. Corrected Reading = Original Receiver Reading + Correct Factor  
 3. Margin = Limit - Corrected Reading  
 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.


Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,  
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,  
 Limit = 40.00dBuV/m.  
 Then Correct Factor =  $30.20 + 2.00 - 32.00 = 0.20$ dB/m;  
 Corrected Reading =  $10$ dBuV +  $0.20$ dB/m =  $10.20$ dBuV/m;  
 Margin =  $40.00$ dBuV/m -  $10.20$ dBuV/m =  $29.80$ dB.

**TEST REPORT****5 Frequency Stability (Temperature Variation)**

Test result: **PASS**

**5.1 Test limit**

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage.

**5.2 Test Configuration**

**TEST REPORT****5.3 Test procedure and test setup**

Test Procedure as per ANSI 63.10 clause 6.8.1.

**5.4 Test protocol**


Voltage (V)	Temp (°C)	Freq measured (MHz)	Freq nominal (MHz)	Tolerance (%)	Limit (%)
120	-20	13.5597	13.56	-0.002	±0.01
	-10	13.5591		-0.007	
	0	13.5601		0.001	
	10	13.5603		0.002	
	20	13.56		0.000	
	30	13.5603		0.002	
	40	13.5595		-0.004	
	50	13.5591		-0.007	

**TEST REPORT****6 Frequency Stability (Voltage Variation)**

**Test result: PASS**

**6.1 Test limit**

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

**6.2 Test Configuration****6.3 Test procedure and test setup**

Test Procedure as per ANSI 63.10 clause 6.8.2.


**TEST REPORT****6.4 Test protocol**

Temp (°C)	Voltage (V)	Freq Measured (MHz)	Freq nominal (MHz)	Tolerance (%)	Limit (%)
20	102	13.5603	13.56	0.002	±0.01
	120	13.5604		0.003	
	138	13.5601		0.001	

**TEST REPORT****7 Conducted emissions**Test result: **Pass****7.1 Limit**

Frequency of Emission (MHz)	Conducted Emissions Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.


**7.2 Test Configuration**

**TEST REPORT****7.3 Measurement Procedure**

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the  $50\ \Omega$  LISN port (to which the EUT is connected), where permitted, terminated into a  $50\ \Omega$  measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the  $50\ \Omega$  measuring port is terminated by a measuring instrument having  $50\ \Omega$  input impedance. All other ports are terminated in  $50\ \Omega$  loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

**TEST REPORT****7.4 Test Results of Conducted Emissions****Test Voltage: 120VAC/60Hz****Test Curve:**

**TEST REPORT**

No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector	Phase
1	186.000kHz	64.21	46.10	-18.11	39.90	6.20	QP	L1
2	204.000kHz	63.45	45.92	-17.53	39.72	6.20	QP	L1
3	276.000kHz	60.94	42.68	-18.26	36.48	6.20	QP	L1
4	591.000kHz	56.00	36.53	-19.47	30.33	6.20	QP	L1
5	699.000kHz	56.00	35.76	-20.24	29.56	6.20	QP	L1
6	13.560MHz	60.00	44.27	-15.73	37.47	6.80	QP	L1
7	163.500kHz	65.28	46.69	-18.59	40.59	6.10	QP	N
8	208.500kHz	63.26	55.07	-8.19	48.87	6.20	QP	N
9	280.500kHz	60.80	46.97	-13.83	40.77	6.20	QP	N
10	600.000kHz	56.00	37.70	-18.30	31.50	6.20	QP	N
11	703.500kHz	56.00	42.74	-13.26	36.54	6.20	QP	N
12	13.560MHz	60.00	44.47	-15.53	37.67	6.80	QP	N
13	199.500kHz	53.63	32.18	-21.45	25.98	6.20	CAV	L1
14	411.000kHz	47.63	24.19	-23.44	17.99	6.20	CAV	L1
15	595.500kHz	46.00	28.95	-17.05	22.75	6.20	CAV	L1
16	717.000kHz	46.00	23.45	-22.55	17.25	6.20	CAV	L1
17	13.560MHz	50.00	42.12	-7.88	35.32	6.80	CAV	L1
18	15.000MHz	50.00	31.00	-19.00	24.10	6.90	CAV	L1
19	199.500kHz	53.63	32.31	-21.32	26.11	6.20	CAV	N
20	582.000kHz	46.00	29.45	-16.55	23.25	6.20	CAV	N
21	717.000kHz	46.00	22.70	-23.30	16.50	6.20	CAV	N
22	825.000kHz	46.00	21.90	-24.10	15.70	6.20	CAV	N
23	13.560MHz	50.00	42.42	-7.58	35.62	6.80	CAV	N
24	15.000MHz	50.00	31.17	-18.83	24.27	6.90	CAV	N


Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.  
 2. Level = Original Receiver Reading + Correct Factor  
 3. Delta = Level - Limit  
 4. If the PK Level is lower than AV limit, the AV test can be elided.  
 5. the emissions of 13.56MHz are the product's RF signal.

**TEST REPORT****8 20dB Bandwidth**

**Test result: Pass**

**8.1 Limit**

The 20dB bandwidth should be fallen in the allocated operating frequency range.  
No limit for 99% bandwidth.

**8.2 Test configuration**

**TEST REPORT****8.3 Test procedure and test set up**

The measurement was applied in a 3m semi-anechoic chamber.


The center of the loop antenna shall be 1 m above the horizontal metal ground plane.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set RBW = 1 % to 5 % of the OBW
3. Set VBW  $\geq 3 \cdot \text{RBW}$
4. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
5. Use the 99 % power bandwidth function of the instrument (if available).
6. the 20dB bandwidth is also measured with the same setting.

**TEST REPORT**
**8.4 Test protocol**

	Lower point (MHz)	Higher point (MHz)	Bandwidth (kHz)	Allocated bandwidth (MHz)
20dB Bandwidth	13.559837	13.560415	0.578	13.553 ~ 13.567
Occupied bandwidth	13.559127	13.561098	1.970	13.553 ~ 13.567



**TEST REPORT**

## 9 Antenna requirement

**Requirement:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**Result:**

EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

\*\*\*\*\* END \*\*\*\*\*