



RF Test Report

FCC ID: 2BHW8-JETDIVEPRO

Test Report No.: RF240321001-01-001

Product(s) Name: Underwater Waist Scooter

Model(s): JETDIVE PRO, JETDIVE, JETDIVE PLUS, JETDIVE MAX

Trade Mark.: N/A

Applicant: Shenzhen Zhongtian Marine Technology Co., Ltd

Address: 5th Floor, Block AB, Tianji Building, Tian'an Digital City, Futian District, Shenzhen, Guangdong, China

Receipt Date: 2024.07.01

Test Date: 2024.07.01~2024.07.25

Issued Date: 2024.07.26

Standards: 47 CFR FCC Part 15, Subpart C(Section 15.247)
ANSI C63.10:2013

Testing Laboratory: Shenzhen Haiyun Standard Technical Co., Ltd.

Prepared By:	Checked By:	Approved By:	
Jason Huang	Tim Zhang	Misue Su	
Jason Huang	Tim Zhang	Misue Su	

Table of Contents

REPORT ISSUED HISTORY	4
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
1.3 TEST ENVIRONMENT CONDITIONS	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 PARAMETERS OF TEST SOFTWARE	9
2.4 SUPPORT UNITS	9
3 . AC POWER LINE CONDUCTED EMISSIONS	10
3.1 LIMIT	10
3.2 TEST PROCEDURE	10
3.3 DEVIATION FROM TEST STANDARD	10
3.4 TEST SETUP	11
3.5 EUT OPERATING CONDITIONS	11
3.6 TEST RESULTS	11
4 . RADIATED EMISSIONS	12
4.1 LIMIT	12
4.2 TEST PROCEDURE	13
4.3 DEVIATION FROM TEST STANDARD	14
4.4 TEST SETUP	14
4.5 EUT OPERATING CONDITIONS	15
4.6 TEST RESULT - 9 KHZ TO 30 MHZ	15
4.7 TEST RESULT - 30 MHZ TO 1000 MHZ	15
4.8 TEST RESULT - ABOVE 1000 MHZ	15
5 . BANDWIDTH	16
5.1 LIMIT	16
5.2 TEST PROCEDURE	16
5.3 DEVIATION FROM STANDARD	16
5.4 TEST SETUP	16
5.5 EUT OPERATION CONDITIONS	16
5.6 TEST RESULTS	16
6 . MAXIMUM OUTPUT POWER	17
6.1 LIMIT	17



6.2 TEST PROCEDURE	17
6.3 DEVIATION FROM STANDARD	17
6.4 TEST SETUP	17
6.5 EUT OPERATION CONDITIONS	17
6.6 TEST RESULTS	17
7 . CONDUCTED SPURIOUS EMISSION	18
7.1 LIMIT	18
7.2 TEST PROCEDURE	18
7.3 DEVIATION FROM STANDARD	18
7.4 TEST SETUP	18
7.5 EUT OPERATION CONDITIONS	18
7.6 TEST RESULTS	18
8 . POWER SPECTRAL DENSITY	19
8.1 LIMIT	19
8.2 TEST PROCEDURE	19
8.3 DEVIATION FROM STANDARD	19
8.4 TEST SETUP	19
8.5 EUT OPERATION CONDITIONS	19
8.6 TEST RESULTS	19
9 . MEASUREMENT INSTRUMENTS LIST	20
10 . ANTENNA REQUIREMENT	21
APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS	22
APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ	25
APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ	26
APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ	29
APPENDIX E - BANDWIDTH	35
APPENDIX F - MAXIMUM OUTPUT POWER	40
APPENDIX G - CONDUCTED SPURIOUS EMISSION	43
APPENDIX H - POWER SPECTRAL DENSITY	50

REPORT ISSUED HISTORY

Original Report Issue Date: 2024.07.26

- No additional attachment
- Additional attachments were issued following record

Attachment No.	Issue Date	Description

1.. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC CFR Title 47, Part 15, Subpart C				
Standard(s) Section	Test Item	Test Result	Judgment	Remark
15.207	AC Power Line Conducted Emissions	APPENDIX A	PASS	-----
15.247(d) 15.205(a) 15.209(a)	Radiated Emissions	APPENDIX B APPENDIX C APPENDIX D	PASS	-----
15.247(a)(2)	Bandwidth	APPENDIX E	PASS	-----
15.247(b)(3)	Maximum Output Power	APPENDIX F	PASS	-----
15.247(d)	Conducted Spurious Emission	APPENDIX G	PASS	-----
15.247(e)	Power Spectral Density	APPENDIX H	PASS	-----
15.203	Antenna Requirement	-----	PASS	Note(2)

Note:

- (1) "N/A" denotes test is not applicable to this device.
- (2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.



1.1. TEST FACILITY

Company:	Shenzhen Haiyun Standard Technical CO., Ltd.
Address:	No. 110-113, 115, 116, Block B, Jinyuan Business Building, Bao'an District, Shenzhen, China
CNAS Registration Number:	CNAS L18252
CAB identifier	CN0145
FCC Test Firm Registration Number	457288
A2LA Certificate Number	6823.01
Telephone:	0755-26024411

1.2. MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Parameter	Uncertainty
Occupied Channel Bandwidth	±102kHz
Power Spectral Density	±0.743dB
Conducted Spurious Emission	±1.328dB
RF power conducted	±0.377dB
Conducted emission(9kHz~30MHz) AC main	±2.68dB
Radiated emission(9kHz~30MHz)	±2.74dB
Radiated emission (30MHz~1GHz)	±4.22dB
Radiated emission (1GHz~18GHz)	±5.06dB
Radiated emission (18GHz~40GHz)	±4.98dB

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3. TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
AC Power Line Conducted Emissions	24.2°C	51%	AC 120V/60Hz	Freedom Zhuo
Radiated Emissions-9 kHz to 30 MHz	23.6°C	57%	DC 21.6 V	Freedom Zhuo
Radiated Emissions-30 MHz to 1000 MHz	23.6°C	57%	DC 21.6 V	Freedom Zhuo
Radiated Emissions-Above 1000 MHz	23.6°C	57%	DC 21.6 V	Freedom Zhuo
Bandwidth	23.6°C	52%	DC 21.6 V	Albert Fan
Maximum Output Power	23.6°C	52%	DC 21.6 V	Albert Fan
Conducted Spurious Emission	23.6°C	52%	DC 21.6 V	Albert Fan
Power Spectral Density	23.6°C	52%	DC 21.6 V	Albert Fan

Note: Adapter supply voltage AC 120V/60Hz.



2.. GENERAL INFORMATION

2.1. GENERAL DESCRIPTION OF EUT

Product No.	POC240321001-S001
Product Name	Underwater Waist Scooter
Model Name	JETDIVE PRO, JETDIVE, JETDIVE PLUS, JETDIVE MAX
Test Model	JETDIVE PRO
Model difference	Only different in model name.
Trade Mark	N/A
Power Supply	DC 21.6V from battery
Adapter Information	Model: XVE126-2520500 Input: 100-240V 50/60Hz 2.5A Max Output: 25.2V---5A 126.0W
Operation Frequency	903 MHz ~ 914.2 MHz
Modulation Type	Lora
Data Rate	LoRa: SF8 / DR4
Max. Output Power	10.25 dBm (0.011W)
Antenna gain	7.2 dBi
Antenna type	SMD antenna

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
64	903.0	68	909.4
65	904.6	69	911.0
66	906.2	70	912.6
67	907.8	71	914.2

2.2. DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

Pretest Mode	Description
Mode 1	Lora Channel 64/67/71
Mode 2	Lora Channel 64

Following mode(s) was (were) found to be the worst case(s) and selected for the final test.

AC power line conducted emissions test	
Final Test Mode	Description
Mode 2	Lora Channel 64

Radiated emissions test – Below 1GHz	
Final Test Mode	Description
Mode 2	Lora Channel 64/67/71

Radiated emissions test – Above 1GHz	
Final Test Mode	Description
Mode 1	Lora Channel 64/67/71

Conducted test	
Final Test Mode	Description
Mode 1	Lora Channel 64/67/71

Note:

- (1) For radiated emission above 1 GHz test, the spurious points of 1GHz~18GHz and 18GHz~26.5GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.
- (2) For AC power line conducted emissions and radiated emissions below 1 GHz test, the TX Mode2_ Lora Channel 64 is found to be the worst case and recorded.



2.3. PARAMETERS OF TEST SOFTWARE

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test Software Version	SSCOM V5.13.1		
Frequency (MHz)	903.0	907.8	914.2
Lora	15	15	15

2.4. SUPPORT UNITS

No.	Equipment	Model	Manufacturer	Series No
/	/	/	/	/

3.. AC POWER LINE CONDUCTED EMISSIONS

3.1. LIMIT

Frequency of Emission (MHz)	Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56*	56 to 46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

3.2. TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:


Receiver Parameters	Setting
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.3. DEVIATION FROM TEST STANDARD

No deviation.



3.4. TEST SETUP



3.5. EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.6. TEST RESULTS

Please refer to the APPENDIX A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of 『Note』 . If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a “ * ” marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150 kHz to 30 MHz.



4.. RADIATED EMISSIONS

4.1. LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000 MHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000 MHz)

Frequency (MHz)	(dBuV/m at 3 m)	
	Peak	Average
Above 1000	74	54

Note:

- (1) The limit for radiated test was performed according to FCC CFR Title 47, Part 15, Subpart C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2. TEST PROCEDURE

- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1 GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1 GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1 GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1 GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

The following table is the setting of the receiver:

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~150 kHz for RBW 200 Hz
Start ~ Stop Frequency	0.15 MHz~30 MHz for RBW 9 kHz
Start ~ Stop Frequency	30 MHz~1000 MHz for RBW 100 kHz

Spectrum Parameters	Setting
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1 MHz / 3 MHz for PK value 1 MHz / 1/T Hz for AVG value

Spectrum Parameters	Setting
Start ~ Stop Frequency	9 kHz~90 kHz for PK/AVG detector
Start ~ Stop Frequency	90 kHz~110 kHz for QP detector
Start ~ Stop Frequency	110 kHz~490 kHz for PK/AVG detector
Start ~ Stop Frequency	490 kHz~30 MHz for QP detector
Start ~ Stop Frequency	30 MHz~1000 MHz for QP detector
Start ~ Stop Frequency	1 GHz~26.5 GHz for PK/AVG detector




4.3. DEVIATION FROM TEST STANDARD


No deviation.

4.4. TEST SETUP

9 kHz to 30 MHz




30 MHz to 1 GHz





Above 1 GHz



4.5. EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6. TEST RESULT - 9 kHz TO 30 MHz

Please refer to the APPENDIX B.

Remark:

- (1) Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB).
- (2) Limit line = specific limits (dBuV) + distance extrapolation factor.

4.7. TEST RESULT - 30 MHz TO 1000 MHz

Please refer to the APPENDIX C.

4.8. TEST RESULT - ABOVE 1000 MHz

Please refer to the APPENDIX D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.
For fundamental signal judgment was referred to Peak output test.

5.. BANDWIDTH

5.1. LIMIT

Section	Test Item	Limit
FCC 15.247(a)(2)	6 dB Bandwidth	>= 500 kHz
	99% Emission Bandwidth	-

5.2. TEST PROCEDURE

- The EUT was directly connected to the tonscend test system and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

For 6 dB Bandwidth:

Spectrum Parameters	Setting
Span Frequency	> Measurement Bandwidth
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


For 99% Emission Bandwidth:

Spectrum Parameters	Setting
Span Frequency	Between 1.5 times and 5.0 times the OBW
RBW	1% to 5% of the OBW
VBW	approximately three times RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

5.3. DEVIATION FROM STANDARD

No deviation.

5.4. TEST SETUP



5.5. EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

5.6. TEST RESULTS

Please refer to the APPENDIX E.

6.. MAXIMUM OUTPUT POWER

6.1. LIMIT

Section	Test Item	Limit
FCC 15.247(b)(3)	Maximum Output Power	1.0000 watt or 30.00 dBm

6.2. TEST PROCEDURE


- The EUT was directly connected to the tonscend test system and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	$\geq 3 \times \text{RBW}$
RBW	1 MHz
VBW	3 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.3. DEVIATION FROM STANDARD

No deviation.

6.4. TEST SETUP



6.5. EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.6. TEST RESULTS

Please refer to the APPENDIX F.

7.. CONDUCTED SPURIOUS EMISSION

7.1. LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required.

7.2. TEST PROCEDURE


- The EUT was directly connected to the tonsend test system and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Start Frequency	30 MHz
Stop Frequency	26.5 GHz
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.3. DEVIATION FROM STANDARD

No deviation.

7.4. TEST SETUP



7.5. EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6. TEST RESULTS

Please refer to the APPENDIX G.

8.. POWER SPECTRAL DENSITY

8.1. LIMIT

Section	Test Item	Limit
FCC 15.247(e)	Power Spectral Density	8 dBm (in any 3 kHz)

8.2. TEST PROCEDURE


- The EUT was directly connected to the tonscend test system and antenna output port as show in the block diagram below.
- The following table is the setting of the spectrum analyzer:

Spectrum Parameters	Setting
Span Frequency	2 MHz
RBW	3 kHz
VBW	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.3. DEVIATION FROM STANDARD

No deviation.

8.4. TEST SETUP



8.5. EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

8.6. TEST RESULTS

Please refer to the APPENDIX H.



9.. MEASUREMENT INSTRUMENTS LIST

Radiated Emissions							
No.	Equipment	Manufacturer	Type No.	Serial No.	Inventory No.	Cal. date (yyyy/mm/dd)	Cal. Due date (yyyy/mm/dd)
1	Test receiver	Rohde&Schwarz	ESU	100184	JLE011	2024/4/24	2025/4/23
2	Log periodic antenna	Schwarzbeck	VULB 9168	1151	JLE012	2024/4/20	2025/4/19
3	Low frequency amplifier	/	LNA 0920N	2014	JLE023	2024/4/24	2025/4/23
4	High frequency amplifier	Schwarzbeck	BBV 9718	284	JLE024	2024/4/24	2025/4/23
5	Horn Antenna	SCHWARZBEC K	BBHA 9120 D	9120D-1273	JLE028	2024/4/20	2025/4/19
6	Temp&Humidity Recorder	Meideshi	JR900	/	JLE021	2024/4/24	2025/4/23
7	Horn Antenna	SCHWARZBEC K	BBHA 9170	9170#68 5	JLE029	2024/7/15	2025/7/14
8	Loop Antenna	SCHWARZBEC K	FMZB15 19B	00029	JLE030	2023/7/16	2024/7/15
9	Broadband preamplifier	Schwarzbeck	BBV9721	9721-019	JLE025	2024/4/24	2025/4/23
10	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2				
Conducted Emission							
1	LISN	Rohde&Schwarz	ENV216	100075	JLE002	2024/4/24	2025/4/23
2	ISN	Schwarzbeck	CATE 5 8158	#171	JLE003	2024/4/24	2025/4/23
3	Test receiver	Rohde&Schwarz	ESCI	100718	JLE010	2024/4/24	2025/4/23
4	Pulse limiter	Rohde&Schwarz	ESH3-Z2	102299	JLE047	2024/4/24	2025/4/23
5	Temp&Humidity Recorder	Meideshi	JR900	/	JLE020	2024/4/24	2025/4/23
6	Test software	Farad Technology Co., Ltd	EZ-EMC Ver.TW-03A2				
RF conducted Emissions							
1	MXA Signal Analyzer	Keysight	N9021B	MY60080 169	JLE050	2024/4/20	2025/4/19
2	RF Control Unit	dsusoft	JS0806-2	21G8060 449	JLE053	2024/4/20	2025/4/19
3	power supply unit	dsusoft	JS0806-4ADC	N/A	JLE055	2024/4/20	2025/4/19
4	VXG Signal Generator	Keysight	M9384B	MY61270 787	JLE051	2024/4/20	2025/4/19
5	EXG Analog Signal Generator	Keysight	N5173B	MY59101 282	JLE052	2024/4/20	2025/4/19
6	Wideband Radio Communication Tester	Rohde&Schwarz	CMW500	1201.000 2K50-116064-Dt	JLE054	2024/4/20	2025/4/19
7	Test software	dsusoft	JS1120-3 Ver.3.2.22.0				



10.. ANTENNA REQUIREMENT

Test standard: FCC part 15.203


According to the manufacturer declared, the EUT has an SMD antenna, the antenna gain is 7.2dBi and the antenna connector is designed with permanent attachment and no consideration of replacement.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS

Test Mode	Lora Channel 64	Phase	Line
-----------	-----------------	-------	------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1 *		0.1500	37.02	20.08	57.10	66.00	-8.90	QP	
2		0.1500	22.91	20.08	42.99	56.00	-13.01	AVG	
3		0.3820	16.82	20.26	37.08	58.24	-21.16	QP	
4		0.3820	4.18	20.26	24.44	48.24	-23.80	AVG	
5		0.5220	16.00	20.15	36.15	56.00	-19.85	QP	
6		0.5220	4.14	20.15	24.29	46.00	-21.71	AVG	
7		0.6460	15.03	20.03	35.06	56.00	-20.94	QP	
8		0.6460	3.69	20.03	23.72	46.00	-22.28	AVG	
9		2.3220	10.99	20.11	31.10	56.00	-24.90	QP	
10		2.3220	4.68	20.11	24.79	46.00	-21.21	AVG	
11		28.3900	12.65	20.26	32.91	60.00	-27.09	QP	
12		28.3900	4.22	20.26	24.48	50.00	-25.52	AVG	

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	Lora Channel 64	Phase	Neutral
-----------	-----------------	-------	---------



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1 *		0.1500	37.00	20.35	57.35	66.00	-8.65	QP	
2		0.1500	21.16	20.35	41.51	56.00	-14.49	AVG	
3		0.1940	22.62	20.35	42.97	63.86	-20.89	QP	
4		0.1940	9.23	20.35	29.58	53.86	-24.28	AVG	
5		0.3860	7.37	20.19	27.56	58.15	-30.59	QP	
6		0.3860	-1.38	20.19	18.81	48.15	-29.34	AVG	
7		0.6820	5.03	20.16	25.19	56.00	-30.81	QP	
8		0.6820	-1.72	20.16	18.44	46.00	-27.56	AVG	
9		1.7660	8.30	20.36	28.66	56.00	-27.34	QP	
10		1.7660	2.53	20.36	22.89	46.00	-23.11	AVG	
11		28.6180	12.97	20.36	33.33	60.00	-26.67	QP	
12		28.6180	4.03	20.36	24.39	50.00	-25.61	AVG	

REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.
 (2) Margin Level = Measurement Value - Limit Value.



APPENDIX B - RADIATED EMISSION - 9 KHZ TO 30 MHZ


Radiated emission: 9KHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

APPENDIX C - RADIATED EMISSION - 30 MHZ TO 1000 MHZ


Test Mode	Lora Channel 64	Polarization	Vertical
-----------	-----------------	--------------	----------



REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	Lora Channel 64	Polarization	Horizontal
-----------	-----------------	--------------	------------




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	cm	degree	
1		36.2540	39.30	-9.98	29.32	40.00	-10.68	peak		
2		96.7750	48.64	-12.94	35.70	43.50	-7.80	peak		
3		145.3505	42.82	-8.03	34.79	43.50	-8.71	peak		
4		265.6757	49.20	-10.14	39.06	46.00	-6.94	peak		
5		374.6225	44.20	-6.70	37.50	46.00	-8.50	peak		
6 *		903.0000	102.87	3.05	105.92	46.00	59.92	peak		

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	Lora Channel 67	Polarization	Vertical
-----------	-----------------	--------------	----------




No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height cm	Table Degree	Comment
			dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	
1		36.1270	43.14	-10.01	33.13	40.00	-6.87	peak		
2		51.6613	42.71	-8.99	33.72	40.00	-6.28	peak		
3		99.5280	45.01	-12.44	32.57	43.50	-10.93	peak		
4		145.3505	40.51	-8.03	32.48	43.50	-11.02	peak		
5		386.6338	45.50	-6.30	39.20	46.00	-6.80	peak		
6 *		907.8000	91.70	2.98	94.68	46.00	48.68	peak		

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	Lora Channel 67	Polarization	Horizontal
-----------	-----------------	--------------	------------



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table
			Level	Factor	ment				
MHz									
1	36.0007	40.57	-10.02	30.55	40.00	-9.45	peak		
2	96.7750	48.54	-12.94	35.60	43.50	-7.90	peak		
3	145.3505	42.61	-8.03	34.58	43.50	-8.92	peak		
4 !	254.7281	51.05	-10.42	40.63	46.00	-5.37	peak		
5	374.6225	45.22	-6.70	38.52	46.00	-7.48	peak		
6 *	907.8000	102.34	2.98	105.32	46.00	59.32	peak		


REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.



海蕴
HAIYUN

Test Mode	Lora Channel 71	Polarization	Vertical
-----------	-----------------	--------------	----------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment				Height	Degree
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	cm	degree	Comment
1	1	31.2892	45.19	-10.68	34.51	40.00	-5.49	peak		
2		36.0007	42.29	-10.02	32.27	40.00	-7.73	peak		
3		53.3180	42.37	-9.00	33.37	40.00	-6.63	peak		
4		121.1230	42.92	-9.97	32.95	43.50	-10.55	peak		
5		387.9920	46.18	-6.25	39.93	46.00	-6.07	peak		
6	*	914.2000	89.37	3.07	92.44	46.00	46.44	peak		

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode	Lora Channel 71	Polarization	Horizontal
-----------	-----------------	--------------	------------



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table
			Level	Factor	ment				
MHz									
1		36.2540	41.34	-9.98	31.36	40.00	-8.64	peak	
2		96.7750	48.54	-12.94	35.60	43.50	-7.90	peak	
3		145.3505	42.50	-8.03	34.47	43.50	-9.03	peak	
4		259.2336	48.75	-10.15	38.60	46.00	-7.40	peak	
5		370.7022	43.73	-6.63	37.10	46.00	-8.90	peak	
6 *		914.2000	98.62	3.07	101.69	46.00	55.69	peak	


REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.



APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ

Test Mode	Lora Channel 64	Polarization	Vertical
-----------	-----------------	--------------	----------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	Degree	
			Level	Factor	ment						
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		1806.000	63.82	-13.51	50.31	74.00	-23.69	peak			
2		2709.000	56.92	-11.04	45.88	74.00	-28.12	peak			
3		3612.000	53.36	-7.23	46.13	74.00	-27.87	peak			
4		4515.000	55.70	-6.18	49.52	74.00	-24.48	peak			
5		5418.000	53.66	-5.43	48.23	74.00	-25.77	peak			
6 *		6321.000	56.88	-3.44	53.44	74.00	-20.56	peak			



海蕴
HAIYUN

Test Mode	Lora Channel 64	Polarization	Horizontal
-----------	-----------------	--------------	------------


Radiated Emission



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	cm	degree	Comment
1		1806.000	58.25	-13.51	44.74	74.00	-29.26	peak		
2		2709.000	53.49	-11.04	42.45	74.00	-31.55	peak		
3		3612.000	54.47	-7.23	47.24	74.00	-26.76	peak		
4		4515.000	53.27	-6.18	47.09	74.00	-26.91	peak		
5 *		5418.000	56.64	-5.43	51.21	74.00	-22.79	peak		
6		6321.000	53.00	-3.44	49.56	74.00	-24.44	peak		



Test Mode	Lora Channel 67	Polarization	Vertical
-----------	-----------------	--------------	----------




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment				Height	Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		1815.600	62.31	-13.46	48.85	74.00	-25.15	peak			
2		2723.400	57.29	-10.90	46.39	74.00	-27.61	peak			
3		3631.200	55.88	-7.01	48.87	74.00	-25.13	peak			
4		4539.000	55.34	-6.24	49.10	74.00	-24.90	peak			
5		5446.800	53.14	-5.53	47.61	74.00	-26.39	peak			
6 *		6354.600	55.37	-3.44	51.93	74.00	-22.07	peak			



Test Mode	Lora Channel 67	Polarization	Horizontal
-----------	-----------------	--------------	------------

Radiated Emission




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment					Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		1815.600	56.52	-13.46	43.06	74.00	-30.94	peak			
2		2723.400	53.98	-10.90	43.08	74.00	-30.92	peak			
3		3631.200	54.24	-7.01	47.23	74.00	-26.77	peak			
4		4539.000	53.72	-6.24	47.48	74.00	-26.52	peak			
5 *		5446.800	55.74	-5.53	50.21	74.00	-23.79	peak			
6		6354.600	52.83	-3.44	49.39	74.00	-24.61	peak			



海蕴
HAIYUN


Test Mode	Lora Channel 71	Polarization	Vertical
-----------	-----------------	--------------	----------



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment			Height	Degree	
		MHz	dBuV	dB/m	dBuV/m	dB	Detector	cm	degree	Comment
1		1828.400	62.59	-13.41	49.18	74.00	-24.82	peak		
2		2742.600	55.99	-10.73	45.26	74.00	-28.74	peak		
3		3656.800	54.04	-6.84	47.20	74.00	-26.80	peak		
4		4571.000	55.72	-6.28	49.44	74.00	-24.56	peak		
5		5485.200	54.71	-5.37	49.34	74.00	-24.66	peak		
6 *		6399.400	55.13	-3.73	51.40	74.00	-22.60	peak		



Test Mode	Lora Channel 71	Polarization	Horizontal
-----------	-----------------	--------------	------------



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment						
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		1828.400	56.07	-13.41	42.66	74.00	-31.34	peak			
2		2742.600	54.16	-10.73	43.43	74.00	-30.57	peak			
3		3656.800	54.53	-6.84	47.69	74.00	-26.31	peak			
4		4571.000	54.91	-6.28	48.63	74.00	-25.37	peak			
5		5485.200	55.97	-5.37	50.60	74.00	-23.40	peak			
6 *		6399.400	55.01	-3.73	51.28	74.00	-22.72	peak			

REMARKS:


- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

APPENDIX E - BANDWIDTH

DTS Bandwidth

Test Mode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
Lora	Ant1	903.0	0.626	902.694	902.320	0.5	PASS
		907.8	0.630	907.486	908.116	0.5	PASS
		914.2	0.636	913.884	914.520	0.5	PASS

Test Graphs






Occupied Channel Bandwidth

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
Lora	Ant1	903.0	0.51235	902.7486	902.2610	---	---
		907.8	0.51425	907.5457	908.0599	---	---
		914.2	0.51548	913.9465	914.4620	---	---

Test Graphs




APPENDIX F - MAXIMUM OUTPUT POWER

Test Mode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
Lora	Ant1	903.0	10.25	≤30	PASS
		907.8	10.01	≤30	PASS
		914.2	9.82	≤30	PASS



Test Graphs Peak







海蕴
HAIYUN

APPENDIX G - CONDUCTED SPURIOUS EMISSION

Conducted Spurious Emission








Band edge measurements



APPENDIX H - POWER SPECTRAL DENSITY

Test Mode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
Lora	Ant1	903.0	-1.24	≤8.00	PASS
		907.8	-0.50	≤8.00	PASS
		914.2	-0.26	≤8.00	PASS

Test Graphs



Statement

1. The report is invalid without the official seal or special seal of Shenzhen Haiyun Standard Technology Co., Ltd. (hereinafter referred to as the unit).
2. The report is invalid without the signature of the approver.
3. The report is invalid if altered arbitrarily.
4. The report shall not be partially copied without the written approval of the unit.
5. The reported test results are only valid for the tested samples.
6. If there is any objection to the test report, it shall be submitted to the test unit within 15 days from the date of receiving the report, and the overdue shall not be accepted.

Shenzhen Haiyun Standard Technology Co., Ltd.

Address: Room 110, 111, 112, 113, 115, 116, Block B, Jinyuan Business Building, No. 302, Xixiang Avenue, Labor Community, Xixiang Street, Baoan District, Shenzhen, China

Tel: 0755-26024411

Email: service@hy-lab.cn

End of Test Report