

**Maximum Permissible Exposure Report****1. Product Information**

Applicant	: Dongguan Chemomo Electronic Technology Co.,Ltd
Address	: 5th Floor, Building A, No. 293 Qingfeng Road, Qingxi Town, Dongguan City, Guangdong Province, China
EUT	: Car CarPlay Stereo
Test Model	: TS0001
Additional Model No.	: 700A, 700B, 800A, 800B, 900A, 900B, 930A, 930B, 101A, 101B, 1025A, 1025B
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Ratings	: Car Charger POWER INPUT: DC 12-24V TYPE-C OUTPUT: 5V $\overline{\text{---}}$ 3000mA
Hardware Version	: V1.0
Software Version	: /
Bluetooth:	
Frequency Range	: 2402MHz~2480MHz
Channel Number	: 79 channels for Bluetooth V4.2 (DSS) 40 channels for Bluetooth V4.2 (DTS)
Channel Spacing	: 1MHz for Bluetooth V4.2 (DSS) 2MHz for Bluetooth V4.2 (DTS)
Modulation Type	: GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth V4.2 (DSS) GFSK for Bluetooth V4.2 (DTS)
Bluetooth Version	: V4.2
Antenna Description	: FPC Antenna, 1.73dBi(Max.)
WIFI(2.4G Band):	
Frequency Range	: 2412MHz~2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channels for 20MHz bandwidth (2412~2462MHz)
Modulation Type	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: FPC Antenna, 1.73dBi(Max.)
WIFI(5.2G Band):	
Frequency Range	: 5180MHz~5240MHz
Channel Number	: 4 Channels for 20MHz bandwidth(5180MHz~5240MHz) 2 channels for 40MHz bandwidth(5190MHz~5230MHz)





Modulation Type	: IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: FPC Antenna, 4.95dBi(Max.)
WIFI(5.8G Band)	
Frequency Range	: 5745MHz~5825MHz
Channel Number	: 5 channels for 20MHz bandwidth(5745MHz~5825MHz) 2 channels for 40MHz bandwidth(5755MHz~5795MHz)
Modulation Type	: IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	: FPC Antenna, 4.95dBi(Max.)
Exposure category	: General population/uncontrolled environment
EUT Type	: Production Unit
Device Type	: Mobile Device





2. Evaluation Method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modelled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3. Limit

3.1 Refer Evaluation Method

[ANSI C95.1-2019](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz

[FCC KDB publication 447498 D01 General 1 RF Exposure Guidance v06](#): Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices.

3.2 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Uncontrolled Exposure				
0.3 – 3.0	614	1.63	(100)*	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density





4. MPE Calculation Method

Predication of MPE limit at a given distance
Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

5. Antenna Information

EUT can only use antennas certificated as follows provided by manufacturer;

Internal/ External Identification	Antenna type and antenna number	Operate frequency band	Maximum antenna gain	Notes
Internal	FPC Antenna	2400MHz ~ 2500MHz	BT/BLE: 1.73dBi	BT Antenna
Internal	FPC Antenna	2400MHz ~ 2500MHz 5150MHz ~ 5850MHz	2.4GWIFI: 1.73dBi 5.2GWIFI: 4.95dBi 5.8GWIFI: 4.95dBi	WIFI Antenna

6. Conducted Power

[BT]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
GFSK	0	2402	-0.52
	39	2441	-0.48
	78	2480	-1.21
$\pi/4$ -DQPSK	0	2402	1.39
	39	2441	1.77
	78	2480	0.61
8DPSK	0	2402	1.76
	39	2441	0.94
	78	2480	0.01

[BLE 1M]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
BLE	0	2402	-0.94
	19	2440	0.45
	39	2480	-0.63





[2.4G WIFI]

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
11B	1	2412	15.33
	6	2437	15.06
	11	2462	14.96
11G	1	2412	14.78
	6	2437	14.56
	11	2462	14.49
11N20 SISO	1	2412	13.05
	6	2437	14.09
	11	2462	13.9

[5.2G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	36	5180	13.44
	40	5200	12.93
	48	5240	12.7
11N20 SISO	36	5180	11.74
	40	5200	11.35
	48	5240	11.13
11N40 SISO	38	5190	10.4
	46	5230	11.29





[5.8G WIFI]

Mode	Channel	Frequency (MHz)	Max Conducted Power(dBm)
11A	149	5745	12.39
	157	5785	12.54
	165	5825	11.94
11N20 SISO	149	5745	11.8
	157	5785	11.9
	165	5825	11.25
11N40 SISO	151	5755	10.46
	159	5795	10.17

7. Manufacturing Tolerance

[BT]

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	0	-1.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
$\pi/4$ -DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	1.0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	1.0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[BLE1M]

BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	0	0	0
Tolerance $\pm$ (dB)	1.0	1.0	1.0





[2.4G WIFI]

11B (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	15.0	15.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11G (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	14.0	14.0	14.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Peak)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	14.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

[5.2G WIFI]

11A (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	13.0	12.0	12.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 38	Channel 46	
Target (dBm)	10.0	11.0	
Tolerance $\pm$ (dB)	1.0	1.0	

[5.8G WIFI]

11A (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	12.0	12.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	11.0	11.0	11.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0
11N40 (Average)			
Channel	Channel 151	Channel 159	
Target (dBm)	10.0	10.0	
Tolerance $\pm$ (dB)	1.0	1.0	





8. Measurement Results

8.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r=20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

[BT]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio1
	dBm	mW					
GFSK	1.0	1.2589	1.73	1.4894	0.0004	1.0000	0.0004
$\pi/4$ -DQPSK	2.0	1.5849	1.73	1.4894	0.0005	1.0000	0.0005
8-DPSK	2.0	1.5849	1.73	1.4894	0.0005	1.0000	0.0005

[BLE1M]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio1
	dBm	mW					
GFSK	1.0	1.2589	1.73	1.4894	0.0004	1.0000	0.0004

[2.4G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio1
	dBm	mW					
IEEE 802.11b	16.0	39.8107	1.73	1.4894	0.0118	1.0000	0.0118
IEEE 802.11g	15.0	31.6228	1.73	1.4894	0.0094	1.0000	0.0094
IEEE 802.11n HT20	15.0	31.6228	1.73	1.4894	0.0094	1.0000	0.0094

[5.2G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio1
	dBm	mW					
IEEE 802.11a	14.0	25.1189	4.95	3.1261	0.0156	1.0000	0.0156
IEEE 802.11n HT20	12.0	15.8489	4.95	3.1261	0.0099	1.0000	0.0099
IEEE 802.11n HT40	12.0	15.8489	4.95	3.1261	0.0099	1.0000	0.0099

[5.8G WIFI]

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)	MPE Ratio1
	dBm	mW					
IEEE 802.11a	13.0	19.9526	4.95	3.1261	0.0124	1.0000	0.0124
IEEE 802.11n HT20	12.0	15.8489	4.95	3.1261	0.0099	1.0000	0.0099
IEEE 802.11n HT40	11.0	12.5893	4.95	3.1261	0.0078	1.0000	0.0078



**Remark:**

1. Output power including tune-up tolerance;
2. Output power was adjusted to duty cycle at 100% if measured duty cycle less than 98%;
3. MPE evaluate distance is 20cm from user manual provide by manufacturer.

8.2 Simultaneous Transmission MPE Evaluation

The sample support one BT/WIFI modular. No need consider simultaneous transmission.

9. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

10. Description of Test Facility

NVLAP Accreditation Code is 600167-0.
FCC Designation Number is CN5024.
CAB identifier is CN0071.
CNAS Registration Number is L4595.
Test Firm Registration Number: 254912.

-----THE END OF REPORT-----

