

Xiamen Hongfa Electric Co Ltd.

MPE ASSESSMENT REPORT

Report Type:
FCC MPE assessment report

MODEL:
HF-CD30-1000A

REPORT NUMBER:
2406B0126SHA-002

ISSUE DATE:
November 21, 2024

DOCUMENT CONTROL NUMBER:
TTRFFCCMPE-01_V1 © 2018 Intertek



TEST REPORT

Applicant: Xiamen Hongfa Electric Co Ltd.
No. 15, Dongfuxi Second Road, Haicang District, Xiamen, 361028, China

Manufacturer: Xiamen Hongfa Electric Co Ltd.
No. 15, Dongfuxi Second Road, Haicang District, Xiamen, 361028, China

Factory: Xiamen Hongfa Electric Co Ltd.
No. 15, Dongfuxi Second Road, Haicang District, Xiamen, 361028, China

FCC ID: 2BHYF- HFCD301000A

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06
FCC Part2.1091, FCC Part1.1307(b)

PREPARED BY:

REVIEWED BY:



Project Engineer
Sky Yang



Reviewer
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
2406B0126SHA-002	Rev. 01	Initial issue of report	November 21, 2024

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	DC EV Charger
Type/Model:	HF-CD30-1000A
Description of EUT:	The EUT is electric vehicle DC charger. It contains a certified LTE module, the LTE module FCC ID is XMR201903EG25G.
Rating:	Input: 480VAC, 60Hz, 40A Max Output: 200-1000VDC, 80A Max
Category of EUT:	Class A
EUT type:	☐ Table top ☒ Floor standing
Software Version:	-
Hardware Version:	-
Serial numbers:	A241118-17
Sample received date:	November 18, 2024
Date of test:	November 18, 2024 ~ November 20, 2024

1.2 Technical Specification

Frequency Range:	13.56 MHz ~ 13.56 MHz
Modulation:	ASK
Antenna:	PCB antenna

1.3 Description of Test Facility

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Member No.: 3598 (Registration No.: R-14243, G-10845, C-14723, T-12252)
	A2LA Accreditation Lab Certificate Number: 3309.02

TEST REPORT

2 MPE Assessment

Test result: Pass

2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: Limit for 13.56MHz is 60.77 V/m

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0**

2.2 Assessment Results

Power density (S) is calculated according to the formula:

$$S = PG / (4\pi R^2)$$

Where S = power density in mW/cm²

P = Transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 2406B0126SHA-001:

$$63.2\text{dBuV/m}@3\text{m}, @20\text{cm}=@3\text{m}+40\log(3/0.2)=110.24\text{dBuV/m}=0.325\text{V/m}<60.77.$$

The power for LTE module refers to certificate of FCC ID: XMR201903EG25G

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency Range (MHz)	P		G		R (cm)	S (mW/cm ²)	Limits (mW/cm ²)
	(dBm)	(mW)	(dBi)	(numeric)			
GSM850	25.81	381.07	3.78	2.39	20	0.181	0.5495
GSM1900	22.81	190.99	3.78	2.39	20	0.091	1.0000
WCDMA Band II	25.00	316.23	3.78	2.39	20	0.150	1.0000
WCDMA Band IV	25.00	316.23	3.78	2.39	20	0.150	1.0000
WCDMA Band V	25.00	316.23	3.78	2.39	20	0.150	0.5509
LTE Band 2	25.00	316.23	3.78	2.39	20	0.150	1.0000
LTE Band 4	25.00	316.23	3.78	2.39	20	0.150	1.0000
LTE Band 5	25.00	316.23	3.78	2.39	20	0.150	0.5498
LTE Band 7	25.00	316.23	3.78	2.39	20	0.150	1.0000
LTE Band 12	25.00	316.23	3.78	2.39	20	0.150	0.4665
LTE Band 13	25.00	316.23	3.78	2.39	20	0.150	0.5197
LTE Band 25	25.00	316.23	3.78	2.39	20	0.150	1.0000
LTE Band 26(814-824)	25.00	316.23	3.78	2.39	20	0.150	0.5431
LTE Band 26(824-849)	25.00	316.23	3.78	2.39	20	0.150	0.5498
LTE Band 38	25.00	316.23	3.78	2.39	20	0.150	1.0000
LTE Band 41	25.00	316.23	3.78	2.39	20	0.150	1.0000

Note: 1 mW/cm² from 1.310 Table 1.

RFID and LTE can transmit simultaneously, so the maximum rate of MPE is,
 $0.325/60.77+0.181/0.5495=0.335 < 1.0$.

Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended.

*****END*****