



## MPE Calculation

Applicant:	Hiigge Co., Ltd.
Address:	Room 208, Floor 12, Building 1, No.588 Zixing Road, Minhang District, Shanghai, China
Product:	Snowball Pet Fountain SE
FCC ID:	2BK23-P355
Model No.:	PI3505
Reference RF report #	709502409407-00B

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

### Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1,500	/	/	f/1500	30
1,500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

#### Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4 \pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);



## Calculated Data: Internal Antenna

Maximum peak output power at antenna input terminal (dBm):	15.74
Maximum peak output power at antenna input terminal (mW):	37.50
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	2.73
Maximum Antenna Gain (numeric):	1.875
The worst case is power density at predication frequency at 20 cm (mW/cm <sup>2</sup> ):	0.01399
MPE limit for general population exposure at prediction frequency (mW/cm <sup>2</sup> ):	1.00

The max power density 0.01399 (mW/cm<sup>2</sup>) < 1 (mW/cm<sup>2</sup>)

Result: Compliant

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Hui TONG

EMC Section Manager

Date:2024-11-21



Prepared by:

Wenqiang LU

EMC Project Engineer

Date:2024-11-21

Tested by:

Tianji XU

EMC Test Engineer

Date:2024-11-21

-----End of Test Report-----