

FCC PART 15.247


TEST REPORT

For

SPACEWALKER PTE. LTD.

60 PAYA LEBAR ROAD SINGAPORE Singapore

FCC ID: 2BK3M-BIR3X02

Report Type: Original Report	Product Name: Electric Golf Push Cart
Report Number: <u>RKSA250527003-00B</u>	
Report Date: <u>2025-08-12</u>	
Reviewed By:	<u>Bard Liu</u> 
Approved By:	<u>Kyle Xu</u> 
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S.Government.

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES.....	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	9
BLOCK DIAGRAM OF TEST SETUP	9
TEST EQUIPMENT LIST	11
SUMMARY OF TEST RESULTS	12
FCC §1.1307(b) & §2.1093 - RF EXPOSURE.....	13
APPLICABLE STANDARD	13
CALCULATED FORMULARY:.....	13
FCC §15.203 – ANTENNA REQUIREMENT	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
TEST SYSTEM SETUP.....	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	17
TEST RESULTS SUMMARY	17
TEST DATA: SEE APPENDIX	17
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD	18
TEST SYSTEM SETUP.....	18
EMI TEST RECEIVER SETUP.....	19
TEST PROCEDURE	19
TEST RESULTS SUMMARY	20
TEST DATA: SEE APPENDIX	20
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATA: SEE APPENDIX	21
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATA: SEE APPENDIX	22
FCC §15.247(d) – BAND EDGE.....	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23

TEST DATA: SEE APPENDIX	23
FCC §15.247(e) - POWER SPECTRAL DENSITY	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATA: SEE APPENDIX	24
EUT PHOTOGRAPHS.....	25
TEST SETUP PHOTOGRAPHS.....	26
APPENDIX - TEST DATA.....	27
AC LINE CONDUCTED EMISSIONS	27
SPURIOUS EMISSIONS.....	31
6 dB EMISSION BANDWIDTH	48
MAXIMUM CONDUCTED OUTPUT POWER.....	50
BAND EDGE	52
POWER SPECTRAL DENSITY	54

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	RKSA250527003-00B	R1V1	2025-08-12	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	SPACEWALKER PTE. LTD.
Tested Model:	Birdie 3X-U
Product Name:	Electric Golf Push Cart
Power Supply:	DC 21.6V from battery or DC 25.2V from adapter
RF Function:	BLE
Operating Band/Frequency:	BLE (1 Mbps): 2402-2480 MHz BLE (2 Mbps): 2404-2478 MHz
Maximum Output Power:	BLE (1 Mbps): 4.22 dBm BLE (2 Mbps): 4.06 dBm
Channel Number:	40
Channel Separation:	2 MHz
Modulation Type	GFSK
Antenna Type:	PCB Antenna
★Maximum Antenna Gain:	1.22 dBi

Adapter Information:

Model: FY0422521500

Input: 100-240V 50/60Hz 1.5A

Output: 25.2V, 1.5A

Note: The maximum antenna gain was provided by the applicant.

All measurement and tested data in this report was gathered from production sample serial number: RKSA250527003-1 (for conducted emissions and radiated emissions test), RKSA250527003-2 (for RF conducted test) (Assigned by BACL (Kunshan). The EUT supplied by the applicant was received on 2025-05-27.)

Objective

This report is prepared for *SPACEWALKER PTE. LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communications Commission rules.

The tests were performed in order to determine Compliant with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10:2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB 558074 D01 15.247 Meas Guidance v05r02.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9 dB
RF Output Power with Power meter		0.5 dB
Radiated emissions	9 kHz~150 kHz	3.8 dB
	150 kHz~30 MHz	3.4 dB
	30MHz~1GHz	6.11 dB
	1GHz~6GHz	4.45 dB
	6GHz~18GHz	5.23 dB
	18GHz~40GHz	5.65 dB
Occupied Bandwidth		0.5 kHz
Temperature		1.0 °C
Humidity		6 %

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu Province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No.: CN5055.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel List for BLE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	/	/
13	2428	27	2456	/	/

EUT BLE 1M was tested with channel 0, 19 and 39, EUT BLE 2M was tested with channel 1, 19 and 38.

EUT Exercise Software

RF Test Tool: RTL8762x_RFTTestTool

★Power level: Default

Note: The power level was declared by the applicant.

Special Accessories

No special accessory.


Equipment Modifications

No modification was made to the EUT tested.


Environmental Conditions & Test Information

Test Date:	2025-06-13 to 2025-06-14
Temperature:	25.5 °C
Relative Humidity:	60-65 %
ATM Pressure:	100.6-101.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

Duty Cycle:



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 13.JUN.2025 15:19:15



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:33:14

Mode	Duty Cycle (%)	T _{on} (ms)	Ton+off(ms)	10log(1/x) (dB)
BLE (1 Mbps)	62.02	0.774	1.248	2.07
BLE (2 Mbps)	32.21	0.401	1.245	4.92

Note: Offset(10.5dB) = Attenuator(10dB)+Cable loss(0.5dB)

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Lenovo	Notebook	Thinkpad T470S	83ECA1B-E1AF-4053-95DE-2E51B8D188D7
Unknown	Debug Board	Unknown	Unknown
SPACEWALKER PTE. LTD.	Remote Control	Birdie 3-A1-U	Unknown

External I/O Cable


Cable Description	Length (m)	From Port	To Port
Power Cable 1	1.5	LISN/AC Source	Adapter
Power Cable 2	1.5	Adapter	EUT
Data Cable 1	0.3	EUT	Debug Board
Data Cable 2	1.5	Debug Board	Notebook
Data Cable 3	1.5	EUT	Notebook
USB Cable	1.0	EUT	Remote Control

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



Note: The EUT Antenna 1.5m above Ground Plane

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber #1)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2025-04-09	2026-04-08
Sunol Sciences	Hybrid Antenna	JB3	A090314-2	2024-10-29	2027-10-28
BACL	Active Loop Antenna	1313-1A	4041511	2024-11-22	2027-11-21
Narda	6 dB Attenuator	771-6	10690812-2-1	2024-10-29	2027-10-28
Sonoma Instrument	Pre-amplifier	310N	171205	2025-04-09	2026-04-08
Rohde & Schwarz	Auto Test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-9	009	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-10	010	2025-04-09	2026-04-08
Radiated Emission Test (Chamber #2)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207/040	2025-04-09	2026-04-08
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2024-11-03	2027-11-02
ETS-LINDGREN	Horn Antenna	3116	2516	2024-12-12	2027-12-11
A.H.Systems,inc	Amplifier	PAM-0118P	512	2025-04-09	2026-04-08
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2024-08-05	2025-08-04
Narda	Attenuator	10dB	010	2025-04-08	2026-04-07
SELECTOR	Amplifier	EM18G40G	60726	2025-04-09	2026-04-08
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-11	011	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-12	012	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-13	013	2025-04-09	2026-04-08
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200103	2025-04-09	2026-04-08
Narda	Attenuator	10dB	010	2025-04-08	2026-04-07
XHFDZ	RG316 Coaxial Cable	SMA-316	XHF-1175	Each time	N/A
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2024-07-28	2025-07-27
Rohde & Schwarz	LISN	ENV216	101115	2025-04-08	2026-04-07
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	100552	2025-04-08	2026-04-07
MICRO-COAX	Coaxial Cable	Cable-15	015	2025-04-08	2026-04-07

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307(b) & §2.1093	RF EXPOSURE	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

FCC §1.1307(b) & §2.1093 - RF EXPOSURE

Applicable Standard

According to §2.1093 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

1. f (GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

RF Exposure for devices that operate above 6 GHz (1.1310):

2.1093 (d): Portable devices that transmit at frequencies above 6 GHz are to be evaluated in terms of the MPE limits specified 47 CFR 1.1310. Measurements and calculations to demonstrate compliance with MPE Field strength or power density limits for device operating above 6 GHz should be made at a minimum distance of 0.5 cm from the radiating source.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	★Max Tune-up Conducted Power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
BLE 1M	2402-2480	4.5	2.82	5.0	0.9	3.0	Yes
BLE 2M	2404-2478	4.5	2.82	5.0	0.9	3.0	Yes

Mode	Frequency Range (MHz)	Antenna Gain★		Max Tune-up Conducted Power★		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
UWB	7987.2	1.84	1.53	-7.0	0.20	0.5	0.097	1.00

BLE and UWB can Simultaneous Transmit

For simultaneously transmit, the worst condition is below:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

$$=0.9/3.0+0.097/1=0.397 < 1.0$$

Result: No SAR test is required.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has a PCB Antenna for BLE, and the antenna gain is 1.22 dBi, which is permanently attached to the unit, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

Test System Setup



The measurement procedure of EUT setup is according with ANSI C63.10:2020. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	VBW
150 kHz – 30 MHz	9 kHz	30 kHz

Test Procedure

ANSI C63.10:2020 clause 6.2

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

Level (dBμV) = Read level (dBμV) + Factor (dB)

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

Over Limit (dB) = Level (dBμV) - Limit (dBμV)



Test Results Summary


According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data: See Appendix

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

Test System Setup**9 kHz - 30 MHz:****30 MHz - 1 GHz:**

Above 1 GHz:

Note: The EUT Antenna 1.5m above Ground Plane

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10:2020. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Measurement
9 kHz - 150 kHz	200 Hz	1 kHz	200 Hz	QP/Average
150 kHz - 30 MHz	9 kHz	30 kHz	9 kHz	QP/ Average
30 MHz - 1000 MHz	100 kHz	300 kHz	/	Peak
	/	/	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	Peak
	1MHz	3 MHz	/	Average

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

If the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

For 9 kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V/m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V/m)}$$

Note: The QuasiPeak (dB μ V/m), MaxPeak (dB μ V/m), Average (dB μ V/m) which shown in the data table are all Corrected Amplitude.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data: See Appendix

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10:2020 sub-clause 11.8.1

- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “–6 dB down amplitude”. If a marker is below this “–6 dB down amplitude” value, then it shall be as close as possible to this value.



Note: the offset=Attenuator (10dB) + Cable loss (0.5dB) has been added in Spectrum Analyzer.

Test Data: See Appendix

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10:2020 sub-clause 11.9.1.1

- a) Set the RBW $\geq$ DTS bandwidth.
- b) Set VBW $\geq [3 \times \text{RBW}]$.
- c) Set span $\geq [3 \times \text{RBW}]$.
- d) Sweep time = No faster than coupled (auto) time.
- e) Detector = peak.
- f) Trace mode = max-hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.



Note: the offset=Attenuator (10dB) + Cable loss (0.5dB) has been added in Spectrum Analyzer.

Test Data: See Appendix

FCC §15.247(d) – BAND EDGE


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10:2020 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Note: the offset=Attenuator (10dB) + Cable loss (0.5dB) has been added in Spectrum Analyzer.

Test Data: See Appendix

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard


For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10:2020 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span >1.5 times the DTS bandwidth.
- c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = peak.
- f) Sweep time = No faster than coupled (auto) time.
- g) Trace mode = max-hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.



Note: the offset=Attenuator (10dB) + Cable loss (0.5dB) has been added in Spectrum Analyzer.

Test Data: See Appendix

EUT PHOTOGRAPHS

Please refer to the attachment EXHIBIT A-EUT EXTERNAL PHOTOGRAPHS and EXHIBIT B-EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment EXHIBIT C-TEST SETUP PHOTOGRAPHS.

APPENDIX - TEST DATA


AC LINE CONDUCTED EMISSIONS

Environmental Conditions & Test Information

Test Date:	2025-06-24
Temperature:	24.1 °C
Relative Humidity:	65 %
ATM Pressure:	101.1 kPa
Test Result:	Pass
Test Engineer:	Myles Miao

EUT operation mode: Transmitting in BLE (1 Mbps) high channel (maximum output power)

AC 120V/60 Hz, Line




Trace: 1

Site : CE
Condition : limit\FCC PART 15.207
: DET:Peak
Project No. : RKSA250527003
Model : Birdie 3X-U
Phase : L
Voltage : 120V/60Hz
Mode : BLE 1M
Test Equipment : ENV216,ESR3
Receiver Setting : RBW: 9 kHz,Sweep Time: Auto
Temperature : 24.1°C
Humidity : 65%
Atmospheric pressure: 101.1kPa
Test Engineer : Myles Miao

	Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB	dBuV	dB	
1	0.381	11.10	20.23	31.33	48.26	-16.93 Average
2	0.381	23.70	20.23	43.93	58.26	-14.33 QP
3	0.573	11.19	20.20	31.39	46.00	-14.61 Average
4	0.573	24.19	20.20	44.39	56.00	-11.61 QP
5	0.659	14.90	20.20	35.10	46.00	-10.90 Average
6	0.659	28.60	20.20	48.80	56.00	-7.20 QP
7	0.758	15.10	20.08	35.18	46.00	-10.82 Average
8	0.758	28.50	20.08	48.58	56.00	-7.42 QP
9	0.925	7.10	19.78	26.88	46.00	-19.12 Average
10	0.925	18.90	19.78	38.68	56.00	-17.32 QP
11	1.037	10.41	19.68	30.09	46.00	-15.91 Average
12	1.037	19.41	19.68	39.09	56.00	-16.91 QP


AC 120V/60 Hz, Neutral



Site : CE
Condition : limit\FCC PART 15.207
: DET:Peak
Project No. : RKSA250527003
Model : Birdie 3X-U
Phase : N
Voltage : 120V/60Hz
Mode : BLE 1M
Test Equipment : ENV216,ESR3
Receiver Setting : RBW: 9 kHz,Sweep Time: Auto
Temperature : 24.1°C
Humidity : 65%
Atmospheric pressure: 101.1kPa
Test Engineer : Myles Miao

	Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.385	11.30	20.23	31.53	48.18	-16.65 Average
2	0.385	23.60	20.23	43.83	58.18	-14.35 QP
3	0.535	7.60	20.19	27.79	46.00	-18.21 Average
4	0.535	22.60	20.19	42.79	56.00	-13.21 QP
5	0.568	11.49	20.20	31.69	46.00	-14.31 Average
6	0.568	25.29	20.20	45.49	56.00	-10.51 QP
7	0.689	18.30	20.20	38.50	46.00	-7.50 Average
8	0.689	30.90	20.20	51.10	56.00	-4.90 QP
9	0.754	18.50	20.09	38.59	46.00	-7.41 Average
10	0.754	29.60	20.09	49.69	56.00	-6.31 QP
11	0.867	10.50	19.88	30.38	46.00	-15.62 Average
12	0.867	21.60	19.88	41.48	56.00	-14.52 QP


EUT operation mode: Transmitting in BLE (2 Mbps) high channel (maximum output power)
AC 120V/60 Hz, Line



Site : CE
Condition : limit\FCC PART 15.207
: DET:Peak
Project No. : RKSA250527003
Model : Birdie 3X-U
Phase : L
Voltage : 120V/60Hz
Mode : BLE 2M
Test Equipment : ENV216,ESR3
Receiver Setting : RBW: 9 kHz,Sweep Time: Auto
Temperature : 24.1°C
Humidity : 65%
Atmospheric pressure: 101.1kPa
Test Engineer : Myles Miao

	Read			Limit	Over	
	Freq	Level	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.429	10.09	20.26	30.35	47.26	-16.91 Average
2	0.429	23.59	20.26	43.85	57.26	-13.41 QP
3	0.588	10.10	20.20	30.30	46.00	-15.70 Average
4	0.588	25.50	20.20	45.70	56.00	-10.30 QP
5	0.696	20.00	20.20	40.20	46.00	-5.80 Average
6	0.696	32.30	20.20	52.50	56.00	-3.50 QP
7	0.837	11.00	19.93	30.93	46.00	-15.07 Average
8	0.837	23.20	19.93	43.13	56.00	-12.87 QP
9	1.012	8.20	19.67	27.87	46.00	-18.13 Average
10	1.012	21.70	19.67	41.37	56.00	-14.63 QP
11	1.199	9.29	19.80	29.09	46.00	-16.91 Average
12	1.199	20.99	19.80	40.79	56.00	-15.21 QP

AC 120V/60 Hz, Neutral



Trace: 1

Site : CE
 Condition : limit\FCC PART 15.207
 : DET:Peak
 Project No. : RKSA250527003
 Model : Birdie 3X-U
 Phase : N
 Voltage : 120V/60Hz
 Mode : BLE 2M
 Test Equipment : ENV216,ESR3
 Receiver Setting : RBW: 9 kHz,Sweep Time: Auto
 Temperature : 24.1°C
 Humidity : 65%
 Atmospheric pressure: 101.1kPa
 Test Engineer : Myles Miao

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.400	11.30	20.24	31.54	47.84	-16.30	Average
2	0.400	24.10	20.24	44.34	57.84	-13.50	QP
3	0.570	9.99	20.20	30.19	46.00	-15.81	Average
4	0.570	24.99	20.20	45.19	56.00	-10.81	QP
5	0.703	18.90	20.19	39.09	46.00	-6.91	Average
6	0.703	32.10	20.19	52.29	56.00	-3.71	QP
7	0.846	10.70	19.91	30.61	46.00	-15.39	Average
8	0.846	25.10	19.91	45.01	56.00	-10.99	QP
9	0.944	7.60	19.75	27.35	46.00	-18.65	Average
10	0.944	21.70	19.75	41.45	56.00	-14.55	QP
11	1.146	9.70	19.76	29.46	46.00	-16.54	Average
12	1.146	22.30	19.76	42.06	56.00	-13.94	QP

SPURIOUS EMISSIONS**Environmental Conditions & Test Information**


Frequency Range:	9kHz - 1GHz	1 GHz - 18 GHz	18 GHz - 25 GHz
Test Date:	2025-06-10	2025-06-11	2025-07-17
Temperature:	23.9 °C	24.1 °C	25.5 °C
Relative Humidity:	51 %	57 %	63 %
ATM Pressure:	100.8 kPa	101.3 kPa	100.2 kPa
Test Result:	Pass	Pass	Pass
Test Engineer:	Jonathan	Destine Hu	Hugh Wu

Test Result: Compliant.


EUT operation mode: Transmitting

**9 kHz-30MHz: Transmitting in maximum output power mode BLE (1 Mbps) high channel
Parallel(worst case)**

9kHz-150kHz



150kHz-30MHz



Project No.RKSA250527003

Tester:Jonathan

Date: 10.JUN.2025 13:36:03

Project No.RKSA250527003

Tester:Jonathan

Date: 10.JUN.2025 13:39:51

9 kHz-150 kHz


Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.029586	45.52	PK	-0.61	118.18	72.66
0.055530	51.56	PK	-4.46	112.71	61.15
0.061170	52.32	PK	-5.11	111.87	59.55
0.062862	49.83	PK	-5.31	111.64	61.81

150 kHz-30 MHz


Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m) @3m	Margin (dB)
0.15000	49.42	PK	-11.34	104.08	54.66
1.16490	52.23	PK	-28.15	66.28	14.05
2.89620	37.19	PK	-31.36	69.54	32.35
6.95580	37.44	PK	-32.35	69.54	32.10

9 kHz-30MHz: Transmitting in maximum output power mode BLE (2 Mbps) high channel
Parallel(worst case)

9kHz-150kHz



150kHz-30MHz



Project No.RKSA250527003
 Date: 10.JUN.2025 13:56:52

Tester:Jonathan

Project No.RKSA250527003
 Date: 10.JUN.2025 14:00:19

Tester:Jonathan

9 kHz-150 kHz


Frequency (MHz)	Corrected Amplitude (dBuV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBuV/m) @3m	Margin (dB)
0.028176	46.80	PK	-0.60	118.61	71.81
0.036918	46.42	PK	-1.72	116.26	69.84
0.045660	49.53	PK	-3.12	114.41	64.88
0.051864	49.25	PK	-4.03	113.31	64.06

150 kHz-30 MHz

Frequency (MHz)	Corrected Amplitude (dBuV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBuV/m) @3m	Margin (dB)
0.15000	52.17	PK	-11.34	104.08	51.91
1.16490	51.96	PK	-28.15	66.28	14.32
3.01560	37.86	PK	-31.42	69.54	31.68
7.19460	37.38	PK	-32.39	69.54	32.16

30 MHz - 1 GHz:**Transmitting in maximum output power BLE 1M high channel****High Channel: 2480 MHz****Common Information**


Project No:	RKSA250527003
EUT Model:	Birdie 3X-U
Test Mode:	Transmitting in BLE-1M mode high channel
Standard:	FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.247
Test Equipment:	ESCI, JB3, 310N
Receiver Setting:	RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto
Temperature:	23.9°C
Humidity:	51%
Barometric Pressure:	100.8 kPa
Test Engineer:	Jonathan
Test Date:	2025/6/10

**Final Result**

Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
30.848750	28.42	40.00	11.58	V	-4.8
33.880000	30.99	40.00	9.01	V	-6.6
68.193750	26.24	40.00	13.76	H	-16.7
132.213750	27.33	43.50	16.17	H	-11.1
137.548750	30.83	43.50	12.67	H	-11.2
271.287500	30.35	46.00	15.65	H	-11.1

30 MHz - 1 GHz:**Transmitting in maximum output power BLE 2M high channel****High Channel: 2478 MHz****Common Information**

Project No:	RKSA250527003
EUT Model:	Birdie 3X-U
Test Mode:	Transmitting in BLE-2M mode high channel
Standard:	FCC Part 15.205 & FCC Part 15.209 & FCC Part 15.247
Test Equipment:	ESCI, JB3, 310N
Receiver Setting:	RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto
Temperature:	23.9°C
Humidity:	51%
Barometric Pressure:	100.8 kPa
Test Engineer:	Jonathan
Test Date:	2025/6/10

**Final Result**


Frequency (MHz)	QuasiPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
30.727500	35.12	40.00	4.88	V	-6.0
33.031250	36.95	40.00	3.05	V	-6.5
45.277500	23.96	40.00	16.04	V	-13.9
134.760000	27.99	43.50	15.51	H	-11.1
183.138750	24.88	43.50	18.62	H	-12.9
267.043750	29.96	46.00	16.04	H	-11.4

1 GHz-18 GHz:**BLE (1 Mbps)****Low Channel: 2402 MHz**

Common Information

Project No.:	RKSA250527003
EUT Model:	Birdie 3X-U
Test Mode:	Transmitting in BLE 1M Low Channel
Standard:	FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	24.1°C
Humidity:	57%
Atmospheric Pressure:	101.3kPa
Test Engineer:	Destine Hu
Test Date:	2025/6/11

Fundamental Test with
Band Reject Filter




Critical Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1159.800000	33.26	---	74.00	40.74	V	-15.4
1159.800000	---	19.86	54.00	34.14	V	-15.4
1992.800000	---	26.69	54.00	27.31	V	-10.6
1992.800000	37.13	---	74.00	36.87	V	-10.6
3546.600000	38.95	---	74.00	35.05	H	-7.2
3546.600000	---	29.01	54.00	24.99	H	-7.2
5984.400000	---	35.95	54.00	18.05	V	-1.1
5984.400000	48.34	---	74.00	25.66	V	-1.1
16969.800000	54.95	---	74.00	19.05	H	11.2
16969.800000	---	44.86	54.00	9.14	H	11.2
17904.800000	52.74	---	74.00	21.26	V	11.5
17904.800000	---	45.82	54.00	8.18	V	11.5

Middle Channel: 2440 MHz**Common Information**

Project No.:	RKSA250527003
EUT Model:	Birdie 3X-U
Test Mode:	Transmitting in BLE 1M Middle Channel
Standard:	FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	24.1°C
Humidity:	57%
Atmospheric Pressure:	101.3kPa
Test Engineer:	Destine Hu
Test Date:	2025/6/11

Fundamental Test with
Band Reject Filter


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µV/m)	Average (dB µV/m)	Limit (dB µV/m)	Margin (dB)	Pol	Corr. (dB/m)
1132.600000	---	22.70	54.00	31.30	V	-15.5
1132.600000	31.59	---	74.00	42.41	V	-15.5
1989.400000	37.66	---	74.00	36.34	H	-10.6
1989.400000	---	25.40	54.00	28.60	H	-10.6
5998.000000	---	39.10	54.00	14.90	V	-1.1
5998.000000	48.79	---	74.00	25.21	V	-1.1
10186.800000	---	41.84	54.00	12.16	H	6.1
10186.800000	52.46	---	74.00	21.54	H	6.1
17585.200000	---	46.05	54.00	7.95	V	10.7
17585.200000	52.27	---	74.00	21.73	V	10.7
17877.600000	---	44.73	54.00	9.27	V	11.4
17877.600000	55.63	---	74.00	18.37	V	11.4

High Channel: 2480 MHz**Common Information**

Project No.:	RKSA250527003
EUT Model:	Birdie 3X-U
Test Mode:	Transmitting in BLE 1M High Channel
Standard:	FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	24.1°C
Humidity:	57%
Atmospheric Pressure:	101.3kPa
Test Engineer:	Destine Hu
Test Date:	2025/6/11

Fundamental Test with
Band Reject Filter


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1992.800000	---	26.83	54.00	27.17	V	-10.6
1992.800000	37.75	---	74.00	36.25	V	-10.6
3594.200000	---	27.87	54.00	26.13	V	-7.1
3594.200000	39.30	---	74.00	34.70	V	-7.1
5998.000000	---	39.35	54.00	14.65	V	-1.1
5998.000000	48.76	---	74.00	25.24	V	-1.1
12114.600000	---	43.76	54.00	10.24	H	8.1
12114.600000	54.51	---	74.00	19.49	H	8.1
17779.000000	54.91	---	74.00	19.09	H	11.2
17779.000000	---	45.01	54.00	8.99	H	11.2
17966.000000	54.08	---	74.00	19.92	V	11.7
17966.000000	---	45.96	54.00	8.04	V	11.7

1 GHz-18 GHz:**BLE (2 Mbps)****Low Channel: 2404 MHz****Common Information**

Project No.:	RKSA250527003
EUT Model:	Birdie 3X-U
Test Mode:	Transmitting in BLE 2M Low Channel
Standard:	FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	24.1℃
Humidity:	57%
Atmospheric Pressure:	101.3kPa
Test Engineer:	Destine Hu
Test Date:	2025/6/11

Fundamental Test with
Band Reject Filter


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1989.400000	---	29.02	54.00	24.98	V	-10.6
1989.400000	38.89	---	74.00	35.11	V	-10.6
5998.000000	---	39.25	54.00	14.75	V	-1.1
5998.000000	46.70	---	74.00	27.30	V	-1.1
7470.200000	---	39.46	54.00	14.54	V	2.8
7470.200000	51.14	---	74.00	22.86	V	2.8
13161.800000	---	43.24	54.00	10.76	H	8.7
13161.800000	54.28	---	74.00	19.72	H	8.7
17014.000000	---	46.51	54.00	7.49	V	11.2
17014.000000	53.09	---	74.00	20.91	V	11.2
17031.000000	---	44.40	54.00	9.60	V	11.2
17031.000000	54.98	---	74.00	19.02	V	11.2

Middle Channel: 2440 MHz**Common Information**

Project No.:	RKSA250527003
EUT Model:	Birdie 3X-U
Test Mode:	Transmitting in BLE 2M Middle Channel
Standard:	FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	24.1 °C
Humidity:	57%
Atmospheric Pressure:	101.3kPa
Test Engineer:	Destine Hu
Test Date:	2025/6/11

Fundamental Test with
Band Reject Filter


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1989.400000	---	27.33	54.00	26.67	V	-10.6
1989.400000	37.64	---	74.00	36.36	V	-10.6
2992.400000	---	27.61	54.00	26.39	V	-9.1
2992.400000	38.93	---	74.00	35.07	V	-9.1
6426.400000	---	36.04	54.00	17.96	H	-0.6
6426.400000	47.61	---	74.00	26.39	H	-0.6
8850.600000	---	41.83	54.00	12.17	H	4.4
8850.600000	51.59	---	74.00	22.41	H	4.4
17034.400000	54.16	---	74.00	19.84	V	11.2
17034.400000	---	45.66	54.00	8.34	V	11.2
17935.400000	---	44.57	54.00	9.43	V	11.6
17935.400000	55.32	---	74.00	18.68	V	11.6

High Channel: 2478 MHz**Common Information**

Project No.:	RKSA250527003
EUT Model:	Birdie 3X-U
Test Mode:	Transmitting in BLE 2M High Channel
Standard:	FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	24.1℃
Humidity:	57%
Atmospheric Pressure:	101.3kPa
Test Engineer:	Destine Hu
Test Date:	2025/6/11

Fundamental Test with
Band Reject Filter


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1996.200000	---	28.87	54.00	25.13	V	-10.5
1996.200000	37.95	---	74.00	36.05	V	-10.5
3856.000000	---	28.58	54.00	25.42	V	-6.7
3856.000000	39.97	---	74.00	34.03	V	-6.7
5998.000000	---	38.10	54.00	15.90	V	-1.1
5998.000000	49.00	---	74.00	25.00	V	-1.1
12043.200000	---	43.49	54.00	10.51	V	8.0
12043.200000	54.71	---	74.00	19.29	V	8.0
16799.800000	---	45.46	54.00	8.54	V	10.6
16799.800000	52.20	---	74.00	21.80	V	10.6
17915.000000	---	43.90	54.00	10.10	H	11.5
17915.000000	55.12	---	74.00	18.88	H	11.5


18 GHz - 25 GHz :

Transmitting in maximum output power BLE (1 Mbps) high channel:

Horizontal



Vertical



Project No :RKSA250527003
Date: 17.JUL.2025 17:32:34

Tester :Rugh Wu

Project No :RKSA250527003
Date: 17.JUL.2025 18:06:30


Tester :Rugh Wu

Frequency (GHz)	Max Peak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
20.21	---	39.04	54	14.96	V	12.47
20.21	49.07	---	74	24.93	V	12.47
20.24	---	38.74	54	15.26	H	12.50
20.24	48.28	---	74	25.72	H	12.50


18 GHz - 25 GHz :

Transmitting in maximum output power BLE (2 Mbps) high channel:

Horizontal



Vertical



Project No :RKSA250527003
Date: 17.JUL.2025 18:39:35

Tester :Rugh Wu

Project No :RKSA250527003
Date: 17.JUL.2025 19:23:07


Tester :Rugh Wu

Frequency (GHz)	Max Peak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB/m)
19.66	---	39.07	54	14.93	V	11.30
19.66	47.94	---	74	26.06	V	11.30
20.22	---	39.23	54	14.77	H	12.48
20.22	49.35	---	74	24.65	H	12.48

RESTRICTED BANDS EMISSION:**BLE (1 Mbps)****Left Side****Common Information**

Project No.:	RKSA250527003
EUT Model:	Birdie 3X-U
Test Mode:	Transmitting in BLE 1M Low Channel
Standard:	FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	24.1°C
Humidity:	57%
Atmospheric Pressure:	101.3kPa
Test Engineer:	Destine Hu
Test Date:	2025/6/11

Full Spectrum

**Critical Freqs**


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2345.056000	---	35.14	54.00	18.86	V	-0.4
2345.056000	46.60	---	74.00	27.40	V	-0.4
2382.352000	---	36.46	54.00	17.54	H	-0.3
2382.352000	48.97	---	74.00	25.03	H	-0.3

Right Side

Common Information

Project No.: RKSA250527003
EUT Model: Birdie 3X-U
Test Mode: Transmitting in BLE 1M High Channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 24.1°C
Humidity: 57%
Atmospheric Pressure: 101.3kPa
Test Engineer: Destine Hu
Test Date: 2025/6/11

Full Spectrum




Critical Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2485.768000	---	35.86	54.00	18.14	H	-0.2
2485.768000	50.43	---	74.00	23.57	H	-0.2
2499.328000	---	38.07	54.00	15.93	H	-0.2
2499.328000	50.82	---	74.00	23.18	H	-0.2

BLE (2 Mbps)**Left Side****Common Information**

Project No.:	RKSA250527003
EUT Model:	Birdie 3X-U
Test Mode:	Transmitting in BLE 2M Low Channel
Standard:	FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment:	ESU40,3115,PAM-0118P
Receiver Setting:	RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature:	24.1°C
Humidity:	57%
Atmospheric Pressure:	101.3kPa
Test Engineer:	Destine Hu
Test Date:	2025/6/11

Full Spectrum


**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2366.168000	---	36.26	54.00	17.74	H	-0.4
2366.168000	44.48	---	74.00	29.52	H	-0.4
2383.696000	---	35.27	54.00	18.73	H	-0.3
2383.696000	48.52	---	74.00	25.48	H	-0.3

Right Side**Common Information**

Project No.: RKSA250527003
EUT Model: Birdie 3X-U
Test Mode: Transmitting in BLE 2M High Channel
Standard: FCC Part 15.247 & FCC Part 15.205 & FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 24.1°C
Humidity: 57%
Atmospheric Pressure: 101.3kPa
Test Engineer: Destine Hu
Test Date: 2025/6/11

Full Spectrum

**Critical Freqs**

Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2495.440000	51.01	---	74.00	22.99	H	-0.2
2495.440000	---	35.87	54.00	18.13	H	-0.2
2496.208000	46.93	---	74.00	27.07	H	-0.2
2496.208000	---	36.99	54.00	17.01	H	-0.2

6 dB EMISSION BANDWIDTH**Environmental Conditions & Test Information**

Test Date:	2025-06-13 to 2025-06-14
Temperature:	25.5 °C
Relative Humidity:	60-65 %
ATM Pressure:	100.6-101.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou


Test Result: Compliant.

EUT operation mode: Transmitting

Mode	Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
BLE (1 Mbps)	Low	2402	0.676	≥ 0.5
	Middle	2440	0.744	≥ 0.5
	High	2480	0.868	≥ 0.5
BLE (2 Mbps)	Low	2404	1.134	≥ 0.5
	Middle	2440	1.128	≥ 0.5
	High	2478	1.128	≥ 0.5


BLE (1 Mbps)

Low Channel




ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 13.JUN.2025 15:10:16

Middle Channel



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 13.JUN.2025 15:19:50


High Channel



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:12:00


BLE (2 Mbps)

Low Channel




ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:21:12

Middle Channel



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:33:49

High Channel



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 16:25:54

MAXIMUM CONDUCTED OUTPUT POWER**Environmental Conditions & Test Information**

Test Date:	2025-06-13 to 2025-06-14
Temperature:	25.5 °C
Relative Humidity:	60-65 %
ATM Pressure:	100.6-101.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou


Test Result: Compliant.

EUT operation mode: Transmitting

Mode	Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
BLE (1 Mbps)	Low	2402	4.10	30	Pass
	Middle	2440	3.98	30	Pass
	High	2480	4.22	30	Pass
BLE (2 Mbps)	Low	2404	3.98	30	Pass
	Middle	2440	3.93	30	Pass
	High	2478	4.06	30	Pass


BLE (1 Mbps)

Low Channel




ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 13.JUN.2025 15:11:39

Middle Channel



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 13.JUN.2025 15:20:29


High Channel



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:12:38


BLE (2 Mbps)

Low Channel




ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:22:41

Middle Channel



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:35:51

High Channel



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 16:27:02

BAND EDGE**Environmental Conditions & Test Information**



Test Date:	2025-06-13 to 2025-06-14
Temperature:	25.5 °C
Relative Humidity:	60-65 %
ATM Pressure:	100.6-101.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

Test Result: Compliant.

EUT operation mode: Transmitting

Mode	Channel	Frequency (MHz)	Result (dBc)	Limit (dBc)
BLE (1 Mbps)	Low	2402	47.38	20
	High	2480	47.97	
BLE (2 Mbps)	Low	2404	47.62	
	High	2478	47.08	



BLE (1 Mbps)



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 13.JUN.2025 15:12:38

ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:13:41

BLE (2 Mbps)



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:23:40

ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 16:28:01

POWER SPECTRAL DENSITY**Environmental Conditions & Test Information**


Test Date:	2025-06-13 to 2025-06-14
Temperature:	25.5 °C
Relative Humidity:	60-65 %
ATM Pressure:	100.6-101.2 kPa
Test Result:	Pass
Test Engineer:	Neil Zhou

Test Result: Compliant.


EUT operation mode: Transmitting

Mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
BLE (1 Mbps)	Low	2402	-11.90	≤8
	Middle	2440	-10.20	≤8
	High	2480	-8.94	≤8
BLE (2 Mbps)	Low	2404	-13.28	≤8
	Middle	2440	-12.80	≤8
	High	2478	-13.35	≤8


BLE (1 Mbps)



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 13.JUN.2025 15:13:01




ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 13.JUN.2025 15:20:54




ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:14:09


BLE (2 Mbps)



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:26:11



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 10:36:26



ProjectNo.:RKSA250527003 Tester:Neil Zhou
Date: 14.JUN.2025 16:28:53

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.

******* END OF REPORT *******