

TEST REPORT

Product : Portable computer
Trade mark : N/A
Model/Type reference : VIGOBOOK G1,VIGOBOOK G3,
VIGOBOOK G5,VIGOBOOK G7,
VIGOBOOK G9
Serial Number : N/A
Report Number : EED32Q81407204
FCC ID : 2BK7AT156A240100001
Date of Issue : Sep. 30, 2024
Test Standards : 47 CFR Part 15 Subpart E
Test result : PASS

Prepared for:

Shenzhen Yuehe Intelligent Technology Co., Ltd.
4F B, Building 2, Phase 3, Huangtian Yangbei Industrial Zone, Huangtian
Community, Hangcheng Street, Baoan District, Shenzhen

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Frazer Li

Frazer Li

Aaron Ma

Aaron Ma

Reviewed by:

Tom Chen

Tom Chen

Date:

Sep. 30, 2024

Approved by:



Check No.:4837090924

1 Content

1 CONTENT	2
2 VERSION	3
3 TEST SUMMARY	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 TEST CONFIGURATION	7
4.4 TEST ENVIRONMENT	7
4.5 DESCRIPTION OF SUPPORT UNITS	8
4.6 TEST LOCATION	8
4.7 DEVIATION FROM STANDARDS	8
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	8
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	8
4.10 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	8
5 EQUIPMENT LIST	9
6 RADIO TECHNICAL REQUIREMENTS SPECIFICATION	12
6.1 ANTENNA REQUIREMENT	12
6.2 AC POWER LINE CONDUCTED EMISSIONS	13
6.3 MAXIMUM CONDUCTED OUTPUT POWER	17
6.4 6dB EMISSION BANDWIDTH	18
6.5 26dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH	19
6.6 MAXIMUM POWER SPECTRAL DENSITY	20
6.7 FREQUENCY STABILITY	21
6.8 RADIATED EMISSION	22
6.9 RADIATED EMISSION WHICH FALL IN THE RESTRICTED BANDS	307
7 APPENDIX A	406
PHOTOGRAPHS OF TEST SETUP	407
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	410

2 Version

Version No.	Date	Description
00	Sep. 30, 2024	Original

3 Test Summary

Test Item	Test Requirement	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart E Section 15.407 (b)(6)	PASS
Duty Cycle	47 CFR Part 15 Subpart E Section 15.407	PASS
Maximum Conducted Output Power	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
26dB emission bandwidth	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
99% Occupied bandwidth	\	PASS
6dB emission bandwidth	47 CFR Part 15 Subpart E Section 15.407 (e)	PASS
Maximum Power Spectral Density	47 CFR Part 15 Subpart E Section 15.407 (a)	PASS
Frequency stability	47 CFR Part 15 Subpart E Section 15.407 (g)	PASS
Radiated Emissions	47 CFR Part 15 Subpart E Section 15.407 (b)	PASS
Radiated Emissions which fall in the restricted bands	47 CFR Part 15 Subpart E Section 15.407 (b)	PASS

Remark:

Company Name and Address shown on Report, the sample(s) and sample Information were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.

Model No.:VIGOBOK G1,VIGOBOK G3 VIGOBOK G5,VIGOBOK G7,VIGOBOK G9

Only the model VIGOBOK G7 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with only differences in these models are the model names. All other features are identical. These differences do not impact the product's safety or electromagnetic compatibility performance.The different models, voltage, current, and power specifications are solely intended to differentiate between various sales markets.

4 General Information

4.1 Client Information

Applicant:	Shenzhen Yuehe Intelligent Technology Co., Ltd.
Address of Applicant:	4F B, Building 2, Phase 3, Huangtian Yangbei Industrial Zone, Huangtian Community, Hangcheng Street, Baoan District, Shenzhen
Manufacturer:	Shenzhen Yuehe Intelligent Technology Co., Ltd.
Address of Manufacturer:	4F B, Building 2, Phase 3, Huangtian Yangbei Industrial Zone, Huangtian Community, Hangcheng Street, Baoan District, Shenzhen
Factory :	Shenzhen Yuehe Intelligent Technology Co., Ltd.
Address of Factory :	4F B, Building 2, Phase 3, Huangtian Yangbei Industrial Zone, Huangtian Community, Hangcheng Street, Baoan District, Shenzhen

4.2 General Description of EUT

Product Name:	Portable computer	
Model No.:	VIGOBOK G1,VIGOBOK G3 VIGOBOK G5, VIGOBOK G7,VIGOBOK G9	
Test Model No.:	VIGOBOK G7	
Trade mark:	N/A	
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location	
Type of Modulation:	IEEE 802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11n(HT20/HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11ac(VHT20/VHT40/VHT80): OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)	
Operating Frequency	U-NII-1: 5180-5240MHz U-NII-3: 5745-5825MHz	
Antenna Type:	Internal Antenna	
Antenna Gain:	Ant1: 2.16dBi; Ant2: 4.82dBi;	
Power Supply:	Adapter:	Model:JHD-AP048U-190237BA-A Input:100-240V~50/60Hz,1.2A Output:19V,2370mA
Test voltage:	DC 19V	
Sample Received Date:	Sep. 09, 2024	
Sample tested Date:	Sep. 09, 2024 to Sep. 24, 2024	

Operation Frequency each of channel

802.11a/802.11n/802.11ac/802.11ax (20MHz) Frequency/Channel Operations:

U-NII-1		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
36	5180	149	5745
40	5200	153	5765
44	5220	157	5785
48	5240	161	5805
-	-	165	5825

802.11n/802.11ac/802.11ax (40MHz) Frequency/Channel Operations:

U-NII-1		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
38	5190	151	5755
46	5230	159	5795

802.11ac/802.11ax (80MHz) Frequency/Channel Operations:

U-NII-1		U-NII-3	
Channel	Frequency(MHz)	Channel	Frequency(MHz)
42	5210	155	5775

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

4.3 Test Configuration

EUT Test Software Settings:	
Test Software:	MPtoolkit.exe (manufacturer declare)
EUT Power Grade:	Default (Power level is built-in set parameters and cannot be changed and selected)
Use test software to set the lowest frequency, the middle frequency and the highest frequency keep transmitting of the EUT.	
Test Mode:	
We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:	
Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.	
Mode	Data rate
802.11a	6 Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0
802.11ac(VHT20)	MCS0
802.11ac(VHT40)	MCS0
802.11ac(VHT80)	MCS0
802.11ax(VHT20)	MCS0
802.11ax(VHT40)	MCS0
802.11ax(VHT80)	MCS0

4.4 Test Environment

Operating Environment:		
Radiated Spurious Emissions:		
Temperature:	22~25.0 °C	
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
Conducted Emissions:		
Temperature:	22~25.0 °C	
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
RF Conducted:		
Humidity:	50~55 % RH	
Atmospheric Pressure:	1010mbar	
Temperature:	NT (Normal Temperature)	22~25.0 °C
	LT (Low Temperature)	0 °C
	HT (High Temperature)	55.0 °C
Working Voltage of the EUT:	NV (Normal Voltage)	19.0 V
	LV (Low Voltage)	17.1 V
	HV (High Voltage)	20.9 V

4.5 Description of Support Units

The EUT has been tested independently.

4.6 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.

4.10 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.46dB (30MHz-1GHz)
		0.55dB (1GHz-18GHz)
3	Radiated Spurious emission test	3.3dB (9kHz-30MHz)
		4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
		3.4dB (18GHz-40GHz)
4	Conduction emission	3.5dB (9kHz to 150kHz)
		3.1dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	3.8%
7	DC power voltages	0.026%

5 Equipment List

BT/WIFI/SRD RF test system					
Equipment	Manufacturer	Mode No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Communication test set	R&S	CMW500	107929	06-26-2024	06-25-2025
Signal Generator	R&S	SMBV100A	1407.6004K02-262149-CV	09-02-2024	09-01-2025
Spectrum Analyzer	R&S	FSV40	101200	07-18-2024	07-17-2025
RF control unit(power unit)	MWRF-test	MW100-RFCB	MW220620CTI-42	06-25-2024	06-24-2025
High-low temperature test chamber	Dong Guang Qin Zhuo	LK-80GA	QZ20150611879	11/12/2023	12/10/2024
Temperature/Humidity Indicator	biaozhi	HM10	1804186	05-29-2024	05-28-2025
BT&WI-FI Automatic test software	MWRF-test	MTS 8310	V2.0.0.0	---	---
Spectrum Analyzer	R&S	FSV3044	101509	01/17/2024	01/16/2025

Conducted Emissions Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	R&S	ESCI	100435	04-18-2024	04-17-2025
LISN	R&S	ENV216	100098	09-19-2024	09-18-2025
Capacitive voltage probe	Schwarzbeck	CVP 9222C	00124	06-18-2024	06-17-2025
ISN	TESEQ	ISN T800	30297	12-14-2023	12-13-2024
Barometer	Changchun	DYM3	1188	---	---
Temperature/Humidity Indicator	Defu	TH128	---	04-25-2024	04-24-2025
Test software	Fara	EZ-EMC	EMC-CON 3A1.1	---	---

3M Semi/full-anechoic Chamber(2#)					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	---	05-22-2022	05-21-2025
Receiver	R&S	ESCI7	100938-003	09-07-2024	09-06-2025
Spectrum Analyzer	R&S	FSV40	101200	07-18-2024	07-17-2025
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-076	04-16-2024	04-15-2025
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	9163-618	05-18-2024	05-17-2025
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1869	04-16-2024	04-15-2025
Horn Antenna	A.H.SYSTEMS	SAS-574	374	07-02-2023	07-01-2026
Preamplifier	Agilent	11909A	12-1	03-22-2024	03-21-2025
Preamplifier	EMCI	EMC051845SE	980380	12-14-2023	12-13-2024
Preamplifier	CD	PAP-1840-60	6041.6042	06-19-2024	06-18-2025
Cable line	Fulai(7M)	SF106	5219/6A	---	---
Cable line	Fulai(6M)	SF106	5220/6A	---	---
Cable line	Fulai(3M)	SF106	5216/6A	---	---
Cable line	Fulai(3M)	SF106	5217/6A	---	---
Test software	Fara	EZ-EMC	EMEC-3A1-Pre	---	---


3M full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Fully Anechoic Chamber	TDK	FAC-3	---	01-09-2024	01-08-2027
Receiver	Keysight	N9038A	MY57290136	01-09-2024	01-08-2025
Spectrum Analyzer	Keysight	N9020B	MY57111112	01-29-2024	01-28-2025
Spectrum Analyzer	Keysight	N9030B	MY57140871	01-23-2024	01-22-2025
TRILOG Broadband Antenna	Schwarzbeck	VULB 9163	9163-1148	04-28-2024	04-27-2025
Horn Antenna	Schwarzbeck	BBHA 9170	9170-832	04-16-2024	04-15-2025
Horn Antenna	ETS-LINDGREN	3117	57407	07-03-2024	07-02-2025
Preamplifier	EMCI	EMC001330	980563	03-08-2024	03-07-2025
Preamplifier	Tonscend	TAP-011858	AP21B806112	07-18-2024	07-17-2025
Preamplifier	Tonscend	EMC051845SE	980380	12-14-2023	12-13-2024
Communication test set	R&S	CMW500	102898	12-14-2023	12-13-2024
Temperature/Humidity Indicator	biaozhi	GM1360	EE1186631	04-07-2024	04-06-2025
RSE Automatic test software	JS Tonscend	JS36-RSE	V4.0.0.0	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0001		---
Cable line	Times	SFT205-NMSM-2.50M	394812-0002	---	---
Cable line	Times	SFT205-NMSM-2.50M	394812-0003	---	---
Cable line	Times	SFT205-NMSM-2.50M	393495-0001	---	---
Cable line	Times	EMC104-NMNM-1000	SN160710	---	---
Cable line	Times	SFT205-NMSM-3.00M	394813-0001	---	---
Cable line	Times	SFT205-NMNM-1.50M	381964-0001	---	---
Cable line	Times	SFT205-NMSM-7.00M	394815-0001	---	---
Cable line	Times	HF160-KMKM-3.00M	393493-0001	---	---

6 Radio Technical Requirements Specification

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	Please see Internal photos
The antenna is FPC antenna. The best case gain of the antenna is Ant1: 2.16dBi; Ant2: 4.82dBi;	


6.2 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150kHz to 30MHz		
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Setup:			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane. 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		

Test Mode:	All modes were tested, only the worst case was recorded in the report.
Test Results:	Pass

Measurement Data

Live line:




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1635	40.01	9.85	49.86	65.28	-15.42	QP	
2		0.1725	28.64	9.86	38.50	54.84	-16.34	AVG	
3		0.2445	37.87	9.72	47.59	61.94	-14.35	QP	
4		0.2445	26.19	9.72	35.91	51.94	-16.03	AVG	
5		0.3209	36.50	9.59	46.09	59.68	-13.59	QP	
6		0.3480	25.07	9.66	34.73	49.01	-14.28	AVG	
7	*	0.6405	33.22	9.76	42.98	56.00	-13.02	QP	
8		0.6495	21.12	9.79	30.91	46.00	-15.09	AVG	
9		1.3875	15.33	9.74	25.07	46.00	-20.93	AVG	
10		6.1979	17.54	9.85	27.39	60.00	-32.61	QP	
11		17.9295	31.81	9.96	41.77	60.00	-18.23	QP	
12		17.9295	22.35	9.96	32.31	50.00	-17.69	AVG	

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral line:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1725	19.97	9.86	29.83	54.84	-25.01	AVG	
2		0.1770	36.95	9.86	46.81	64.63	-17.82	QP	
3		0.2445	34.58	9.72	44.30	61.94	-17.64	QP	
4		0.3525	34.04	9.67	43.71	58.90	-15.19	QP	
5		0.3525	20.09	9.67	29.76	48.90	-19.14	AVG	
6	*	0.6134	21.25	9.65	30.90	46.00	-15.10	AVG	
7		0.7980	26.54	9.78	36.32	56.00	-19.68	QP	
8		1.7610	11.93	9.75	21.68	46.00	-24.32	AVG	
9		5.3970	20.79	9.84	30.63	60.00	-29.37	QP	
10		5.8020	11.36	9.84	21.20	50.00	-28.80	AVG	
11		10.3065	23.69	9.83	33.52	60.00	-26.48	QP	
12		19.2975	20.41	10.01	30.42	50.00	-19.58	AVG	


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.


6.3 Maximum Conducted Output Power

Test Requirement:	47 CFR Part 15C Section 15.407 (a)													
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E													
Test Setup:														
Test Procedure:	1. The testing follows the Measurement Procedure of KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section E, 3, a 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Measure the conducted output power and record the results in the test report.													
Limit:	<table border="1"> <thead> <tr> <th>Frequency band (MHz)</th><th>Limit</th></tr> </thead> <tbody> <tr> <td rowspan="2">5150-5250</td><td>≤1W(30dBm) for master device</td></tr> <tr> <td>≤250mW(24dBm) for client device</td></tr> <tr> <td>5250-5350</td><td>≤250mW(24dBm) for client device or 11dBm+10logB*</td></tr> <tr> <td>5470-5725</td><td>≤250mW(24dBm) for client device or 11dBm+10logB*</td></tr> <tr> <td>5725-5850</td><td>≤1W(30dBm)</td></tr> <tr> <td>Remark:</td><td>* Where B is the 26dB emission bandwidth in MHz The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.</td></tr> </tbody> </table>	Frequency band (MHz)	Limit	5150-5250	≤1W(30dBm) for master device	≤250mW(24dBm) for client device	5250-5350	≤250mW(24dBm) for client device or 11dBm+10logB*	5470-5725	≤250mW(24dBm) for client device or 11dBm+10logB*	5725-5850	≤1W(30dBm)	Remark:	* Where B is the 26dB emission bandwidth in MHz The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.
Frequency band (MHz)	Limit													
5150-5250	≤1W(30dBm) for master device													
	≤250mW(24dBm) for client device													
5250-5350	≤250mW(24dBm) for client device or 11dBm+10logB*													
5470-5725	≤250mW(24dBm) for client device or 11dBm+10logB*													
5725-5850	≤1W(30dBm)													
Remark:	* Where B is the 26dB emission bandwidth in MHz The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.													
Test Mode:	Transmitting mode with modulation													
Test Results:	Refer to Appendix A													


6.4 6dB Emission Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.407 (e)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section C 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Limit:	≥ 500 kHz
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix A


6.5 26dB Emission Bandwidth and 99% Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.407 (a)
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1. KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section D 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. 4. Measure and record the results in the test report.
Limit:	No restriction limits
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix A

6.6 Maximum Power Spectral Density




Test Requirement:	47 CFR Part 15C Section 15.407 (a)												
Test Method:	KDB789033 D02 General UNII Test Procedures New Rules v02r01 Section F												
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.												
Test Procedure:	- Set the spectrum analyzer or EMI receiver span to view the entire emission bandwidth. 1. Set RBW = 510 kHz/1 MHz, VBW ≥ 3*RBW, Sweep time = Auto, Detector = RMS. - Allow the sweeps to continue until the trace stabilizes. - Use the peak marker function to determine the maximum amplitude level.												
Limit:	<table border="1"> <thead> <tr> <th>Frequency band (MHz)</th><th>Limit</th></tr> </thead> <tbody> <tr> <td>5150-5250</td><td> $\leq 17\text{dBm}$ in 1MHz for master device $\leq 11\text{dBm}$ in 1MHz for client device </td></tr> <tr> <td>5250-5350</td><td>$\leq 11\text{dBm}$ in 1MHz for client device</td></tr> <tr> <td>5470-5725</td><td>$\leq 11\text{dBm}$ in 1MHz for client device</td></tr> <tr> <td>5725-5850</td><td>$\leq 30\text{dBm}$ in 500kHz</td></tr> <tr> <td>Remark:</td><td>The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.</td></tr> </tbody> </table>	Frequency band (MHz)	Limit	5150-5250	$\leq 17\text{dBm}$ in 1MHz for master device $\leq 11\text{dBm}$ in 1MHz for client device	5250-5350	$\leq 11\text{dBm}$ in 1MHz for client device	5470-5725	$\leq 11\text{dBm}$ in 1MHz for client device	5725-5850	$\leq 30\text{dBm}$ in 500kHz	Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.
Frequency band (MHz)	Limit												
5150-5250	$\leq 17\text{dBm}$ in 1MHz for master device $\leq 11\text{dBm}$ in 1MHz for client device												
5250-5350	$\leq 11\text{dBm}$ in 1MHz for client device												
5470-5725	$\leq 11\text{dBm}$ in 1MHz for client device												
5725-5850	$\leq 30\text{dBm}$ in 500kHz												
Remark:	The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.												
Test Mode:	Transmitting mode with modulation												
Test Results:	Refer to Appendix A												

6.7 Frequency Stability

Test Requirement:	47 CFR Part 15C Section 15.407 (g)
Test Method:	ANSI C63.10: 2013
Test Setup:	 Remark: Offset=Cable loss+ attenuation factor.
Test Procedure:	1.The EUT was placed inside the environmental test chamber and powered by nominal AC/DC voltage. 2. Turn the EUT on and couple its output to a spectrum analyzer. 3. Turn the EUT off and set the chamber to the highest temperature specified. d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. 4. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature. 5. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of 0 degrees to 45 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.
Test Mode:	Transmitting mode with modulation
Test Results:	Refer to Appendix A

6.8 Radiated Emission

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.407 (b)				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10kHz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (4) For transmitters operating in the 5.725-5.85 GHz band: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed				


	the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. Note: (i) $EIRP = ((E*d)^2) / 30$ where: • E is the field strength in V/m; • d is the measurement distance in meters; • EIRP is the equivalent isotropically radiated power in watts. (ii) Working in dB units, the above equation is equivalent to: $EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[meters]) - 104.77$ (iii) Or, if d is 3 meters: $EIRP[dBm] = E[dB\mu V/m] - 95.2$
Test Setup:	 Figure 1. Below 30MHz  Figure 2. 30MHz to 1GHz  Figure 3. Above 1 GHz
Test Procedure:	a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. Note: For the radiated emission test above 1GHz:


	Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel and the highest channel h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. i. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Transmitting mode with modulation
Test Results:	Pass

Radiated Spurious Emissions test Data:
Radiated Emission below 1GHz

Remark: During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes, only the worst case lowest channel of 6Mbps for 802.11 a was recorded in the report.

Test Graph






Transmitter Emission above 1GHz

Remark: Through Pre-scan, for SISO,Ant1 was the worst case mode.Only the worst case of was recorded in the report.

SISO:

Test_Mode	802.11 a Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1923.5424	11.83	36.29	48.12	68.20	20.08	PASS	Horizontal	PK
2	2712.3212	12.25	36.20	48.45	68.20	19.75	PASS	Horizontal	PK
3	3563.2563	14.90	35.59	50.49	68.20	17.71	PASS	Horizontal	PK
4	8559.753	-0.65	47.05	46.40	68.20	21.80	PASS	Horizontal	PK
5	10980.624	6.00	45.24	51.24	68.20	16.96	PASS	Horizontal	PK
6	14458.3979	11.14	41.58	52.72	68.20	15.48	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1491.7492	8.02	36.84	44.86	68.20	23.34	PASS	Vertical	PK
2	2438.9439	12.00	36.41	48.41	68.20	19.79	PASS	Vertical	PK
3	3296.4796	14.36	36.20	50.56	68.20	17.64	PASS	Vertical	PK
4	3800.8801	16.48	33.84	50.32	68.20	17.88	PASS	Vertical	PK
5	8555.7278	-0.62	46.45	45.83	68.20	22.37	PASS	Vertical	PK
6	10992.6996	6.53	44.91	51.44	68.20	16.76	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	18697.3879	-25.28	63.20	37.92	74.00	36.08	PASS	Horizontal	PK
2	21640.5856	-24.81	61.62	36.81	74.00	37.19	PASS	Horizontal	PK
3	26575.663	-19.41	58.68	39.27	74.00	34.73	PASS	Horizontal	PK
4	31502.4601	-17.27	55.63	38.36	74.00	35.64	PASS	Horizontal	PK
5	36150.486	-14.99	52.33	37.34	74.00	36.66	PASS	Horizontal	PK
6	40703.7482	-10.50	46.56	36.06	74.00	37.94	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19332.2133	-24.08	62.75	38.67	74.00	35.33	PASS	Vertical	PK
2	23912.1565	-20.63	59.00	38.37	74.00	35.63	PASS	Vertical	PK
3	25334.5334	-19.17	57.91	38.74	74.00	35.26	PASS	Vertical	PK
4	29650.426	-19.35	57.72	38.37	74.00	35.63	PASS	Vertical	PK
5	32406.8563	-15.48	54.98	39.50	74.00	34.50	PASS	Vertical	PK
6	39226.169	-11.03	46.97	35.94	74.00	38.06	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1601.2101	8.79	36.54	45.33	68.20	22.87	PASS	Horizontal	PK
2	2193.6194	10.16	38.38	48.54	68.20	19.66	PASS	Horizontal	PK
3	3342.1342	14.64	35.65	50.29	68.20	17.91	PASS	Horizontal	PK
4	8742.6121	0.20	46.27	46.47	68.20	21.73	PASS	Horizontal	PK
5	11984.6242	5.99	45.25	51.24	68.20	16.96	PASS	Horizontal	PK
6	16607.8554	10.90	42.86	53.76	68.20	14.44	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1694.7195	9.01	36.54	45.55	68.20	22.65	PASS	Vertical	PK
2	3064.9065	13.50	36.09	49.59	68.20	18.61	PASS	Vertical	PK
3	4295.9296	18.98	32.98	51.96	68.20	16.24	PASS	Vertical	PK
4	8302.7151	-1.50	46.47	44.97	68.20	23.23	PASS	Vertical	PK
5	11003.0502	6.78	44.87	51.65	68.20	16.55	PASS	Vertical	PK
6	15891.3696	10.37	44.14	54.51	68.20	13.69	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20054.4422	-23.31	61.57	38.26	74.00	35.74	PASS	Horizontal	PK
2	22484.2594	-24.38	60.74	36.36	74.00	37.64	PASS	Horizontal	PK
3	26328.1731	-19.50	58.01	38.51	74.00	35.49	PASS	Horizontal	PK
4	28705.5482	-20.67	58.87	38.20	74.00	35.80	PASS	Horizontal	PK
5	32408.6963	-15.49	54.71	39.22	74.00	34.78	PASS	Horizontal	PK
6	36249.85	-14.92	52.10	37.18	74.00	36.82	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	21182.4073	-24.65	61.84	37.19	74.00	36.81	PASS	Vertical	PK
2	23883.6353	-20.70	59.16	38.46	74.00	35.54	PASS	Vertical	PK
3	25708.9884	-18.82	58.38	39.56	74.00	34.44	PASS	Vertical	PK
4	28258.4103	-20.53	59.67	39.14	74.00	34.86	PASS	Vertical	PK
5	32439.9776	-15.65	54.91	39.26	74.00	34.74	PASS	Vertical	PK
6	38132.2453	-13.24	49.97	36.73	74.00	37.27	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1951.5952	12.34	36.24	48.58	68.20	19.62	PASS	Horizontal	PK
2	3000	12.69	37.24	49.93	68.20	18.27	PASS	Horizontal	PK
3	4267.8768	18.30	34.08	52.38	68.20	15.82	PASS	Horizontal	PK
4	7907.0954	-1.83	47.42	45.59	68.20	22.61	PASS	Horizontal	PK
5	9278.5389	1.92	45.86	47.78	68.20	20.42	PASS	Horizontal	PK
6	13999.525	11.91	40.97	52.88	68.20	15.32	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1690.319	8.97	36.79	45.76	68.20	22.44	PASS	Vertical	PK
2	3293.1793	14.30	35.95	50.25	68.20	17.95	PASS	Vertical	PK
3	4399.3399	19.11	32.88	51.99	68.20	16.21	PASS	Vertical	PK
4	8989.2995	-0.06	46.37	46.31	68.20	21.89	PASS	Vertical	PK
5	11241.1121	6.43	45.12	51.55	68.20	16.65	PASS	Vertical	PK
6	15902.8701	10.47	43.20	53.67	68.20	14.53	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20968.0387	-24.71	62.08	37.37	74.00	36.63	PASS	Horizontal	PK
2	23849.594	-20.80	58.71	37.91	74.00	36.09	PASS	Horizontal	PK
3	25635.3854	-18.75	59.04	40.29	74.00	33.71	PASS	Horizontal	PK
4	27882.1153	-20.30	59.89	39.59	74.00	34.41	PASS	Horizontal	PK
5	34064.7626	-16.08	53.05	36.97	74.00	37.03	PASS	Horizontal	PK
6	38488.2995	-12.17	49.20	37.03	74.00	36.97	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20590.8236	-24.68	62.21	37.53	74.00	36.47	PASS	Vertical	PK
2	23846.8339	-20.81	59.24	38.43	74.00	35.57	PASS	Vertical	PK
3	26551.7421	-19.42	57.70	38.28	74.00	35.72	PASS	Vertical	PK
4	30857.5143	-17.64	56.42	38.78	74.00	35.22	PASS	Vertical	PK
5	36530.4612	-14.44	51.41	36.97	74.00	37.03	PASS	Vertical	PK
6	38680.5872	-11.91	49.96	38.05	74.00	35.95	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1427.9428	8.31	36.91	45.22	68.20	22.98	PASS	Horizontal	PK
2	3056.6557	13.37	36.52	49.89	68.20	18.31	PASS	Horizontal	PK
3	3798.6799	16.50	34.90	51.40	68.20	16.80	PASS	Horizontal	PK
4	7612.6806	-2.72	47.53	44.81	68.20	23.39	PASS	Horizontal	PK
5	11243.4122	6.45	45.61	52.06	68.20	16.14	PASS	Horizontal	PK
6	15902.2951	10.53	43.26	53.79	68.20	14.41	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1799.2299	10.08	38.36	48.44	68.20	19.76	PASS	Vertical	PK
2	2329.4829	10.75	37.10	47.85	68.20	20.35	PASS	Vertical	PK
3	2944.9945	13.56	36.72	50.28	68.20	17.92	PASS	Vertical	PK
4	8729.9615	-0.07	46.33	46.26	68.20	21.94	PASS	Vertical	PK
5	10606.8553	5.97	45.12	51.09	68.20	17.11	PASS	Vertical	PK
6	14248.5124	14.66	40.50	55.16	68.20	13.04	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20009.3604	-23.09	61.21	38.12	74.00	35.88	PASS	Horizontal	PK
2	21835.6334	-24.79	61.95	37.16	74.00	36.84	PASS	Horizontal	PK
3	27856.3543	-20.26	58.42	38.16	74.00	35.84	PASS	Horizontal	PK
4	31415.9766	-17.38	55.81	38.43	74.00	35.57	PASS	Horizontal	PK
5	33627.7451	-15.48	53.80	38.32	74.00	35.68	PASS	Horizontal	PK
6	38676.9071	-11.94	48.70	36.76	74.00	37.24	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20853.9542	-24.47	62.14	37.67	74.00	36.33	PASS	Vertical	PK
2	24341.8137	-20.14	59.39	39.25	74.00	34.75	PASS	Vertical	PK
3	28290.6116	-20.55	59.24	38.69	74.00	35.31	PASS	Vertical	PK
4	30995.5198	-17.36	56.84	39.48	74.00	34.52	PASS	Vertical	PK
5	35860.6744	-15.12	52.31	37.19	74.00	36.81	PASS	Vertical	PK
6	38487.3795	-12.16	48.92	36.76	74.00	37.24	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1515.9516	8.04	36.83	44.87	68.20	23.33	PASS	Horizontal	PK
2	2855.3355	13.08	36.04	49.12	68.20	19.08	PASS	Horizontal	PK
3	3947.1947	17.76	34.52	52.28	68.20	15.92	PASS	Horizontal	PK
4	8515.4758	-1.13	47.14	46.01	68.20	22.19	PASS	Horizontal	PK
5	10777.0639	5.02	46.80	51.82	68.20	16.38	PASS	Horizontal	PK
6	15096.1048	11.12	40.90	52.02	68.20	16.18	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1568.2068	8.40	36.60	45.00	68.20	23.20	PASS	Vertical	PK
2	2072.6073	10.65	36.86	47.51	68.20	20.69	PASS	Vertical	PK
3	3451.0451	15.59	34.68	50.27	68.20	17.93	PASS	Vertical	PK
4	8444.1722	-0.88	48.57	47.69	68.20	20.51	PASS	Vertical	PK
5	11246.2873	6.48	45.58	52.06	68.20	16.14	PASS	Vertical	PK
6	15898.8449	10.73	43.21	53.94	68.20	14.26	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20324.013	-24.03	61.23	37.20	74.00	36.80	PASS	Horizontal	PK
2	22611.2244	-24.34	60.37	36.03	74.00	37.97	PASS	Horizontal	PK
3	25312.4525	-19.12	58.27	39.15	74.00	34.85	PASS	Horizontal	PK
4	29095.6438	-20.21	58.46	38.25	74.00	35.75	PASS	Horizontal	PK
5	33303.8922	-16.10	54.40	38.30	74.00	35.70	PASS	Horizontal	PK
6	38709.1084	-11.78	49.30	37.52	74.00	36.48	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	19330.3732	-24.08	62.16	38.08	74.00	35.92	PASS	Vertical	PK
2	23364.7346	-22.70	59.53	36.83	74.00	37.17	PASS	Vertical	PK
3	26211.3285	-19.58	58.93	39.35	74.00	34.65	PASS	Vertical	PK
4	29987.1595	-19.62	57.67	38.05	74.00	35.95	PASS	Vertical	PK
5	36142.2057	-15.01	51.96	36.95	74.00	37.05	PASS	Vertical	PK
6	38969.4788	-10.83	48.21	37.38	74.00	36.62	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1580.308	8.56	37.31	45.87	68.20	22.33	PASS	Horizontal	PK
2	2194.7195	10.14	38.32	48.46	68.20	19.74	PASS	Horizontal	PK
3	3444.9945	15.57	35.09	50.66	68.20	17.54	PASS	Horizontal	PK
4	7608.0804	-2.56	47.63	45.07	68.20	23.13	PASS	Horizontal	PK
5	11017.4259	6.43	45.41	51.84	68.20	16.36	PASS	Horizontal	PK
6	15901.1451	10.66	43.15	53.81	68.20	14.39	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1846.5347	11.05	35.84	46.89	68.20	21.31	PASS	Vertical	PK
2	3057.7558	13.39	36.47	49.86	68.20	18.34	PASS	Vertical	PK
3	3806.3806	16.10	34.11	50.21	68.20	17.99	PASS	Vertical	PK
4	7753.5627	-2.37	47.53	45.16	68.20	23.04	PASS	Vertical	PK
5	10994.4247	6.60	45.21	51.81	68.20	16.39	PASS	Vertical	PK
6	13850.0175	11.06	41.53	52.59	68.20	15.61	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20394.8558	-24.05	61.71	37.66	74.00	36.34	PASS	Horizontal	PK
2	24119.1648	-20.70	59.16	38.46	74.00	35.54	PASS	Horizontal	PK
3	25960.1584	-19.07	58.01	38.94	74.00	35.06	PASS	Horizontal	PK
4	29518.8608	-19.58	57.89	38.31	74.00	35.69	PASS	Horizontal	PK
5	32397.6559	-15.45	54.88	39.43	74.00	34.57	PASS	Horizontal	PK
6	37207.6083	-14.93	51.39	36.46	74.00	37.54	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	21038.8816	-24.75	62.39	37.64	74.00	36.36	PASS	Vertical	PK
2	25294.0518	-19.07	57.84	38.77	74.00	35.23	PASS	Vertical	PK
3	28002.6401	-20.49	59.05	38.56	74.00	35.44	PASS	Vertical	PK
4	31054.4022	-17.49	56.52	39.03	74.00	34.97	PASS	Vertical	PK
5	34929.5972	-15.43	53.18	37.75	74.00	36.25	PASS	Vertical	PK
6	37222.3289	-14.91	50.82	35.91	74.00	38.09	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1624.3124	8.66	36.36	45.02	68.20	23.18	PASS	Horizontal	PK
2	2435.0935	12.04	36.61	48.65	68.20	19.55	PASS	Horizontal	PK
3	3940.5941	17.64	34.38	52.02	68.20	16.18	PASS	Horizontal	PK
4	6893.8947	-4.38	48.44	44.06	68.20	24.14	PASS	Horizontal	PK
5	8770.2135	-0.39	47.97	47.58	68.20	20.62	PASS	Horizontal	PK
6	13254.2877	8.60	43.58	52.18	68.20	16.02	PASS	Horizontal	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1776.1276	9.54	36.62	46.16	68.20	22.04	PASS	Vertical	PK
2	3048.4048	13.25	36.56	49.81	68.20	18.39	PASS	Vertical	PK
3	3952.6953	17.76	33.91	51.67	68.20	16.53	PASS	Vertical	PK
4	8562.6281	-0.66	46.47	45.81	68.20	22.39	PASS	Vertical	PK
5	9793.7647	4.06	46.17	50.23	68.20	17.97	PASS	Vertical	PK
6	16600.955	11.34	42.30	53.64	68.20	14.56	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20027.7611	-23.18	61.17	37.99	74.00	36.01	PASS	Horizontal	PK
2	23233.1693	-23.30	59.31	36.01	74.00	37.99	PASS	Horizontal	PK
3	25106.3643	-19.30	58.06	38.76	74.00	35.24	PASS	Horizontal	PK
4	26957.4783	-20.13	58.59	38.46	74.00	35.54	PASS	Horizontal	PK
5	31011.1604	-17.38	56.14	38.76	74.00	35.24	PASS	Horizontal	PK
6	35613.1845	-14.71	51.94	37.23	74.00	36.77	PASS	Horizontal	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20450.978	-24.22	61.40	37.18	74.00	36.82	PASS	Vertical	PK
2	23383.1353	-22.62	59.77	37.15	74.00	36.85	PASS	Vertical	PK
3	25279.3312	-19.03	58.21	39.18	74.00	34.82	PASS	Vertical	PK
4	28977.8791	-20.18	58.29	38.11	74.00	35.89	PASS	Vertical	PK
5	32404.0962	-15.46	54.68	39.22	74.00	34.78	PASS	Vertical	PK
6	38353.9742	-12.23	49.28	37.05	74.00	36.95	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1526.4026	8.08	37.08	45.16	68.20	23.04	PASS	Horizontal	PK
2	2656.2156	11.91	36.93	48.84	68.20	19.36	PASS	Horizontal	PK
3	4402.6403	18.97	33.27	52.24	68.20	15.96	PASS	Horizontal	PK
4	8297.5399	-1.47	46.81	45.34	68.20	22.86	PASS	Horizontal	PK
5	10598.8049	6.30	45.80	52.10	68.20	16.10	PASS	Horizontal	PK
6	13850.5925	11.02	43.16	54.18	68.20	14.02	PASS	Horizontal	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1434.5435	8.29	36.85	45.14	68.20	23.06	PASS	Vertical	PK
2	2288.7789	10.89	35.86	46.75	68.20	21.45	PASS	Vertical	PK
3	3405.3905	15.00	35.29	50.29	68.20	17.91	PASS	Vertical	PK
4	8420.021	-1.43	46.65	45.22	68.20	22.98	PASS	Vertical	PK
5	12982.2991	7.76	44.39	52.15	68.20	16.05	PASS	Vertical	PK
6	15891.3696	10.37	42.51	52.88	68.20	15.32	PASS	Vertical	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20748.1499	-24.45	61.61	37.16	74.00	36.84	PASS	Horizontal	PK
2	23217.5287	-23.36	58.96	35.60	74.00	38.40	PASS	Horizontal	PK
3	28795.7118	-20.43	59.24	38.81	74.00	35.19	PASS	Horizontal	PK
4	32496.0998	-15.94	54.67	38.73	74.00	35.27	PASS	Horizontal	PK
5	35923.2369	-15.20	52.04	36.84	74.00	37.16	PASS	Horizontal	PK
6	38756.9503	-11.54	49.44	37.90	74.00	36.10	PASS	Horizontal	PK

Test_Mode	802.11 n(HT40) Transmitting	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19900.796	-23.33	61.10	37.77	74.00	36.23	PASS	Vertical	PK
2	21567.9027	-24.84	61.95	37.11	74.00	36.89	PASS	Vertical	PK
3	24722.7089	-19.82	58.10	38.28	74.00	35.72	PASS	Vertical	PK
4	28805.8322	-20.41	59.25	38.84	74.00	35.16	PASS	Vertical	PK
5	31732.4693	-17.22	55.22	38.00	74.00	36.00	PASS	Vertical	PK
6	38073.3629	-13.57	49.87	36.30	74.00	37.70	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1715.0715	9.03	36.55	45.58	68.20	22.62	PASS	Horizontal	PK
2	2567.6568	12.25	36.18	48.43	68.20	19.77	PASS	Horizontal	PK
3	3805.2805	16.17	34.12	50.29	68.20	17.91	PASS	Horizontal	PK
4	8177.3589	-1.98	47.05	45.07	68.20	23.13	PASS	Horizontal	PK
5	9782.8391	3.59	45.47	49.06	68.20	19.14	PASS	Horizontal	PK
6	13168.6084	7.59	44.61	52.20	68.20	16.00	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1799.2299	10.08	37.45	47.53	68.20	20.67	PASS	Vertical	PK
2	2565.4565	12.27	36.20	48.47	68.20	19.73	PASS	Vertical	PK
3	3954.8955	17.69	34.01	51.70	68.20	16.50	PASS	Vertical	PK
4	7905.3703	-1.78	46.61	44.83	68.20	23.37	PASS	Vertical	PK
5	11958.7479	5.49	46.08	51.57	68.20	16.63	PASS	Vertical	PK
6	15907.4704	9.95	43.95	53.90	68.20	14.30	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19662.5065	-23.84	61.99	38.15	74.00	35.85	PASS	Horizontal	PK
2	21858.6343	-24.83	62.02	37.19	74.00	36.81	PASS	Horizontal	PK
3	24472.4589	-19.82	57.82	38.00	74.00	36.00	PASS	Horizontal	PK
4	26570.1428	-19.41	58.77	39.36	74.00	34.64	PASS	Horizontal	PK
5	30035.9214	-19.64	57.64	38.00	74.00	36.00	PASS	Horizontal	PK
6	33551.3821	-15.57	53.79	38.22	74.00	35.78	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20118.8448	-23.62	61.86	38.24	74.00	35.76	PASS	Vertical	PK
2	22466.7787	-24.39	60.41	36.02	74.00	37.98	PASS	Vertical	PK
3	25225.969	-18.90	57.88	38.98	74.00	35.02	PASS	Vertical	PK
4	27834.2734	-20.22	59.25	39.03	74.00	34.97	PASS	Vertical	PK
5	31013.9206	-17.39	56.25	38.86	74.00	35.14	PASS	Vertical	PK
6	34943.3977	-15.42	52.00	36.58	74.00	37.42	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1774.4774	9.50	36.71	46.21	68.20	21.99	PASS	Horizontal	PK
2	2561.0561	12.31	36.53	48.84	68.20	19.36	PASS	Horizontal	PK
3	4517.0517	20.39	33.57	53.96	68.20	14.24	PASS	Horizontal	PK
4	8323.4162	-2.08	47.20	45.12	68.20	23.08	PASS	Horizontal	PK
5	10587.3044	5.71	45.49	51.20	68.20	17.00	PASS	Horizontal	PK
6	15136.3568	11.56	40.74	52.30	68.20	15.90	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1630.363	8.63	36.57	45.20	68.20	23.00	PASS	Vertical	PK
2	2277.7778	10.92	36.44	47.36	68.20	20.84	PASS	Vertical	PK
3	3085.2585	13.82	36.45	50.27	68.20	17.93	PASS	Vertical	PK
4	7384.3942	-3.95	48.38	44.43	68.20	23.77	PASS	Vertical	PK
5	9010.0005	0.07	46.06	46.13	68.20	22.07	PASS	Vertical	PK
6	14461.2731	11.03	40.88	51.91	68.20	16.29	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	21265.2106	-24.71	61.98	37.27	74.00	36.73	PASS	Horizontal	PK
2	24586.5435	-19.85	58.63	38.78	74.00	35.22	PASS	Horizontal	PK
3	28910.7164	-20.27	58.47	38.20	74.00	35.80	PASS	Horizontal	PK
4	31788.5915	-17.25	55.06	37.81	74.00	36.19	PASS	Horizontal	PK
5	34948.918	-15.41	52.50	37.09	74.00	36.91	PASS	Horizontal	PK
6	38685.1874	-11.89	49.52	37.63	74.00	36.37	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19973.4789	-23.13	60.54	37.41	74.00	36.59	PASS	Vertical	PK
2	22509.1004	-24.37	60.16	35.79	74.00	38.21	PASS	Vertical	PK
3	24876.3551	-19.81	57.99	38.18	74.00	35.82	PASS	Vertical	PK
4	25938.0775	-19.04	58.07	39.03	74.00	34.97	PASS	Vertical	PK
5	30195.0878	-19.77	57.74	37.97	74.00	36.03	PASS	Vertical	PK
6	34025.201	-16.14	53.06	36.92	74.00	37.08	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1574.8075	8.49	36.75	45.24	68.20	22.96	PASS	Horizontal	PK
2	3075.3575	13.67	36.13	49.80	68.20	18.40	PASS	Horizontal	PK
3	3905.9406	16.96	33.98	50.94	68.20	17.26	PASS	Horizontal	PK
4	8085.9293	-2.65	47.29	44.64	68.20	23.56	PASS	Horizontal	PK
5	10997.8749	6.76	45.70	52.46	68.20	15.74	PASS	Horizontal	PK
6	13832.7666	10.16	42.67	52.83	68.20	15.37	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1420.242	8.35	36.95	45.30	68.20	22.90	PASS	Vertical	PK
2	2422.9923	12.16	36.86	49.02	68.20	19.18	PASS	Vertical	PK
3	2932.3432	13.36	36.34	49.70	68.20	18.50	PASS	Vertical	PK
4	7383.2442	-3.95	48.72	44.77	68.20	23.43	PASS	Vertical	PK
5	10601.1051	6.30	44.39	50.69	68.20	17.51	PASS	Vertical	PK
6	16599.23	11.31	41.47	52.78	68.20	15.42	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19923.797	-23.27	61.20	37.93	74.00	36.07	PASS	Horizontal	PK
2	22507.2603	-24.37	59.81	35.44	74.00	38.56	PASS	Horizontal	PK
3	25190.0876	-18.88	57.41	38.53	74.00	35.47	PASS	Horizontal	PK
4	29861.1144	-19.60	57.13	37.53	74.00	36.47	PASS	Horizontal	PK
5	33623.1449	-15.46	53.76	38.30	74.00	35.70	PASS	Horizontal	PK
6	38677.8271	-11.93	48.93	37.00	74.00	37.00	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20006.6003	-23.08	61.44	38.36	74.00	35.64	PASS	Vertical	PK
2	23741.0296	-21.21	58.66	37.45	74.00	36.55	PASS	Vertical	PK
3	25999.72	-19.10	57.90	38.80	74.00	35.20	PASS	Vertical	PK
4	30386.4555	-18.74	56.70	37.96	74.00	36.04	PASS	Vertical	PK
5	33603.8242	-15.40	53.51	38.11	74.00	35.89	PASS	Vertical	PK
6	37684.1874	-13.89	49.89	36.00	74.00	38.00	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1451.0451	8.22	36.86	45.08	68.20	23.12	PASS	Horizontal	PK
2	2528.0528	12.24	36.68	48.92	68.20	19.28	PASS	Horizontal	PK
3	4096.8097	18.12	33.53	51.65	68.20	16.55	PASS	Horizontal	PK
4	7607.5054	-2.54	47.20	44.66	68.20	23.54	PASS	Horizontal	PK
5	10602.2551	6.23	44.39	50.62	68.20	17.58	PASS	Horizontal	PK
6	14457.8229	11.16	41.12	52.28	68.20	15.92	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1507.7008	8.01	37.07	45.08	68.20	23.12	PASS	Vertical	PK
2	2534.6535	12.29	36.59	48.88	68.20	19.32	PASS	Vertical	PK
3	3911.4411	17.07	34.37	51.44	68.20	16.76	PASS	Vertical	PK
4	7333.2167	-3.76	47.69	43.93	68.20	24.27	PASS	Vertical	PK
5	10599.955	6.36	44.93	51.29	68.20	16.91	PASS	Vertical	PK
6	14263.4632	13.70	41.20	54.90	68.20	13.30	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19975.319	-23.12	60.99	37.87	74.00	36.13	PASS	Horizontal	PK
2	21813.5525	-24.74	61.01	36.27	74.00	37.73	PASS	Horizontal	PK
3	23879.9552	-20.72	59.00	38.28	74.00	35.72	PASS	Horizontal	PK
4	27321.8129	-20.41	58.03	37.62	74.00	36.38	PASS	Horizontal	PK
5	30824.393	-17.71	56.60	38.89	74.00	35.11	PASS	Horizontal	PK
6	37214.9686	-14.92	51.06	36.14	74.00	37.86	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20234.7694	-24.01	61.43	37.42	74.00	36.58	PASS	Vertical	PK
2	23102.5241	-24.22	60.12	35.90	74.00	38.10	PASS	Vertical	PK
3	26794.6318	-19.88	58.41	38.53	74.00	35.47	PASS	Vertical	PK
4	29627.4251	-19.31	56.71	37.40	74.00	36.60	PASS	Vertical	PK
5	32656.1862	-16.44	54.93	38.49	74.00	35.51	PASS	Vertical	PK
6	38640.1056	-12.11	50.38	38.27	74.00	35.73	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1666.6667	8.70	36.98	45.68	68.20	22.52	PASS	Horizontal	PK
2	2673.2673	12.07	36.61	48.68	68.20	19.52	PASS	Horizontal	PK
3	3779.4279	15.82	34.03	49.85	68.20	18.35	PASS	Horizontal	PK
4	7195.2098	-4.79	54.01	49.22	68.20	18.98	PASS	Horizontal	PK
5	8767.3384	-0.28	47.13	46.85	68.20	21.35	PASS	Horizontal	PK
6	14246.7873	14.32	41.21	55.53	68.20	12.67	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1740.9241	8.95	37.32	46.27	68.20	21.93	PASS	Vertical	PK
2	2940.5941	13.50	36.01	49.51	68.20	18.69	PASS	Vertical	PK
3	4102.8603	18.24	33.14	51.38	68.20	16.82	PASS	Vertical	PK
4	8125.6063	-2.21	47.06	44.85	68.20	23.35	PASS	Vertical	PK
5	10595.3548	6.12	44.45	50.57	68.20	17.63	PASS	Vertical	PK
6	13462.4481	9.57	42.49	52.06	68.20	16.14	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20523.6609	-24.45	61.41	36.96	74.00	37.04	PASS	Horizontal	PK
2	23990.3596	-20.39	58.58	38.19	74.00	35.81	PASS	Horizontal	PK
3	26435.8174	-19.43	58.60	39.17	74.00	34.83	PASS	Horizontal	PK
4	31109.6044	-17.64	55.77	38.13	74.00	35.87	PASS	Horizontal	PK
5	35502.7801	-14.77	51.31	36.54	74.00	37.46	PASS	Horizontal	PK
6	38742.2297	-11.61	48.70	37.09	74.00	36.91	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT40) Transmitting	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	21115.2446	-24.70	62.12	37.42	74.00	36.58	PASS	Vertical	PK
2	24610.4644	-19.85	58.31	38.46	74.00	35.54	PASS	Vertical	PK
3	27768.0307	-20.22	59.01	38.79	74.00	35.21	PASS	Vertical	PK
4	31710.3884	-17.20	54.76	37.56	74.00	36.44	PASS	Vertical	PK
5	35813.7526	-15.05	52.71	37.66	74.00	36.34	PASS	Vertical	PK
6	39851.7941	-10.67	46.11	35.44	74.00	38.56	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5210MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1466.4466	8.14	36.75	44.89	68.20	23.31	PASS	Horizontal	PK
2	2557.2057	12.35	35.97	48.32	68.20	19.88	PASS	Horizontal	PK
3	3547.3047	15.17	34.46	49.63	68.20	18.57	PASS	Horizontal	PK
4	8564.9282	-0.67	47.26	46.59	68.20	21.61	PASS	Horizontal	PK
5	13854.0427	10.81	42.31	53.12	68.20	15.08	PASS	Horizontal	PK
6	16591.7546	10.37	42.73	53.10	68.20	15.10	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5210MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1608.9109	8.74	36.66	45.40	68.20	22.80	PASS	Vertical	PK
2	3049.505	13.26	37.01	50.27	68.20	17.93	PASS	Vertical	PK
3	4104.5105	18.19	33.69	51.88	68.20	16.32	PASS	Vertical	PK
4	8340.667	-2.55	48.00	45.45	68.20	22.75	PASS	Vertical	PK
5	13843.6922	10.72	41.81	52.53	68.20	15.67	PASS	Vertical	PK
6	16600.955	11.34	41.37	52.71	68.20	15.49	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5210MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19918.2767	-23.28	62.01	38.73	74.00	35.27	PASS	Horizontal	PK
2	21883.4753	-24.87	61.91	37.04	74.00	36.96	PASS	Horizontal	PK
3	25063.1225	-19.52	57.78	38.26	74.00	35.74	PASS	Horizontal	PK
4	27458.8984	-20.41	57.66	37.25	74.00	36.75	PASS	Horizontal	PK
5	33292.8517	-16.10	54.35	38.25	74.00	35.75	PASS	Horizontal	PK
6	38451.4981	-12.11	49.37	37.26	74.00	36.74	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT80) Transmitting	Test_Frequency	5210MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20568.7428	-24.61	62.15	37.54	74.00	36.46	PASS	Vertical	PK
2	23051.002	-24.63	60.16	35.53	74.00	38.47	PASS	Vertical	PK
3	27365.0546	-20.39	58.49	38.10	74.00	35.90	PASS	Vertical	PK
4	30985.3994	-17.38	55.97	38.59	74.00	35.41	PASS	Vertical	PK
5	35088.7636	-15.16	51.76	36.60	74.00	37.40	PASS	Vertical	PK
6	38950.158	-10.88	48.16	37.28	74.00	36.72	PASS	Vertical	PK

Test_Mode	802.11ax(HE20)Transmittin	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1635.8636	8.60	37.38	45.98	68.20	22.22	PASS	Horizontal	PK
2	2535.2035	12.30	37.08	49.38	68.20	18.82	PASS	Horizontal	PK
3	4102.8603	18.24	34.11	52.35	68.20	15.85	PASS	Horizontal	PK
4	7434.4217	-4.06	48.34	44.28	68.20	23.92	PASS	Horizontal	PK
5	9307.8654	2.22	45.17	47.39	68.20	20.81	PASS	Horizontal	PK
6	12840.267	7.78	42.79	50.57	68.20	17.63	PASS	Horizontal	PK

Test_Mode	802.11ax(HE20)Transmittin	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1466.9967	8.14	37.47	45.61	68.20	22.59	PASS	Vertical	PK
2	2091.8592	10.58	39.82	50.40	68.20	17.80	PASS	Vertical	PK
3	3057.2057	13.38	36.07	49.45	68.20	18.75	PASS	Vertical	PK
4	8129.6315	-2.17	47.16	44.99	68.20	23.21	PASS	Vertical	PK
5	10056.5528	4.12	44.71	48.83	68.20	19.37	PASS	Vertical	PK
6	15000.65	11.51	40.69	52.20	68.20	16.00	PASS	Vertical	PK

Test_Mode	802.11 ax(HE20)Transmittin	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20732.5093	-24.48	60.96	36.48	74.00	37.52	PASS	Horizontal	PK
2	24468.7788	-19.83	57.64	37.81	74.00	36.19	PASS	Horizontal	PK
3	27075.243	-20.30	58.19	37.89	74.00	36.11	PASS	Horizontal	PK
4	30171.1668	-19.76	57.63	37.87	74.00	36.13	PASS	Horizontal	PK
5	34006.8003	-16.16	53.13	36.97	74.00	37.03	PASS	Horizontal	PK
6	39429.4972	-12.09	47.51	35.42	74.00	38.58	PASS	Horizontal	PK

Test_Mode	802.11ax(HE20)Transmittin	Test_Frequency	5180MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20840.1536	-24.44	61.45	37.01	74.00	36.99	PASS	Vertical	PK
2	23901.116	-20.65	58.02	37.37	74.00	36.63	PASS	Vertical	PK
3	26620.7448	-19.46	57.57	38.11	74.00	35.89	PASS	Vertical	PK
4	31394.8158	-17.42	55.55	38.13	74.00	35.87	PASS	Vertical	PK
5	36109.0844	-15.08	51.53	36.45	74.00	37.55	PASS	Vertical	PK
6	38992.4797	-10.76	48.03	37.27	74.00	36.73	PASS	Vertical	PK

Test_Mode	802.11ax(HE20)Transmittin	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1575.3575	8.49	36.20	44.69	68.20	23.51	PASS	Horizontal	PK
2	2414.1914	12.25	36.42	48.67	68.20	19.53	PASS	Horizontal	PK
3	3562.1562	14.93	35.35	50.28	68.20	17.92	PASS	Horizontal	PK
4	7607.5054	-2.54	48.56	46.02	68.20	22.18	PASS	Horizontal	PK
5	11014.5507	6.51	44.93	51.44	68.20	16.76	PASS	Horizontal	PK
6	15507.2504	9.61	41.38	50.99	68.20	17.21	PASS	Horizontal	PK

Test_Mode	802.11ax(HE20)Transmittin	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1625.9626	8.65	37.16	45.81	68.20	22.39	PASS	Vertical	PK
2	2930.143	13.33	35.97	49.30	68.20	18.90	PASS	Vertical	PK
3	3952.1452	17.77	33.87	51.64	68.20	16.56	PASS	Vertical	PK
4	7593.1297	-2.54	48.34	45.80	68.20	22.40	PASS	Vertical	PK
5	10610.8805	5.75	45.77	51.52	68.20	16.68	PASS	Vertical	PK
6	15106.4553	11.63	40.52	52.15	68.20	16.05	PASS	Vertical	PK

Test_Mode	802.11 ax(HE20)Transmittin	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19891.5957	-23.36	61.98	38.62	74.00	35.38	PASS	Horizontal	PK
2	21605.6242	-24.83	61.15	36.32	74.00	37.68	PASS	Horizontal	PK
3	23125.525	-24.04	59.28	35.24	74.00	38.76	PASS	Horizontal	PK
4	26239.8496	-19.56	58.28	38.72	74.00	35.28	PASS	Horizontal	PK
5	29998.1999	-19.62	57.16	37.54	74.00	36.46	PASS	Horizontal	PK
6	35449.418	-14.82	51.00	36.18	74.00	37.82	PASS	Horizontal	PK

Test_Mode	802.11 ax(HE20)Transmittin	Test_Frequency	5200MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20451.8981	-24.22	60.82	36.60	74.00	37.40	PASS	Vertical	PK
2	24193.6877	-20.91	58.65	37.74	74.00	36.26	PASS	Vertical	PK
3	28609.8644	-20.94	58.17	37.23	74.00	36.77	PASS	Vertical	PK
4	30796.7919	-17.78	55.97	38.19	74.00	35.81	PASS	Vertical	PK
5	35161.4465	-14.99	50.77	35.78	74.00	38.22	PASS	Vertical	PK
6	39046.7619	-10.77	47.53	36.76	74.00	37.24	PASS	Vertical	PK

Test_Mode	802.11 ax(HE20)Transmittin	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1698.0198	9.05	36.25	45.30	68.20	22.90	PASS	Horizontal	PK
2	2556.6557	12.36	36.32	48.68	68.20	19.52	PASS	Horizontal	PK
3	3536.3036	14.76	35.80	50.56	68.20	17.64	PASS	Horizontal	PK
4	8441.2971	-0.94	46.69	45.75	68.20	22.45	PASS	Horizontal	PK
5	11956.4478	5.44	45.57	51.01	68.20	17.19	PASS	Horizontal	PK
6	15896.5448	10.62	43.79	54.41	68.20	13.79	PASS	Horizontal	PK

Test_Mode	802.11 ax(HE20)Transmittin	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1564.9065	8.37	35.80	44.17	68.20	24.03	PASS	Vertical	PK
2	2944.9945	13.56	35.41	48.97	68.20	19.23	PASS	Vertical	PK
3	4122.6623	17.64	33.51	51.15	68.20	17.05	PASS	Vertical	PK
4	9798.9399	4.28	45.39	49.67	68.20	18.53	PASS	Vertical	PK
5	12000.15	6.28	44.42	50.70	68.20	17.50	PASS	Vertical	PK
6	16439.372	9.16	43.33	52.49	68.20	15.71	PASS	Vertical	PK

Test_Mode	802.11ax(HE20)Transmittin	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20417.8567	-24.11	61.69	37.58	74.00	36.42	PASS	Horizontal	PK
2	22898.2759	-24.71	59.97	35.26	74.00	38.74	PASS	Horizontal	PK
3	26631.7853	-19.48	57.65	38.17	74.00	35.83	PASS	Horizontal	PK
4	29605.3442	-19.28	57.18	37.90	74.00	36.10	PASS	Horizontal	PK
5	33099.644	-16.32	54.48	38.16	74.00	35.84	PASS	Horizontal	PK
6	39025.601	-10.75	47.74	36.99	74.00	37.01	PASS	Horizontal	PK

Test_Mode	802.11ax(HE20)Transmittin	Test_Frequency	5240MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20304.6922	-24.03	60.62	36.59	74.00	37.41	PASS	Vertical	PK
2	22629.6252	-24.35	59.21	34.86	74.00	39.14	PASS	Vertical	PK
3	24459.5784	-19.82	57.82	38.00	74.00	36.00	PASS	Vertical	PK
4	29650.426	-19.35	57.16	37.81	74.00	36.19	PASS	Vertical	PK
5	34299.372	-15.87	51.86	35.99	74.00	38.01	PASS	Vertical	PK
6	38268.4107	-12.58	48.63	36.05	74.00	37.95	PASS	Vertical	PK

Test_Mode	802.11ax(HE40)Transmittin	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1613.3113	8.73	36.65	45.38	68.20	22.82	PASS	Horizontal	PK
2	2821.2321	12.63	36.32	48.95	68.20	19.25	PASS	Horizontal	PK
3	4100.11	18.32	33.56	51.88	68.20	16.32	PASS	Horizontal	PK
4	8898.4449	-1.00	47.23	46.23	68.20	21.97	PASS	Horizontal	PK
5	12991.4996	8.11	44.07	52.18	68.20	16.02	PASS	Horizontal	PK
6	17189.2095	13.27	40.39	53.66	68.20	14.54	PASS	Horizontal	PK

Test_Mode	802.11ax(HE40)Transmittin	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1530.8031	8.10	36.26	44.36	68.20	23.84	PASS	Vertical	PK
2	2189.769	10.21	38.04	48.25	68.20	19.95	PASS	Vertical	PK
3	3082.5083	13.78	35.51	49.29	68.20	18.91	PASS	Vertical	PK
4	7402.2201	-4.08	48.75	44.67	68.20	23.53	PASS	Vertical	PK
5	9618.9559	2.96	45.71	48.67	68.20	19.53	PASS	Vertical	PK
6	15506.1003	9.67	41.63	51.30	68.20	16.90	PASS	Vertical	PK

Test_Mode	802.11 ax(HE40)Transmittin	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	21106.9643	-24.70	61.40	36.70	74.00	37.30	PASS	Horizontal	PK
2	23370.2548	-22.68	59.87	37.19	74.00	36.81	PASS	Horizontal	PK
3	25500.14	-19.02	57.89	38.87	74.00	35.13	PASS	Horizontal	PK
4	28243.6897	-20.52	58.26	37.74	74.00	36.26	PASS	Horizontal	PK
5	31749.95	-17.23	54.54	37.31	74.00	36.69	PASS	Horizontal	PK
6	37053.9622	-15.59	51.22	35.63	74.00	38.37	PASS	Horizontal	PK

Test_Mode	802.11 ax(HE40)Transmittin	Test_Frequency	5190MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20345.1738	-24.04	61.23	37.19	74.00	36.81	PASS	Vertical	PK
2	22556.9423	-24.35	59.54	35.19	74.00	38.81	PASS	Vertical	PK
3	26001.5601	-19.10	57.97	38.87	74.00	35.13	PASS	Vertical	PK
4	27157.1263	-20.41	57.96	37.55	74.00	36.45	PASS	Vertical	PK
5	31013.0005	-17.38	55.89	38.51	74.00	35.49	PASS	Vertical	PK
6	34970.0788	-15.39	52.00	36.61	74.00	37.39	PASS	Vertical	PK

Test_Mode	802.11 ax(HE40)Transmittin	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1658.4158	8.61	36.31	44.92	68.20	23.28	PASS	Horizontal	PK
2	3083.6084	13.79	35.96	49.75	68.20	18.45	PASS	Horizontal	PK
3	3921.3421	17.26	33.66	50.92	68.20	17.28	PASS	Horizontal	PK
4	7581.0541	-3.00	48.67	45.67	68.20	22.53	PASS	Horizontal	PK
5	10786.2643	4.99	47.96	52.95	68.20	15.25	PASS	Horizontal	PK
6	14259.438	14.07	40.43	54.50	68.20	13.70	PASS	Horizontal	PK

Test_Mode	802.11 ax(HE40)Transmittin	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1427.9428	8.31	36.42	44.73	68.20	23.47	PASS	Vertical	PK
2	2068.7569	10.66	36.34	47.00	68.20	21.20	PASS	Vertical	PK
3	3060.5061	13.44	35.76	49.20	68.20	19.00	PASS	Vertical	PK
4	7900.195	-1.66	45.53	43.87	68.20	24.33	PASS	Vertical	PK
5	9801.2401	4.30	44.93	49.23	68.20	18.97	PASS	Vertical	PK
6	14000.1	11.89	40.60	52.49	68.20	15.71	PASS	Vertical	PK

Test_Mode	802.11ax(HE40)Transmittin	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20166.6867	-23.85	61.64	37.79	74.00	36.21	PASS	Horizontal	PK
2	22215.6086	-24.69	61.18	36.49	74.00	37.51	PASS	Horizontal	PK
3	25728.3091	-18.85	57.59	38.74	74.00	35.26	PASS	Horizontal	PK
4	27416.5767	-20.39	58.55	38.16	74.00	35.84	PASS	Horizontal	PK
5	32132.6853	-17.00	54.24	37.24	74.00	36.76	PASS	Horizontal	PK
6	38067.8427	-13.61	50.06	36.45	74.00	37.55	PASS	Horizontal	PK

Test_Mode	802.11 ax(HE40)Transmittin	Test_Frequency	5230MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20680.0672	-24.57	62.06	37.49	74.00	36.51	PASS	Vertical	PK
2	23156.8063	-23.79	59.82	36.03	74.00	37.97	PASS	Vertical	PK
3	27878.4351	-20.30	59.24	38.94	74.00	35.06	PASS	Vertical	PK
4	31692.9077	-17.20	55.09	37.89	74.00	36.11	PASS	Vertical	PK
5	36488.1395	-14.62	52.44	37.82	74.00	36.18	PASS	Vertical	PK
6	39360.4944	-11.86	48.31	36.45	74.00	37.55	PASS	Vertical	PK

Test_Mode	802.11ax(HE80)Transmittin	Test_Frequency	5210MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1628.7129	8.63	36.84	45.47	68.20	22.73	PASS	Horizontal	PK
2	2796.4796	12.25	36.54	48.79	68.20	19.41	PASS	Horizontal	PK
3	3768.9769	15.45	34.53	49.98	68.20	18.22	PASS	Horizontal	PK
4	7009.4755	-4.71	48.72	44.01	68.20	24.19	PASS	Horizontal	PK
5	9079.579	0.47	45.77	46.24	68.20	21.96	PASS	Horizontal	PK
6	13839.092	10.48	43.00	53.48	68.20	14.72	PASS	Horizontal	PK

Test_Mode	802.11ax(HE80)Transmittin	Test_Frequency	5210MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1571.5072	8.45	36.55	45.00	68.20	23.20	PASS	Vertical	PK
2	2570.407	12.22	36.92	49.14	68.20	19.06	PASS	Vertical	PK
3	3808.5809	15.95	34.88	50.83	68.20	17.37	PASS	Vertical	PK
4	7755.2878	-2.39	46.84	44.45	68.20	23.75	PASS	Vertical	PK
5	10592.4796	5.98	45.45	51.43	68.20	16.77	PASS	Vertical	PK
6	14253.1127	14.66	40.02	54.68	68.20	13.52	PASS	Vertical	PK

Test_Mode	802.11 ax(HE80)Transmittin	Test_Frequency	5210MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20778.5111	-24.40	61.77	37.37	74.00	36.63	PASS	Horizontal	PK
2	23422.6969	-22.47	58.82	36.35	74.00	37.65	PASS	Horizontal	PK
3	26240.7696	-19.56	58.36	38.80	74.00	35.20	PASS	Horizontal	PK
4	30370.8148	-18.83	56.47	37.64	74.00	36.36	PASS	Horizontal	PK
5	32658.0263	-16.44	54.46	38.02	74.00	35.98	PASS	Horizontal	PK
6	37194.7278	-14.97	51.38	36.41	74.00	37.59	PASS	Horizontal	PK

Test_Mode	802.11 ax(HE80)Transmittin	Test_Frequency	5210MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19796.8319	-23.63	60.94	37.31	74.00	36.69	PASS	Vertical	PK
2	23847.7539	-20.81	59.29	38.48	74.00	35.52	PASS	Vertical	PK
3	27020.9608	-20.23	59.05	38.82	74.00	35.18	PASS	Vertical	PK
4	30972.5189	-17.40	56.10	38.70	74.00	35.30	PASS	Vertical	PK
5	34372.9749	-15.88	52.25	36.37	74.00	37.63	PASS	Vertical	PK
6	38045.7618	-13.73	50.26	36.53	74.00	37.47	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBµV]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Result	Polarity	Remark
1	1135.8636	7.17	37.38	44.55	68.20	23.65	PASS	Horizontal	PK
2	1794.2794	9.65	39.16	48.81	68.20	19.39	PASS	Horizontal	PK
3	2552.2552	12.40	38.17	50.57	68.20	17.63	PASS	Horizontal	PK
4	3776.6777	15.77	35.85	51.62	68.20	16.58	PASS	Horizontal	PK
5	7589.506	-2.68	47.81	45.13	68.20	23.07	PASS	Horizontal	PK
6	12839.9893	7.77	43.63	51.40	68.20	16.80	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1394.3894	8.26	37.53	45.79	68.20	22.41	PASS	Vertical	PK
2	2552.8053	12.39	37.89	50.28	68.20	17.92	PASS	Vertical	PK
3	4097.9098	18.18	35.31	53.49	68.20	14.71	PASS	Vertical	PK
4	7598.7066	-2.32	47.04	44.72	68.20	23.48	PASS	Vertical	PK
5	10610.374	5.77	45.90	51.67	68.20	16.53	PASS	Vertical	PK
6	15896.1264	10.60	42.72	53.32	68.20	14.88	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19486.7795	-23.94	62.05	38.11	74.00	35.89	PASS	Horizontal	PK
2	21753.7502	-24.74	61.82	37.08	74.00	36.92	PASS	Horizontal	PK
3	25240.6896	-18.93	57.48	38.55	74.00	35.45	PASS	Horizontal	PK
4	28700.948	-20.69	58.73	38.04	74.00	35.96	PASS	Horizontal	PK
5	31271.5309	-17.71	55.98	38.27	74.00	35.73	PASS	Horizontal	PK
6	36503.7802	-14.56	51.65	37.09	74.00	36.91	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20094.9238	-23.50	61.69	38.19	74.00	35.81	PASS	Vertical	PK
2	23388.6555	-22.60	60.04	37.44	74.00	36.56	PASS	Vertical	PK
3	26974.959	-20.16	58.17	38.01	74.00	35.99	PASS	Vertical	PK
4	30533.6613	-18.77	56.65	37.88	74.00	36.12	PASS	Vertical	PK
5	34531.2212	-15.27	52.34	37.07	74.00	36.93	PASS	Vertical	PK
6	38690.7076	-11.86	49.98	38.12	74.00	35.88	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5785MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1280.5187	6.95	36.85	43.80	68.20	24.40	PASS	Horizontal	PK
2	2097.8732	10.60	41.36	51.96	68.20	16.24	PASS	Horizontal	PK
3	3954.0636	17.38	33.10	50.48	68.20	17.72	PASS	Horizontal	PK
4	7184.679	-4.68	50.86	46.18	68.20	22.02	PASS	Horizontal	PK
5	10999.0999	6.81	43.71	50.52	68.20	17.68	PASS	Horizontal	PK
6	15886.9258	10.14	42.29	52.43	68.20	15.77	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5785MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1367.7912	7.99	36.97	44.96	68.20	23.24	PASS	Vertical	PK
2	2402.9602	12.30	36.06	48.36	68.20	19.84	PASS	Vertical	PK
3	4524.2683	20.34	32.39	52.73	68.20	15.47	PASS	Vertical	PK
4	7375.5917	-3.89	47.66	43.77	68.20	24.43	PASS	Vertical	PK
5	11004.467	6.75	43.34	50.09	68.20	18.11	PASS	Vertical	PK
6	15896.1264	10.60	41.33	51.93	68.20	16.27	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5785MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19334.9734	-24.07	64.21	40.14	74.00	33.86	PASS	Horizontal	PK
2	22718.8688	-24.37	59.80	35.43	74.00	38.57	PASS	Horizontal	PK
3	26055.8422	-19.24	58.50	39.26	74.00	34.74	PASS	Horizontal	PK
4	29542.7817	-19.49	57.45	37.96	74.00	36.04	PASS	Horizontal	PK
5	33984.7194	-16.16	53.56	37.40	74.00	36.60	PASS	Horizontal	PK
6	38718.3087	-11.73	48.55	36.82	74.00	37.18	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5785MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19350.614	-24.04	61.77	37.73	74.00	36.27	PASS	Vertical	PK
2	22843.0737	-24.53	60.37	35.84	74.00	38.16	PASS	Vertical	PK
3	26374.175	-19.46	57.66	38.20	74.00	35.80	PASS	Vertical	PK
4	29555.6622	-19.44	57.04	37.60	74.00	36.40	PASS	Vertical	PK
5	33491.5797	-15.78	53.81	38.03	74.00	35.97	PASS	Vertical	PK
6	37204.8482	-14.94	51.70	36.76	74.00	37.24	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5825MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1285.4785	7.04	38.71	45.75	68.20	22.45	PASS	Horizontal	PK
2	2195.2695	10.09	42.12	52.21	68.20	15.99	PASS	Horizontal	PK
3	3789.3289	16.22	36.36	52.58	68.20	15.62	PASS	Horizontal	PK
4	7199.2466	-4.82	51.56	46.74	68.20	21.46	PASS	Horizontal	PK
5	10600.4067	6.34	44.81	51.15	68.20	17.05	PASS	Horizontal	PK
6	15250.55	11.62	41.58	53.20	68.20	15.00	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5825MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1221.1221	6.29	38.63	44.92	68.20	23.28	PASS	Vertical	PK
2	2196.9197	10.08	39.59	49.67	68.20	18.53	PASS	Vertical	PK
3	3962.0462	17.21	35.26	52.47	68.20	15.73	PASS	Vertical	PK
4	6991.4661	-4.83	48.61	43.78	68.20	24.42	PASS	Vertical	PK
5	10998.3332	6.78	45.53	52.31	68.20	15.89	PASS	Vertical	PK
6	15899.1933	10.75	42.45	53.20	68.20	15.00	PASS	Vertical	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5825MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19229.1692	-24.28	62.68	38.40	74.00	35.60	PASS	Horizontal	PK
2	22280.0112	-24.59	60.87	36.28	74.00	37.72	PASS	Horizontal	PK
3	25236.0894	-18.92	57.92	39.00	74.00	35.00	PASS	Horizontal	PK
4	28298.892	-20.55	58.08	37.53	74.00	36.47	PASS	Horizontal	PK
5	31353.4141	-17.52	55.86	38.34	74.00	35.66	PASS	Horizontal	PK
6	37092.6037	-15.42	51.18	35.76	74.00	38.24	PASS	Horizontal	PK

Test_Mode	802.11 a Transmitting	Test_Frequency	5825MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19429.7372	-23.94	61.48	37.54	74.00	36.46	PASS	Vertical	PK
2	22464.9386	-24.39	61.03	36.64	74.00	37.36	PASS	Vertical	PK
3	26311.6125	-19.51	57.91	38.40	74.00	35.60	PASS	Vertical	PK
4	30011.0804	-19.63	58.05	38.42	74.00	35.58	PASS	Vertical	PK
5	33544.9418	-15.59	53.73	38.14	74.00	35.86	PASS	Vertical	PK
6	37661.1864	-13.83	50.77	36.94	74.00	37.06	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1224.4224	6.31	38.74	45.05	68.20	23.15	PASS	Horizontal	PK
2	2295.9296	10.89	38.09	48.98	68.20	19.22	PASS	Horizontal	PK
3	3783.8284	16.03	35.98	52.01	68.20	16.19	PASS	Horizontal	PK
4	7042.0695	-4.80	48.52	43.72	68.20	24.48	PASS	Horizontal	PK
5	11007.5338	6.67	45.71	52.38	68.20	15.82	PASS	Horizontal	PK
6	16602.2735	11.26	41.58	52.84	68.20	15.36	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1322.8823	7.53	37.88	45.41	68.20	22.79	PASS	Vertical	PK
2	2095.7096	10.61	40.31	50.92	68.20	17.28	PASS	Vertical	PK
3	3793.7294	16.38	35.38	51.76	68.20	16.44	PASS	Vertical	PK
4	7026.7351	-4.75	48.25	43.50	68.20	24.70	PASS	Vertical	PK
5	11019.0346	6.39	45.32	51.71	68.20	16.49	PASS	Vertical	PK
6	15895.3597	10.56	42.97	53.53	68.20	14.67	PASS	Vertical	PK

Test_Mode	802.11 n(H240) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20370.9348	-24.04	61.60	37.56	74.00	36.44	PASS	Horizontal	PK
2	24478.8992	-19.83	59.06	39.23	74.00	34.77	PASS	Horizontal	PK
3	27848.994	-20.24	59.01	38.77	74.00	35.23	PASS	Horizontal	PK
4	31035.0814	-17.44	56.32	38.88	74.00	35.12	PASS	Horizontal	PK
5	36135.7654	-15.02	51.79	36.77	74.00	37.23	PASS	Horizontal	PK
6	39069.7628	-10.78	48.29	37.51	74.00	36.49	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19814.3126	-23.58	61.56	37.98	74.00	36.02	PASS	Vertical	PK
2	22475.059	-24.39	60.33	35.94	74.00	38.06	PASS	Vertical	PK
3	25980.3992	-19.08	58.66	39.58	74.00	34.42	PASS	Vertical	PK
4	29584.1834	-19.33	57.19	37.86	74.00	36.14	PASS	Vertical	PK
5	32738.9896	-16.40	54.46	38.06	74.00	35.94	PASS	Vertical	PK
6	38742.2297	-11.61	48.67	37.06	74.00	36.94	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5785MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1405.3905	8.31	37.96	46.27	68.20	21.93	PASS	Horizontal	PK
2	2097.3597	10.60	40.81	51.41	68.20	16.79	PASS	Horizontal	PK
3	3548.4048	15.32	37.53	52.85	68.20	15.35	PASS	Horizontal	PK
4	7186.9791	-4.71	49.71	45.00	68.20	23.20	PASS	Horizontal	PK
5	12399.8933	6.79	45.92	52.71	68.20	15.49	PASS	Horizontal	PK
6	15893.0595	10.44	43.35	53.79	68.20	14.41	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5785MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1416.9417	8.30	38.11	46.41	68.20	21.79	PASS	Vertical	PK
2	2389.4389	11.96	38.05	50.01	68.20	18.19	PASS	Vertical	PK
3	3798.6799	16.57	35.08	51.65	68.20	16.55	PASS	Vertical	PK
4	7007.5672	-4.70	48.63	43.93	68.20	24.27	PASS	Vertical	PK
5	11035.1357	6.01	45.79	51.80	68.20	16.40	PASS	Vertical	PK
6	16438.1959	9.16	43.43	52.59	68.20	15.61	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5785MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19404.8962	-23.94	62.22	38.28	74.00	35.72	PASS	Horizontal	PK
2	21559.6224	-24.83	61.77	36.94	74.00	37.06	PASS	Horizontal	PK
3	25061.2825	-19.53	57.37	37.84	74.00	36.16	PASS	Horizontal	PK
4	28914.3966	-20.27	58.12	37.85	74.00	36.15	PASS	Horizontal	PK
5	32476.7791	-15.84	55.49	39.65	74.00	34.35	PASS	Horizontal	PK
6	38768.9108	-11.48	49.38	37.90	74.00	36.10	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5785MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19159.2464	-24.37	62.23	37.86	74.00	36.14	PASS	Vertical	PK
2	22177.8871	-24.75	60.48	35.73	74.00	38.27	PASS	Vertical	PK
3	24716.2687	-19.82	58.19	38.37	74.00	35.63	PASS	Vertical	PK
4	29010.0804	-20.15	58.19	38.04	74.00	35.96	PASS	Vertical	PK
5	34087.7635	-16.04	52.64	36.60	74.00	37.40	PASS	Vertical	PK
6	38702.6681	-11.81	49.77	37.96	74.00	36.04	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1178.5786	6.83	37.75	44.58	68.20	23.62	PASS	Horizontal	PK
2	2098.6066	10.61	42.19	52.80	68.20	15.40	PASS	Horizontal	PK
3	3442.8962	15.15	34.60	49.75	68.20	18.45	PASS	Horizontal	PK
4	5061.1041	21.70	31.18	52.88	68.20	15.32	PASS	Horizontal	PK
5	7865.5244	-1.75	45.73	43.98	68.20	24.22	PASS	Horizontal	PK
6	10769.0846	5.04	45.81	50.85	68.20	17.35	PASS	Horizontal	PK
7	15897.6598	10.68	41.06	51.74	68.20	16.46	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1365.9577	7.97	36.51	44.48	68.20	23.72	PASS	Vertical	PK
2	2412.4942	12.25	35.87	48.12	68.20	20.08	PASS	Vertical	PK
3	4493.8329	20.72	31.62	52.34	68.20	15.86	PASS	Vertical	PK
4	7417.7612	-4.06	47.55	43.49	68.20	24.71	PASS	Vertical	PK
5	11231.4154	6.34	43.75	50.09	68.20	18.11	PASS	Vertical	PK
6	15899.96	10.79	40.76	51.55	68.20	16.65	PASS	Vertical	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	20037.8815	-23.23	61.70	38.47	74.00	35.53	PASS	Horizontal	PK
2	23141.1656	-23.91	59.48	35.57	74.00	38.43	PASS	Horizontal	PK
3	26620.7448	-19.46	58.40	38.94	74.00	35.06	PASS	Horizontal	PK
4	30497.7799	-18.75	57.24	38.49	74.00	35.51	PASS	Horizontal	PK
5	34970.9988	-15.39	52.86	37.47	74.00	36.53	PASS	Horizontal	PK
6	39014.5606	-10.75	48.47	37.72	74.00	36.28	PASS	Horizontal	PK

Test_Mode	802.11 n(HT20) Transmitting	Test_Frequency	5825MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\18
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19983.5993	-23.10	61.40	38.30	74.00	35.70	PASS	Vertical	PK
2	23719.8688	-21.31	58.78	37.47	74.00	36.53	PASS	Vertical	PK
3	27097.3239	-20.32	58.44	38.12	74.00	35.88	PASS	Vertical	PK
4	30152.7661	-19.73	57.72	37.99	74.00	36.01	PASS	Vertical	PK
5	33648.906	-15.54	53.81	38.27	74.00	35.73	PASS	Vertical	PK
6	38924.397	-10.96	48.31	37.35	74.00	36.65	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\20
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1373.2916	8.05	36.65	44.70	68.20	23.50	PASS	Horizontal	PK
2	2198.7132	10.06	37.95	48.01	68.20	20.19	PASS	Horizontal	PK
3	4272.7182	18.50	32.07	50.57	68.20	17.63	PASS	Horizontal	PK
4	6805.9204	-4.77	48.06	43.29	68.20	24.91	PASS	Horizontal	PK
5	11268.9846	5.54	45.14	50.68	68.20	17.52	PASS	Horizontal	PK
6	15896.8931	10.64	40.54	51.18	68.20	17.02	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\20
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1289.686	7.11	37.29	44.40	68.20	23.80	PASS	Vertical	PK
2	2197.9799	10.06	36.70	46.76	68.20	21.44	PASS	Vertical	PK
3	3941.5961	17.37	32.78	50.15	68.20	18.05	PASS	Vertical	PK
4	6887.1925	-4.49	46.87	42.38	68.20	25.82	PASS	Vertical	PK
5	11001.4001	6.82	44.12	50.94	68.20	17.26	PASS	Vertical	PK
6	16442.7962	9.13	42.06	51.19	68.20	17.01	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\20
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19396.6159	-23.95	62.35	38.40	74.00	35.60	PASS	Horizontal	PK
2	21561.4625	-24.83	62.14	37.31	74.00	36.69	PASS	Horizontal	PK
3	25782.5913	-18.90	57.94	39.04	74.00	34.96	PASS	Horizontal	PK
4	29202.3681	-20.27	58.54	38.27	74.00	35.73	PASS	Horizontal	PK
5	33425.337	-16.01	55.00	38.99	74.00	35.01	PASS	Horizontal	PK
6	39058.7223	-10.78	48.43	37.65	74.00	36.35	PASS	Horizontal	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5745MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\20
Remark	\		


Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	19479.4192	-23.94	62.31	38.37	74.00	35.63	PASS	Vertical	PK
2	22771.3109	-24.39	59.82	35.43	74.00	38.57	PASS	Vertical	PK
3	26608.7844	-19.43	58.93	39.50	74.00	34.50	PASS	Vertical	PK
4	31698.4279	-17.19	55.77	38.58	74.00	35.42	PASS	Vertical	PK
5	36624.305	-14.30	51.41	37.11	74.00	36.89	PASS	Vertical	PK
6	38722.9089	-11.71	49.08	37.37	74.00	36.63	PASS	Vertical	PK

Test_Mode	802.11 ac(VHT20) Transmitting	Test_Frequency	5785MHz
Tset_Engineer	Aiden.wang	Test_Date	2024\09\20
Remark	\		

Test Graph



Suspected List									
NO	Freq. [MHz]	Factor [dB]	Reading [dBμV]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Result	Polarity	Remark
1	1362.4862	7.93	38.26	46.19	68.20	22.01	PASS	Horizontal	PK
2	2064.3564	10.63	37.97	48.60	68.20	19.60	PASS	Horizontal	PK
3	3912.5413	17.06	35.61	52.67	68.20	15.53	PASS	Horizontal	PK
4	6892.5595	-4.40	48.53	44.13	68.20	24.07	PASS	Horizontal	PK
5	10597.3398	6.23	45.02	51.25	68.20	16.95	PASS	Horizontal	PK
6	15111.7741	11.62	42.07	53.69	68.20	14.51	PASS	Horizontal	PK