

Dongguan AD Plaus
Technology Limited

TEST REPORT

SCOPE OF WORK

SAR Assessment– 15W WIRELESS CHARGING PAD

REPORT NUMBER

240821041SZN-002

ISSUE DATE

12 October 2024

[REVISED DATE]

[-----]

PAGES

6

DOCUMENT CONTROL NUMBER

RF Exposure

© 2017 INTERTEK



Test Report

Applicant : Dongguan AD Plaus Technology Limited
No.5, Baihao Yanhe 2nd Road, Houjie Town, Dongguan, Guangdong Province, China

Sample Description

FCC ID : 2BK83-411701

Product : GS Wireless Charging Pad

Model No. : 15W WIRELESS CHARGING PAD

Brand Name : MARVEL, STARWARS, GameStop

Electrical Rating : Input: DC 5V 2A, 9V 2A, 12V 2A
Wireless Output: 5W/7.5W/10W/15.0W Max

Date Received : 21 August 2024

Date Test Conducted : 21 August 2024 to 19 September 2024

Test Requested : Test for compliance with CFR 47 part 1

Test Method : Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310 KDB 680106 D01 Wireless Power Transfer v04

Test Result : Pass

Conclusion : When determining of test conclusion, measurement uncertainty of tests have been considered.

Prepared and Checked By:

Tony Tang
Engineer**Approved By:**


Johnny Wang
Project Engineer
Date: 12 October 2024

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Shenzhen Ltd. Longhua Branch101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen.
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

Test Report

Test Setup Configuration



Note

- The RF exposure test is performed in the shield room.
- The test distance is between the edge of the charger and the the measurement probe.

Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Cal. Date	Due Date
SZ186-06	The Magnetic Amplitude and Gradient Probe System	SPEAG	MAGPy-8D3D+E3D	2024-03-07	2025-03-07

Support Equipment List

Description	Manufacturer	Detail
Mobile phone	Samsung (Provided by Intertek)	Model: S7
Adapter	Quick Wall Charger (Provided by Intertek)	Model: G5-W30A0936 Input: 100-240Vac 50/60Hz 0.5A Output: 5Vdc 3A, 9Vdc 3A, 12Vdc 2.5A

Reference Limit:

Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation.

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	(100) *	30

Note: * = Plane wave equivalent power density

Test Result: Pass
H-Field Strength at 20 cm surrounding the EUT

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (A/m)	Probe Position Rear (A/m)	Probe Position Left (A/m)	Probe Position Right (A/m)	Probe Position Top (A/m)	Limits (A/m)
0.112-0.205	1% Battery Level	0.01	0.01	0.01	0.02	0.01	1.63
0.112-0.205	50% Battery Level	0.01	0.01	0.01	0.02	0.01	1.63
0.112-0.205	99% Battery Level	0.01	0.01	0.01	0.01	0.01	1.63
0.112-0.205	Stand-by	0.01	0.01	0.01	0.01	0.01	1.63

E-Field Strength at 20 cm surrounding the EUT

Frequency Range (MHz)	EUT Operation mode	Probe Position Front (V/m)	Probe Position Rear (V/m)	Probe Position Left (V/m)	Probe Position Right (V/m)	Probe Position Top (V/m)	Limits (V/m)
0.112-0.205	1% Battery Level	1.25	0.97	1.16	1.25	0.88	614
0.112-0.205	50% Battery Level	1.23	0.86	1.12	1.16	0.76	614
0.112-0.205	99% Battery Level	1.16	0.75	1.03	1.06	0.71	614
0.112-0.205	Stand-by	1.12	0.73	1.01	1.02	0.69	614


Configuration photo of the test:

H-Field & E-Field Strength test photos

Front




Rear




Left



Right





***** End of Report*****