

## Analysis Report

**The Equipment Under Test (EUT), is a 2.4GHz BT Transceiver for a Bluetooth Speaker. The sample supplied operated on 79 channels, normally at 2402 - 2480MHz. The channels are separated with 1MHz spacing.**

**The EUT is powered by 1 x 3.7V Lithium-ion battery. After switching on EUT, it can be paired up with a smartphone and will be used to play different sound based on the sound received from the paired smartphone.**

Antenna Type: Internal, Integral antenna

Antenna Gain: 6dBi

Nominal rated field strength is 82.9dB $\mu$ V/m at 3m (Peak), 70.5dB $\mu$ V/m at 3m (Average)

Maximum allowed production tolerance: +/- 3dB

According to the KDB 447498:

Based on the maximum average field strength of production tolerance was 73.5dB $\mu$ V/m at 3m in frequency 2.440GHz.

Thus, it below calculated field strength according to minimum SAR exclusion threshold level as follows:

The worst case of SAR Exclusion Threshold Level:

$$\begin{aligned} &= 3.0 * (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}} \\ &= 3.0 * 5 / \sqrt{2.483.5} \text{ mW} \\ &= 9.52 \text{ mW} \end{aligned}$$

According to the KDB 412172 D01:

$$\text{EIRP} = [(FS \cdot D)^2 \cdot 1000 / 30]$$

Calculated Field Strength for 9.52mW is 105dB $\mu$ V/m @3m

Since maximum average field strength plus production tolerance  $\leq$  105dB $\mu$ V/m @3m and antenna gain is  $\geq$  0.0dBi, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.