

**FCC ID: 2BKBE-KJ106**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

434.124MHz

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
OOK	0.43412	-22.8	0.01	-22±1	-21.00	0.01	<5	0.00105	3.00	YES

Note:  $\text{dbm} = \text{dbuv/m} - 95.2 - 2.15 = 76.65 - 95.2 - 2.15 = -20.7 \text{ dBm (ERP)}$ , so the conduct peak power =  $20.7 - 2.1 = -22.8 \text{ dBm}$

**Conclusion:**

For the max result :  $0.00105 \leq \text{FCC Limit 3.0 for 1g SAR}$ .