



RF EXPOSURE REPORT

Applicant	:	Guangdong Jsoul Technology Co., LTD
Address of Applicant	:	Room 2410, No. 13, Dongguan Avenue, Dongcheng Street, Dongguan City, Guangdong Province
Manufacturer	:	Guangdong Jsoul Technology Co., LTD
Address of Manufacturer	:	Room 2410, No. 13, Dongguan Avenue, Dongcheng Street, Dongguan City, Guangdong Province
Equipment under Test	:	True Wireless Earbuds
Model No.	:	JS05
FCC ID	:	2BKCV-JS05
Test Standard(s)	:	KDB447498 D01 General RF Exposure Guidance v06
Report No.	:	DDT-RE24081307-1E03
Issue Date	:	2024/12/12
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1. General Test Information.....5

1.1. Description of EUT5

1.2. Accessories of EUT5

1.3. Test laboratory5

2. RF Exposure evaluation for FCC.....6

2.1. Assessment procedure.....6

2.2. Assess result.....6

Test Report Declare

Applicant	:	Guangdong Jsoul Technology Co., LTD
Address of Applicant	:	Room 2410, No. 13, Dongguan Avenue, Dongcheng Street, Dongguan City, Guangdong Province
Equipment under Test	:	True Wireless Earbuds
Model No.	:	JS05
Manufacturer	:	Guangdong Jsoul Technology Co., LTD
Address of Manufacturer	:	Room 2410, No. 13, Dongguan Avenue, Dongcheng Street, Dongguan City, Guangdong Province

Test Standard Used:

KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24081307-1E03		
Date of Receipt:	2024/10/08	Date of Test:	2024/10/08~2024/12/12

Prepared By:*Ziqin Chen***Ziqin Chen/Engineer****Approved By:***Damon Hu***Damon/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2024/12/12	

1. General Test Information

1.1. Description of EUT

EUT Name	: True Wireless Earbuds
Model Number	: JS05
Difference of model number	: /
EUT Function Description	: Please reference user manual of this device
Power Supply	: Case: DC 5V from USB cable or DC 3.7V built-in battery; Earbud: DC 5V from external charging case or DC 3.85V built-in battery

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

1.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

1.3. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2. RF Exposure evaluation for FCC

2.1. Assessment procedure

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

2.2. Assess result

Manufacturing Tolerance:

BT:

Mode	Antenna	Frequency [MHz]	Target Power	Tolerance $\pm$ (dBm)
GFSK (Peak)	Left side and Right side	2402	-4	1
		2441	-4	1
		2480	-4.5	1
$\pi/4$ DQPSK (Peak)	Left side and Right side	2402	-3	1
		2441	-3	1
		2480	-3.5	1

BLE:

Mode	Antenna	Frequency [MHz]	Target Power	Tolerance $\pm$ (dBm)
GFSK 1M(Peak)	Left side and Right side	2402	-4	1
		2440	-4	1
		2480	-4.5	1

Estimation Result:

Worse case is as below: [2441 MHz, -2 dBm, (0.63 mW) output power]

$(0.63/5) \cdot [\sqrt{2.441(\text{GHz})}] = 0.197 < 3.0$ for 1-g SAR

Then SAR evaluation is not required.

-----End Report-----