

# MPE ESTIMATION

FCC ID: 2BKDR-XXRMX001

## 1, According to §1.1310, Limit for General Population/ Uncontrolled Exposures

Frequency	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

Note: F= Frequency in MHz

## 2, Estimation Result

	Frequency (MHz)	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (numerical)	MPE (mW/cm <sup>2</sup> )
2.4G WiFi	2462	15.27	15±1(16)	39.811	3.25	2.11	0.01675

$$Pd = \frac{P_{out} * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power in mW.

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna in cm

Conducted power see the test report **HK2507033603-E**, antenna gain=3.25dBi.

When the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.01675 mW/cm<sup>2</sup> which is< 1.0 mW/cm<sup>2</sup>, RF Exposure testing is not required.

-----The End-----