

TEST REPORT

Report No.: **BCTC2408834386-1E**

Applicant: **Shenzhen One-Netbook Project Technology Co., Ltd**

Product Name: **Portable computer**

Test Model: **ONE XPLAYER**

Tested Date: **2024-08-08 to 2024-08-27**

Issued Date: **2024-09-19**

Shenzhen BCTC Testing Co., Ltd.



FCC ID:2BKG2-ONEXPLAYER

Product Name: Portable computer

Trademark: ONE XPLAYER

Model/Type Reference: ONE XPLAYER,X1 Mini,X1Mini,X1Pro,X1 Pro,One Xplayer,One xPlayer,OneXplayer,OneGx,One-Netbook,T1,T2,T3,X1,X2,X3,PL1,PL2,PL3,P1,P2,P3,L1,L2,L3,G1,G2,G3,M1,M2,M3,F1,F2,F3,A1,A2,A3,i1,i3,i5

Prepared For: Shenzhen One-Netbook Project Technology Co., Ltd

Address: 3F, Building C, NO.9 of garden New village Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, China, 518129

Manufacturer: Shenzhen One-Netbook Project Technology Co., Ltd

Address: 3F, Building C, NO.9 of garden New village Road, Xiangjiaotang Community, Bantian Street, Longgang District, Shenzhen, China, 518129

Prepared By: Shenzhen BCTC Testing Co., Ltd

Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2024-08-08

Sample Tested Date: 2024-08-08 to 2024-08-27

Report No.: BCTC2408834386-1E

Test Standards: FCC Part15.247
ANSI C63.10-2013

Test Results: PASS

Remark: This is Bluetooth Classic radio test report.

Tested by:



Brave Zeng/ Project Handler

Approved by:




Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table of Content


Test Report Declaration	Page
1. Version	5
2. Test Summary	6
3. Measurement Uncertainty	7
4. Product Information and Test Setup.....	8
4.1 Product Information.....	8
4.2 Test Setup Configuration	8
4.3 Support Equipment	9
4.4 Channel List	9
4.5 Test Mode	10
4.6 Table Of Parameters Of Text Software Setting.....	10
5. Test Facility And Test Instrument Used.....	11
5.1 Test Facility.....	11
5.2 Test Instrument Used.....	11
6. Conducted Emissions.....	13
6.1 Block Diagram Of Test Setup.....	13
6.2 Limit	13
6.3 Test procedure	13
6.4 EUT operating Conditions	13
6.5 Test Result.....	14
7. Radiated emissions	16
7.1 Block Diagram Of Test Setup.....	16
7.2 Limit	17
7.3 Test procedure	18
7.4 EUT operating Conditions	19
7.5 Test Result.....	20
8. Radiated Band Emission Measurement and Restricted Bands of Operation	26
8.1 Block Diagram Of Test Setup.....	26
8.2 Limit	26
8.3 Test procedure	27
8.4 EUT operating Conditions	27
8.5 Test Result.....	28
9. Spurious RF Conducted Emissions	29
9.1 Block Diagram Of Test Setup.....	29
9.2 Limit	29
9.3 Test procedure	29
9.4 Test Result.....	30
10. 20 dB Bandwidth	51
10.1 Block Diagram Of Test Setup.....	51
10.2 Limit	51
10.3 Test procedure	51
10.4 Test Result.....	52
11. Maximum Peak Output Power.....	58
11.1 Block Diagram Of Test Setup.....	58
11.2 Limit	58
11.3 Test procedure	58
11.4 Test Result.....	58

12. Hopping Channel Separation	64
12.1 Block Diagram Of Test Setup.....	64
12.2 Limit	64
12.3 Test procedure	64
12.4 Test Result.....	64
13. Number of Hopping Frequency	70
13.1 Block Diagram Of Test Setup.....	70
13.2 Limit	70
13.3 Test procedure	70
13.4 Test Result.....	70
14. Dwell Time.....	73
14.1 Block Diagram Of Test Setup.....	73
14.2 Limit	73
14.3 Test procedure	73
14.4 Test Result.....	73
15. Antenna Requirement	80
15.1 Limit	80
15.2 Test Result.....	80
16. EUT Test Setup Photographs.....	81



1. Version

Report No.	Issue Date	Description	Approved
BCTC2408834386-1E	2024-09-19	Original	Valid



2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	Conducted emission AC power port	§15.207	PASS
2	Conducted peak output power for FHSS	§15.247(b)(1)	PASS
3	20dB Occupied bandwidth	§15.247(a)(1)	PASS
4	Number of hopping frequencies	§15.247(a)(1)(iii)	PASS
5	Dwell Time	§15.247(a)(1)(iii)	PASS
6	Spurious RF conducted emissions	§15.247(d)	PASS
7	Band edge	§15.247(d)	PASS
8	Spurious radiated emissions for transmitter	§15.247(d) & §15.209 & §15.205	PASS
9	Antenna Requirement	15.203	PASS

NOTE1: N/A (Not Applicable)

NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.

3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(30MHz-1GHz)	$U=4.3\text{dB}$
2	3m chamber Radiated spurious emission(9KHz-30MHz)	$U=3.7\text{dB}$
3	3m chamber Radiated spurious emission(1GHz-18GHz)	$U=4.5\text{dB}$
4	3m chamber Radiated spurious emission(18GHz-40GHz)	$U=3.34\text{dB}$
5	Conducted Emission (150kHz-30MHz)	$U=3.20\text{dB}$
6	Conducted Adjacent channel power	$U=1.38\text{dB}$
7	Conducted output power uncertainty Above 1G	$U=1.576\text{dB}$
8	Conducted output power uncertainty below 1G	$U=1.28\text{dB}$
9	humidity uncertainty	$U=5.3\%$
10	Temperature uncertainty	$U=0.59^\circ\text{C}$

4. Product Information and Test Setup


4.1 Product Information

Model/Type reference:	ONE XPLAYER,X1 Mini,X1Mini,X1Pro,X1 Pro,One Xplayer,One xPlayer,OnexPlayer, OneXplayer,OneGx,One-Netbook,T1,T2,T3,X1,X2,X3,PL1,PL2,PL3,P1,P2,P3,L1,L2,L3 ,G1,G2,G3,M1,M2,M3,F1,F2,F3,A1,A2,A3,i1,i3,i5
Model differences:	The following models of units we produce are identical in electrical, mechanical and physical structure; The difference is only in the model name and color, we finally have ONE XPLAYER as test model.
Hardware Version:	N/A
Software Version:	N/A
Operation Frequency:	Bluetooth: 2402-2480MHz
Type of Modulation:	Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
Number Of Channel	79CH
Antenna installation:	Internal antenna
Antenna Gain:	3.46dBi
Remark:	The antenna gain of the product comes from the antenna report provided by the customer, and the test data is affected by the customer information.
Adapter:	Input:100-240V~,50/60Hz, 2A Max; Output : 5Vdc/ 3A, 9Vdc/ 3A, 12Vdc/ 3A, 15Vdc /3A, 20Vdc/ 5A Max. PPS:3.3-20Vdc /3.25A
Battery:	DC 13.2V, 5630mAh


4.2 Test Setup Configuration

See test photographs attached in eut test setup photographs for the actual connections between product and support equipment.

Conducted Emission:



Radiated Spurious Emission



4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Portable computer	N/A	ONE XPLAYER	N/A	EUT
E-2	Adapter	N/A	N/A	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note
C-1	N/A	N/A	N/A	N/A

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

CH	Frequency (MHz)						
0	2402	1	2403	2	2404	3	2405
4	2406	5	2407	6	2408	7	2409
8	2410	9	2411	10	2412	11	2413
12	2414	13	2415	14	2416	15	2417
16	2418	17	2419	18	2420	19	2421
20	2422	21	2423	22	2424	23	2425
24	2426	25	2427	26	2428	27	2429
28	2430	29	2431	30	2432	31	2433
32	2434	33	2435	34	2436	35	2437
36	2438	37	2439	38	2440	39	2441
40	2442	41	2443	42	2444	43	2445
44	2446	45	2447	46	2448	47	2449
48	2450	49	2451	50	2452	51	2453
52	2454	53	2455	54	2456	55	2457
56	2458	57	2459	58	2460	59	2461
60	2462	61	2463	62	2464	63	2465
64	2466	65	2467	66	2468	67	2469
68	2470	69	2471	70	2472	71	2473
72	2474	73	2475	74	2476	75	2477
76	2478	77	2479	78	2480	79	/

4.5 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Test Mode	Test mode	Low channel	Middle channel	High channel
1	Transmitting(GFSK)	2402MHz	2441MHz	2480MHz
2	Transmitting($\pi/4$ DQPSK)	2402MHz	2441MHz	2480MHz
3	Transmitting(8DPSK)	2402MHz	2441MHz	2480MHz
4	Transmitting (Conducted emission & Radiated emission)			

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) Fully-charged battery is used during the test

4.6 Table Of Parameters Of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

Test software Version	FCC_assist 1.0.1.2		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters	DEF	DEF	DEF

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

IC Registered No.: 23583

5.2 Test Instrument Used


Conducted Emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESR3	102075	May 16, 2024	May 15, 2025
LISN	R&S	ENV216	101375	May 16, 2024	May 15, 2025
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\
Pulse limiter	Schwarzbeck	VTSD9561-F	01323	May 16, 2024	May 15, 2025

RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power meter	Keysight	E4419	\	May 16, 2024	May 15, 2025
Power Sensor (AV)	Keysight	E9300A	\	May 16, 2024	May 15, 2025
Signal Analyzer20kHz -26.5GHz	Keysight	N9020A	MY49100060	May 16, 2024	May 15, 2025
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 16, 2024	May 15, 2025

Radiated Emissions Test (966 Chamber)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	May 16, 2024	May 15, 2025
Receiver	R&S	ESR3	102075	May 16, 2024	May 15, 2025
Receiver	R&S	ESRP	101154	May 16, 2024	May 15, 2025
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 16, 2024	May 15, 2025
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	May 21, 2024	May 20, 2025
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	May 21, 2024	May 20, 2025
Amplifier	SKET	LAPA_01G1 8G-45dB	SK202104090 1	May 16, 2024	May 15, 2025
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 21, 2024	May 20, 2025
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35- HG	2034381	May 16, 2024	May 15, 2025
Horn Antenn(18GH z-40GHz)	Schwarzbeck	BBHA9170	00822	May 21, 2024	May 20, 2025
Spectrum Analyzer9kHz- 40GHz	R&S	FSP40	100363	May 16, 2024	May 15, 2025
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

Frequency (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:

- *Decreasing linearly with logarithm of frequency.
- The lower limit shall apply at the transition frequencies.

6.3 Test procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N.).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

6.5 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	L
Test Mode:	Mode 4	Test Voltage :	AC120V/60Hz




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	F
1	0.2445	31.95	10.27	42.22	61.94	-19.72	QP	
2	0.2445	21.77	10.27	32.04	51.94	-19.90	AVG	
3	0.3615	29.84	10.29	40.13	58.69	-18.56	QP	
4	0.3615	17.04	10.29	27.33	48.69	-21.36	AVG	
5	0.4470	29.36	10.30	39.66	58.93	-17.27	QP	
6	0.4470	18.08	10.30	28.38	46.93	-18.55	AVG	
7	0.6090	32.21	10.34	42.55	56.00	-13.45	QP	
8	0.6090	18.43	10.34	28.77	46.00	-17.23	AVG	
9	0.7665	32.41	10.32	42.73	56.00	-13.27	QP	
10	0.7665	18.88	10.32	29.20	46.00	-16.80	AVG	
11	1.5225	28.42	10.32	38.74	56.00	-17.26	QP	
12	1.5225	15.75	10.32	26.07	46.00	-19.93	AVG	

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	N
Test Mode:	Mode 4	Test Voltage :	AC120V/60Hz


Remark:


1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	
1	0.2265	30.35	10.27	40.62	62.58	-21.96	QP	
2	0.2265	21.12	10.27	31.39	52.58	-21.19	AVG	
3	0.3615	28.14	10.29	38.43	58.69	-20.26	QP	
4	0.3615	16.90	10.29	27.19	48.69	-21.50	AVG	
5	0.4515	29.99	10.30	40.29	56.85	-16.56	QP	
6	0.4515	15.45	10.30	25.75	46.85	-21.10	AVG	
7 *	0.6675	30.61	10.33	40.94	56.00	-15.06	QP	
8	0.6675	15.05	10.33	25.38	46.00	-20.62	AVG	
9	0.8655	28.35	10.30	38.65	56.00	-17.35	QP	
10	0.8655	14.13	10.30	24.43	46.00	-21.57	AVG	
11	6.1665	25.07	10.73	35.80	60.00	-24.20	QP	
12	6.1665	14.78	10.73	25.51	50.00	-24.49	AVG	


7. Radiated emissions

7.1 Block Diagram Of Test Setup


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



7.2 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength uV/m	Distance (m)	Field Strength Limit at 3m Distance	
			uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	20log ^{(2400/F(kHz))} + 80
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	20log ^{(24000/F(kHz))} + 40
1.705 ~ 30	30	30	100 * 30	20log ⁽³⁰⁾ + 40
30 ~ 88	100	3	100	20log ⁽¹⁰⁰⁾
88 ~ 216	150	3	150	20log ⁽¹⁵⁰⁾
216 ~ 960	200	3	200	20log ⁽²⁰⁰⁾
Above 960	500	3	500	20log ⁽⁵⁰⁰⁾

Limits Of Radiated Emission Measurement (Above 1000MHz)

Frequency (MHz)	Limit (dBuV/m) (at 3M)	
	Peak	Average
Above 1000	74	54

Notes:

- (1)The limit for radiated test was performed according to FCC PART 15C.
- (2)The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Frequency Range Of Radiated Measurement

(a) For an intentional radiator the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in this paragraph:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator operates at or above 95 GHz: To the third harmonic of the highest fundamental frequency or to 750 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (5) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a) (1) through (4) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this section, whichever is the higher frequency range of investigation.

7.3 Test procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP

Spectrum Parameter	Setting
1-25GHz	RBW 1 MHz /VBW 1. MHz for Peak, RBW 1 MHz / VBW 10Hz for Average

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel, the middlest channel, the Highest channel.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

7.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

7.5 Test Result

Below 30MHz

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage :	DC 13.2V
Test Mode:	Mode 4		

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State
--	--	--	--	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})(\text{dB})$;

Limit line = specific limits(dBuV) + distance extrapolation factor.

Between 30MHz – 1GHz

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 4	Test Voltage :	DC 13.2V




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement = Reading Level + Correct Factor
3. Over = Measurement - Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	38.7518	26.27	-17.05	9.22	40.00	-30.78	QP
2	54.8348	26.27	-16.98	9.29	40.00	-30.71	QP
3	175.0368	28.56	-15.95	12.61	43.50	-30.89	QP
4	300.3672	30.67	-13.63	17.04	46.00	-28.96	QP
5	350.4768	30.31	-11.91	18.40	46.00	-27.60	QP
6 *	875.2470	27.13	0.54	27.67	46.00	-18.33	QP

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 4	Test Voltage :	DC 13.2V


Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement = Reading Level + Correct Factor
3. Over = Measurement - Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	43.5057	31.90	-16.88	15.02	40.00	-24.98	QP
2	73.3593	36.61	-19.12	17.49	40.00	-22.51	QP
3	183.8440	34.89	-16.51	18.38	43.50	-25.12	QP
4	300.3672	30.36	-13.63	16.73	46.00	-29.27	QP
5	472.1760	31.77	-8.36	23.41	46.00	-22.59	QP
6 *	586.8437	34.75	-5.31	29.44	46.00	-16.56	QP

Between 1GHz – 25GHz

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
GFSK Low channel							
V	4804.00	71.14	-19.99	51.15	74.00	-22.85	PK
V	4804.00	61.82	-19.99	41.83	54.00	-12.17	AV
V	7206.00	60.19	-14.22	45.97	74.00	-28.03	PK
V	7206.00	49.91	-14.22	35.69	54.00	-18.31	AV
H	4804.00	68.05	-19.99	48.06	74.00	-25.94	PK
H	4804.00	58.22	-19.99	38.23	54.00	-15.77	AV
H	7206.00	57.71	-14.22	43.49	74.00	-30.51	PK
H	7206.00	49.02	-14.22	34.80	54.00	-19.20	AV
GFSK Middle channel							
V	4882.00	68.13	-19.84	48.29	74.00	-25.71	PK
V	4882.00	59.19	-19.84	39.35	54.00	-14.65	AV
V	7323.00	57.16	-13.90	43.26	74.00	-30.74	PK
V	7323.00	48.66	-13.90	34.76	54.00	-19.24	AV
H	4882.00	65.98	-19.84	46.14	74.00	-27.86	PK
H	4882.00	55.02	-19.84	35.18	54.00	-18.82	AV
H	7323.00	54.84	-13.90	40.94	74.00	-33.06	PK
H	7323.00	46.04	-13.90	32.14	54.00	-21.86	AV
GFSK High channel							
V	4960.00	70.94	-19.68	51.26	74.00	-22.74	PK
V	4960.00	62.20	-19.68	42.52	54.00	-11.48	AV
V	7440.00	62.67	-13.57	49.10	74.00	-24.90	PK
V	7440.00	52.94	-13.57	39.37	54.00	-14.63	AV
H	4960.00	68.27	-19.68	48.59	74.00	-25.41	PK
H	4960.00	57.33	-19.68	37.65	54.00	-16.35	AV
H	7440.00	59.80	-13.57	46.23	74.00	-27.77	PK
H	7440.00	51.20	-13.57	37.63	54.00	-16.37	AV

Remark:

1. Emission Level = Meter Reading + Factor, Factor = Antenna Factor + Cable Loss – Pre-amplifier. Over-Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
$\pi/4$ DQPSK Low channel							
V	4804.00	72.31	-19.99	52.32	74.00	-21.68	PK
V	4804.00	62.22	-19.99	42.23	54.00	-11.77	AV
V	7206.00	62.44	-14.22	48.22	74.00	-25.78	PK
V	7206.00	51.51	-14.22	37.29	54.00	-16.71	AV
H	4804.00	70.11	-19.99	50.12	74.00	-23.88	PK
H	4804.00	59.48	-19.99	39.49	54.00	-14.51	AV
H	7206.00	59.46	-14.22	45.24	74.00	-28.76	PK
H	7206.00	51.34	-14.22	37.12	54.00	-16.88	AV
$\pi/4$ DQPSK Middle channel							
V	4882.00	70.13	-19.84	50.29	74.00	-23.71	PK
V	4882.00	63.68	-19.84	43.84	54.00	-10.16	AV
V	7323.00	62.73	-13.90	48.83	74.00	-25.17	PK
V	7323.00	54.66	-13.90	40.76	54.00	-13.24	AV
H	4882.00	67.05	-19.84	47.21	74.00	-26.79	PK
H	4882.00	57.03	-19.84	37.19	54.00	-16.81	AV
H	7323.00	60.53	-13.90	46.63	74.00	-27.37	PK
H	7323.00	52.06	-13.90	38.16	54.00	-15.84	AV
$\pi/4$ DQPSK High channel							
V	4960.00	72.33	-19.68	52.65	74.00	-21.35	PK
V	4960.00	62.12	-19.68	42.44	54.00	-11.56	AV
V	7440.00	63.79	-13.57	50.22	74.00	-23.78	PK
V	7440.00	54.44	-13.57	40.87	54.00	-13.13	AV
H	4960.00	70.45	-19.68	50.77	74.00	-23.23	PK
H	4960.00	60.19	-19.68	40.51	54.00	-13.49	AV
H	7440.00	62.17	-13.57	48.60	74.00	-25.40	PK
H	7440.00	54.41	-13.57	40.84	54.00	-13.16	AV

Remark:

1. Emission Level = Meter Reading + Factor, Factor = Antenna Factor + Cable Loss – Pre-amplifier. Over-Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
8DPSK Low channel							
V	4804.00	72.05	-19.99	52.06	74.00	-21.94	PK
V	4804.00	63.15	-19.99	43.16	54.00	-10.84	AV
V	7206.00	64.61	-14.22	50.39	74.00	-23.61	PK
V	7206.00	54.11	-14.22	39.89	54.00	-14.11	AV
H	4804.00	68.20	-19.99	48.21	74.00	-25.79	PK
H	4804.00	58.72	-19.99	38.73	54.00	-15.27	AV
H	7206.00	61.90	-14.22	47.68	74.00	-26.32	PK
H	7206.00	54.24	-14.22	40.02	54.00	-13.98	AV
8DPSK Middle channel							
V	4882.00	68.21	-19.84	48.37	74.00	-25.63	PK
V	4882.00	59.61	-19.84	39.77	54.00	-14.23	AV
V	7323.00	58.12	-13.90	44.22	74.00	-29.78	PK
V	7323.00	49.54	-13.90	35.64	54.00	-18.36	AV
H	4882.00	65.41	-19.84	45.57	74.00	-28.43	PK
H	4882.00	55.30	-19.84	35.46	54.00	-18.54	AV
H	7323.00	56.77	-13.90	42.87	74.00	-31.13	PK
H	7323.00	48.59	-13.90	34.69	54.00	-19.31	AV
8DPSK High channel							
V	4960.00	71.17	-19.68	51.49	74.00	-22.51	PK
V	4960.00	62.02	-19.68	42.34	54.00	-11.66	AV
V	7440.00	63.18	-13.57	49.61	74.00	-24.39	PK
V	7440.00	53.61	-13.57	40.04	54.00	-13.96	AV
H	4960.00	68.93	-19.68	49.25	74.00	-24.75	PK
H	4960.00	59.54	-19.68	39.86	54.00	-14.14	AV
H	7440.00	61.01	-13.57	47.44	74.00	-26.56	PK
H	7440.00	52.11	-13.57	38.54	54.00	-15.46	AV


Remark:

1. Emission Level = Meter Reading + Factor, Factor = Antenna Factor + Cable Loss – Pre-amplifier. Over-Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8. Radiated Band Emission Measurement and Restricted Bands of Operation

8.1 Block Diagram Of Test Setup

Radiated Emission Test-Up Frequency Above 1GHz



8.2 Limit

FCC Part15 C Section 15.209 and 15.205

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Limits Of Radiated Emission Measurement (Above 1000MHz)

Frequency (MHz)	Limit (dBuV/m) (at 3M)	
	Peak	Average
Above 1000	74	54

Notes:

- (1)The limit for radiated test was performed according to FCC PART 15C.
- (2)The tighter limit applies at the band edges.
- (3)Emission level (dBuV/m)=20log Emission level (uV/m).

8.3 Test procedure

Receiver Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (Emission In Restricted Band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Above 1GHz test procedure as below:

- a.The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b.The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c.The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d.For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e.The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middlest channel, the Highest channel.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

8.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

8.5 Test Result

Test mode	Polar (H/V)	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measure- ment (dBuV/m)	Limits (dBuV/m)		Result
					PK	PK	AV	
Low Channel 2402MHz								
GFSK	H	2390.00	72.23	-25.43	46.80	74.00	54.00	PASS
	H	2400.00	73.84	-25.40	48.44	74.00	54.00	PASS
	V	2390.00	73.18	-25.43	47.75	74.00	54.00	PASS
	V	2400.00	73.33	-25.40	47.93	74.00	54.00	PASS
	High Channel 2480MHz							
	H	2483.50	72.60	-25.15	47.45	74.00	54.00	PASS
	H	2500.00	68.17	-25.10	43.07	74.00	54.00	PASS
	V	2483.50	71.40	-25.15	46.25	74.00	54.00	PASS
	V	2500.00	67.56	-25.10	42.46	74.00	54.00	PASS
Low Channel 2402MHz								
$\pi/4$ DQPSK	H	2390.00	73.12	-25.43	47.69	74.00	54.00	PASS
	H	2400.00	75.18	-25.40	49.78	74.00	54.00	PASS
	V	2390.00	73.16	-25.43	47.73	74.00	54.00	PASS
	V	2400.00	73.57	-25.40	48.17	74.00	54.00	PASS
	High Channel 2480MHz							
	H	2483.50	71.72	-25.15	46.57	74.00	54.00	PASS
	H	2500.00	68.29	-25.10	43.19	74.00	54.00	PASS
	V	2483.50	72.86	-25.15	47.71	74.00	54.00	PASS
	V	2500.00	68.52	-25.10	43.42	74.00	54.00	PASS
Low Channel 2402MHz								
8DPSK	H	2390.00	72.00	-25.43	46.57	74.00	54.00	PASS
	H	2400.00	73.94	-25.40	48.54	74.00	54.00	PASS
	V	2390.00	71.42	-25.43	45.99	74.00	54.00	PASS
	V	2400.00	72.99	-25.40	47.59	74.00	54.00	PASS
	High Channel 2480MHz							
	H	2483.50	70.20	-25.15	45.05	74.00	54.00	PASS
	H	2500.00	67.19	-25.10	42.09	74.00	54.00	PASS
	V	2483.50	71.72	-25.15	46.57	74.00	54.00	PASS
	V	2500.00	67.76	-25.10	42.66	74.00	54.00	PASS
Remark:								
1. Emission Level = Meter Reading + Factor, Factor = Antenna Factor + Cable Loss – Pre-amplifier. Over-Emission Level - Limit								
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.								
3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB								
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.								

9. Spurious RF Conducted Emissions

9.1 Block Diagram Of Test Setup



9.2 Limit

Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

9.3 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;

2. Set the spectrum analyzer:

Below 30MHz:

RBW = 100kHz, VBW = 300kHz, Sweep = auto


Detector function = peak, Trace = max hold


Above 30MHz:


RBW = 100KHz, VBW = 300KHz, Sweep = auto


Detector function = peak, Trace = max hold


9.4 Test Result


















































10. 20 dB Bandwidth

10.1 Block Diagram Of Test Setup



10.2 Limit

N/A

10.3 Test procedure

1. Set RBW = 30kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.

7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

10.4 Test Result

Condition	Mode	Frequency (MHz)	-20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH5	2402	0.946	Pass
NVNT	1-DH5	2441	0.955	Pass
NVNT	1-DH5	2480	0.951	Pass
NVNT	2-DH5	2402	1.509	Pass
NVNT	2-DH5	2441	1.513	Pass
NVNT	2-DH5	2480	1.512	Pass
NVNT	3-DH5	2402	1.47	Pass
NVNT	3-DH5	2441	1.571	Pass
NVNT	3-DH5	2480	1.492	Pass

