

深圳市亿圣邦科技有限公司

样品承认书

SPECIFICATION FOR APPROVAL

公 司 名 称 (客户填写): 深圳市茂现智能科技有限公司

物 料 代 码 (客户填写): _____

规 格 型 号 (客户填写): JB03

承 认 日 期 (客户填写): _____

供 应 商 名 称 (SLK 填写): 深圳市亿圣邦科技有限公司

供 应 商 名 称 (SLK 填写): WIFI :SLK-MX-4318-R-120IV-B

Bluetooth:SLK-MX-4318-R-75IV-G

承 认 签 章

供 应 商 承 认			深圳市茂现科技有限公司		
工 程 师	审 核	批 准	工 程 师	审 核	批 准
曾立文	黄 震	林美财			
盖章签署			盖章签署		
日 期 2021-9-22			日 期		
批示: ☐ 接受 ☐ 有条件接受					
备注 (客户填写):					

供应商名称: 深圳市亿圣邦科技有限公司

供应商地址: 东莞市塘厦镇蛟乙塘银园街 13 号 2 楼

电 话: 0769-82553115

传 真: 0769-82553116


WIFI/Bluetooth Antenna (4318)

1. Explanation of Product number :

S L K - M X - 4 3 1 8 - R - 1 2 0 I V - B

S L K - M X - 4 3 1 8 - R - 7 5 I V - G

1 2 3 4 5



Product Code:

(1) Customer:

MX:茂现

(2) Project:

4318: SLK-MX-4318(WIFI/Bluetooth antenna 2.4~2.5GHz 5~5.85GHz)

(3) Welding Position

R:Right R:Right

(4) Cable Length:

120IV:120*0.81MM 75IV:75*0.81MM

(5)Cable Color

B: Black G: Grey

2. Features

- *Stable and reliable in performances
- *Compact size
- *RoHS compliance

3. Applications

- * IEEE802.11 (b/g/n/a)
- * Hand-held devices when WIFI (802.11b/g/n/a) functions are needed

4. Description

Holy bond's External antenna series are specially designed for WIFI (802.11 b/g/n/a) applications. Based on Holy bond's proprietary design and processes, this External antenna has excellent stability and sensitivity to consistently

provide high signal reception efficiency.


5. Electrical Specifications

5-1

Characteristics	Specifications	Unit
Outline Dimensions	43.2*18.51*0.12	mm
Bandwidth(under-10dB return loss)	130min	MHz
VSWR	3max	

5-2


Main - VSWR



Main - S11



Aux - VSWR



Aux - S11







5-3.WIFI/BT Antenna Gain/Efficiency/Radiation Pattern of 3D

WIFI


Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)
2400	38.82	-4.11	2.13
2410	39.06	-4.08	2.11
2420	40.64	-3.91	2.19
2430	44.99	-3.47	2.56
2440	44.28	-3.54	2.44
2450	48.16	-3.17	2.74
2460	45.14	-3.45	2.51
2470	41.25	-3.85	2.05
2480	44.6	-3.51	2.38
2490	37.72	-4.23	1.72
2500	42.9	-3.68	2.31
5150	58.29	-2.34	3.99
5350	54.26	-2.65	4.35
5550	53.06	-2.75	3.85
5650	58.67	-2.32	4.43
5850	53.63	-2.71	4.12

BT


Freq (MHz)	Effi (%)	Effi (dB)	Gain (dBi)
2400	40.36	-3.94	2.29
2410	36.1	-4.42	1.99
2420	37.02	-4.32	2.2
2430	41.4	-3.83	2.96
2440	39.08	-4.08	2.77
2450	44.22	-3.54	3.3
2460	34.93	-4.57	2.26
2470	42.22	-3.74	2.89
2480	39.91	-3.99	2.39
2490	47.28	-3.25	2.94
2500	38.08	-4.19	1.74
5150	48.15	-3.17	2.64
5350	48.24	-3.17	2.6
5500	52.62	-2.79	2.91
5650	51.52	-2.88	2.75
5850	54.17	-2.66	3.74



6. Antenna Dimensions (unit: mm)



7. Antenna Picture



Bluetooth

WIFI