产品规格书



规格编号	20240605
生效日期	2024/6/5

客户名称	深圳市亿贝电子技有限公司
产品类型	Bare copper coil
辉愽雅料号	TD-HBY20240605001-43.5 Double slot L=40MM
客户料号	

【 ★新版发行,□ 版本修订】 【 本规范含目录共 3页 】 【 RoHS Compliant Parts 】

编制	审核	批准
肖树芳	彭勇	朱辉

安福县辉博雅电子有限公司

本承认书在客户收到**30**天内,请务必签章返回,逾期视为生产时按此承认书的标准执行。

【客户核准】 日期:

承认状态: □完全承认 □条件承认 □拒绝承认

审核	复检	检查

说明:


产品规格书

客户名称 深圳市亿		深圳市亿	贝电子科技有限公司 客户料号			
辉愽羽	推料号	TD-HBY20240605001-43.5开双槽L=40MM		规格编号	20240605001	
发行/ 修订记录						
版本 生效日期		3	逐更内容/ 原因		核准	
01		024/6/5		新规格发行		
	编制 审核 批准		比准			
	肖树	芳	彭勇		Ä	卡辉

产品规格书

客户名称	深圳市亿贝电子科技有限公司	客户料号			
辉博雅料号	TD-HBY20240605001-43.5开双槽L=40MM	规格编号	20240605001	版本	01

◆、外形尺寸



(单位: mm)				
Α	43.5±0.5			
В	39±1			
С	20.5±0.5			
D	5.3			
E	12ref			
F	3±1			
G	1.7 Max			
Н	40±2			
ı	0.6±0.1(Diskette thickness)			

- (1) Wire diameter: 0.08*24P bare copper wire
- (2) Winding number :10TS
- (3) Whether the starting and ending lines
- cross: Yes
- (4) Coil package 8mm wide hightemperature tape
- (5) The coil and magnetic disc need to be pasted in the center
- (6) The back of the magnetic disc 42 with white round back glue

◆、电气特性Electrical specification:

	•			
parameter	specificati	on	test condition	test instrument
L0	6.5 ±10%	μH	100KHz/1V	■TH1816B
Q	>40	min	100KHz/1V	■TH1816B
DCR	<50	mΩ	@ 25 ℃	■CH-502BC

◆、温度等级Temperature grade:

Operating temperature :-40 ℃~ 125 ℃

天线增益Antenna gain:

Operation frequency:	113kHz-205kHz	
Antenna Type:	Loop coil Antenna	
Antenna gain:	OdBi	

编制	审核	批准
肖树芳	彭勇	朱辉