


TEST REPORT

Applicant: Shenzhen ELECQ Technology Co. Ltd
Address: 7th Floor, Building 9, Changyuan Xincai, Gaoxin Middle 1st Road, Nanshan, Shenzhen, Guangdong, China
Equipment Type: Elecq Home UL50 J1772
Model Name: AU105 (refer to section 2.3)
Brand Name: ELECQ
FCC ID: 2BKKM-EHAU101
Test Standard: 47 CFR Part 2.1093
KDB 447498 D01 v06
Sample Arrival Date: Sep. 15, 2024
Test Date: Sep. 19, 2024 - Oct. 18, 2024
Date of Issue: Oct. 29, 2024

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Xiong Lining**Checked by:** Xu Rui**Approved by:** Tolan Tu

(Testing Director)



Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Oct. 29, 2024</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information	4
2.3	General Description for Equipment under Test (EUT)	4
2.4	Technical Information	5
3	SUMMARY OF TEST RESULT	6
3.1	Test Standards	6
4	DEVICE CATEGORY AND LEVELS LIMITS	7
5	ASSESSMENT RESULT	9
5.1	Output Power	9
5.2	Tune-up power	9
5.3	RF Exposure Evaluation Result	10
5.4	Collocated Power Calculation	11
5.5	Conclusion	11

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China <input checked="" type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen ELECQ Technology Co. Ltd
Address	7th Floor, Building 9, Changyuan Xincai, Gaoxin Middle 1st Road, Nanshan, Shenzhen, Guangdong, China

2.2 Manufacturer Information

Manufacturer	Shenzhen ELECQ Technology Co. Ltd
Address	7th Floor, Building 9, Changyuan Xincai, Gaoxin Middle 1st Road, Nanshan, Shenzhen, Guangdong, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Elecq Home UL50 J1772					
Model Name Under Test	AU105					
Series Model Name	AU101, AU102, AU106					
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ as below:					
Product Name	Model	Max Current	Max Power	Plug	Output Charging Cable	
Elecq Home UL40 NEMA14-50 J1772	AU101	40A	9.6kW	NEMA14-50 plug	Type1	7.5m
Elecq Home UL40 NEMA14-50 NACS	AU102				NACS	7.5m
Elecq Home UL50 J1772	AU105	50A	12kW	Not support	Type1	7.5m
Elecq Home UL50 NACS	AU106				NACS	7.5m
(this information provided by the applicant)						
Hardware Version	N/A					
Software Version	N/A					
Dimensions (Approx.)	N/A					
Weight (Approx.)	N/A					

2.4 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE) WIFI 802.11a, 802.11b, 802.11g, 802.11n, 802.11ac and 802.11ax Wi-SUN, NFC
-----------------------------------	---

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	Bluetooth, WIFI, Wi-SUN, NFC	
Frequency Range	802.11b/g	2412 ~ 2462 MHz
	802.11n(HT20/HT40)	2412 ~ 2462 MHz
	802.11ax(HE20)	2412 ~ 2462 MHz
	802.11a	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	802.11n(HT20/HT40)	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	802.11 ac(VHT20/VHT40/VHT80)	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	802.11 ax(HE20/HE40/HE80)	5150 ~ 5250 MHz
		5250 ~ 5350 MHz
		5470 ~ 5725 MHz
		5725 ~ 5850 MHz
	Bluetooth	2400 ~ 2462 MHz
	Wi-SUN	915 MHz
	NFC	13.56 MHz
Antenna Type	WIFI	Shrapnel Antenna
	Bluetooth	Shrapnel Antenna
	Wi-SUN	Shrapnel Antenna
	NFC	Coil Antenna
Exposure Category	General Population/Uncontrolled Exposure	
Product Type	Mobile Device	

3 SUMMARY OF TEST RESULT

3.1 Test Standards

No.	Identity	Document Title
1	KDB 447498 D01 v06	KDB 447498 General RF Exposure Guidance D01 v06

3.2 Limit Standards

No.	Identity	Document Title
1	47 CFR Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices

4 DEVICE CATEGORY AND LEVELS LIMITS

Portable Derives:

CFR Title 47 §2.1093(b)

(b) For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

FCC KDB 447498 D01 General RF Exposure Guidance v06 Limit

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

Where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

b) For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following (also illustrated in Appendix B):

- 1) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance – 50 mm)·(f(MHz)/150)]} mW, for 100 MHz to 1500 MHz
- 2) {[Power allowed at numeric threshold for 50 mm in step a)] + [(test separation distance – 50 mm)·10]} mW, for > 1500 MHz and ≤ 6 GHz

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f(\text{MHz}))]$
- 2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz.

When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any SAR test results below 100 MHz to be acceptable.

Appendix C

SAR Test Exclusion Thresholds for < 100 MHz and < 200 mm

Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	< 50	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	237	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	mW
50	308	617	625	634	643	651	660	669	677	686	695	703	712	721	729	738	
10	474	948	961	975	988	1001	1015	1028	1041	1055	1068	1081	1095	1108	1121	1135	
1	711	1422	1442	1462	1482	1502	1522	1542	1562	1582	1602	1622	1642	1662	1682	1702	
0.1	948	1896	1923	1949	1976	2003	2029	2056	2083	2109	2136	2163	2189	2216	2243	2269	
0.05	1019	2039	2067	2096	2125	2153	2182	2211	2239	2268	2297	2325	2354	2383	2411	2440	
0.01	1185	2370	2403	2437	2470	2503	2537	2570	2603	2637	2670	2703	2737	2770	2803	2837	

5 ASSESSMENT RESULT

5.1 Output Power

Mode	NFC
Field Strength (dBuV/m)	64.46
Conducted Power (dBm)	-22.65
Antenna Gain (dBi)	0
ERP (dBm)	-24.80

Note 1: This table listed the worst case power value, please refer to BL-SZ2481098-402 report for more details.

Note 2: Add the appropriate maximum ground reflection factor to the EIRP level (6dB for frequencies≤30MHz, 4.7dB for frequencies between 30MHz and 1000MHz, inclusive and 0dB for frequencies > 1000 MHz).

Note 3: Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

E=EIRP-20logD+104.8+maximum ground reflection factor

where:

E=electric field strength in dBuV/m

EIRP =equivalent isotropic radiated power dBm

D=specified measurement distance in meters

Note 4: When frequencies≤1000MHz, radiated power is ERP.

Mode	Bluetooth	2.4G WIFI	5.2G WIFI	5.3G WIFI	5.6G WIFI	5.8G WIFI	Wi-SUN
Conducted Power (dBm)	11.27	16.09	14.87	15.07	14.99	14.92	18.25
Antenna Gain (dBi)	4.50	4.50	6.05	6.74	6.89	5.59	0
EIRP/ERP (dBm)	15.77	20.59	20.92	21.81	21.88	20.51	18.25

Note: This report listed the worst case conducted power value, please refer to BL-SZ2481098-601, BL-SZ2481098-602, BL-SZ2481098, BL-SZ2481098-604, BL-SZ2481098-606 report for more details.

5.2 Tune-up power

Mode	Conducted Power Range (dBm)	ERP/EIRP Range (dBm)
NFC	[-24.50, -22.50]	[-26.65, -24.65]
Bluetooth	[9.50, 11.50]	[14.00, 16.00]
2.4G WIFI	[14.50, 16.50]	[19.00, 21.00]
5.2G WIFI	[13.00, 15.00]	[19.05, 21.05]
5.3G WIFI	[13.50, 15.50]	[20.24, 22.24]
5.6G WIFI	[13.00, 15.00]	[19.89, 21.89]
5.8G WIFI	[13.00, 15.00]	[18.59, 20.59]
Wi-SUN	[16.50, 18.50]	[14.35, 16.35]

Note: According KDB 447498 D01, used the greater of maximum conducted power or radiated power to compare with the threshold value Pth.

5.3 RF Exposure Evaluation Result

Mode	Maximum power (dBm)	Distance (mm)	Calculation Frequency (MHz)	Max Power (mW)	Threshold Value (mW)	Power / Limit	Verdict
NFC	-22.50	200	13.56	0.006	738.00	0.001	Pass

Note: According to the table in Appendix C of KDB 447498 D01v06, the higher the frequency, the lower the threshold power when the interval distance is less than or equal to 50mm. The frequency of this product is 13.56MHz. We use the more conservative 50MHz power threshold to evaluate the test exemption of this product.

Mode	Maximum power (dBm)	Maximum power (mw)	Distance (mm)	Threshold Power (mW)	Power / Limit	Verdict
Bluetooth	13.85	24.27	200	1496.00	0.016	Pass
2.4G WIFI	18.85	76.74	200	1496.00	0.051	Pass
5.2G WIFI	18.90	77.62	200	1466.00	0.053	Pass
5.3G WIFI	20.09	102.09	200	1465.00	0.070	Pass
5.6G WIFI	19.74	94.19	200	1465.00	0.064	Pass
5.8G WIFI	18.44	69.82	200	1462.00	0.048	Pass
Wi-SUN	18.50	70.79	200	998.00	0.071	Pass

5.4 Collocated Power Calculation

Evolution Mode	Frequency (GHz)	Power /Limit	$\Sigma(\text{Power / Limit})$ of Wi-SUN + 2.4G WIFI + NFC	Verdict
Wi-SUN	0.915	0.071	0.123	Pass
2.4G WIFI	2.412	0.051		
NFC	0.01356	0.001		
Evolution Mode	Frequency (GHz)	Power /Limit	$\Sigma(\text{Power / Limit})$ of Wi-SUN + 5G WIFI + NFC	Verdict
Wi-SUN	0.915	0.071	0.142	Pass
5G WIFI	5.25	0.070		
NFC	0.01356	0.001		
Evolution Mode	Frequency (GHz)	Power /Limit	$\Sigma(\text{Power / Limit})$ of Wi-SUN + Bluetooth + NFC	Verdict
Wi-SUN	0.915	0.071	0.088	Pass
Bluetooth	2.4	0.016		
NFC	0.01356	0.001		

Note:

1. $\Sigma(\text{Power / Limit})$: This is a summation of [(power for each transmitter/ antenna included in the simultaneous transmission)/ (corresponding Power limit)], for Wi-SUN + 5G WIFI + NFC.
2. Both of the 0.915GHz/5.25GHz/0.01356GHz can transmit simultaneously, the formula of calculated the Power is

$$CP1 / LP1 + CP2 / LP2 + \dots \text{etc.} < 1$$

CP = Calculation power
LP = Limit of power
3. The worst-case situation is 0.142, which is less than "1". This confirmed that the device comply with FCC KDB 447498 D01 Power limit.
4. The DUT work frequency range used is 915 MHz, 13.56 MHz and 5250 MHz ~ 5350 MHz the result close to the limit by the above formula, so we select worst case power to calculate the exclusion power threshold.

5.5 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--