



TEST Report

Applicant: Shenzhen Xiaoyuge Industry Co. , Ltd.

Address of Applicant: 5F, Building B, Jinli Industrial Park, No. 34, Xinhe Road, Mugu Community, Pinghu Street, Longgang, Shenzhen, Guangdong, China

Manufacturer : Shenzhen Xiaoyuge Industry Co. , Ltd.

Address of Manufacturer : 5F, Building B, Jinli Industrial Park, No. 34, Xinhe Road, Mugu Community, Pinghu Street, Longgang, Shenzhen, Guangdong, China

Equipment Under Test (EUT)

Product Name: Network converter

Model No.: ZMT01

Series model: ZX01, ZX02, ZX03, ZX04, ZX05, ZX06, ZX07, ZX08, ZX09, Q1, Q2, Q3, Q4, Q5, Q6, Q7, Q8, Q9, ZMT02, ZMT03, ZMT04, ZMT05, ZMT06, ZMT07, ZMT08, ZMT09, ZMT11, ZMT12, ZMT13, ZMT14, ZMT15, ZMT16, ZMT17, ZMT18, ZMT19, ZMT20, ZMT21, ZMT22, ZMT23, ZMT24, ZMT25, ZMT26, ZMT27, ZMT28, ZMT29, ZMT30, ZMT31, ZMT32, ZMT33, ZMT34, ZMT35, ZMT36, ZMT37, ZMT38, ZMT39

Trade Mark: N/A

FCC ID: 2BKLI-ZMT01

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: Aug. 02, 2024

Date of Test: Aug. 02, 2024 ~ Aug. 09, 2024

Date of report issued: Aug. 09, 2024

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.



1. Version

Version No.	Date	Description
00	Aug. 09, 2024	Original

Tested/ Prepared By

Heber He

Date:

Aug. 09, 2024

Project Engineer

Check By:

Bruce Zhu

Date:

Aug. 09, 2024

Reviewer

Approved By :

Kevin Yang

Date:

Aug. 09, 2024

Authorized Signature



2. Contents

Page

1. VERSION.....	2
2. CONTENTS	3
3. TEST SUMMARY	4
4. GENERAL INFORMATION.....	5
4.1. GENERAL DESCRIPTION OF EUT	5
4.2. TEST MODE	7
4.3. DESCRIPTION OF SUPPORT UNITS	7
4.4. DEVIATION FROM STANDARDS	7
4.5. ABNORMALITIES FROM STANDARD CONDITIONS.....	7
4.6. TEST FACILITY	7
4.7. TEST LOCATION	7
4.8. ADDITIONAL INSTRUCTIONS	7
5. TEST INSTRUMENTS LIST.....	7
6. TEST RESULTS AND MEASUREMENT DATA	9
6.1. CONDUCTED EMISSIONS	9
6.2. CONDUCTED PEAK OUTPUT POWER	12
6.3. CHANNEL BANDWIDTH.....	15
6.4. POWER SPECTRAL DENSITY	21
6.5. BAND EDGE.....	28
6.5.1. <i>Conducted Emission Method</i>	28
6.5.2. <i>Radiated Emission Method</i>	33
6.6. SPURIOUS EMISSION.....	35
6.6.1. <i>Conducted Emission Method</i>	35
6.6.2. <i>Radiated Emission Method</i>	43
6.7. ANTENNA REQUIREMENT.....	50
7. TEST SETUP PHOTO.....	51
8. EUT CONSTRUCTIONAL DETAILS	51



3. Test Summary

Test Item	Section	Result
Antenna requirement	FCC part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	FCC part 15.207	Pass
Conducted Peak Output Power	FCC part 15.247 (b)(3)	Pass
6dB Bandwidth	FCC part 15.247 (a)(2)	Pass
Power Spectral Density	FCC part 15.247 (e)	Pass
Band Edge	FCC part 15.247(d)	Pass
Spurious Emission	FCC part 15.205/15.209	Pass

Remark: Test according to ANSI C63.10:2013 and RSS-Gen

Pass: The EUT complies with the essential requirements in the standard.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.37 dB	(1)
Radiated Emission	1~18GHz	5.40 dB	(1)
Radiated Emission	18-40GHz	5.45 dB	(1)
Conducted Disturbance	0.15~30MHz	2.68 dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.



Report No.: HTT202408074F01

4. General Information

4.1. General Description of EUT

Product Name:	Network converter
Model No.:	ZMT01
Series model:	ZX01, ZX02, ZX03, ZX04, ZX05, ZX06, ZX07, ZX08, ZX09, Q1, Q2, Q3, Q4, Q5, Q6, Q7, Q8, Q9, ZMT02, ZMT03, ZMT04, ZMT05, ZMT06, ZMT07, ZMT08, ZMT09, ZMT11, ZMT12, ZMT13, ZMT14, ZMT15, ZMT16, ZMT17, ZMT18, ZMT19, ZMT20, ZMT21, ZMT22, ZMT23, ZMT24, ZMT25, ZMT26, ZMT27, ZMT28, ZMT29, ZMT30, ZMT31, ZMT32, ZMT33, ZMT34, ZMT35, ZMT36, ZMT37, ZMT38, ZMT39
Test sample(s) ID:	HTT202408074-1(Engineer sample) HTT202408074-2(Normal sample)
Channel numbers:	802.11b/802.11g /802.11n(HT20): 11 802.11n(HT40):7
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(H20)/802.11n(HT40): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	FPC Antenna
Antenna gain:	0.00 dBi for ANT 1 and ANT 2
Power supply:	DC 5V From External Circuit



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz



Report No.: HTT202408074F01

4.2. Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13Mbps

4.3. Description of Support Units

None.

4.4. Deviation from Standards

None.

4.5. Abnormalities from Standard Conditions

None.

4.6. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 779513 Designation Number: CN1319

Shenzhen HTT Technology Co.,Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6435.01

Shenzhen HTT Technology Co.,Ltd. has been accredited by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

4.7. Test Location

All tests were performed at:

Shenzhen HTT Technology Co.,Ltd.

1F, Building B, Huafeng International Robotics Industrial Park, Hangcheng Road,Nanchang Community, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China

Tel: 0755-23595200

Fax: 0755-23595201

4.8. Additional Instructions

Test Software	Special AT test command provided by manufacturer to Keep the EUT in continuously transmitting mode and hopping mode
Power level setup	Default

5. Test Instruments list

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
------	----------------	--------------	-----------	---------------	---------------------	-------------------------



Report No.: HTT202408074F01

1	3m Semi- Anechoic Chamber	Shenzhen C.R.T technology co., LTD	9*6*6	HTT-E028	Aug. 10 2021	Aug. 09 2024
2	Control Room	Shenzhen C.R.T technology co., LTD	4.8*3.5*3.0	HTT-E030	Aug. 10 2021	Aug. 09 2024
3	EMI Test Receiver	Rohde&Schwar	ESCI7	HTT-E022	Apr. 26 2024	Apr. 25 2025
4	Spectrum Analyzer	Rohde&Schwar	FSP	HTT-E037	Apr. 26 2024	Apr. 25 2025
5	Coaxial Cable	ZDecl	ZT26-NJ-NJ-0.6M	HTT-E018	Apr. 26 2024	Apr. 25 2025
6	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-2M	HTT-E019	Apr. 26 2024	Apr. 25 2025
7	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-0.6M	HTT-E020	Apr. 26 2024	Apr. 25 2025
8	Coaxial Cable	ZDecl	ZT26-NJ-SMAJ-8.5M	HTT-E021	Apr. 26 2024	Apr. 25 2025
9	Composite logarithmic antenna	Schwarzbeck	VULB 9168	HTT-E017	May. 21 2024	May. 20 2025
10	Horn Antenna	Schwarzbeck	BBHA9120D	HTT-E016	May. 20 2024	May. 19 2025
11	Loop Antenna	Zhinan	ZN30900C	HTT-E039	Apr. 26 2024	Apr. 25 2025
12	Horn Antenna	Beijing Hangwei Dayang	OBH100400	HTT-E040	Apr. 26 2024	Apr. 25 2025
13	low frequency Amplifier	Sonoma Instrument	310	HTT-E015	Apr. 26 2024	Apr. 25 2025
14	high-frequency Amplifier	HP	8449B	HTT-E014	Apr. 26 2024	Apr. 25 2025
15	Variable frequency power supply	Shenzhen Anbiao Instrument Co., Ltd	ANB-10VA	HTT-082	Apr. 26 2024	Apr. 25 2025
16	EMI Test Receiver	Rohde & Schwarz	ESCS30	HTT-E004	Apr. 26 2024	Apr. 25 2025
17	Artificial Mains	Rohde & Schwarz	ESH3-Z5	HTT-E006	May. 23 2024	May. 22 2025
18	Artificial Mains	Rohde & Schwarz	ENV-216	HTT-E038	May. 23 2024	May. 22 2025
19	Cable Line	Robinson	Z302S-NJ-BNCJ-1.5M	HTT-E001	Apr. 26 2024	Apr. 25 2025
20	Attenuator	Robinson	6810.17A	HTT-E007	Apr. 26 2024	Apr. 25 2025
21	Variable frequency power supply	Shenzhen Yanghong Electric Co., Ltd	YF-650 (5KVA)	HTT-E032	Apr. 26 2024	Apr. 25 2025
22	Control Room	Shenzhen C.R.T technology co., LTD	8*4*3.5	HTT-E029	Aug. 10 2021	Aug. 09 2024
23	DC power supply	Agilent	E3632A	HTT-E023	Apr. 26 2024	Apr. 25 2025
24	EMI Test Receiver	Agilent	N9020A	HTT-E024	Apr. 26 2024	Apr. 25 2025
25	Analog signal generator	Agilent	N5181A	HTT-E025	Apr. 26 2024	Apr. 25 2025
26	Vector signal generator	Agilent	N5182A	HTT-E026	Apr. 26 2024	Apr. 25 2025
27	Power sensor	Keysight	U2021XA	HTT-E027	Apr. 26 2024	Apr. 25 2025
28	Temperature and humidity meter	Shenzhen Anbiao Instrument Co., Ltd	TH10R	HTT-074	Apr. 28 2024	Apr. 27 2025
29	Radiated Emission Test Software	Farad	EZ-EMC	N/A	N/A	N/A
30	Conducted Emission Test Software	Farad	EZ-EMC	N/A	N/A	N/A
31	RF Test Software	panshanrf	TST	N/A	N/A	N/A

6. Test results and Measurement Data

6.1. Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane LISN AUX Equipment E.U.T 40cm 80cm LISN Filter EMI Receiver AC power Test table/Insulation plane Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	PASS					

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.


Measurement data:

Line:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
				dB	dBuV	dBuV	dB	
1		0.1905	35.23	10.20	45.43	64.01	-18.58	QP
2		0.1905	17.27	10.20	27.47	54.01	-26.54	AVG
3		0.2993	28.33	10.24	38.57	60.26	-21.69	QP
4		0.2993	9.87	10.24	20.11	50.26	-30.15	AVG
5		0.6313	20.91	10.32	31.23	56.00	-24.77	QP
6		0.6313	9.39	10.32	19.71	46.00	-26.29	AVG
7		2.5530	19.47	10.46	29.93	56.00	-26.07	QP
8		2.5530	9.82	10.46	20.28	46.00	-25.72	AVG
9		5.7750	16.27	10.61	26.88	60.00	-33.12	QP
10		5.7750	8.12	10.61	18.73	50.00	-31.27	AVG
11	*	19.2210	35.01	11.24	46.25	60.00	-13.75	QP
12		19.2210	24.91	11.24	36.15	50.00	-13.85	AVG

Neutral:



No.	Mk.	Freq. MHz	Reading Level dB	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1828	30.95	10.19	41.14	64.36	-23.22	QP
2		0.1828	20.82	10.19	31.01	54.36	-23.35	AVG
3		0.3345	19.08	10.24	29.32	59.34	-30.02	QP
4		0.3345	7.79	10.24	18.03	49.34	-31.31	AVG
5		0.6360	16.19	10.35	26.54	56.00	-29.46	QP
6		0.6360	6.60	10.35	16.95	46.00	-29.05	AVG
7		2.5304	18.96	10.43	29.39	56.00	-26.61	QP
8		2.5304	9.88	10.43	20.31	46.00	-25.69	AVG
9		5.7073	15.38	10.60	25.98	60.00	-34.02	QP
10		5.7073	7.95	10.60	18.55	50.00	-31.45	AVG
11		19.1490	32.10	11.27	43.37	60.00	-16.63	QP
12	*	19.1490	25.80	11.27	37.07	50.00	-12.93	AVG


Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Los



Report No.: HTT202408074F01

6.2. Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)				
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02				
Limit:	30dBm				
Test setup:	Power sensor and Spectrum analyzer  Non-Conducted Table Ground Reference Plane				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.: 1012mbar

Measurement Data

ANT 1

Type	Channel	Output power PK (dBm)	Limit (dBm)	Result
802.11b	01	2.27	30.00	Pass
	06	1.52		
	11	1.58		
802.11g	01	5.47	30.00	Pass
	06	5.89		
	11	6.19		
802.11n(HT20)	01	6.05	30.00	Pass
	06	5.46		
	11	5.44		
802.11n(HT40)	03	3.98	30.00	Pass
	06	3.98		
	09	3.69		



Report No.: HTT202408074F01

ANT 2

Type	Channel	Output power PK (dBm)	Limit (dBm)	Result
802.11b	01	2.47	30.00	Pass
	06	1.45		
	11	1.78		
802.11g	01	6.45	30.00	Pass
	06	6.14		
	11	5.96		
802.11n(HT20)	01	6.11	30.00	Pass
	06	5.81		
	11	5.97		
802.11n(HT40)	03	3.09	30.00	Pass
	06	3.02		
	09	3.74		

Note:

- 1) Measured output power at difference data rate for each mode and recorded worst case for each mode.
- 2) Test results including cable loss.
- 3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13Mbps at IEEE 802.11n HT40;




Report No.: HTT202408074F01

For MIMO:

Type	Channel	Output power PK(dBm) ANT1	Output power PK(dBm) ANT2	Output power PK(dBm) MIMO	Limit (dBm)	Result
802.11n(HT20)	01	6.05	6.11	9.09	30.0	Pass
	06	5.46	5.81	8.65		
	11	5.44	5.97	8.72		
802.11n(HT40)	03	3.98	3.09	6.57	30.0	Pass
	06	3.98	3.02	6.54		
	09	3.69	3.74	6.73		

6.3. Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	>500KHz					
Test setup:						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar

Measurement Data

ANT 1

Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	01	10.060	≥500	Pass
	06	11.109		
	11	11.094		
802.11g	01	15.402	≥500	Pass
	06	17.100		
	11	17.084		
802.11n(HT20)	01	18.196	≥500	Pass
	06	18.269		
	11	18.145		
802.11n(HT40)	03	35.167	≥500	Pass
	06	35.181		
	09	35.138		



Report No.: HTT202408074F01

ANT 2

Type	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11b	01	10.586	≥500	Pass
	06	11.573		
	11	11.114		
802.11g	01	15.241	≥500	Pass
	06	17.109		
	11	16.679		
802.11n(HT20)	01	16.718	≥500	Pass
	06	18.232		
	11	18.228		
802.11n(HT40)	03	35.147	≥500	Pass
	06	35.175		
	09	35.065		





Report No.: HTT202408074F01



Test plot as follows:

ANT 1



802.11b	802.11g
---------	---------



Lowest channel



Middle channel





Highest channel





Report No.: HTT202408074F01



802.11n(HT20)	802.11n(HT40)
---------------	---------------



Lowest channel



Middle channel





Highest channel





Report No.: HTT202408074F01

ANT 2



802.11b	802.11g
---------	---------



Lowest channel



Middle channel





Highest channel





Report No.: HTT202408074F01

802.11n(HT20)



802.11n(HT40)



Lowest channel




Middle channel



Highest channel

6.4. Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	8dBm/3kHz					
Test setup:						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar

Measurement Data

ANT 1

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-25.17	8.00	Pass
	06	-25.47		
	11	-25.37		
802.11g	01	-26.86	8.00	Pass
	06	-27.87		
	11	-28.09		
802.11n(HT20)	01	-27.64	8.00	Pass
	06	-27.25		
	11	-29.37		
802.11n(HT40)	03	-32.35	8.00	Pass
	06	-33.24		
	09	-31.05		



ANT 2

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-24.76	8.00	Pass
	06	-26.76		
	11	-25.32		
802.11g	01	-25.74	8.00	Pass
	06	-27.40		
	11	-27.87		
802.11n(HT20)	01	-26.62	8.00	Pass
	06	-27.86		
	11	-26.96		
802.11n(HT40)	03	-31.27	8.00	Pass
	06	-32.24		
	09	-32.42		

Note:

- 1) Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
- 2) Test results including cable loss;
- 3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20;13Mbps at IEEE 802.11n HT40



Report No.: HTT202408074F01

For MIMO:



Type	Channel	Power Spectral Density (dBm/3KHz) ANT1	Power Spectral Density (dBm/3KHz) ANT2	Power Spectral Density (dBm/3KHz) MIMO	Limit (dBm)	Result
802.11n(HT20)	01	-27.64	-26.62	-24.09	8.00	Pass
	06	-27.25	-27.86	-24.53		
	11	-29.37	-26.96	-24.99		
802.11n(HT40)	03	-32.35	-31.27	-28.77	8.00	Pass
	06	-33.24	-32.24	-29.70		
	09	-31.05	-32.42	-28.67		





Report No.: HTT202408074F01

Test plot as follows:
ANT 1



802.11b		802.11g	
---------	--	---------	--



Lowest channel



Middle channel





Highest channel





Report No.: HTT202408074F01



802.11n(HT20)	802.11n(HT40)
---------------	---------------



Lowest channel



Middle channel





Highest channel





Report No.: HTT202408074F01

ANT 2



802.11b		802.11g	
---------	--	---------	--



Lowest channel



Middle channel





Highest channel





Report No.: HTT202408074F01



802.11n(HT20)		802.11n(HT40)	
---------------	--	---------------	--



Lowest channel




Middle channel



Highest channel

6.5. Band Edge

6.5.1. Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test setup:						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar




Report No.: HTT202408074F01


Test plot as follows:

ANT 1

Test mode:	802.11b
------------	---------




Lowest channel




Highest channel

Test mode:	802.11g
------------	---------




Lowest channel




Highest channel



Test mode:	802.11n(HT20)
------------	---------------




Lowest channel




Highest channel

Test mode:	802.11n(HT40)
------------	---------------



Lowest channel





Highest channel



Report No.: HTT202408074F01

ANT 2



Test mode:	802.11b
------------	---------



Lowest channel

Highest channel

Test mode:	802.11g
------------	---------




Lowest channel

Highest channel




Report No.: HTT202408074F01

Test mode:	802.11n(HT20)
------------	---------------




Lowest channel




Highest channel

Test mode:	802.11n(HT40)
------------	---------------




Lowest channel



Highest channel

6.5.2. Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205						
Test Method:	ANSI C63.10: 2013						
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.						
Test site:	Measurement Distance: 3m						
Receiver setup:	Frequency	Detector		RBW	VBW	Remark	
	Above 1GHz	Peak		1MHz	3MHz	Peak Value	
		Peak		1MHz	10Hz	Average Value	
Limit:	Frequency			Limit (dBuV/m @3m)		Remark	
	Above 1GHz			54.00		Average Value	
				74.00		Peak Value	
Test setup:							
Test Procedure:	1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test results:	Pass						
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar	

Measurement Data




Report No.: HTT202408074F01

Remark: During the test, pre-scan the 802.11b/802.11g/802.11n (H20)/802.11n (H40) modulation, and found the 802.11b modulation which it is worse case.

Frequency(MHz):			2412		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	62.43	PK	74	11.57	63.82	27.2	4.31	32.9	-1.39
2390.00	42.85	AV	54	11.15	44.24	27.2	4.31	32.9	-1.39
Frequency(MHz):			2412		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	60.02	PK	74	13.98	61.41	27.2	4.31	32.9	-1.39
2390.00	46.57	AV	54	7.43	47.96	27.2	4.31	32.9	-1.39
Frequency(MHz):			2462		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	55.87	PK	74	18.13	56.80	27.4	4.47	32.8	-0.93
2483.50	43.37	AV	54	10.63	44.30	27.4	4.47	32.8	-0.93
Frequency(MHz):			2462		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	55.36	PK	74	18.64	56.29	27.4	4.47	32.8	-0.93
2483.50	44.19	AV	54	9.81	45.12	27.4	4.47	32.8	-0.93

6.6. Spurious Emission


6.6.1. Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)					
Test Method:	KDB558074 D01 15.247 Meas Guidance v05r02					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test results:	Pass					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar




Measurement Data:
ANT 1


Reference



802.11b



802.11g



802.11n(HT20)