

**CFR 47 FCC PART 15 SUBPART C**

**TEST REPORT**

*For*

**WiFi Digital Picture Frame**

**MODEL NUMBER: TR-D007-01, TR-D007-02, TR-D007-03, TR-D007-04, TR-D010-01, TR-D010-02, TR-D010-03, TR-D010-04, TR-D156-01, TR-D156-02, TR-D156-03, TR-D156-04, TR-DX-A, TR-DX-B, TR-DX-C, TR-DX-D**

**REPORT NUMBER: E04A24080495F00101**

**ISSUE DATE: September 18, 2024**

**FCC ID: 2BKLJ-01**

*Prepared for*

**Shenzhen Jiu'anshun Technology Co., Ltd.**

**Room 1219, Shangyou Mansion, Shangyousong Village, Yousong Community, Longhua Street, Longhua District, Shenzhen City, China**

*Prepared by*

**Guangdong Global Testing Technology Co., Ltd.**

**Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808**

**This report shall not be reproduced, except in full, without the written approval of  
Guangdong Global Testing Technology Co., Ltd.**

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	September 18, 2024	Initial Issue	

### Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.11 & Clause 11.12	FCC Part 15.247 (d) FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

\*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

\*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C> when <Accuracy Method> decision rule is applied.

## CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>5</b>
<b>2. TEST METHODOLOGY.....</b>	<b>7</b>
<b>3. FACILITIES AND ACCREDITATION.....</b>	<b>7</b>
<b>4. CALIBRATION AND UNCERTAINTY .....</b>	<b>8</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION.....</i>	<i>8</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>8</i>
<b>5. EQUIPMENT UNDER TEST .....</b>	<b>9</b>
5.1. <i>DESCRIPTION OF EUT .....</i>	<i>9</i>
5.2. <i>CHANNEL LIST.....</i>	<i>10</i>
5.3. <i>MAXIMUM AVERAGE EIRP .....</i>	<i>10</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>10</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>11</i>
5.6. <i>DESCRIPTION OF AVAILABLE ANTENNAS .....</i>	<i>12</i>
5.7. <i>SUPPORT UNITS FOR SYSTEM TEST.....</i>	<i>12</i>
5.8. <i>SETUP DIAGRAM .....</i>	<i>12</i>
<b>6. MEASURING EQUIPMENT AND SOFTWARE USED.....</b>	<b>13</b>
<b>7. ANTENNA PORT TEST RESULTS .....</b>	<b>14</b>
7.1. <i>Conducted Output Power.....</i>	<i>14</i>
7.2. <i>6dB Bandwidth and 99% Occupied Bandwidth.....</i>	<i>16</i>
7.3. <i>Power Spectral Density.....</i>	<i>18</i>
7.4. <i>Conducted Band edge and spurious emission .....</i>	<i>20</i>
7.5. <i>Duty Cycle .....</i>	<i>22</i>
<b>8. RADIATED TEST RESULTS .....</b>	<b>23</b>
<b>9. ANTENNA REQUIREMENT .....</b>	<b>41</b>
<b>10. AC POWER LINE CONDUCTED EMISSION .....</b>	<b>42</b>
<b>11. TEST DATA.....</b>	<b>45</b>
<b>APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION .....</b>	<b>46</b>
<b>APPENDIX: PHOTOGRAPHS OF THE EUT .....</b>	<b>48</b>

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Shenzhen Jiu'anshun Technology Co., Ltd.  
 Address: Room 1219, Shangyou Mansion, Shangyousong Village, Yousong Community, Longhua Street, Longhua District, Shenzhen City, China

### Manufacturer Information

Company Name: TROCOTN  
 Address: Room 1219, Shangyou Mansion, Shangyousong Village, Yousong Community, Longhua Street, Longhua District, Shenzhen City, China

### Factory Information

Company Name: TROCOTN  
 Address: Room 1219, Shangyou Mansion, Shangyousong Village, Yousong Community, Longhua Street, Longhua District, Shenzhen City, China

### EUT Information

Product Description: WiFi Digital Picture Frame  
 Model: TR-D010-01  
 Series Model: TR-D007-01, TR-D007-02, TR-D007-03, TR-D007-04, TR-D010-02, TR-D010-03, TR-D010-04, TR-D156-01, TR-D156-02, TR-D156-03, TR-D156-04, TR-DX-A, TR-DX-B, TR-DX-C, TR-DX-D  
 Trademark: TROCOTN  
 Sample Received Date: August 19 2024  
 Sample Status: Normal  
 Sample ID: A24080495 001  
 Date of Tested: August 19 2024 to August 28 2024

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	Pass

Prepared By:

Win Huang

Win Huang

Project Engineer

Checked By:

Alan He

Alan He

Laboratory Leader

Approved By:

Shawn Wen

Shawn Wen

Laboratory Manager



## 2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C(DTS)

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p><b>A2LA (Certificate No.: 6947.01)</b> Guangdong Global Testing Technology Co., Ltd. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1343)</b> Guangdong Global Testing Technology Co., Ltd. has been recognized to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification rules</p> <p><b>ISED (Company No.: 30714)</b> Guangdong Global Testing Technology Co., Ltd. has been registered and fully described in a report filed with ISED. The Company Number is 30714 and the test lab Conformity Assessment Body Identifier (CABID) is CN0148.</p>
---------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at  
Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city,  
Guangdong, People's Republic of China, 523808

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Items	k	Uncertainty
DTS Bandwidth	1.96	±9.2 PPM
20dB Emission Bandwidth	1.96	±9.2 PPM
Carrier Frequency Separation	1.96	±9.2 PPM
Time of Occupancy	1.96	±0.57%
Conducted Output Power	1.96	±1.5 dB
Power Spectral Density Level	1.96	±1.9 dB
Conducted Spurious Emission	1.96	9 kHz-30 MHz: ± 0.95 dB 30 MHz-1 GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.8 dB 12.75 GHz-26.5 GHz: ± 2.1dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports (AMN)	150 kHz ~ 30 MHz	2	3.37
Radiated emissions	9 kHz ~ 30 MHz	2	4.16
Radiated emissions	30 MHz ~ 1 GHz	2	3.79
Radiated emissions	1 GHz ~ 18 GHz	2	5.62
Radiated emissions	18 GHz ~ 40 GHz	2	5.54

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

EUT Name	WiFi Digital Picture Frame	
Model	TR-D010-01	
Series Model	TR-D007-01, TR-D007-02, TR-D007-03, TR-D007-04, TR-D010-02, TR-D010-03, TR-D010-04, TR-D156-01, TR-D156-02, TR-D156-03, TR-D156-04, TR-DX-A, TR-DX-B, TR-DX-C, TR-DX-D	
Hardware Version	V1.0	
Software Version	V1.0	
Ratings	Input: AC 100-240V~, 50/60Hz, 0.4A Output: DC 5V, 2A	
Power Supply	AC	AC120V/60Hz

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2412 MHz to 2462 MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20, IEEE 802.11n-HT40
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n: Up to MCS7
Number of Channels:	IEEE 802.11b/g/n-HT20: 11 IEEE 802.11n-HT40: 7
Maximum Peak Power:	IEEE 802.11b: 16.68 dBm IEEE 802.11g: 17.63 dBm IEEE 802.11n-HT20: 14.44 dBm IEEE 802.11n-HT40: 14.28 dBm
Antenna Type:	Internal antenna
Antenna Gain:	5.36dBi
Normal Test Voltage:	5 Vdc
EUT Test software:	WLAN Test Tool

## 5.2. CHANNEL LIST

Channel List for 802.11b/g/n (20 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List for 802.11n (40 MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

## 5.3. MAXIMUM PEAK EIRP

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted Peak Output Power (dBm)
b	2412 ~ 2462	1-11[11]	16.68
g	2412 ~ 2462	1-11[11]	17.63
n HT20	2412 ~ 2462	1-11[11]	14.44
n HT40	2422 ~ 2452	3-9[7]	14.28

## 5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

## 5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band						
Test Software		WLAN Test Tool				
Modulation Mode	Transmit Antenna Number	Test Channel				
		NCB: 20MHz			NCB: 40MHz	
		CH 1	CH 6	CH 11	CH 3	CH 6
802.11b	1	39	39	39		
802.11g	1	39	39	39		
802.11n HT20	1	39	39	39		
802.11n HT40	1				39	39

## WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps

802.11g mode: 6 Mbps

802.11n HT20 mode: MCS0

802.11n HT40 mode: MCS0

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Conducted output power, power spectral density tests separately on each port with all supported SISO & MIMO port combinations.

Conducted bandedge and spurious emissions tests were performed with SISO mode, as this port was found to have the worst case in terms of power settings amongst all supported possible SISO & MIMO port combinations.

Radiated emissions tests were performed with the MIMO modes. These were found to be the worst modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest conducted output power level, it was deemed to be the worst case.

The EUT support Cyclic Shift Diversity(CDD), Space Time Coding(STBC), Spartial Division Multiplexing(SDM) modes. They use the same conducted power per chain in any given mode, so we only chose the worst case mode CDD for final testing.

## 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	Internal antenna	5.36

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	<input checked="" type="checkbox"/> 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.

Note: The value of the antenna gain was declared by customer.


## 5.7. SUPPORT UNITS FOR SYSTEM TEST

The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	SWITCHING ADAPTER	Jiu'anshun	SJ-05020001	N/A	

## 5.8. SETUP DIAGRAM

Radiated emissions:



## 6. MEASURING EQUIPMENT AND SOFTWARE USED

Test Equipment of Conducted RF					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40	102257	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51285127	2023/09/18	2024/09/17
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61253075	2023/09/18	2024/09/17
Vector Signal Generator	Rohde & Schwarz	SMM100A	101899	2023/09/18	2024/09/17
RF Control box	MWRF-test	MW100-RFCB	MW220926GTG	2023/09/18	2024/09/17
Wideband Radio Communication Tester	Rohde & Schwarz	CMW270	102792	2023/09/18	2024/09/17
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	103235	2023/09/18	2024/09/17
temperature humidity chamber	Espec	SH-241	SH-241-2014	2023/09/18	2024/09/17
RF Test Software	MWRF-test	MTS8310E (Ver. V2/0)	N/A	N/A	N/A

Test Equipment of Radiated emissions below 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2146	2022/08/30	2025/08/29
EMI Test Receiver	Rohde & Schwarz	ESCI3	101409	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2023/09/18	2024/09/17
Pre-Amplifier	HzEMC	HPA-9K0130	HYPA21001	2023/09/18	2024/09/17
Biconilog Antenna	Schwarzbeck	VULB 9168	01315	2022/10/10	2025/10/09
Biconilog Antenna	ETS	3142E	00243646	2022/03/23	2025/03/22
Loop Antenna	ETS	6502	243668	2022/03/30	2025/03/29
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE)	N/A	N/A	N/A

Test Equipment of Radiated emissions above 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2149	2022/08/30	2025/08/29
Spectrum Analyzer	Rohde & Schwarz	FSV40	101413	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2023/09/18	2024/09/17
Pre-Amplifier	A-INFO	HPA-1G1850	HYPA21003	2023/09/18	2024/09/17
Horn antenna	A-INFO	3117	246069	2022/03/11	2025/03/10
Pre-Amplifier	ZKJC	HPA-184057	HYPA21004	2023/09/18	2024/09/17
Horn antenna	ZKJC	3116C	246265	2022/03/29	2025/03/28
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE+)	N/A	N/A	N/A

Test Equipment of Conducted emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Shielded Room	CHENG YU	8m*5m*4m	N/A	2022/10/29	2025/10/28
EMI Test Receiver	Rohde & Schwarz	ESR3	102647	2023/09/18	2024/09/17
LISN/AMN	Rohde & Schwarz	ENV216	102843	2023/09/18	2024/09/17
NNLK 8129 RC	Schwarzbeck	NNLK 8129 RC	5046	2023/09/18	2024/09/17
Test Software	Farad	EZ-EMC (Ver. EMC-con-3A1 1+)	N/A	N/A	N/A

## 7. ANTENNA PORT TEST RESULTS

### 7.1. CONDUCTED OUTPUT POWER

#### LIMITS


CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5

#### TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

**TEST SETUP**



**TEST ENVIRONMENT**

Temperature	24°C	Relative Humidity	55%
Atmosphere Pressure	101kPa		

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A

## 7.2. 6DB BANDWIDTH OCCUPIED BANDWIDTH

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	$\geq 500$ kHz	2400-2483.5

### TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	24°C	Relative Humidity	55%
Atmosphere Pressure	101kPa		

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A

### 7.3. POWER SPECTRAL DENSITY

#### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

#### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	PEAK
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### TEST SETUP



#### TEST ENVIRONMENT

Temperature	24°C	Relative Humidity	55%
Atmosphere Pressure	101kPa		

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A

## 7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

### LIMITS

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times$ RBW
measurement points	$\geq$ span/RBW
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

**TEST SETUP**



**TEST ENVIRONMENT**

Temperature	24°C	Relative Humidity	55%
Atmosphere Pressure	101kPa		

**TEST RESULTS**

Please refer to section "Test Data" - Appendix A

## 7.5. DUTY CYCLE


### LIMITS

None; for reporting purposes only.

### TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

### TEST SETUP



### TEST ENVIRONMENT

Temperature	24°C	Relative Humidity	55%
Atmosphere Pressure	101kPa		

### TEST RESULTS

Please refer to section "Test Data" - Appendix A

## 8. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz		
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
		Quasi-Peak
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54
Above 1000	500	Peak
		Average
		74
		54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
<sup>1</sup> 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	( <sup>2</sup> )
13.36-13.41			

Note:1. Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

2. Above 38.6c

### TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.

7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of  $377\Omega$ . For example, the measurement frequency  $X$  KHz resulted in a level of  $Y$  dBuV/m, which is equivalent to  $Y-51.5 = Z$  dBuA/m, which has the same margin,  $W$  dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


## Above 1G

## The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold



1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.


X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

### TEST SETUP






#### TEST ENVIRONMENT

Temperature	24.1 °C	Relative Humidity	53%
Atmosphere Pressure	101kPa		

#### TEST RESULTS

The worst data of the mode (802.11b 2412MHz) are recorded in the following pages.


Mode:	11B-2412
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/22
T/A/P	23.7°C/51%/101Kpa



### Critical\_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	133.790	54.68	-24.01	30.67	43.50	12.83	PK+	V
2	197.810	61.99	-22.23	39.76	43.50	3.74	PK+	V
3	257.950	45.79	-18.68	27.11	46.00	18.89	PK+	V
4	395.690	44.67	-14.14	30.53	46.00	15.47	PK+	V
5	735.190	42.08	-7.05	35.03	46.00	10.97	PK+	V
6	998.060	38.14	-3.69	34.45	53.90	19.45	PK+	V

Mode:	11B-2412
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/22
T/A/P	23.7°C/51%/101Kpa




### Critical\_Freqs

No.	Freq. (MHz)	Reading (dB $\mu$ V)	Corr. (dB)	Meas. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Det.	Pol.
1	197.810	56.56	-22.23	34.33	43.50	9.17	PK+	H
2	315.180	51.40	-18.2	33.20	46.00	12.80	PK+	H
3	367.560	49.59	-15.49	34.10	46.00	11.90	PK+	H
4	682.810	39.29	-7.75	31.54	46.00	14.46	PK+	H
5	735.190	41.50	-7.05	34.45	46.00	11.55	PK+	H
6	787.570	39.94	-6.73	33.21	46.00	12.79	PK+	H

Above 1GHz

The worst result as bellow:


Mode:	11B-2412
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/21
T/A/P	23.7°C/51%/101Kpa



### Critical\_Freqs

No.	Freq. (MHz)	Reading (dB $\mu$ V)	Corr. (dB)	Meas. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Det.	Pol.
1	1980.000	61.43	-9.14	52.29	74.00	21.71	PK+	H
2	2494.000	57.09	-8.42	48.67	74.00	25.33	PK+	H
3	3366.000	56.92	-14.49	42.43	74.00	31.57	PK+	H
4	4824.000	56.03	-11.47	44.56	74.00	29.44	PK+	H
5	7234.500	61.38	-8.13	53.25	74.00	20.75	PK+	H
6	17710.500	46.17	-0.05	46.12	74.00	27.88	PK+	H


Mode:	11B-2412
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/21
T/A/P	23.7°C/51%/101Kpa



### Critical\_Freqs

No.	Freq. (MHz)	Reading (dB $\mu$ V)	Corr. (dB)	Meas. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Det.	Pol.
1	1188.000	68.16	-14.68	53.48	74.00	20.52	PK+	V
2	1980.000	61.81	-9.14	52.67	74.00	21.33	PK+	V
3	4752.000	59.49	-11.44	48.05	74.00	25.95	PK+	V
4	7236.000	61.50	-8.14	53.36	74.00	20.64	PK+	V
5	9648.000	53.55	-6.78	46.77	74.00	27.23	PK+	V
6	16689.000	46.74	-0.49	46.25	74.00	27.75	PK+	V

Mode:	11B-2437
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/21
T/A/P	23.7°C/51%/101Kpa




### Critical\_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	1188.000	67.55	-14.68	52.87	74.00	21.13	PK+	V
2	1982.000	61.64	-9.13	52.51	74.00	21.49	PK+	V
3	4356.000	57.52	-12.19	45.33	74.00	28.67	PK+	V
4	7309.500	62.12	-7.55	54.57	74.00	19.43	PK+	V
5	9748.500	54.76	-6.59	48.17	74.00	25.83	PK+	V
6	17707.500	47.02	0.02	47.04	74.00	26.96	PK+	V

### Final\_Result

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.	Verdict
1	7309.500	59.12	-7.55	51.57	53.90	2.33	AVG	V	PASS


Mode:	11B-2437
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/21
T/A/P	23.7°C/51%/101Kpa



### Critical\_Freqs

No.	Freq. (MHz)	Reading (dB $\mu$ V)	Corr. (dB)	Meas. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Det.	Pol.
1	1980.000	62.17	-9.14	53.03	74.00	20.97	PK+	H
2	2532.000	58.06	-8.61	49.45	74.00	24.55	PK+	H
3	2756.000	57.40	-7.99	49.41	74.00	24.59	PK+	H
4	7311.000	61.27	-7.6	53.67	74.00	20.33	PK+	H
5	9748.500	50.32	-6.59	43.73	74.00	30.27	PK+	H
6	17704.500	46.97	0.08	47.05	74.00	26.95	PK+	H


Mode:	11B-2462
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/21
T/A/P	23.7°C/51%/101Kpa



### Critical\_Freqs

No.	Freq. (MHz)	Reading (dB $\mu$ V)	Corr. (dB)	Meas. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Det.	Pol.
1	1980.000	60.85	-9.14	51.71	74.00	22.29	PK+	H
2	2544.000	59.13	-8.32	50.81	74.00	23.19	PK+	H
3	4086.000	54.38	-12.69	41.69	74.00	32.31	PK+	H
4	7387.500	59.56	-8.29	51.27	74.00	22.73	PK+	H
5	10789.500	47.74	-4.92	42.82	74.00	31.18	PK+	H
6	17688.000	45.97	0.25	46.22	74.00	27.78	PK+	H

Mode:	11B-2462
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/21
T/A/P	23.7°C/51%/101Kpa



### Critical\_Freqs

No.	Freq. (MHz)	Reading (dB $\mu$ V)	Corr. (dB)	Meas. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Det.	Pol.
1	1188.000	64.03	-14.68	49.35	74.00	24.65	PK+	V
2	1980.000	59.23	-9.14	50.09	74.00	23.91	PK+	V
3	2774.000	55.85	-8.31	47.54	74.00	26.46	PK+	V
4	3564.000	61.38	-13.98	47.40	74.00	26.60	PK+	V
5	7386.000	60.96	-8.3	52.66	74.00	21.34	PK+	V
6	9847.500	55.46	-6.9	48.56	74.00	25.44	PK+	V

No others harmonics emissions are higher than 20 dB below the limits of 47 CFR Part 15.247.


**Note:**

- (1) All Readings are Peak Value.
- (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
- (3) The average measurement was not performed when the peak measured data under the limit of average detection.
- (4) Measuring frequencies from 1GHz to 25GHz.

## Band Edge


The worst result as bellow:

Mode:	11B-2412
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/21
T/A/P	23.7°C/51%/101Kpa

**Critical\_Freqs**

No.	Freq. (MHz)	Reading (dB $\mu$ V)	Corr. (dB)	Meas. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Det.	Pol.
1	2389.040	24.19	22.7	46.89	74.00	27.11	PK+	V
2	2390.000	22.31	22.72	45.03	74.00	28.97	PK+	V


Mode:	11B-2412
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/21
T/A/P	23.7°C/51%/101Kpa



### Critical\_Freqs

No.	Freq. (MHz)	Reading (dB $\mu$ V)	Corr. (dB)	Meas. (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Det.	Pol.
1	2385.920	25.86	22.64	48.50	74.00	25.50	PK+	H
2	2390.000	23.93	22.72	46.65	74.00	27.35	PK+	H


Mode:	11B-2462
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/21
T/A/P	23.7°C/51%/101Kpa



### Critical\_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2483.500	22.34	23.15	45.49	74.00	28.51	PK+	V
2	2491.040	22.18	23.13	45.31	74.00	28.69	PK+	V

Mode:	11B-2462
Power:	AC 120V/60Hz
TE:	Berny
Date	2024/8/21
T/A/P	23.7°C/51%/101Kpa



### Critical\_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	2483.500	26.32	23.15	49.47	74.00	24.53	PK+	H
2	2487.360	28.33	23.14	51.47	74.00	22.53	PK+	H

#### Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

## 9. ANTENNA REQUIREMENT

### REQUIREMENT

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### DESCRIPTION

The EUT's antenna, permanent attached antenna, used Internal antenna, The antenna's gain is 5.36dBi and meets the requirement.

## 10. AC POWER LINE CONDUCTED EMISSION

### LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

### TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.


The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

### TEST SETUP



### TEST ENVIRONMENT


Temperature	26°C	Relative Humidity	54%
Atmosphere Pressure	101kPa		

**TEST RESULTS**

Phase: N

Mode: 802.11b 2412MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	52.20	9.90	62.10	65.52	-3.42	QP
2	0.1590	35.10	9.90	45.00	55.52	-10.52	AVG
3	0.2130	47.77	9.91	57.68	63.09	-5.41	QP
4	0.2130	32.73	9.91	42.64	53.09	-10.45	AVG
5	0.3165	43.50	9.89	53.39	59.80	-6.41	QP
6	0.3165	32.66	9.89	42.55	49.80	-7.25	AVG
7	0.4695	39.93	9.83	49.76	56.52	-6.76	QP
8	0.4695	31.33	9.83	41.16	46.52	-5.36	AVG
9	1.1490	40.43	10.05	50.48	56.00	-5.52	QP
10	1.1490	29.52	10.05	39.57	46.00	-6.43	AVG
11	2.1030	41.20	10.16	51.36	56.00	-4.64	QP
12	2.1030	31.18	10.16	41.34	46.00	-4.66	AVG



Phase: L1

Mode: 802.11b 2412MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	42.73	9.97	52.70	65.52	-12.82	QP
2	0.1590	22.57	9.97	32.54	55.52	-22.98	AVG
3	0.4335	41.53	9.95	51.48	57.19	-5.71	QP
4	0.4335	28.17	9.95	38.12	47.19	-9.07	AVG
5	0.8385	39.59	10.04	49.63	56.00	-6.37	QP
6	0.8385	19.81	10.04	29.85	46.00	-16.15	AVG
7	1.9410	38.98	10.13	49.11	56.00	-6.89	QP
8	1.9410	22.09	10.13	32.22	46.00	-13.78	AVG
9	4.5555	33.74	10.27	44.01	56.00	-11.99	QP
10	4.5555	14.37	10.27	24.64	46.00	-21.36	AVG
11	14.2215	33.67	10.99	44.66	60.00	-15.34	QP
12	14.2215	13.20	10.99	24.19	50.00	-25.81	AVG

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

## **11. TEST DATA**


Please refer to section "Test Data" - Appendix A


## APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION

AC Power Line Conducted Emission






Radiated Band edge and Spurious Emission









## APPENDIX: PHOTOGRAPHS OF THE EUT






















**END OF REPORT**