


FCC REPORT

For LTE

Report No.	CHTW24090016	Report Verification:
Project No.	SHT2408085301W	
FCC ID	2BKRZ-WL432EG25G	
Applicant	Suzhou Inovance Technology Co., Ltd.	
Address.....	No. 52, Tian E Dang Road, Wuzhong District, 215104, Suzhou City, Jiangsu Province, P.R. China	
Product Name	LTE Module	
Trade Mark	-	
Model No.	EG25-G	
Listed Model(s)	-	
Standard	FCC CFR Title 47 Part 2 FCC CFR Title 47 Part 22 Subpart H FCC CFR Title 47 Part 24 Subpart E FCC CFR Title 47 Part 27	
Date of receipt of test sample.....	Aug. 28, 2024	
Date of testing.....	Aug. 30, 2024- Sep. 04, 2024	
Date of issue.....	Sep. 09, 2024	
Result.....	Pass	

Compiled by (position+printedname+signature)....:	File administrators Xiaodong Zhao	
Supervised by (position+printedname+signature)....:	Project Engineer Xiaodong Zhao	
Approved by (position+printedname+signature)....:	Manager Xu Yang	

Testing Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.
Address.....	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1. TEST STANDARDS AND REPORT VERSION</u>	3
1.1. Applicable Standards	3
1.2. Report version information	3
<u>2. TEST DESCRIPTION</u>	4
<u>3. SUMMARY</u>	5
3.1. Client Information	5
3.2. Product Description	5
3.3. Radio Specification Description	5
3.4. Testing Laboratory Information	6
<u>4. TEST CONFIGURATION</u>	7
4.1. Test frequency list	7
4.2. Test mode	8
4.3. Test sample information	8
4.4. Support unit used in test configuration and system	8
4.5. Testing environmental condition	9
4.6. Statement of the measurement uncertainty	9
4.7. Equipments Used during the Test	9
<u>5. TEST CONDITIONS AND RESULTS</u>	10
5.1. Radiated Spurious Emission	10
5.2. Radiated Spurious Emission	23

1. **TEST STANDARDS AND REPORT VERSION**

1.1. **Applicable Standards**

The tests were performed according to following standards:

[FCC CFR Title 47 Part 2](#): Frequency Allocations and Radio Treaty Matters; General Rules and Regulations

[FCC CFR Title 47 Part 22 Subpart H](#): Cellular Radiotelephone Service

[FCC CFR Title 47 Part 24 Subpart E](#): Broadband PCS

[FCC CFR Title 47 Part 27](#): Miscellaneous Wireless Communications Services

[ANSI C63.26-2015](#): American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services

[KDB 971168 D01 Power Meas License Digital Systems v03](#): MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS

1.2. **Report version information**

Revision No.	Date of issue	Description
N/A	2024-09-09	Original

2. TEST DESCRIPTION

Section	Test Item	Section in CFR 47	Result #1	Test Engineer
5.1	Radiated Spurious Emissions	Part 2.1053 Part 22.917 Part 24.238 Part 27.53	Pass	Yifan Wang
5.2	Radiated Band Edge	Part 2.1053 Part 22.917 Part 24.238 Part 27.53	Pass	Yifan Wang

Note:

- 1) #1: The test result does not include measurement uncertainty value.

3. SUMMARY

3.1. Client Information

Applicant:	Suzhou Inovance Technology Co., Ltd.
Address:	No. 52, Tian E Dang Road, Wuzhong District, 215104, Suzhou City, Jiangsu Province, P.R. China
Manufacturer:	Suzhou Inovance Technology Co., Ltd.
Address:	No. 52, Tian E Dang Road, Wuzhong District, 215104, Suzhou City, Jiangsu Province, P.R. China

3.2. Product Description

Module information:	
Product Name:	LTE Module
Trade Mark:	-
Model No.:	EG25-G
Listed Model(s):	-

3.3. Radio Specification Description

Support Operating Band:	<input checked="" type="checkbox"/> LTE Band 2	<input checked="" type="checkbox"/> LTE Band 4	<input checked="" type="checkbox"/> LTE Band 5
	<input checked="" type="checkbox"/> LTE Band 7	<input checked="" type="checkbox"/> LTE Band 12	
Operating Frequency Range:	Please refer to note #2		
Channel bandwidth:	Please refer to note #3		
Uplink Modulation type:	<input checked="" type="checkbox"/> QPSK	<input checked="" type="checkbox"/> 16QAM	<input type="checkbox"/> 64QAM
Downlink Modulation type:	<input checked="" type="checkbox"/> QPSK	<input checked="" type="checkbox"/> 16QAM	<input type="checkbox"/> 64QAM
Antenna type:	linear antenna		
Antenna gain #4:	Band 2: 1.496dB _i	Band 4: 1.963dB _i	Band 5: 2.066dB _i
	Band 7: 2.994dB _i	Band 12: 0.366dB _i	

Note:

- : means that this feature is supported; : means that this feature is not supported
- #2: Operating frequency range is as follow:

LTE Band	Uplink frequency	Downlink frequency
LTE Band 2	1850.7 – 1909.3 MHz	1930.7 – 1989.3 MHz
LTE Band 4	1710.7 – 1754.3 MHz	2110.7 – 2154.3 MHz
LTE Band 5	824.7 – 848.3 MHz	869.7 – 893.3 MHz
LTE Band 7	2502.5 – 2567.5 MHz	2622.5 – 2687.5 MHz
LTE Band 12	699.7 – 715.3 MHz	729.7 – 745.3 MHz

- Supported channel bandwidth is as follow:

LTE Band	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz
LTE Band 2	√	√	√	√	√	√
LTE Band 4	√	√	√	√	√	√
LTE Band 5	√	√	√	√	-	-
LTE Band 7	-	-	√	√	√	√
LTE Band 12	√	√	√	√	-	-

√: means that this feature is supported; -: means that this feature is not supported

- #4: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, HTW lab has not verified the authenticity of its information

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China	
Contact information:	Phone: 86-755-26715499 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC Registration Number	762235
	FCC Designation Number	CN1181

4. TEST CONFIGURATION

4.1. Test frequency list

LTE Band 2	<table border="1"> <thead> <tr> <th>Test Frequency ID</th><th>Bandwidth [MHz]</th><th>N_{UL}</th><th>Frequency of Uplink [MHz]</th><th>N_{DL}</th><th>Frequency of Downlink [MHz]</th></tr> </thead> <tbody> <tr> <td>1.4</td><td>18607</td><td>1850.7</td><td>607</td><td>1930.7</td></tr> <tr> <td>3</td><td>18615</td><td>1851.5</td><td>615</td><td>1931.5</td></tr> <tr> <td>5</td><td>18625</td><td>1852.5</td><td>625</td><td>1932.5</td></tr> <tr> <td>10</td><td>18650</td><td>1855</td><td>650</td><td>1935</td></tr> <tr> <td>15^[1]</td><td>18675</td><td>1857.5</td><td>675</td><td>1937.5</td></tr> <tr> <td>20^[1]</td><td>18700</td><td>1860</td><td>700</td><td>1940</td></tr> <tr> <td>Mid Range</td><td>1.4/3/5/10 15^[1]/20^[1]</td><td>18900</td><td>1880</td><td>900</td><td>1960</td></tr> <tr> <td>High Range</td><td>1.4</td><td>19193</td><td>1909.3</td><td>1193</td><td>1989.3</td></tr> <tr> <td></td><td>3</td><td>19185</td><td>1908.5</td><td>1185</td><td>1988.5</td></tr> <tr> <td></td><td>5</td><td>19175</td><td>1907.5</td><td>1175</td><td>1987.5</td></tr> <tr> <td></td><td>10</td><td>19150</td><td>1905</td><td>1150</td><td>1985</td></tr> <tr> <td></td><td>15^[1]</td><td>19125</td><td>1902.5</td><td>1125</td><td>1982.5</td></tr> <tr> <td></td><td>20^[1]</td><td>19100</td><td>1900</td><td>1100</td><td>1980</td></tr> </tbody> </table>	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]	1.4	18607	1850.7	607	1930.7	3	18615	1851.5	615	1931.5	5	18625	1852.5	625	1932.5	10	18650	1855	650	1935	15 ^[1]	18675	1857.5	675	1937.5	20 ^[1]	18700	1860	700	1940	Mid Range	1.4/3/5/10 15 ^[1] /20 ^[1]	18900	1880	900	1960	High Range	1.4	19193	1909.3	1193	1989.3		3	19185	1908.5	1185	1988.5		5	19175	1907.5	1175	1987.5		10	19150	1905	1150	1985		15 ^[1]	19125	1902.5	1125	1982.5		20 ^[1]	19100	1900	1100	1980
Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]																																																																										
1.4	18607	1850.7	607	1930.7																																																																											
3	18615	1851.5	615	1931.5																																																																											
5	18625	1852.5	625	1932.5																																																																											
10	18650	1855	650	1935																																																																											
15 ^[1]	18675	1857.5	675	1937.5																																																																											
20 ^[1]	18700	1860	700	1940																																																																											
Mid Range	1.4/3/5/10 15 ^[1] /20 ^[1]	18900	1880	900	1960																																																																										
High Range	1.4	19193	1909.3	1193	1989.3																																																																										
	3	19185	1908.5	1185	1988.5																																																																										
	5	19175	1907.5	1175	1987.5																																																																										
	10	19150	1905	1150	1985																																																																										
	15 ^[1]	19125	1902.5	1125	1982.5																																																																										
	20 ^[1]	19100	1900	1100	1980																																																																										
Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]																																																																										
1.4	19957	1710.7	1957	2110.7																																																																											
3	19965	1711.5	1965	2111.5																																																																											
5	19975	1712.5	1975	2112.5																																																																											
10	20000	1715	2000	2115																																																																											
15	20025	1717.5	2025	2117.5																																																																											
20	20050	1720	2050	2120																																																																											
Mid Range	1.4/3/5/10/15/20	20175	1732.5	2175	2132.5																																																																										
High Range	1.4	20393	1754.3	2393	2154.3																																																																										
	3	20385	1753.5	2385	2153.5																																																																										
	5	20375	1752.5	2375	2152.5																																																																										
	10	20350	1750	2350	2150																																																																										
	15	20325	1747.5	2325	2147.5																																																																										
	20	20300	1745	2300	2145																																																																										
Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]																																																																										
1.4	20407	824.7	2407	869.7																																																																											
3	20415	825.5	2415	870.5																																																																											
5	20425	826.5	2425	871.5																																																																											
10 ^[1]	20450	829	2450	874																																																																											
Mid Range	1.4/3/5 10 ^[1]	20525	836.5	2525	881.5																																																																										
High Range	1.4	20643	848.3	2643	893.3																																																																										
	3	20635	847.5	2635	892.5																																																																										
	5	20625	846.5	2625	891.5																																																																										
	10 ^[1]	20600	844	2600	889																																																																										
Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]																																																																										
5	20775	2502.5	2775	2622.5																																																																											
10	20800	2505	2800	2625																																																																											
15	20825	2507.5	2825	2627.5																																																																											
20 ^[1]	20850	2510	2850	2630																																																																											
Mid Range	5/10/15 20 ^[1]	21100	2535	3100	2655																																																																										
High Range	5	21425	2567.5	3425	2687.5																																																																										
	10	21400	2565	3400	2685																																																																										
	15	21375	2562.5	3375	2682.5																																																																										
	20 ^[1]	21350	2560	3350	2680																																																																										
Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]																																																																										
1.4	23017	699.7	5017	729.7																																																																											
3	23025	700.5	5025	730.5																																																																											
5 ^[1]	23035	701.5	5035	731.5																																																																											
10 ^[1]	23060	704	5060	734																																																																											
Mid Range	1.4/3 5 ^[1] /10 ^[1]	23095	707.5	5095	737.5																																																																										
High Range	1.4	23173	715.3	5173	745.3																																																																										
	3	23165	714.5	5165	744.5																																																																										
	5 ^[1]	23155	713.5	5155	743.5																																																																										
	10 ^[1]	23130	711	5130	741																																																																										
LTE Band 2	<table border="1"> <thead> <tr> <th>Test Frequency ID</th><th>Bandwidth [MHz]</th><th>N_{UL}</th><th>Frequency of Uplink [MHz]</th><th>N_{DL}</th><th>Frequency of Downlink [MHz]</th></tr> </thead> <tbody> <tr> <td>1.4</td><td>18607</td><td>1850.7</td><td>607</td><td>1930.7</td></tr> <tr> <td>3</td><td>18615</td><td>1851.5</td><td>615</td><td>1931.5</td></tr> <tr> <td>5</td><td>18625</td><td>1852.5</td><td>625</td><td>1932.5</td></tr> <tr> <td>10</td><td>18650</td><td>1855</td><td>650</td><td>1935</td></tr> <tr> <td>15^[1]</td><td>18675</td><td>1857.5</td><td>675</td><td>1937.5</td></tr> <tr> <td>20^[1]</td><td>18700</td><td>1860</td><td>700</td><td>1940</td></tr> <tr> <td>Mid Range</td><td>1.4/3/5/10 15^[1]/20^[1]</td><td>18900</td><td>1880</td><td>900</td><td>1960</td></tr> <tr> <td>High Range</td><td>1.4</td><td>19193</td><td>1909.3</td><td>1193</td><td>1989.3</td></tr> <tr> <td></td><td>3</td><td>19185</td><td>1908.5</td><td>1185</td><td>1988.5</td></tr> <tr> <td></td><td>5</td><td>19175</td><td>1907.5</td><td>1175</td><td>1987.5</td></tr> <tr> <td></td><td>10</td><td>19150</td><td>1905</td><td>1150</td><td>1985</td></tr> <tr> <td></td><td>15^[1]</td><td>19125</td><td>1902.5</td><td>1125</td><td>1982.5</td></tr> <tr> <td></td><td>20^[1]</td><td>19100</td><td>1900</td><td>1100</td><td>1980</td></tr> </tbody> </table>	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]	1.4	18607	1850.7	607	1930.7	3	18615	1851.5	615	1931.5	5	18625	1852.5	625	1932.5	10	18650	1855	650	1935	15 ^[1]	18675	1857.5	675	1937.5	20 ^[1]	18700	1860	700	1940	Mid Range	1.4/3/5/10 15 ^[1] /20 ^[1]	18900	1880	900	1960	High Range	1.4	19193	1909.3	1193	1989.3		3	19185	1908.5	1185	1988.5		5	19175	1907.5	1175	1987.5		10	19150	1905	1150	1985		15 ^[1]	19125	1902.5	1125	1982.5		20 ^[1]	19100	1900	1100	1980
Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]																																																																										
1.4	18607	1850.7	607	1930.7																																																																											
3	18615	1851.5	615	1931.5																																																																											
5	18625	1852.5	625	1932.5																																																																											
10	18650	1855	650	1935																																																																											
15 ^[1]	18675	1857.5	675	1937.5																																																																											
20 ^[1]	18700	1860	700	1940																																																																											
Mid Range	1.4/3/5/10 15 ^[1] /20 ^[1]	18900	1880	900	1960																																																																										
High Range	1.4	19193	1909.3	1193	1989.3																																																																										
	3	19185	1908.5	1185	1988.5																																																																										
	5	19175	1907.5	1175	1987.5																																																																										
	10	19150	1905	1150	1985																																																																										
	15 ^[1]	19125	1902.5	1125	1982.5																																																																										
	20 ^[1]	19100	1900	1100	1980																																																																										
<p>NOTE 1: Bandwidth for which a relaxation of the specified UE receiver sensitivity requirement (TS 36.101 [27] Clause 7.3) is allowed.</p>																																																																															
LTE Band 4	<table border="1"> <thead> <tr> <th>Test Frequency ID</th><th>Bandwidth [MHz]</th><th>N_{UL}</th><th>Frequency of Uplink [MHz]</th><th>N_{DL}</th><th>Frequency of Downlink [MHz]</th></tr> </thead> <tbody> <tr> <td>1.4</td><td>19957</td><td>1710.7</td><td>1957</td><td>2110.7</td></tr> <tr> <td>3</td><td>19965</td><td>1711.5</td><td>1965</td><td>2111.5</td></tr> <tr> <td>5</td><td>19975</td><td>1712.5</td><td>1975</td><td>2112.5</td></tr> <tr> <td>10</td><td>20000</td><td>1715</td><td>2000</td><td>2115</td></tr> <tr> <td>15</td><td>20025</td><td>1717.5</td><td>2025</td><td>2117.5</td></tr> <tr> <td>20</td><td>20050</td><td>1720</td><td>2050</td><td>2120</td></tr> <tr> <td>Mid Range</td><td>1.4/3/5/10/15/20</td><td>20175</td><td>1732.5</td><td>2175</td><td>2132.5</td></tr> <tr> <td>High Range</td><td>1.4</td><td>20393</td><td>1754.3</td><td>2393</td><td>2154.3</td></tr> <tr> <td></td><td>3</td><td>20385</td><td>1753.5</td><td>2385</td><td>2153.5</td></tr> <tr> <td></td><td>5</td><td>20375</td><td>1752.5</td><td>2375</td><td>2152.5</td></tr> <tr> <td></td><td>10</td><td>20350</td><td>1750</td><td>2350</td><td>2150</td></tr> <tr> <td></td><td>15</td><td>20325</td><td>1747.5</td><td>2325</td><td>2147.5</td></tr> <tr> <td></td><td>20</td><td>20300</td><td>1745</td><td>2300</td><td>2145</td></tr> </tbody> </table>	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]	1.4	19957	1710.7	1957	2110.7	3	19965	1711.5	1965	2111.5	5	19975	1712.5	1975	2112.5	10	20000	1715	2000	2115	15	20025	1717.5	2025	2117.5	20	20050	1720	2050	2120	Mid Range	1.4/3/5/10/15/20	20175	1732.5	2175	2132.5	High Range	1.4	20393	1754.3	2393	2154.3		3	20385	1753.5	2385	2153.5		5	20375	1752.5	2375	2152.5		10	20350	1750	2350	2150		15	20325	1747.5	2325	2147.5		20	20300	1745	2300	2145
Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]																																																																										
1.4	19957	1710.7	1957	2110.7																																																																											
3	19965	1711.5	1965	2111.5																																																																											
5	19975	1712.5	1975	2112.5																																																																											
10	20000	1715	2000	2115																																																																											
15	20025	1717.5	2025	2117.5																																																																											
20	20050	1720	2050	2120																																																																											
Mid Range	1.4/3/5/10/15/20	20175	1732.5	2175	2132.5																																																																										
High Range	1.4	20393	1754.3	2393	2154.3																																																																										
	3	20385	1753.5	2385	2153.5																																																																										
	5	20375	1752.5	2375	2152.5																																																																										
	10	20350	1750	2350	2150																																																																										
	15	20325	1747.5	2325	2147.5																																																																										
	20	20300	1745	2300	2145																																																																										
<p>NOTE 1: Bandwidth for which a relaxation of the specified UE receiver sensitivity requirement (TS 36.101 [27] Clause 7.3) is allowed.</p>																																																																															
LTE Band 5	<table border="1"> <thead> <tr> <th>Test Frequency ID</th><th>Bandwidth [MHz]</th><th>N_{UL}</th><th>Frequency of Uplink [MHz]</th><th>N_{DL}</th><th>Frequency of Downlink [MHz]</th></tr> </thead> <tbody> <tr> <td>1.4</td><td>20407</td><td>824.7</td><td>2407</td><td>869.7</td></tr> <tr> <td>3</td><td>20415</td><td>825.5</td><td>2415</td><td>870.5</td></tr> <tr> <td>5</td><td>20425</td><td>826.5</td><td>2425</td><td>871.5</td></tr> <tr> <td>10^[1]</td><td>20450</td><td>829</td><td>2450</td><td>874</td></tr> <tr> <td>Mid Range</td><td>1.4/3/5 10^[1]</td><td>20525</td><td>836.5</td><td>2525</td><td>881.5</td></tr> <tr> <td>High Range</td><td>1.4</td><td>20643</td><td>848.3</td><td>2643</td><td>893.3</td></tr> <tr> <td></td><td>3</td><td>20635</td><td>847.5</td><td>2635</td><td>892.5</td></tr> <tr> <td></td><td>5</td><td>20625</td><td>846.5</td><td>2625</td><td>891.5</td></tr> <tr> <td></td><td>10^[1]</td><td>20600</td><td>844</td><td>2600</td><td>889</td></tr> </tbody> </table>	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]	1.4	20407	824.7	2407	869.7	3	20415	825.5	2415	870.5	5	20425	826.5	2425	871.5	10 ^[1]	20450	829	2450	874	Mid Range	1.4/3/5 10 ^[1]	20525	836.5	2525	881.5	High Range	1.4	20643	848.3	2643	893.3		3	20635	847.5	2635	892.5		5	20625	846.5	2625	891.5		10 ^[1]	20600	844	2600	889																						
Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]																																																																										
1.4	20407	824.7	2407	869.7																																																																											
3	20415	825.5	2415	870.5																																																																											
5	20425	826.5	2425	871.5																																																																											
10 ^[1]	20450	829	2450	874																																																																											
Mid Range	1.4/3/5 10 ^[1]	20525	836.5	2525	881.5																																																																										
High Range	1.4	20643	848.3	2643	893.3																																																																										
	3	20635	847.5	2635	892.5																																																																										
	5	20625	846.5	2625	891.5																																																																										
	10 ^[1]	20600	844	2600	889																																																																										
<p>NOTE 1: Bandwidth for which a relaxation of the specified UE receiver sensitivity requirement (TS 36.101 [27] Clause 7.3) is allowed.</p>																																																																															
LTE Band 7	<table border="1"> <thead> <tr> <th>Test Frequency ID</th><th>Bandwidth [MHz]</th><th>N_{UL}</th><th>Frequency of Uplink [MHz]</th><th>N_{DL}</th><th>Frequency of Downlink [MHz]</th></tr> </thead> <tbody> <tr> <td>5</td><td>20775</td><td>2502.5</td><td>2775</td><td>2622.5</td></tr> <tr> <td>10</td><td>20800</td><td>2505</td><td>2800</td><td>2625</td></tr> <tr> <td>15</td><td>20825</td><td>2507.5</td><td>2825</td><td>2627.5</td></tr> <tr> <td>20^[1]</td><td>20850</td><td>2510</td><td>2850</td><td>2630</td></tr> <tr> <td>Mid Range</td><td>5/10/15 20^[1]</td><td>21100</td><td>2535</td><td>3100</td><td>2655</td></tr> <tr> <td>High Range</td><td>5</td><td>21425</td><td>2567.5</td><td>3425</td><td>2687.5</td></tr> <tr> <td></td><td>10</td><td>21400</td><td>2565</td><td>3400</td><td>2685</td></tr> <tr> <td></td><td>15</td><td>21375</td><td>2562.5</td><td>3375</td><td>2682.5</td></tr> <tr> <td></td><td>20^[1]</td><td>21350</td><td>2560</td><td>3350</td><td>2680</td></tr> </tbody> </table>	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]	5	20775	2502.5	2775	2622.5	10	20800	2505	2800	2625	15	20825	2507.5	2825	2627.5	20 ^[1]	20850	2510	2850	2630	Mid Range	5/10/15 20 ^[1]	21100	2535	3100	2655	High Range	5	21425	2567.5	3425	2687.5		10	21400	2565	3400	2685		15	21375	2562.5	3375	2682.5		20 ^[1]	21350	2560	3350	2680																						
Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]																																																																										
5	20775	2502.5	2775	2622.5																																																																											
10	20800	2505	2800	2625																																																																											
15	20825	2507.5	2825	2627.5																																																																											
20 ^[1]	20850	2510	2850	2630																																																																											
Mid Range	5/10/15 20 ^[1]	21100	2535	3100	2655																																																																										
High Range	5	21425	2567.5	3425	2687.5																																																																										
	10	21400	2565	3400	2685																																																																										
	15	21375	2562.5	3375	2682.5																																																																										
	20 ^[1]	21350	2560	3350	2680																																																																										
<p>NOTE 1: Bandwidth for which a relaxation of the specified UE receiver sensitivity requirement (TS 36.101 [27] Clause 7.3) is allowed.</p>																																																																															
LTE Band 12	<p>Table 4.3.1.1.12-1: Test frequencies for E-UTRA channel bandwidth for operating band 12</p> <table border="1"> <thead> <tr> <th>Test Frequency ID</th><th>Bandwidth [MHz]</th><th>N_{UL}</th><th>Frequency of Uplink [MHz]</th><th>N_{DL}</th><th>Frequency of Downlink [MHz]</th></tr> </thead> <tbody> <tr> <td>1.4</td><td>23017</td><td>699.7</td><td>5017</td><td>729.7</td></tr> <tr> <td>3</td><td>23025</td><td>700.5</td><td>5025</td><td>730.5</td></tr> <tr> <td>5^[1]</td><td>23035</td><td>701.5</td><td>5035</td><td>731.5</td></tr> <tr> <td>10^[1]</td><td>23060</td><td>704</td><td>5060</td><td>734</td></tr> <tr> <td>Mid Range</td><td>1.4/3 5^[1]/10^[1]</td><td>23095</td><td>707.5</td><td>5095</td><td>737.5</td></tr> <tr> <td>High Range</td><td>1.4</td><td>23173</td><td>715.3</td><td>5173</td><td>745.3</td></tr> <tr> <td></td><td>3</td><td>23165</td><td>714.5</td><td>5165</td><td>744.5</td></tr> <tr> <td></td><td>5^[1]</td><td>23155</td><td>713.5</td><td>5155</td><td>743.5</td></tr> <tr> <td></td><td>10^[1]</td><td>23130</td><td>711</td><td>5130</td><td>741</td></tr> </tbody> </table>	Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]	1.4	23017	699.7	5017	729.7	3	23025	700.5	5025	730.5	5 ^[1]	23035	701.5	5035	731.5	10 ^[1]	23060	704	5060	734	Mid Range	1.4/3 5 ^[1] /10 ^[1]	23095	707.5	5095	737.5	High Range	1.4	23173	715.3	5173	745.3		3	23165	714.5	5165	744.5		5 ^[1]	23155	713.5	5155	743.5		10 ^[1]	23130	711	5130	741																						
Test Frequency ID	Bandwidth [MHz]	N _{UL}	Frequency of Uplink [MHz]	N _{DL}	Frequency of Downlink [MHz]																																																																										
1.4	23017	699.7	5017	729.7																																																																											
3	23025	700.5	5025	730.5																																																																											
5 ^[1]	23035	701.5	5035	731.5																																																																											
10 ^[1]	23060	704	5060	734																																																																											
Mid Range	1.4/3 5 ^[1] /10 ^[1]	23095	707.5	5095	737.5																																																																										
High Range	1.4	23173	715.3	5173	745.3																																																																										
	3	23165	714.5	5165	744.5																																																																										
	5 ^[1]	23155	713.5	5155	743.5																																																																										
	10 ^[1]	23130	711	5130	741																																																																										
<p>NOTE 1: Bandwidth for which a relaxation of the specified UE receiver sensitivity requirement (TS 36.101 [27] Clause 7.3) is allowed.</p>																																																																															

4.2. Test mode

Test mode	Link mode
-----------	-----------

- 1) Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems and ANSI C63.26 with maximum output power.
- 2) Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Test configuration is as follow:

Test Items	Bandwidth	Modulation	RB #		
			1	Half	Full
Radiated Spurious Emission	#5	#6	o	-	-
Radiated Band Edge	#5	#6	o	-	o

Note:

- o #5: Test all kind of bandwidth in section 3.3
- o #6: Test all kind of uplink modulation in section 3.3
- o o: means that this configuration is chosen for testing
- o -: means that this configuration is not tested.
- o The device is investigated from 30MHz to 10 times off fundamental signal for radiated spurious emission test under different bandwidth, modulations and RB size/offset in exploratory test. Subsequently, only the worst case emissions(highest bandwidth, QPSK, and 1RB0) are reported.

4.3. Test sample information

Test item	HTW sample no.
Radiated test items	YPHT24080853001

Note:

Radiated test items: Radiated Spurious Emission, Radiated Band Edge

4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?				
<input checked="" type="checkbox"/> No				
Item	Equipment	Trade Name	Model No.	Other
1				
2				

4.5. Testing environmental condition

Voltage	VN=Nominal Voltage	DC 24V
Temperature	TN=Normal Temperature	25 °C
Humidity	30~60 %	
Air Pressure	950-1050 hPa	

4.6. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	Radiated Spurious Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.7. Equipments Used during the Test

● Radiated Spurious Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2023/4/17	2026/4/16
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2024/8/12	2025/8/11
●	Spectrum Analyzer	R&S	HTWE0385	N9020A	MY54486658	2024/8/12	2025/8/11
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0123	VULB9163	538	2024/4/8	2027/4/7
●	Horn Antenna	SCHWARZBECK	HTWE0126	BBHA 9120D	1011	2023/2/14	2026/2/13
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2023/2/20	2026/2/19
●	Pre-Amplifier	CD	HTWE0071	PAP-0102	12004	2024/6/6	2025/6/5
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0551	SCU18F	100855	2024/6/6	2025/6/5
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

● Auxiliary Equipment							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Radio communication tester	R&S	HTWE0287	CMW500	137688-Lv	2024/08/12	2025/08/11
●	High pass filter	Wainwright	HTWE0297	WHKX3.0/18G-10SS	38	2024/03/26	2025/03/25
●	Band Stop filter	-	HTWE0039	N/A	N/A	2024/01/23	2025/01/24

5. TEST CONDITIONS AND RESULTS

5.1. Radiated Spurious Emission

LIMIT

Part 22.917&Part 24.238:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Part 27.53(g):

For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB.


Part 27.53(h):

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log(P)$ dB.

Part 27.53(m)(4):

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT in the center of the turntable.
 - a) For radiated emissions measurements performed at frequencies less than or equal to 1 GHz, the EUT shall be placed on a RF-transparent table at a nominal height of 80 cm above the reference ground plane
 - b) For radiated measurements performed at frequencies above 1 GHz, the EUT shall be placed on an RF transparent table at a nominal height of 1.5 m above the ground plane.
2. Unless the EUT uses an integral antenna, the EUT shall be terminated with a non-radiating transmitter load. In cases where the EUT uses an adjustable antenna, the antenna shall be adjusted through typical positions and lengths to maximize emissions levels.
3. The EUT shall be tested while operating on the frequency per manufacturer specification. Set the transmitter to operate in continuous transmit mode.
4. Receiver or Spectrum set as follow:

Below 1GHz, RBW=100kHz, VBW=300kHz, Detector=Peak, Sweep time=Auto

Above 1GHz, RBW=1MHz, VBW=3MHz, Detector=Peck, Sweep time=Auto
5. Each emission under consideration shall be evaluated:
 - a) Raise and lower the measurement antenna from 1 m to 4 m, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
 - b) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - c) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - d) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
 - e) Record the measured emission amplitude level and frequency
6. Repeat step 5 for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
7. Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
8. Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
9. Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
10. For each emission that was detected and measured in the initial test
 - a) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
 - b) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step 5 and step 6.
 - c) Record the output power level of the signal generator when equivalence is achieved in step b).
11. Repeat step 8 through step 10 with the measurement antenna oriented in the opposite polarization.
12. Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:
$$Pe = Ps(dBm) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$
where
Pe = equivalent emission power in dBm
Ps = source (signal generator) power in dBm
NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.
13. Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from:
$$\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB.}$$

- If necessary, the antenna gain can be calculated from calibrated antenna factor information
14. Provide the complete measurement results as a part of the test report.

TEST MODE

Please refer to the clause 4.2

TEST RESULTS

Passed **Not Applicable**

Note: only show the worse case for QPSK modulation.

LTE Band 2										
Test channel:		Low			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	70.26	-60.90	16.93	1.55	30.62	-73.04	-13.00	-60.04	Peak	
2	143.46	-61.39	17.66	2.26	30.44	-71.91	-13.00	-58.91	Peak	
3	4996.69	-60.34	44.35	6.00	40.20	-50.19	-13.00	-37.19	Peak	
4	7432.62	-51.10	48.40	7.73	39.91	-34.88	-13.00	-21.88	Peak	
5	9298.80	-53.53	49.63	8.52	39.88	-35.26	-13.00	-22.26	Peak	
6	11140.85	-64.14	52.93	8.91	40.56	-42.86	-13.00	-29.86	Peak	
Test channel:		Low			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	70.26	-61.76	19.39	1.55	30.62	-71.44	-13.00	-58.44	Peak	
2	143.46	-61.52	21.38	2.26	30.44	-68.32	-13.00	-55.32	Peak	
3	5574.67	-55.48	43.93	6.48	39.61	-44.68	-13.00	-31.68	Peak	
4	7432.62	-50.28	48.53	7.73	39.91	-33.93	-13.00	-20.93	Peak	
5	9298.80	-50.42	49.78	8.52	39.88	-32.00	-13.00	-19.00	Peak	
6	11140.85	-60.42	52.91	8.91	40.56	-39.16	-13.00	-26.16	Peak	
Test channel:		Mid			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-62.54	17.66	2.26	30.44	-73.06	-13.00	-60.06	Peak	
2	400.56	-74.13	25.43	3.95	29.80	-74.55	-13.00	-61.55	Peak	
3	3747.66	-58.45	42.24	5.24	40.68	-51.65	-13.00	-38.65	Peak	
4	5631.73	-58.84	43.77	6.54	39.53	-48.06	-13.00	-35.06	Peak	
5	7508.69	-49.78	48.05	7.79	39.93	-33.87	-13.00	-20.87	Peak	
6	9393.97	-54.49	50.01	8.56	39.84	-35.76	-13.00	-22.76	Peak	
Test channel:		Mid			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	85.85	-59.40	24.05	1.73	30.70	-64.32	-13.00	-51.32	Peak	
2	143.46	-61.11	21.38	2.26	30.44	-67.91	-13.00	-54.91	Peak	
3	5631.73	-54.88	43.94	6.54	39.53	-43.93	-13.00	-30.93	Peak	
4	7508.69	-45.64	48.40	7.79	39.93	-29.38	-13.00	-16.38	Peak	
5	9393.97	-53.25	49.83	8.56	39.84	-34.70	-13.00	-21.70	Peak	
6	11254.86	-62.87	53.01	9.00	40.45	-41.31	-13.00	-28.31	Peak	

Test channel:		High			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	40.74	-65.62	27.43	1.16	30.96	-67.99	-13.00	-54.99	Peak	
2	143.46	-62.86	17.66	2.26	30.44	-73.38	-13.00	-60.38	Peak	
3	4996.69	-60.93	44.35	6.00	40.20	-50.78	-13.00	-37.78	Peak	
4	7585.53	-54.92	47.70	7.86	39.95	-39.31	-13.00	-26.31	Peak	
5	9490.10	-56.22	49.93	8.60	39.80	-37.49	-13.00	-24.49	Peak	
6	11283.55	-65.64	52.95	9.03	40.42	-44.08	-13.00	-31.08	Peak	

Test channel:		High			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	63.22	-66.38	22.27	1.46	30.67	-73.32	-13.00	-60.32	Peak	
2	143.46	-63.63	21.38	2.26	30.44	-70.43	-13.00	-57.43	Peak	
3	5689.36	-55.06	44.00	6.60	39.45	-43.91	-13.00	-30.91	Peak	
4	7585.53	-50.98	48.27	7.86	39.95	-34.80	-13.00	-21.80	Peak	
5	9490.10	-49.51	49.73	8.60	39.80	-30.98	-13.00	-17.98	Peak	
6	11545.04	-66.12	53.19	9.25	40.26	-43.94	-13.00	-30.94	Peak	

LTE Band 4										
Test channel:		Low			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	40.88	-66.44	27.37	1.16	30.96	-68.87	-13.00	-55.87	Peak	
2	143.46	-64.23	17.66	2.26	30.44	-74.75	-13.00	-61.75	Peak	
3	3428.21	-54.40	39.99	4.93	40.85	-50.33	-13.00	-37.33	Peak	
4	6868.65	-62.96	47.06	7.40	39.40	-47.90	-13.00	-34.90	Peak	
5	8593.22	-49.86	47.37	8.27	40.16	-34.38	-13.00	-21.38	Peak	
6	10295.50	-64.20	51.17	8.84	40.08	-44.27	-13.00	-31.27	Peak	

Test channel:		Low			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-63.27	21.38	2.26	30.44	-70.07	-13.00	-57.07	Peak	
2	374.67	-70.36	24.67	3.80	30.16	-72.05	-13.00	-59.05	Peak	
3	3428.21	-53.82	40.01	4.93	40.85	-49.73	-13.00	-36.73	Peak	
4	6868.65	-53.68	47.39	7.40	39.40	-38.29	-13.00	-25.29	Peak	
5	8593.22	-59.22	47.74	8.27	40.16	-43.37	-13.00	-30.37	Peak	
6	10295.50	-61.18	51.59	8.84	40.08	-40.83	-13.00	-27.83	Peak	

Test channel:		Mid			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	40.74	-62.10	27.43	1.16	30.96	-64.47	-13.00	-51.47	Peak	
2	374.67	-67.97	24.80	3.80	30.16	-69.53	-13.00	-56.53	Peak	
3	4996.69	-60.55	44.35	6.00	40.20	-50.40	-13.00	-37.40	Peak	
4	6921.30	-62.95	47.30	7.39	39.43	-47.69	-13.00	-34.69	Peak	
5	9660.72	-66.74	50.05	8.60	39.83	-47.92	-13.00	-34.92	Peak	
6	11457.21	-66.44	52.97	9.17	40.24	-44.54	-13.00	-31.54	Peak	

Test channel:		Mid			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	39.75	-67.45	21.03	1.15	30.96	-76.23	-13.00	-63.23	Peak	
2	143.46	-62.93	21.38	2.26	30.44	-69.73	-13.00	-56.73	Peak	
3	4996.69	-61.12	44.50	6.00	40.20	-50.82	-13.00	-37.82	Peak	
4	6921.30	-59.04	47.37	7.39	39.43	-43.71	-13.00	-30.71	Peak	
5	8659.10	-59.85	48.28	8.29	40.14	-43.42	-13.00	-30.42	Peak	
6	10374.42	-65.03	51.87	8.90	40.12	-44.38	-13.00	-31.38	Peak	

Test channel:		High			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	41.75	-66.42	26.96	1.18	30.95	-69.23	-13.00	-56.23	Peak	
2	598.09	-74.49	27.78	4.92	29.54	-71.33	-13.00	-58.33	Peak	
3	3480.97	-54.52	40.74	5.03	40.91	-49.66	-13.00	-36.66	Peak	
4	5217.66	-57.31	43.96	6.18	39.94	-47.11	-13.00	-34.11	Peak	
5	6974.36	-51.84	47.53	7.38	39.46	-36.39	-13.00	-23.39	Peak	
6	8703.29	-57.35	48.14	8.31	40.12	-41.02	-13.00	-28.02	Peak	

Test channel:		High			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	41.75	-65.64	21.29	1.18	30.95	-74.12	-13.00	-61.12	Peak	
2	143.46	-62.37	21.38	2.26	30.44	-69.17	-13.00	-56.17	Peak	
3	3480.97	-56.34	40.83	5.03	40.91	-51.39	-13.00	-38.39	Peak	
4	6974.36	-55.93	47.36	7.38	39.46	-40.65	-13.00	-27.65	Peak	
5	8703.29	-60.86	48.68	8.31	40.12	-43.99	-13.00	-30.99	Peak	
6	10453.95	-59.96	52.16	8.96	40.17	-39.01	-13.00	-26.01	Peak	

LTE Band 5										
Test channel:		Low			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	31.96	-65.34	26.49	1.02	30.99	-68.82	-13.00	-55.82	Peak	
2	143.46	-64.41	17.66	2.26	30.44	-74.93	-13.00	-61.93	Peak	
3	4159.93	-64.28	42.07	5.65	40.29	-56.85	-13.00	-43.85	Peak	
4	5504.17	-66.35	43.89	6.40	39.71	-55.77	-13.00	-42.77	Peak	
5	8002.06	-66.39	48.12	8.04	39.94	-50.17	-13.00	-37.17	Peak	
6	10916.26	-67.63	52.71	8.83	40.62	-46.71	-13.00	-33.71	Peak	

Test channel:		Low			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-65.19	21.38	2.26	30.44	-71.99	-13.00	-58.99	Peak	
2	374.67	-73.17	24.67	3.80	30.16	-74.86	-13.00	-61.86	Peak	
3	3625.67	-64.76	42.54	5.20	40.88	-57.90	-13.00	-44.90	Peak	
4	5689.36	-67.09	44.00	6.60	39.45	-55.94	-13.00	-42.94	Peak	
5	7470.56	-66.95	48.47	7.76	39.92	-50.64	-13.00	-37.64	Peak	
6	10723.47	-68.28	52.53	8.91	40.42	-47.26	-13.00	-34.26	Peak	

Test channel:		Mid			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	33.10	-59.55	26.69	1.04	30.99	-62.81	-13.00	-49.81	Peak	
2	143.46	-65.07	17.66	2.26	30.44	-75.59	-13.00	-62.59	Peak	
3	4159.93	-57.75	42.07	5.65	40.29	-50.32	-13.00	-37.32	Peak	
4	4996.69	-60.87	44.35	6.00	40.20	-50.72	-13.00	-37.72	Peak	
5	7489.60	-62.70	48.13	7.78	39.93	-46.72	-13.00	-33.72	Peak	
6	11341.14	-67.49	52.96	9.07	40.36	-45.82	-13.00	-32.82	Peak	

Test channel:		Mid			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	33.93	-59.23	19.23	1.05	30.98	-69.93	-13.00	-56.93	Peak	
2	143.46	-65.55	21.38	2.26	30.44	-72.35	-13.00	-59.35	Peak	
3	4159.93	-55.45	42.33	5.65	40.29	-47.76	-13.00	-34.76	Peak	
4	4996.69	-61.14	44.50	6.00	40.20	-50.84	-13.00	-37.84	Peak	
5	7489.60	-61.42	48.44	7.78	39.93	-45.13	-13.00	-32.13	Peak	
6	10400.86	-67.03	51.97	8.92	40.14	-46.28	-13.00	-33.28	Peak	

Test channel:		High			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-66.23	17.66	2.26	30.44	-76.75	-13.00	-63.75	Peak	
2	374.67	-71.93	24.80	3.80	30.16	-73.49	-13.00	-60.49	Peak	
3	4366.07	-64.75	42.82	5.89	40.56	-56.60	-13.00	-43.60	Peak	
4	7135.98	-67.34	47.79	7.45	39.61	-51.71	-13.00	-38.71	Peak	
5	7941.19	-66.41	48.06	8.03	39.95	-50.27	-13.00	-37.27	Peak	
6	10453.95	-67.71	51.57	8.96	40.17	-47.35	-13.00	-34.35	Peak	

Test channel:		High			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	40.74	-68.86	21.18	1.16	30.96	-77.48	-13.00	-64.48	Peak	
2	143.46	-66.87	21.38	2.26	30.44	-73.67	-13.00	-60.67	Peak	
3	4159.93	-63.46	42.33	5.65	40.29	-55.77	-13.00	-42.77	Peak	
4	6063.19	-67.11	45.00	6.69	39.21	-54.63	-13.00	-41.63	Peak	
5	7489.60	-65.31	48.44	7.78	39.93	-49.02	-13.00	-36.02	Peak	
6	10641.89	-68.47	52.46	8.94	40.34	-47.41	-13.00	-34.41	Peak	

LTE Band 7										
Test channel:			Low			Polarization:			Horizontal	
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-61.10	17.66	2.26	30.44	-71.62	-25.00	-46.62	Peak	
2	400.56	-74.12	25.43	3.95	29.80	-74.54	-25.00	-49.54	Peak	
3	5009.43	-49.14	44.34	6.01	40.19	-38.98	-25.00	-13.98	Peak	
4	6527.71	-60.69	46.35	7.14	39.24	-46.44	-25.00	-21.44	Peak	
5	7527.83	-47.92	47.96	7.81	39.94	-32.09	-25.00	-7.09	Peak	
6	10036.73	-57.24	50.50	8.63	39.92	-38.03	-25.00	-13.03	Peak	
Test channel:			Low			Polarization:			Vertical	
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-61.86	21.38	2.26	30.44	-68.66	-25.00	-43.66	Peak	
2	343.14	-73.64	24.72	3.63	29.99	-75.28	-25.00	-50.28	Peak	
3	5009.43	-51.13	44.48	6.01	40.19	-40.83	-25.00	-15.83	Peak	
4	6527.71	-62.36	46.82	7.14	39.24	-47.64	-25.00	-22.64	Peak	
5	7527.83	-50.45	48.37	7.81	39.94	-34.21	-25.00	-9.21	Peak	
6	10036.73	-49.87	50.64	8.63	39.92	-30.52	-25.00	-5.52	Peak	
Test channel:			Mid			Polarization:			Horizontal	
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-61.62	17.66	2.26	30.44	-72.14	-25.00	-47.14	Peak	
2	400.56	-73.25	25.43	3.95	29.80	-73.67	-25.00	-48.67	Peak	
3	5060.69	-48.92	44.23	6.05	40.13	-38.77	-25.00	-13.77	Peak	
4	6561.03	-61.14	46.41	7.19	39.26	-46.80	-25.00	-21.80	Peak	
5	7604.87	-49.89	47.64	7.87	39.96	-34.34	-25.00	-9.34	Peak	
6	10139.45	-54.88	50.76	8.71	39.98	-35.39	-25.00	-10.39	Peak	
Test channel:			Mid			Polarization:			Vertical	
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-62.10	21.38	2.26	30.44	-68.90	-25.00	-43.90	Peak	
2	235.54	-69.12	19.98	2.95	30.22	-76.41	-25.00	-51.41	Peak	
3	5060.69	-50.51	44.33	6.05	40.13	-40.26	-25.00	-15.26	Peak	
4	6561.03	-62.57	46.85	7.19	39.26	-47.79	-25.00	-22.79	Peak	
5	7604.87	-52.65	48.26	7.87	39.96	-36.48	-25.00	-11.48	Peak	
6	10139.45	-50.68	51.02	8.71	39.98	-30.93	-25.00	-5.93	Peak	

Test channel:		High			Polarization:			Horizontal		
Mark	Frequency	Reading	Antenna	Cable	Preamp	Level	Limit	Over	Remark	
	MHz	dBm	dB	dB	dB	dBm	dBm	limit		
1	143.46	-60.97	17.66	2.26	30.44	-71.49	-25.00	-46.49	Peak	
2	449.85	-67.87	25.95	4.20	29.90	-67.62	-25.00	-42.62	Peak	
3	5112.49	-49.52	44.13	6.09	40.07	-39.37	-25.00	-14.37	Peak	
4	6577.75	-64.47	46.44	7.22	39.26	-50.07	-25.00	-25.07	Peak	
5	7682.70	-51.99	47.73	7.94	39.98	-36.30	-25.00	-11.30	Peak	
6	10243.22	-55.13	51.03	8.79	40.05	-35.36	-25.00	-10.36	Peak	

Test channel:		High			Polarization:			Vertical		
Mark	Frequency	Reading	Antenna	Cable	Preamp	Level	Limit	Over	Remark	
	MHz	dBm	dB	dB	dB	dBm	dBm	limit		
1	41.75	-67.81	21.29	1.18	30.95	-76.29	-25.00	-51.29	Peak	
2	143.46	-69.25	21.38	2.26	30.44	-76.05	-25.00	-51.05	Peak	
3	5112.49	-50.58	44.18	6.09	40.07	-40.38	-25.00	-15.38	Peak	
4	6577.75	-63.40	46.86	7.22	39.26	-48.58	-25.00	-23.58	Peak	
5	7682.70	-54.17	48.38	7.94	39.98	-37.83	-25.00	-12.83	Peak	
6	10243.22	-50.32	51.40	8.79	40.05	-30.18	-25.00	-5.18	Peak	

LTE Band 12										
Test channel:		Low			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	60.40	-97.31	24.20	1.43	0.00	-71.68	-13.00	-58.68	Peak	
2	462.68	-95.03	25.76	4.27	0.00	-65.00	-13.00	-52.00	Peak	
3	4688.62	-64.77	43.55	5.86	40.33	-55.69	-13.00	-42.69	Peak	
4	6331.33	-67.45	45.85	6.85	39.20	-53.95	-13.00	-40.95	Peak	
5	7981.72	-66.69	48.11	8.03	39.94	-50.49	-13.00	-37.49	Peak	
6	10971.98	-68.17	52.84	8.81	40.67	-47.19	-13.00	-34.19	Peak	
Test channel:		Low			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	103.44	-96.46	25.28	1.90	0.00	-69.28	-13.00	-56.28	Peak	
2	428.24	-95.35	25.47	4.09	0.00	-65.79	-13.00	-52.79	Peak	
3	4065.71	-63.69	41.86	5.52	40.25	-56.56	-13.00	-43.56	Peak	
4	6267.19	-67.35	45.93	6.81	39.20	-53.81	-13.00	-40.81	Peak	
5	7781.10	-67.08	48.53	8.00	40.00	-50.55	-13.00	-37.55	Peak	
6	11341.14	-69.00	53.08	9.07	40.36	-47.21	-13.00	-34.21	Peak	
Test channel:		Mid			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	56.50	-95.17	24.19	1.38	0.00	-69.60	-13.00	-56.60	Peak	
2	428.24	-94.30	26.01	4.09	0.00	-64.20	-13.00	-51.20	Peak	
3	5338.58	-64.56	44.04	6.28	39.83	-54.07	-13.00	-41.07	Peak	
4	7081.70	-65.79	47.74	7.40	39.55	-50.20	-13.00	-37.20	Peak	
5	9275.16	-65.79	49.53	8.51	39.89	-47.64	-13.00	-34.64	Peak	
6	11112.52	-67.59	52.93	8.89	40.59	-46.36	-13.00	-33.36	Peak	
Test channel:		Mid			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	96.76	-95.45	25.79	1.84	0.00	-67.82	-13.00	-54.82	Peak	
2	431.26	-93.71	25.51	4.10	0.00	-64.10	-13.00	-51.10	Peak	
3	4996.69	-61.82	44.50	6.00	40.20	-51.52	-13.00	-38.52	Peak	
4	7451.57	-64.82	48.50	7.75	39.92	-48.49	-13.00	-35.49	Peak	
5	9204.60	-66.97	49.73	8.48	39.92	-48.68	-13.00	-35.68	Peak	
6	10480.59	-67.02	52.25	8.98	40.19	-45.98	-13.00	-32.98	Peak	

Test channel:		High			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	67.36	-95.87	18.86	1.51	0.00	-75.50	-13.00	-62.50	Peak	
2	414.90	-95.35	25.84	4.01	0.00	-65.50	-13.00	-52.50	Peak	
3	4455.89	-65.06	43.08	5.88	40.48	-56.58	-13.00	-43.58	Peak	
4	6696.01	-64.96	46.61	7.42	39.30	-50.23	-13.00	-37.23	Peak	
5	9834.41	-67.42	50.57	8.60	39.87	-48.12	-13.00	-35.12	Peak	
6	11370.05	-68.21	52.96	9.10	40.33	-46.48	-13.00	-33.48	Peak	

Test channel:		High			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	97.78	-96.98	25.78	1.85	0.00	-69.35	-13.00	-56.35	Peak	
2	411.99	-95.06	25.32	4.00	0.00	-65.74	-13.00	-52.74	Peak	
3	4570.77	-64.52	43.43	5.87	40.39	-55.61	-13.00	-42.61	Peak	
4	4996.69	-64.56	44.50	6.00	40.20	-54.26	-13.00	-41.26	Peak	
5	7451.57	-66.77	48.50	7.75	39.92	-50.44	-13.00	-37.44	Peak	
6	10480.59	-68.72	52.25	8.98	40.19	-47.68	-13.00	-34.68	Peak	

5.2. Radiated Spurious Emission

LIMIT

Part 22.917&Part 24.238:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Part 27.53(g):

For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB.


Part 27.53(h):

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts, by at least $43 + 10 \log(P)$ dB.

Part 27.53(m)(4):

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT in the center of the turntable.
 - a) For radiated emissions measurements performed at frequencies less than or equal to 1 GHz, the EUT shall be placed on a RF-transparent table at a nominal height of 80 cm above the reference

ground plane

- b) For radiated measurements performed at frequencies above 1 GHz, the EUT shall be placed on an RF transparent table at a nominal height of 1.5 m above the ground plane.
2. Unless the EUT uses an integral antenna, the EUT shall be terminated with a non-radiating transmitter load. In cases where the EUT uses an adjustable antenna, the antenna shall be adjusted through typical positions and lengths to maximize emissions levels.
3. The EUT shall be tested while operating on the frequency per manufacturer specification. Set the transmitter to operate in continuous transmit mode.
4. Each emission under consideration shall be evaluated:
 - a) Raise and lower the measurement antenna from 1 m to 4 m, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
 - b) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - c) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - d) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
 - e) Record the measured emission amplitude level and frequency
5. Repeat step 5 for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
6. Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
7. Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
8. Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
9. For each emission that was detected and measured in the initial test
 - a) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
 - b) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step 5 and step 6.
 - c) Record the output power level of the signal generator when equivalence is achieved in step b).
10. Repeat step 8 through step 10 with the measurement antenna oriented in the opposite polarization.
11. Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:
$$Pe = Ps(dBm) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$
where
Pe = equivalent emission power in dBm
Ps = source (signal generator) power in dBm
NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.
12. Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from:
$$\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB}.$$
If necessary, the antenna gain can be calculated from calibrated antenna factor information
13. Provide the complete measurement results as a part of the test report.

TEST MODE

Please refer to the clause 4.2

TEST RESULTS

Passed Not Applicable

Note: only show the worse case for QPSK modulation.

LTE Band 2										
Test channel:		Low			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1850.00	-65.32	37.34	3.54	0.00	-24.44	-13.00	-11.44	Peak	
Test channel:		Low			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1850.00	-56.69	36.95	3.54	0.00	-16.20	-13.00	-3.20	Peak	

Test channel:		High			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1910.00	-65.55	38.07	3.59	0.00	-23.89	-13.00	-10.89	Peak	
Test channel:		High			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1910.00	-57.17	37.51	3.59	0.00	-16.07	-13.00	-3.07	Peak	

LTE Band 4										
Test channel:		Low			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1709.99	-65.34	36.39	3.37	0.00	-25.58	-13.00	-12.58	Peak	

Test channel:		High			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1754.99	-64.98	36.56	3.43	0.00	-24.99	-13.00	-11.99	Peak	

Test channel:		High			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1754.99	-55.50	36.37	3.43	0.00	-15.70	-13.00	-2.70	Peak	

LTE Band 5										
Test channel:		Low			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	823.99	-63.49	29.93	5.89	0.00	-27.67	-13.00	-14.67	Peak	
Test channel:		Low			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	823.99	-68.84	29.80	5.89	0.00	-33.15	-13.00	-20.15	Peak	

Test channel:		High			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	849.00	-67.18	29.77	6.00	0.00	-31.41	-13.00	-18.41	Peak	
Test channel:		High			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	849.00	-67.35	29.83	6.00	0.00	-31.52	-13.00	-18.52	Peak	

LTE Band 7										
Test channel:		Low			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	2494.00	-79.40	39.31	4.19	0.00	-35.90	-25.00	-10.90	Peak	
2	2495.00	-77.80	39.30	4.19	0.00	-34.31	-13.00	-21.31	Peak	
3	2500.00	-71.82	39.27	4.20	0.00	-28.35	-10.00	-18.35	Peak	

Test channel:		Low			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	2494.00	-73.43	39.24	4.19	0.00	-30.00	-25.00	-5.00	Peak	
2	2495.00	-71.33	39.24	4.19	0.00	-27.90	-13.00	-14.90	Peak	
3	2500.00	-66.45	39.23	4.20	0.00	-23.02	-10.00	-13.02	Peak	

Test channel:		High			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	2570.03	-69.33	38.90	4.24	0.00	-26.19	-10.00	-16.19	Peak	
2	2575.06	-75.61	38.88	4.24	0.00	-32.49	-13.00	-19.49	Peak	
3	2576.04	-75.07	38.87	4.24	0.00	-31.96	-25.00	-6.96	Peak	

Test channel:		High			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	2570.03	-65.04	39.17	4.24	0.00	-21.63	-10.00	-11.63	Peak	
2	2575.06	-78.28	39.17	4.24	0.00	-34.87	-13.00	-21.87	Peak	
3	2576.04	-79.51	39.17	4.24	0.00	-36.10	-25.00	-11.10	Peak	

LTE Band 12										
Test channel:			Low		Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	699.01	-64.60	28.19	5.36	0.00	-31.05	-13.00	-18.05	Peak	
Test channel:			Low		Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	699.01	-66.27	28.48	5.36	0.00	-32.43	-13.00	-19.43	Peak	

Test channel:			High		Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	716.01	-62.31	28.42	5.43	0.00	-28.46	-13.00	-15.46	Peak	
Test channel:			High		Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	716.01	-64.22	28.88	5.43	0.00	-29.91	-13.00	-16.91	Peak	

-----End of the report-----