

FCC REPORT

For WCDMA



Report No. : **CHTW24090015**

Report Verification:

Project No. : **SHT2408085301W**

FCC ID : **2BKRZ-WL432EG25G**

Applicant : **Suzhou Inovance Technology Co., Ltd.**

Address.....: No. 52, Tian E Dang Road, Wuzhong District, 215104, Suzhou
City, Jiangsu Province, P.R. China

Product Name : **LTE Module**

Trade Mark : -

Model No. : **EG25-G**

Listed Model(s) : -

Standard : **FCC CFR Title 47 Part 2
FCC CFR Title 47 Part 22 Subpart H
FCC CFR Title 47 Part 24 Subpart E
FCC CFR Title 47 Part 27**

Date of receipt of test sample.....: Aug. 28, 2024


Date of testing.....: Aug. 30, 2024- Sep. 04, 2024

Date of issue.....: Sep. 09, 2024

Result.....: **Pass**


Compiled by

(position+printedname+signature)....: File administrators Xiaodong Zhao




Supervised by

(position+printedname+signature)....: Project Engineer Xiaodong Zhao



Approved by

(position+printedname+signature)....: Manager Xu Yang



Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address.....: Building 7, Baiwang Idea Factory, No.1051, Songbai Road,
Yangguang Community, Xili Subdistrict, Nanshan District,
Shenzhen, Guangdong, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1. TEST STANDARDS AND REPORT VERSION</u>	3
1.1. Applicable Standards	3
1.2. Report version information	3
<u>2. TEST DESCRIPTION</u>	4
<u>3. SUMMARY</u>	5
3.1. Client Information	5
3.2. Product Description	5
3.3. Radio Specification Description	5
3.4. Testing Laboratory Information	6
<u>4. TEST CONFIGURATION</u>	7
4.1. Test frequency list	7
4.2. Test mode	7
4.3. Test sample information	7
4.4. Support unit used in test configuration and system	8
4.5. Testing environmental condition	8
4.6. Statement of the measurement uncertainty	8
4.7. Equipments Used during the Test	9
<u>5. TEST CONDITIONS AND RESULTS</u>	10
5.1. Radiated Spurious Emission	10
5.2. Radiated Band Edge	18

1. TEST STANDARDS AND REPORT VERSION

1.1. Applicable Standards

The tests were performed according to following standards:

[FCC CFR Title 47 Part 2](#): Frequency Allocations and Radio Treaty Matters; General Rules and Regulations

[FCC CFR Title 47 Part 22 Subpart H](#): Cellular Radiotelephone Service

[FCC CFR Title 47 Part 24 Subpart E](#): Broadband PCS

[FCC CFR Title 47 Part 27](#): Miscellaneous Wireless Communications Services

[ANSI C63.26-2015](#): American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services

[KDB 971168 D01 Power Meas License Digital Systems v03](#): MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS

1.2. Report version information

Revision No.	Date of issue	Description
N/A	2024-09-09	Original

2. TEST DESCRIPTION

Section	Test Item	Section in CFR 47	Result #1	Test Engineer
5.1	Radiated Spurious Emissions	Part 2.1053 Part 22.917 Part 24.238 Part 27.53	Pass	Yifan Wang
5.2	Radiated Band Edge	Part 2.1053 Part 22.917 Part 24.238 Part 27.53	Pass	Yifan Wang

Note:

- 1) #1: The test result does not include measurement uncertainty value.

3. **SUMMARY**

3.1. Client Information

Applicant:	Suzhou Inovance Technology Co., Ltd.
Address:	No. 52, Tian E Dang Road, Wuzhong District, 215104, Suzhou City, Jiangsu Province, P.R. China
Manufacturer:	Suzhou Inovance Technology Co., Ltd.
Address:	No. 52, Tian E Dang Road, Wuzhong District, 215104, Suzhou City, Jiangsu Province, P.R. China

3.2. Product Description

Module information:	
Product Name:	LTE Module
Trade Mark:	-
Model No.:	EG25-G
Listed Model(s):	-

3.3. Radio Specification Description

Support Operating Band:	<input checked="" type="checkbox"/> Band II	<input checked="" type="checkbox"/> Band IV	<input checked="" type="checkbox"/> Band V
Operating Frequency Range:	Please refer to note #2		
Support Type:	<input checked="" type="checkbox"/> WCDMA	<input checked="" type="checkbox"/> HSDPA	<input checked="" type="checkbox"/> HSUPA
Modulation Type:	<input checked="" type="checkbox"/> QPSK <input checked="" type="checkbox"/> 16QAM		
Power Class:	<input checked="" type="checkbox"/> Class 3 <input type="checkbox"/> Class 4		
Antenna type:	linear antenna		
Antenna gain #3:	Band II: 1.496dBi	Band IV: 1.963dBi	Band V: 2.066dBi

Note:

- : means that this feature is supported; : means that this feature is not supported
- #2: Operating frequency range is as follow:

WCDMA Band	Uplink frequency	Downlink frequency
Band II	1852.40~1907.60MHz	1932.40~1987.60MHz
Band IV	1712.40~1752.60MHz	2112.40~2152.60MHz
Band V	826.40~846.60MHz	871.40~891.60MHz

- #3: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, HTW lab has not verified the authenticity of its information

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China	
Contact information:	Phone: 86-755-26715499 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC Registration Number	762235
	FCC Designation Number	CN1181

4. TEST CONFIGURATION

4.1. Test frequency list

FDD Band II		FDD Band IV		FDD Band V	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
9262	1852.40	1312	1712.40	4132	826.40
9400	1880.00	1413	1732.60	4182	836.40
9538	1907.60	1513	1752.60	4233	846.60

4.2. Test mode

Test mode 1	WCDMA, QPSK modulation, Link
Test mode 2	WCDMA, 16QAM modulation, Link

- 1) Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems and ANSI C63.26 with maximum output power.
- 2) Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

All modes and data rates and positions were investigated, test modes are chosen to be reported as the worst case configuration below:

Band	Radiated test items
WCDMA Band V	Test mode 2
WCDMA Band II	Test mode 2
WCDMA Band IV	Test mode 2

4.3. Test sample information

Test item	HTW sample no.
Radiated test items	YPHT24080853001

Radiated test items: Radiated Spurious Emission, Radiated Band Edge

4.4. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?				
<input checked="" type="checkbox"/> No				
Item	Equipment	Trade Name	Model No.	Other
1				
2				

4.5. Testing environmental condition

Voltage	VN=Nominal Voltage	DC 24V
Temperature	TN=Normal Temperature	25 °C
Humidity	30~60 %	
Air Pressure	950-1050 hPa	

4.6. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	Radiated Spurious Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.7. Equipments Used during the Test

● Radiated Spurious Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2023/4/17	2026/4/16
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2024/8/12	2025/8/11
●	Spectrum Analyzer	R&S	HTWE0385	N9020A	MY54486658	2024/8/12	2025/8/11
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0123	VULB9163	538	2024/4/8	2027/4/7
●	Horn Antenna	SCHWARZBECK	HTWE0126	BBHA 9120D	1011	2023/2/14	2026/2/13
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2023/2/20	2026/2/19
●	Pre-Amplifier	CD	HTWE0071	PAP-0102	12004	2024/6/6	2025/6/5
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0551	SCU18F	100855	2024/6/6	2025/6/5
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

● Auxiliary Equipment							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Radio communication tester	R&S	HTWE0287	CMW500	137688-Lv	2024/08/12	2025/08/11
●	High pass filter	Wainwright	HTWE0297	WHKX3.0/18G-10SS	38	2024/03/26	2025/03/25
●	Band Stop filter	-	HTWE0039	N/A	N/A	2024/01/23	2025/01/24

5. TEST CONDITIONS AND RESULTS

5.1. Radiated Spurious Emission

LIMIT


Part 22.917&Part 24.238:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Part 27.53(h):

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT in the center of the turntable.
 - a) For radiated emissions measurements performed at frequencies less than or equal to 1 GHz, the EUT shall be placed on a RF-transparent table at a nominal height of 80 cm above the reference ground plane
 - b) For radiated measurements performed at frequencies above 1 GHz, the EUT shall be placed on an RF transparent table at a nominal height of 1.5 m above the ground plane.
2. Unless the EUT uses an integral antenna, the EUT shall be terminated with a non-radiating transmitter load. In cases where the EUT uses an adjustable antenna, the antenna shall be adjusted through typical positions and lengths to maximize emissions levels.
3. The EUT shall be tested while operating on the frequency per manufacturer specification. Set the transmitter to operate in continuous transmit mode.
4. Receiver or Spectrum set as follow:
 - Below 1GHz, RBW=100kHz, VBW=300kHz, Detector=Peak, Sweep time=Auto
 - Above 1GHz, RBW=1MHz, VBW=3MHz, Detector=Peck, Sweep time=Auto
5. Each emission under consideration shall be evaluated:

- a) Raise and lower the measurement antenna from 1 m to 4 m, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
- b) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
- c) Return the turntable to the azimuth where the highest emission amplitude level was observed.
- d) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
- e) Record the measured emission amplitude level and frequency

6. Repeat step 5 for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.

7. Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.

8. Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.

9. Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.

10. For each emission that was detected and measured in the initial test

- a) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
- b) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step 5 and step 6.
- c) Record the output power level of the signal generator when equivalence is achieved in step b).

11. Repeat step 8 through step 10 with the measurement antenna oriented in the opposite polarization.

12. Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:

$$Pe = Ps(dBm) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$

where

Pe = equivalent emission power in dBm

Ps = source (signal generator) power in dBm

NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.

13. Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from:

$$\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB.}$$

If necessary, the antenna gain can be calculated from calibrated antenna factor information

14. Provide the complete measurement results as a part of the test report.

TEST MODE

Please refer to the clause 4.2

TEST RESULTS

Passed Not Applicable

WCDMA Band II										
Test channel:		9262			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-61.75	17.66	2.26	30.44	-72.27	-13.00	-59.27	Peak	
2	374.67	-67.34	24.80	3.80	30.16	-68.90	-13.00	-55.90	Peak	
3	4996.69	-60.60	44.35	6.00	40.20	-50.45	-13.00	-37.45	Peak	
4	5560.50	-61.71	43.79	6.46	39.64	-51.10	-13.00	-38.10	Peak	
5	7413.73	-57.83	48.49	7.72	39.91	-41.53	-13.00	-28.53	Peak	
6	9275.16	-62.14	49.53	8.51	39.89	-43.99	-13.00	-30.99	Peak	

Test channel:		9262			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-62.30	21.38	2.26	30.44	-69.10	-13.00	-56.10	Peak	
2	400.56	-73.43	25.25	3.95	29.80	-74.03	-13.00	-61.03	Peak	
3	5560.50	-60.28	43.94	6.46	39.64	-49.52	-13.00	-36.52	Peak	
4	7413.73	-55.04	48.57	7.72	39.91	-38.66	-13.00	-25.66	Peak	
5	9275.16	-57.92	49.77	8.51	39.89	-39.53	-13.00	-26.53	Peak	
6	11112.52	-63.39	52.89	8.89	40.59	-42.20	-13.00	-29.20	Peak	

Test channel:		9400			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-63.52	17.66	2.26	30.44	-74.04	-13.00	-61.04	Peak	
2	400.56	-72.62	25.43	3.95	29.80	-73.04	-13.00	-60.04	Peak	
3	5646.08	-56.92	43.79	6.56	39.51	-46.08	-13.00	-33.08	Peak	
4	7527.83	-52.49	47.96	7.81	39.94	-36.66	-13.00	-23.66	Peak	
5	9417.91	-55.13	50.01	8.57	39.83	-36.38	-13.00	-23.38	Peak	
6	11312.31	-63.54	52.95	9.05	40.39	-41.93	-13.00	-28.93	Peak	

Test channel:		9400			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-61.60	21.38	2.26	30.44	-68.40	-13.00	-55.40	Peak	
2	449.85	-67.00	25.28	4.20	29.90	-67.42	-13.00	-54.42	Peak	
3	3757.21	-57.91	42.15	5.24	40.66	-51.18	-13.00	-38.18	Peak	
4	5646.08	-56.39	43.95	6.56	39.51	-45.39	-13.00	-32.39	Peak	
5	7527.83	-49.96	48.37	7.81	39.94	-33.72	-13.00	-20.72	Peak	
6	9417.91	-56.35	49.81	8.57	39.83	-37.80	-13.00	-24.80	Peak	

Test channel:		9538			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-62.49	17.66	2.26	30.44	-73.01	-13.00	-60.01	Peak	
2	449.85	-67.06	25.95	4.20	29.90	-66.81	-13.00	-53.81	Peak	
3	5718.40	-56.31	43.89	6.64	39.41	-45.19	-13.00	-32.19	Peak	
4	7624.25	-52.96	47.66	7.89	39.96	-37.37	-13.00	-24.37	Peak	
5	9538.54	-58.27	49.88	8.60	39.81	-39.60	-13.00	-26.60	Peak	
6	11515.68	-64.18	52.97	9.22	40.22	-42.21	-13.00	-29.21	Peak	

Test channel:		9538			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	69.28	-63.87	19.64	1.54	30.63	-73.32	-13.00	-60.32	Peak	
2	143.46	-63.15	21.38	2.26	30.44	-69.95	-13.00	-56.95	Peak	
3	4996.69	-60.00	44.50	6.00	40.20	-49.70	-13.00	-36.70	Peak	
4	5718.40	-54.68	44.04	6.64	39.41	-43.41	-13.00	-30.41	Peak	
5	7624.25	-50.45	48.29	7.89	39.96	-34.23	-13.00	-21.23	Peak	
6	9538.54	-54.25	49.68	8.60	39.81	-35.78	-13.00	-22.78	Peak	

WCDMA Band IV										
Test channel:		1312			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-62.17	17.66	2.26	30.44	-72.69	-13.00	-59.69	Peak	
2	449.85	-68.20	25.95	4.20	29.90	-67.95	-13.00	-54.95	Peak	
3	3419.49	-58.37	39.86	4.92	40.84	-54.43	-13.00	-41.43	Peak	
4	5138.58	-61.92	44.07	6.11	40.04	-51.78	-13.00	-38.78	Peak	
5	6851.19	-61.28	46.98	7.41	39.39	-46.28	-13.00	-33.28	Peak	
6	11545.04	-66.59	52.94	9.25	40.26	-44.66	-13.00	-31.66	Peak	

Test channel:		1312			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-62.17	21.38	2.26	30.44	-68.97	-13.00	-55.97	Peak	
2	449.85	-67.94	25.28	4.20	29.90	-68.36	-13.00	-55.36	Peak	
3	3428.21	-57.27	40.01	4.93	40.85	-53.18	-13.00	-40.18	Peak	
4	5138.58	-61.64	44.10	6.11	40.04	-51.47	-13.00	-38.47	Peak	
5	6851.19	-59.36	47.39	7.41	39.39	-43.95	-13.00	-30.95	Peak	
6	11574.46	-66.68	53.17	9.29	40.30	-44.52	-13.00	-31.52	Peak	

Test channel:		1413			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-61.46	17.66	2.26	30.44	-71.98	-13.00	-58.98	Peak	
2	449.85	-68.34	25.95	4.20	29.90	-68.09	-13.00	-55.09	Peak	
3	3463.29	-58.85	40.49	5.00	40.89	-54.25	-13.00	-41.25	Peak	
4	4996.69	-62.12	44.35	6.00	40.20	-51.97	-13.00	-38.97	Peak	
5	6938.94	-62.12	47.37	7.38	39.44	-46.81	-13.00	-33.81	Peak	
6	10860.83	-66.13	52.57	8.86	40.56	-45.26	-13.00	-32.26	Peak	

Test channel:		1413			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-64.04	21.38	2.26	30.44	-70.84	-13.00	-57.84	Peak	
2	400.56	-73.94	25.25	3.95	29.80	-74.54	-13.00	-61.54	Peak	
3	3291.39	-53.81	40.59	4.83	40.80	-49.19	-13.00	-36.19	Peak	
4	4996.69	-60.66	44.50	6.00	40.20	-50.36	-13.00	-37.36	Peak	
5	6938.94	-58.90	47.37	7.38	39.44	-43.59	-13.00	-30.59	Peak	
6	10400.86	-65.20	51.97	8.92	40.14	-44.45	-13.00	-31.45	Peak	

Test channel:		1513			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-64.21	17.66	2.26	30.44	-74.73	-13.00	-61.73	Peak	
2	238.04	-73.75	22.40	2.97	30.23	-78.61	-13.00	-65.61	Peak	
3	3507.65	-58.79	41.11	5.09	40.94	-53.53	-13.00	-40.53	Peak	
4	4996.69	-60.49	44.35	6.00	40.20	-50.34	-13.00	-37.34	Peak	
5	7027.82	-60.88	47.68	7.36	39.49	-45.33	-13.00	-32.33	Peak	
6	11457.21	-66.81	52.97	9.17	40.24	-44.91	-13.00	-31.91	Peak	

Test channel:		1513			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-63.64	21.38	2.26	30.44	-70.44	-13.00	-57.44	Peak	
2	374.67	-69.10	24.67	3.80	30.16	-70.79	-13.00	-57.79	Peak	
3	3507.65	-55.83	41.23	5.09	40.94	-50.45	-13.00	-37.45	Peak	
4	4996.69	-60.70	44.50	6.00	40.20	-50.40	-13.00	-37.40	Peak	
5	7027.82	-58.18	47.53	7.36	39.49	-42.78	-13.00	-29.78	Peak	
6	8770.01	-62.16	49.27	8.33	40.09	-44.65	-13.00	-31.65	Peak	

WCDMA Band V										
Test channel:			4132			Polarization:			Horizontal	
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	32.99	-60.66	26.67	1.04	30.99	-63.94	-13.00	-50.94	Peak	
2	143.46	-65.59	17.66	2.26	30.44	-76.11	-13.00	-63.11	Peak	
3	3249.76	-63.42	40.91	4.82	40.80	-58.49	-13.00	-45.49	Peak	
4	5420.74	-66.06	44.04	6.34	39.77	-55.45	-13.00	-42.45	Peak	
5	7820.82	-65.62	47.91	8.01	39.98	-49.68	-13.00	-36.68	Peak	
6	10348.05	-68.03	51.30	8.88	40.11	-47.96	-13.00	-34.96	Peak	

Test channel:			4132			Polarization:			Vertical	
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	33.93	-57.54	19.23	1.05	30.98	-68.24	-13.00	-55.24	Peak	
2	143.46	-64.11	21.38	2.26	30.44	-70.91	-13.00	-57.91	Peak	
3	4034.78	-64.80	41.71	5.48	40.28	-57.89	-13.00	-44.89	Peak	
4	5448.41	-65.88	44.06	6.36	39.75	-55.21	-13.00	-42.21	Peak	
5	7761.32	-67.11	48.50	8.00	40.00	-50.61	-13.00	-37.61	Peak	
6	11370.05	-67.52	53.10	9.10	40.33	-45.65	-13.00	-32.65	Peak	

Test channel:			4183			Polarization:			Horizontal	
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	33.93	-61.16	26.84	1.05	30.98	-64.25	-13.00	-51.25	Peak	
2	143.46	-66.96	17.66	2.26	30.44	-77.48	-13.00	-64.48	Peak	
3	4223.95	-65.43	42.36	5.75	40.41	-57.73	-13.00	-44.73	Peak	
4	5747.59	-66.68	43.93	6.67	39.36	-55.44	-13.00	-42.44	Peak	
5	7941.19	-66.08	48.06	8.03	39.95	-49.94	-13.00	-36.94	Peak	
6	11027.98	-69.05	52.91	8.82	40.67	-47.99	-13.00	-34.99	Peak	

Test channel:			4183			Polarization:			Vertical	
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	33.93	-57.54	19.23	1.05	30.98	-68.24	-13.00	-55.24	Peak	
2	143.46	-64.11	21.38	2.26	30.44	-70.91	-13.00	-57.91	Peak	
3	3625.67	-64.41	42.54	5.20	40.88	-57.55	-13.00	-44.55	Peak	
4	5393.22	-66.25	44.10	6.32	39.79	-55.62	-13.00	-42.62	Peak	
5	7451.57	-66.10	48.50	7.75	39.92	-49.77	-13.00	-36.77	Peak	
6	10971.98	-67.85	52.76	8.81	40.67	-46.95	-13.00	-33.95	Peak	

Test channel:		4233			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	34.77	-62.49	26.98	1.07	30.98	-65.42	-13.00	-52.42	Peak	
2	143.46	-66.45	17.66	2.26	30.44	-76.97	-13.00	-63.97	Peak	
3	4605.81	-65.69	43.47	5.87	40.37	-56.72	-13.00	-43.72	Peak	
4	6816.39	-67.35	46.82	7.41	39.37	-52.49	-13.00	-39.49	Peak	
5	9275.16	-67.97	49.53	8.51	39.89	-49.82	-13.00	-36.82	Peak	
6	11399.03	-68.88	52.97	9.12	40.30	-47.09	-13.00	-34.09	Peak	

Test channel:		4233			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	143.46	-65.78	21.38	2.26	30.44	-72.58	-13.00	-59.58	Peak	
2	593.90	-76.18	27.20	4.90	29.58	-73.66	-13.00	-60.66	Peak	
3	3653.46	-63.15	42.46	5.21	40.83	-56.31	-13.00	-43.31	Peak	
4	5338.58	-65.69	44.05	6.28	39.83	-55.19	-13.00	-42.19	Peak	
5	7282.79	-66.86	48.62	7.59	39.78	-50.43	-13.00	-37.43	Peak	
6	10269.32	-67.75	51.49	8.82	40.06	-47.50	-13.00	-34.50	Peak	

5.2. Radiated Band Edge

LIMIT


Part 22.917&Part 24.238:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Part 27.53(h):

Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT in the center of the turntable.
 - a) For radiated emissions measurements performed at frequencies less than or equal to 1 GHz, the EUT shall be placed on a RF-transparent table at a nominal height of 80 cm above the reference ground plane
 - b) For radiated measurements performed at frequencies above 1 GHz, the EUT shall be placed on an RF transparent table at a nominal height of 1.5 m above the ground plane.
2. Unless the EUT uses an integral antenna, the EUT shall be terminated with a non-radiating transmitter load. In cases where the EUT uses an adjustable antenna, the antenna shall be adjusted through typical positions and lengths to maximize emissions levels.
3. The EUT shall be tested while operating on the frequency per manufacturer specification. Set the transmitter to operate in continuous transmit mode.
4. Each emission under consideration shall be evaluated:
 - a) Raise and lower the measurement antenna from 1 m to 4 m, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
 - b) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - c) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - d) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.

- e) Record the measured emission amplitude level and frequency
5. Repeat step 5 for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
6. Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
7. Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
8. Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
9. For each emission that was detected and measured in the initial test
 - a) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
 - b) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step 5 and step 6.
 - c) Record the output power level of the signal generator when equivalence is achieved in step b).
10. Repeat step 8 through step 10 with the measurement antenna oriented in the opposite polarization.
11. Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:
$$Pe = Ps(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$
where
Pe = equivalent emission power in dBm
Ps = source (signal generator) power in dBm
NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.
12. Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from:
$$\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB.}$$
If necessary, the antenna gain can be calculated from calibrated antenna factor information
13. Provide the complete measurement results as a part of the test report.

TEST MODE

Please refer to the clause 4.2

TEST RESULTS

Passed Not Applicable

WCDMA Band II										
Test channel:		9262			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1850.00	-65.90	37.34	3.54	0.00	-25.02	-13.00	-12.02	Peak	
Test channel:		9262			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1850.00	-55.70	36.95	3.54	0.00	-15.21	-13.00	-2.21	Peak	

Test channel:		9538			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1910.00	-69.42	38.07	3.59	0.00	-27.76	-13.00	-14.76	Peak	
Test channel:		9538			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1910.00	-60.52	37.51	3.59	0.00	-19.42	-13.00	-6.42	Peak	

WCDMA Band IV										
Test channel:		1312			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1709.99	-67.78	36.39	3.37	0.00	-28.02	-13.00	-15.02	Peak	
Test channel:		1312			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1709.99	-60.07	36.26	3.37	0.00	-20.44	-13.00	-7.44	Peak	

Test channel:		1513			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1754.99	-65.55	36.56	3.43	0.00	-25.56	-13.00	-12.56	Peak	
Test channel:		1513			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	1754.99	-58.69	36.37	3.43	0.00	-18.89	-13.00	-5.89	Peak	

WCDMA Band V										
Test channel:		4132			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	824.00	-60.39	29.93	5.89	0.00	-24.57	-13.00	-11.57	Peak	

Test channel:		4233			Polarization:			Horizontal		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	849.00	-60.79	29.77	6.00	0.00	-25.02	-13.00	-12.02	Peak	

Test channel:		4233			Polarization:			Vertical		
Mark	Frequency MHz	Reading dBm	Antenna dB	Cable dB	Preamp dB	Level dBm	Limit dBm	Over limit	Remark	
1	849.00	-58.68	29.83	6.00	0.00	-22.85	-13.00	-9.85	Peak	

-----End of the report-----