



Screw the bottom
battery cover



Load the remote
control car battery




Cover the battery
and turn on the switch

Nissan
nismo


LET THE ENGINE DURST




DIY modification
バッジ・カスタム




Fine reduction
バッジ・カスタム



Four-wheel drive
バッジ・カスタム



Convertible tire
バッジ・カスタム



Reinforced case
バッジ・カスタム



24G remote control
バッジ・カスタム

1, the battery should be removed and installed according to the polarity and voltage signs on the toy battery room into the correct operation, the battery should not short circuit.

2, non-rechargeable batteries can not be charged.

3, different types of electricity or old and new batteries can not be mixed.

4, only the recommended battery is the same or equivalent battery can be used.

5. Do not short circuit the power terminal.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction