

FCC Part 2 section 2.1091

(ii) Limits for General Population/Uncontrolled Exposure				
Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

$$S = \text{EIRP} / (4 R^2 \pi)$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna(Over 20cm)

Maximum Permissible Exposure Calculation

Operation Mode	Evaluation Frequency (MHz)	MAX Output Power (dBm)	Antenna Gain (dBi)	MAX. EIRP (dBm)	MAX. EIRP (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Result
2.4GHz BT	2402~2480	6.71	3.42	10.13	10.30	20	0.002 0	1	Pass
2.4GHz LE	2402~2480	3.83	3.42	7.25	5.31	20	0.001 1	1	Pass

Conclusion

maximum calculations of above situations are less than the “1” limit.