

产品规格书

| 制造商名称 | SHENZHEN JIUYI ELECTRONICS CO.,LTD | | 客户料号 | DJ.CJ.A1143006 | | | | | | | | | | | | | | | | | | | |
|---------------|---|-------------------------------------|-----------|----------------|----|---|----------|---|-----------|---|-----------|---|-----------|---|-----------|---|-----------|---|----------|---|-----------|---|-----------------|
| | | | 规格编号 | 202401002800 | 版本 | | | | | | | | | | | | | | | | | | |
| ◆、外形尺寸 | (单位: mm) | | | | | | | | | | | | | | | | | | | | | | |
| | <table border="1" style="margin-left: 20px;"> <tr> <td>A</td><td>5.0 ±1.5</td></tr> <tr> <td>B</td><td>20.5 ±1.5</td></tr> <tr> <td>C</td><td>40.0 ±1.5</td></tr> <tr> <td>D</td><td>43.5 ±1.5</td></tr> <tr> <td>E</td><td>43.3 ±1.0</td></tr> <tr> <td>F</td><td>30.0 ±2.0</td></tr> <tr> <td>G</td><td>3.0 ±1.5</td></tr> <tr> <td>H</td><td>2.15 ±0.3</td></tr> <tr> <td>I</td><td>0.65 ±0.2(磁片厚度)</td></tr> </table> | | | | | A | 5.0 ±1.5 | B | 20.5 ±1.5 | C | 40.0 ±1.5 | D | 43.5 ±1.5 | E | 43.3 ±1.0 | F | 30.0 ±2.0 | G | 3.0 ±1.5 | H | 2.15 ±0.3 | I | 0.65 ±0.2(磁片厚度) |
| A | 5.0 ±1.5 | | | | | | | | | | | | | | | | | | | | | | |
| B | 20.5 ±1.5 | | | | | | | | | | | | | | | | | | | | | | |
| C | 40.0 ±1.5 | | | | | | | | | | | | | | | | | | | | | | |
| D | 43.5 ±1.5 | | | | | | | | | | | | | | | | | | | | | | |
| E | 43.3 ±1.0 | | | | | | | | | | | | | | | | | | | | | | |
| F | 30.0 ±2.0 | | | | | | | | | | | | | | | | | | | | | | |
| G | 3.0 ±1.5 | | | | | | | | | | | | | | | | | | | | | | |
| H | 2.15 ±0.3 | | | | | | | | | | | | | | | | | | | | | | |
| I | 0.65 ±0.2(磁片厚度) | | | | | | | | | | | | | | | | | | | | | | |
| | (1)线径: 0.07*100P丝包线 (2)线圈圈数: 10Ts (3)起尾线是否交叉: 是 (4)线圈包8mm宽高温胶带 (5)线圈与磁片需粘贴居中 (6)磁片背42圆白胶 | | | | | | | | | | | | | | | | | | | | | | |
| ◆、电气特性: | | | | | | | | | | | | | | | | | | | | | | | |
| 参数 | 规格 | 测试条件 | 测试仪器 | | | | | | | | | | | | | | | | | | | | |
| L0 | 6.5 ±10% μH | 100KHZ/1V | ■TH1816B | | | | | | | | | | | | | | | | | | | | |
| Q | >30 min | 100KHZ/1V | ■TH1816B | | | | | | | | | | | | | | | | | | | | |
| DCR | <80 mΩ | @ 25°C | ■CH-502BC | | | | | | | | | | | | | | | | | | | | |
| ◆、温度等级: | | | | | | | | | | | | | | | | | | | | | | | |
| 操作温度 | -40°C~ 125°C | | | | | | | | | | | | | | | | | | | | | | |
| ◆、材料清单: | | | | | | | | | | | | | | | | | | | | | | | |
| Serial number | name | 材料规格 | 供应商 | 备注 | | | | | | | | | | | | | | | | | | | |
| 1 | Diskette | 43.5*53*0.65T with two slots | | PC40猛锌 | | | | | | | | | | | | | | | | | | | |
| 2 | Copper wire | 0.07*100P | | 漆包线 | | | | | | | | | | | | | | | | | | | |
| 3 | Tape | 8MM high temperature adhesive paper | | 环保胶带 | | | | | | | | | | | | | | | | | | | |
| 4 | glue | 42 rounds of white glue | | 环保胶纸 | | | | | | | | | | | | | | | | | | | |
| 4 | tin | 107H | | 千岛环保锡 | | | | | | | | | | | | | | | | | | | |
| 5 | Glue | yellow glue | | 环保胶水 | | | | | | | | | | | | | | | | | | | |
| 编制 | | 审核 | | 批准 | | | | | | | | | | | | | | | | | | | |
| 钟建立 | | / | | 马湘平 | | | | | | | | | | | | | | | | | | | |