

TEST REPORT

Reference No...... : WTX24X08204444W
Applicant..... : The Stack System Baseball, GP
Address..... : 850 W Lincoln Street, Phoenix, AZ 85007
Manufacturer..... : The Stack System Baseball, GP
Address..... : 850 W Lincoln Street, Phoenix, AZ 85007
Product Name..... : Stack Sensor
Model No...... : stacksensor24
Standards..... : ANSI/ IEEE 149-2021
Date of Receipt sample..... : 2024-09-03
Date of Test..... : 2024-09-03 to 2024-09-05
Date of Issue..... : 2024-09-05
Test Report Form No...... : WTX_IEEE 149
Test Result..... : **Pass**

Remarks:


The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.


Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Mike Shi

Approved by:



Jason Su

TABLE OF CONTENTS

1.GENERAL INFORMATION 4
 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4

2. SUMMARY OF TEST RESULTS5

3. ANTENNA TEST CONFIGURATIONS6
 3.1 TEST LOCATION6
 3.1 TEST ENVIRONMENTS6
 3.2 TEST EQUIPMENT LIST 6
 3.3 MEASUREMENT UNCERTAINTY 6
 3.4 TEST SETUP 6

4. ANTENNA TEST RESULT 7
 4.1 GAIN AND EFFICIENCY 7
 4.2 RADIATION PATTERN 2D VIEW 8
 4.3 RADIATION PATTERN 3D VIEW 9

EXHIBIT 1 - EUT PHOTOGRAPHS 11

EXHIBIT 2 - TEST SETUP PHOTOGRAPHS 12

Report version

Version No.	Date of issue	Description
Rev.00	2024-09-05	Original
/	/	/


1.GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Stack Sensor
Trade Name:	/
Model No.:	stacksensor24
Adding Model(s):	/
Note: The test data is gathered from a production sample, provided by the manufacturer.	

Technical Characteristics of EUT	
Frequency Range:	2400-2500MHz
Gain of Antenna:	-2.73dBi (Max.)
Type of Antenna:	PCB antenna
Size:	/

Dimension:



2. SUMMARY OF TEST RESULTS

Standards	Description of Test Item	Result
ANSI/ IEEE 149-2021	IEEE Recommended Practice for Antenna Measurements	Compliant

N/A: not applicable

3. Antenna Test Configurations

3.1 Test Location

Name:	Shenzhen Morlab Communications Technology Co.,Ltd.
Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen, GuangDong Province, P.R. China

3.1 Test Environments

Environments Parameter	Temperature	Voltage	Humidit
NTNV	25° C	--	50%


3.2 Test Equipment List

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Network Analyzer	Agilent	E5071C	MY46110140	2024-05-30	2025-05-29
OTA Chamber	ETS	AMS-8923-150	TJ2235-Q1793	2022-11-30	2025-11-29
Antenna Measurement System	ETS	EMQuest EMQ-100 V1.13 Build 21267	1685	N/A	N/A

3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the“Guide to the Expression of Uncertainty in Measurement” (GUM) published by ISO. When the test result is a critical value,we will use the measurement uncertainty give the judgment result based on the 95%Confidence intervals.

3.4 Test Setup




4. Antenna Test Result

4.1 Gain and Efficiency


Frequency (MHz)	Efficiency (%)	Gain (dBi)
2400	9.80	-2.73
2410	9.47	-2.74
2420	9.11	-3.10
2430	8.96	-3.31
2440	9.06	-3.23
2450	9.17	-3.02
2460	9.20	-3.12
2470	9.13	-3.16
2480	9.11	-3.07
2490	8.97	-3.11
2500	9.07	-3.14

4.2 Radiation Pattern 2D View


PHI=0



PHI=90




THETA=90




4.3 Radiation Pattern 3D View


2400MHz




2440MHz



2450MHz



2480MHz



2500MHz




EXHIBIT 1 - EUT PHOTOGRAPHS

EUT View 1






EXHIBIT 2 - TEST SETUP PHOTOGRAPHS

OTA Test View 1:



OTA Test View 2:



***** END OF REPORT *****