

4/22/2025

Maztech Industries
1641 Reynolds Ave.
Irvine, CA 92614
USA

Dear Craig Cronin,

Enclosed is the EMC test report for testing of the Maztech Industries, X4-LRF tested to the requirements of FCC Part 2.1093

Thank you for using the services of Eurofins E&E North America. If you have any questions regarding these results or if MET can be of further service to you, please do feel free to contact me.

Sincerely,



Nancy LaBrecque
Documentation Department
Eurofins Electrical and Electronic Testing NA, Inc.

Reference: WIRA134602_MPE_R3



Certificates and reports shall not be reproduced except in full, without the written permission of Eurofins E&E North America. While use of the A2LA logo in this report reflects MET accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.

Eurofins MET Laboratories Inc. (Eurofins E&E North America) is part of the Eurofins Electrical & Electronics (E&E) global compliance network.

**RF Exposure Criteria
Test Report
Using Maximum Permissible Exposure (MPE) Calculations**

for the

Maztech Industries
X4-LRF

Tested under

FCC Part 2.1093

Report: WIRA134602_MPE_R3

4/22/2025



Bryan Taylor, Wireless Team Lead
Electromagnetic Compatibility Lab



Nancy LaBrecque
Documentation Department

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Part 15.247 under normal use and maintenance.



Matthew Hinojosa
EMC Manager, Austin Electromagnetic Compatibility Lab

Report Status Sheet

Revision	Report Date	Reason for Revision
0	2/12/2025	Initial Issue.
1	2/13/2025	Customer requested changes
2	3/24/2025	Additional customer requested changes. Updated report to reflect a portable device and show SAR exemption for the BLE transmitter
3	4/22/2025	Updated Antenna Gain

Table of Contents

1.0 Requirements Summary.....
2.0 Equipment Configuration.....
2.1 Overview.....
2.2 Test Site
2.3 References.....
2.4 Description of Test Sample
2.5 Modifications.....
2.5.1 Modifications to EUT
2.5.2 Modifications to Test Standard
2.6 Disposition of EUT.....
3.0 Transmitter Requirements.....

8
9
9
10
10
11
11
11
11
11
12

List of Tables

Table 1. Summary of Test Results.....8

Table 2. EUT Summary Table9

Table 3. References..... 10

List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
<i>d</i>	Measurement Distance
dB	Decibels
dBμA	Decibels above one microamp
dBμV	Decibels above one microvolt
dBμA/m	Decibels above one microamp per meter
dBμV/m	Decibels above one microvolt per meter
DC	Direct Current
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
<i>f</i>	Frequency
CISPR	Comite International Special des Perturbations Radioelectriques (International Special Committee on Radio Interference)
GRP	Ground Reference Plane
H	Magnetic Field
HCP	Horizontal Coupling Plane
Hz	Hertz
IEC	International Electrotechnical Commission
kHz	kiloHertz
kPa	kiloPascal
kV	kilovolt
LISN	Line Impedance Stabilization Network
MHz	MegaHertz
μH	microHenry
μF	microFarad
μs	microseconds
PRF	Pulse Repetition Frequency
RF	Radio Frequency
RMS	Root-Mean-Square
V/m	Volts per meter
VCP	Vertical Coupling Plane

1.0 Requirements Summary

Page Number	Test Name	Result
12	FCC Part 2.1093 Limits (For General Public Exposure)	Compliant

Table 1. Summary of Test Results

2.0 Equipment Configuration

2.1 Overview

Eurofins METLabs was contracted by Maztech Industries to perform testing on the X4-LRF, under Maztech Industries's purchase order number 1MAZ1911.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Maztech Industries X4-LRF.

The results obtained relate only to the item(s) tested.

Product Name:	X4 Laser Rangefinder (X4-LRF)	
Model Number:	X4-LRF	
FCCID:	2BKWD-LRF01	
EUT Specifications:	Primary Power: 1.5-4.2VDC	
	Antenna Gain ¹ :	BLE: 2.15dBi UWB: 4.16dBi
	EUT Frequency Ranges:	BLE: 2402MHz – 2480MHz UWB: 3.1GHz – 6GHz
	Maximum Conducted Output Power:	BLE: 0dBm UWB: -13.0dBm
Analysis:	The results obtained relate only to the item(s) tested.	
Environmental Test Conditions:	Temperature: 15-35° C	
	Relative Humidity: 30-60%	
	Barometric Pressure: 860-1060 mbar	
Type of Filing:	Original	
Evaluated by:	Bryan Taylor	
Report Date(s):	4/22/2025	

Table 2. EUT Summary Table

¹ The antenna gain information was provided by Maztech Industries at the time of testing.

2.2 Test Site

All testing was performed at Eurofins E&E North America, Austin, TX. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

2.3 References

FCC Part 2.1093	Radiofrequency radiation exposure evaluation: portable devices.
------------------------	---

Table 3. References

2.4 Description of Test Sample

Determines distances to items that are pointed to. It has wireless interfaces to communicate with accessories: UWB (3.1 GHz-5.8 GHz) and to communicate with smartphone for a command/control app: BLE 5.0 (2.4 GHz).

2.5 Modifications

2.5.1 Modifications to EUT

No modifications were made to the EUT.

2.5.2 Modifications to Test Standard

No modifications were made to the test standard.


2.6 Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Maztech Industries upon completion of testing.

3.0 Maximum Permissible Exposure Results

3.1 FCC SAR Exemption Thresholds

The FCC SAR exemption threshold limits from KDB447498D04 v01 are shown below.



11/29/2021

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20\text{ cm}}(d/20\text{ cm})^x & d \leq 20\text{ cm} \\ ERP_{20\text{ cm}} & 20\text{ cm} < d \leq 40\text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20\text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{ cm}}$ is per Formula (B.1).
The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

TABLE 2.2 – Example Tower Dimensions (mW)											
Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

3.1 FCC Blanket 1mW Exemption Criteria

Per the FCCs KDB 447498D04 v01, transmitters that meet the 1mW blanket exemption power level are exempt from the RF exposure criteria.

B.1 General

This appendix provides the exemption criteria and summarizes relevant parameters and usage considerations based on descriptions in FCC 19-126.

B.2 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1 mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph § 1.1307(b)(3)(ii)(A).

The 1 mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

KDB 447498D01 Blanket Exemption for Transmitters Outputting Less than 1mW

Test Procedure:

For the Ultra-Wideband transmitter, the maximum radiated power was compared to the 1mW blanket exemption limit. For the BLE transmitter the maximum conducted power was added to the antenna gain and the resultant EIRP was compared to the SAR exemption limit at 2402MHz and a separation distance of 5mm.

Test Results:

The X4 Laser Rangefinder (X4-LRF) was **compliant** with FCC Part 2.1093. The EIRP from the BLE transmitter was less than the power threshold limit for SAR based exemption with a separation distance of 5mm. Additionally, the Ultra-Wideband transmitter onboard met the 1mW blanket exemption criteria from KDB447498 D04.

Test Data:

Maximum Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)	Pth	Result
0	2.15	2.15	1.6406	3.0000	exempt

SAR Power Threshold Data for the BLE Transmitter at 2402MHz

EIRP (Including Tune-Up Tolerance) (dBm)	EIRP (mW)
-13	0.0501187234

The worst case output power including tune-up tolerance was converted to mW and compared to the 1mW Exemption Criteria.

1mW Exemption for the Ultra-Wideband Transmitter

Test Engineer(s): Bryan Taylor

Test Date(s): 1/27/2025

Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ISO/IEC 17025:2017.

Asset #	Description	Manufacturer	Model	Last Cal Date	Cal Due Date
1A1250	Receiver	Rohde & Schwarz	ESW44	04/08/2024	04/08/2025
1A1234	FSV Signal Analyzer	Rohde & Schwarz	FSV 40	1/23/2023	02/23/2025
1A1176	Active Loop Antenna (9KHz-30MHz)	ETS-Lindgren	6502	8/22/2024	8/22/2026
1A1147	Bi-Log Antenna	Suno Sciences Corp	JB3	04/06/2023	04/06/2025
1A1047	Horn Antenna (1GHz – 18GHz)	ETS - Lindgren	3117	06/26/2024	06/26/2025
1A1161	Horn Antenna (18GHz – 40GHz)	ETS Lindgren	3116C	08/01/2024	08/01/2026
1A1088	Preamplifier	Rohde & Schwarz	TS-PR1	See Note	
1A1044	Generator	Com-Power	CG-520	See Note	
1A1073	Multi Device Controller	ETS	2090	See Note	
1A1074	System Controller	Panasonic	WV-CU101	See Note	
1A1080	Multi-Device	ETS	2090	See Note	
1A1180	Preamplifier	Miteq	AMF-7D- 01001800-22- 10P	See Note	

Table 4. Test Equipment List

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.

End of Report